

BUTT JOINT DETAIL

STA 954+50 TO STA 954+80 STA 963+20 TO STA 963+50



NOTES:

- 1. MILLING SHALL BE DONE TO ATTAIN A $^316^{\prime\prime\prime\prime}$ SLOPE IN CROWN SECTIONS
- 2. EXISTING S.E. AND S.E. TRANSITIONS SHALL BE MAINTAINED UNLESS OTHERWISE SHOWN ON THE PLANS.
- MILLING TO THE BOTTOM OF WHEEL RUTS SHALL NOT BE NECESSARY UNLESS REQUIRED TO OBTAIN SLOPE OR THE DESIGN DEPTH AT CENTERLINES.
- 4. THE AVERAGE DEPTH OF MILLING IS ESTIMATED TO BE $\frac{1}{2}$ " BUT MAY VARY IN ISOLATED LOCATIONS.

HOT-MIX ASPHALT SURFACE REMOVAL (VARIABLE DEPTH) DETAIL

FIL	E NAME =	USER NAME = steffenmk	DESIGNED -	REVISED -		SN 070-0037 Details				F.A.P	SECTION	COUNTY	TOTAL SHEE	ĒT	
0:/	.projects\74183d\shtdet_74183.dgn		DRAWN	REVISED -	STATE OF ILLINOIS				770	(116R1)B-1 (116RR1)BR	MOULTRIE		<u>"</u>		
- 1		PLOT SCALE = 20.00000 '/ IN.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION						TISONO INTOCKATOR	CONTRACT NO. 74183			
		PLOT DATE = 8/19/2008	DATE -	REVISED ~		SCALE:	SHEET NO. OF	SHEETS	STA.	TO STA.	FED. RO	AD DIST. NO. ILLINOIS FED.	AID PROJECT		\exists