

€ 1'4" ¢ Hole

<u>SIDE RETAINER</u>

Equivalent rolled angle with stiffeners will be allowed in lieu of welded plates. Cost included with, Bearing Assembly, Type-I Elastomeric.



EXPANSION BEARING (EAST ABUTMENT)



Notes:

Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.

Anchor bolts at fixed bearings may be either cast in place or installed in holes drilled after the supported member is in place.

Anchor bolts for side retainers may be cast in place or installed in holes drilled before or after members are in place.

Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications.

Side retainers and other steel members required for the bearing assembly shall be included in the cost of

Elastomeric Bearing Assembly, Type I. The structural steel plates of the Bearing Assembly

shall conform to the requirements of AASHTO M 270 Grade 50.

2"-3/4" H.S. Bolts w/lock washers (Typ. Ea. End)







BILL OF MATERIAL

Item	Unit	Total
Elastomeric Bearing Assembly Type I	Each	6
Anchor Bolts, 1"	Each	24





SECTION C-C

BEARINGS STRUCTURE NO. 083-0063

EET NO.13	F.A.S. RTE.	SECTION		COUNTY	TOTAL SHEETS	SHEET NO.			
	2881	301	3-1	SALINE	45	27			
9 SHEETS	RALEIGH I	RD. OVER ELDORADO P	CONTRACT	NO. 98533					
· · · ·									