

| CLASS B PAVEMENT PATCHING 16 INCH SCHEDULE | | | | | | | | | | | |
|--|---------|--------|------------|----------------------|-----------------------|------------------------|-----------------------|--------------------------|----------|-----------------|--------|
| LOCATION | LANE | LENGTH | LANE WIDTH | CLASS B PATCH TYPE I | CLASS B PATCH TYPE II | CLASS B PATCH TYPE III | CLASS B PATCH TYPE IV | DOWEL BARS 1 1/2 Inch | TIE BARS | PAVEMENT FABRIC | SAWCUT |
| | | (FT) | (FT) | (SQ YD) | (SQ YD) | (SQ YD) | (SQ YD) | (EACH) | (EACH) | (SQ YD) | (FT) |
| IL 15 WB | INSIDE | 6.0 | 12.0 | | 8.0 | | | 20 | | | 48.0 |
| IL 15 WB | OUTSIDE | 8.0 | 12.0 | | 10.7 | | | 20 | | | 52.0 |
| IL 15 WB | MIDDLE | 10.0 | 12.0 | | 13.3 | | | 20 | | | 56.0 |
| IL 15 WB | INSIDE | 14.0 | 12.0 | | | 18.7 | | 20 | | 18.7 | 64.0 |
| IL 15 WB | OUTSIDE | 20.0 | 12.0 | | | | 26.7 | 20 | 9 | 26.7 | 76.0 |
| RAMP | | 6.0 | 14.0 | | 9.3 | | | 24 | | | 54.0 |
| RAMP | | 6.0 | 16.0 | | 10.7 | | | 28 | | | 60.0 |
| SHOULDER | INSIDE | 6.0 | 6.0 | | | | | 20 | | | 30.0 |
| SHOULDER | OUTSIDE | 6.0 | 8.0 | | | | | 20 | | | 36.0 |
| SHOULDER | OUTSIDE | 6.0 | 10.0 | | 6.7 | | | 20 | | | 42.0 |
| SUBTOTAL: | | | | | 58.7 | 18.7 | 26.7 | 212 | 9 | 45.3 | 518.0 |
| ANTICIPATED FAILURES (15%): | | | | | 8.8 | 2.8 | 4.0 | 32 | 2 | 6.8 | 77.7 |
| TOTAL: | | | | | 67 | 21 | 31 | 244 | 11 | 52 | 596 |

PATCHING CAN BE USED THROUGHOUT THE PROJECT LIMITS AS NEEDED AND AS DIRECTED BY THE RESIDENT ENGINEER.