

GENERAL NOTES

14 (356) min. for 7 (178) opening

Frame and grate

12(300)

min.

bars 7

(150)

8 (200)

(See General Notes)

- 1. Inlet construction shall be in accordance with Section 602 of the Standard Specifications.
- Combination Concrete Curb & Gutter shall be constructed in accordance with Section 606 of the Standard Specifications.
- 3. See District CADD Standard 604001-D4 for frame and grates.

Set frame level and at elevation of edge of pavement at the intersection of \mathbb{C} of inlet frame.

Grate type- 12 (300)

Pavement

thickness

#4 (#15) bars

sand cushion

停 6 (150)

see plans

¾ (20) Mortar

30 (750)

ELEVATION SIDE

> All dimensions are in inches (millimeters) unless otherwise noted.

01-01-97 RENUM. B-4.01, NEW REVISION BOX SECTION COUNTY STATE OF ILLINOIS INLETS, TYPE G-1 10-99 REVISION TO GENERAL NOTES J.A. 7W-1, RS-3 PEORIA 617 354 1380 02-00 REVISION TO DESIGNER NOTES J.A. **DEPARTMENT OF TRANSPORTATION** CONTRACT NO. 88792 10-16-06 REVISED TO 2007 SPEC. NOT TO SCALE CADD STD. 602001-D4 FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT