



STATION 746+00 TO STATION 751+80

TYPICAL SECTION LEGEND

- 1 TOPSOIL FURNISH AND PLACE, 4", SEEDING CLASS 4
- 2 SUB-BASE GRANULAR MATERIAL, TYPE B 8"
- 3 BITUMINOUS MATERIALS (PRIME COAT)
- 4 LEVELING BINDER (MACHINE METHOD), N50 1 1/2"
- 5 HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N50 1 1/2"
- 6 EXISTING SHOULDER REMOVAL, AGGREGATE SHOULDERS, TYPE B 6"

- NOTES:**
- 1 SEE DETAILS FOR SUPERELEVATION TRANSITION LAYOUT FOR CURVES.
 - 2 EXISTING SHOULDER REMOVAL SHALL BE PAID FOR AS EARTH EXCAVATION.
 - 3 SEE STATION CROSS SECTIONS. 5.00' MINIMUM

MIXTURE REQUIREMENTS

| LOCATION | U.S. ROUTE 66 BIKEWAY | U.S. ROUTE 66 BIKEWAY |
|---|-----------------------|-----------------------|
| MIXTURE USE (S): | SURFACE COURSE | LEVELING BINDER |
| AC/PG: | PG 64-22 | PG 64-22 |
| RAP % (MAX): | 15% | 25% |
| DESIGN AIR VOIDS: | 4.0% @ N DESIGN = 50 | 4.0% @ N DESIGN = 50 |
| MIXTURE COMPOSITION (GRADATION MIXTURE) | IL 9.5 | IL 9.5 |
| FRICTION AGGREGATE | MIX "C" | MIX "C" |