

 ROUTE
 SECTION
 COUNTY
 TOTAL SHEETS NC

 T.R. 186A
 05-10127-00-BR
 JASPER
 15
 5

 CONTRACT NO. 95620
 ILLINOIS
 PROJECT BROS-079(140)

GENERAL NOTES

- 1. The Contractor shall drive test pile(s) to 110% of the nominal required bearing specified in production locations at North abutment or approved by the Engineer before ordering the remainder of piles.
- 2. See Bridge Plan Sheet 8 for boring logs.
- 3. A Corrosion inhibitor, as covered in the Special Provisions, shall be used in the concrete for precast prestressed concrete deck beams.
- 4. Concrete sealer shall be applied to exterior face of each fascia beam.
- 5. Reinforcement bars shall conform to the requirements of AASHTO M31 or M322 Grade 60.
- 6. The Steel H-piles shall be according to AASHTO M270 Grade 50.
- 7. Reinforcement bars shall conform to the requirements of ASTM A 706 Fr 60 (IL Modified). See Special Provisions.
- 8. Reinforcement bars designated (E) shall be epoxy coated.
- 9. Layout of the slope protection system may be varied to suit ground conditions in the field as directed by the Engineer.

TOTAL BILL OF MATERIAL

ltem	Unit	Super	Sı	Total	
			Piers	Abuts.	. 5 (0)
Removal of Existing Structures	Each	_		-	1
Concrete Structures	Cu. Yd.	_		26.4	26.4
Precast Prestressed Concrete Deck Beams (33" Depth)	Sq. Ft.	2025		_	2025
Steel Railing, Type S-1	Foot	150	-	_	150
Reinforcement Bars, Epoxy Coated	Pound	_		3000	3000
Furnishing Steel Piles HP 12x53	Foot	-	_	187.5	187.5
Setting Piles in Rock	Each		_	5	5
Driving Piles	Foot	_		120	120
Test Pile Steel HP 12x53	Each	-	_	1	1
Name Plates	Each	_		1	1
Concrete Encasement	Cu. Yd.			8.5	8.5
Aggregate Base Course, Type B	Tons	-	_	85	85
Stone Dumped Riprap, Class A4	Tons		_	180	180
Channel Excavation	Cu. Yd.		-	240	240

I certify that to the best of knowledge, information and belief, this bridge design is structurally adequate for the design loading shown on the plans. The design is an economical one for the style of structure and complies with requirements of the current AASHTO Standard Specifications for Highway Bridges.



CHARLESTON ENGINEERING, INC.
CONSULTING ENGINEERS

105 NORTH KITCHELL P.O. BOX 397 OLNEY, ILLINOIS 62450 (618) 392-0736

GENERAL PLAN & ELEVATION

STRUCTURE NO. 040-3260 T.R. 186A OVER BRUSH CREEK

SECTION 05-10127-00-BR JASPER COUNTY STATION 5+14.25

2007 AASHTO LRFD B Design Specifications SEISMIC DATA BRUSH CREEK SEC. 05-10127-00-BR BUILT 201_ WADE ROAD DISTRICT JASPER COUNTY LOADING HI - 93

LOADING HL-93 STR. NO. 040-3260

LETTERING FOR NAME PLATE

Locate Name Plate at S.E. Corner of Bridge (See Std. 515001)

PILE DATA (SOUTH ABUT.)

Design Spectral Acceleration at 1.0 sec. $(S_{D1}) = 0.220g$

Design Spectral Acceleration at 0.2 sec. $(S_{DS}) = 0.500g$

Seismic Performance Zone (SPZ) = 2

Soil Site Class = D

Type	HP 12 X 53
Nominal Required Bearing	Set in Rock
Factored Resistance Available	170 kips
Estimated Pile Length	13.5 Feet
Number of Production Piles	5
Number of Test Piles	Ō
Estimated Top of Rock Elevation	465.00
Rock Socket Depth	5.0 Feet
Rock Socket Diameter	2.0 Feet

PILE DATA (NORTH ABUT.)

TIEL DITTIN (HORTH	71001.7
Type Nominal Required Bearing Factored Resistance Available Estimated Pile Length Number of Production Piles Number of Test Piles	HP 12 X 53 419 kips

LOCATION SKETCH

R. 10 E

WATERWAY INFORMATION

Superstructure

7. Pile Details

8. Boring Logs

Superstructure Details

6. North Abutment Details

Steel Railing, Type S-1

South Abutment Details

Drainage Area = 11.0 SQ MI Low Grade Elev = 472.2 © Sta. 7+55									
Flood	Freq.	Q.	Opening Sq. Ft.		Nat.	Head	– Ft.	Headwater El.	
F1000	Yr.	C.F.S.	Exist.	Prop.	H.W.E.	Exist.	Prop.	Exist.	Prop.
Design	15	2380	317	426	471.2	0.6	0.0	471.8	471.2
Base	100	4140	390	656	474.9	0.3	0.2	475.2	475.1
Overtopping									
Max. Calc.	500								