NOTES

SEE STANDARD 602701 FOR DETAILS OF STEPS.

EXCEPT AS NOTED HEREON INLET SPECIAL SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.

THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTED SECTIONS.

ALL VOIDS AROUND PIPE ENTRANCE. BOTH INSIDE AND OUTSIDE, SHALL BE SEALED WITH MORTAR.


WEIGHT OF CAST IRON FRAME & GRATE = 530 lbs. \pm . STEPS SHALL BE OMITTED WHEN DEPTH OF "H" IS LESS THAN 5 ft.

DETAIL OF FRAME & GRATE

NOTES


CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT, PRECAST CONCRETE SHALL BE IN ACCORDANCE WITH SECTION 504.01 THRU 504.05 OF THE STANDARD SPECIFICATIONS EXCEPT THAT CONCRETE STRENGTH SHALL BE 4.000 psi AFTER 28 DAYS.


THE CONTRACT UNIT PRICE EACH FOR INLET SPECIAL SHALL INCLUDE THE COST OF CONSTRUCTING THE INLET BOX, FURNISHING AND INSTALLING THE FRAME AND GRATE, THE CAST IRON STEPS (IF USED), THE PRECAST FLOOR SLABS. SAND CUSHION (WHEN USED) AND REINFORCEMENT BARS.




PLAN OF GRATE *

* THIS GRAYE TO BE USED WITHOUT CURB BOX WHEN INLET IS IN DRIVEWAY.





ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.



SEC. A-A

NOTES

SEE STANDARD 602701 FOR DETAILS OF STEPS.


SEC. B-B

EXCEPT AS NOTED HEREON DOUBLE INLET SPECIAL SHALL BE CONSTRUCTED IN ACCORDANCE WITH SECTION 602 OF THE STANDARD SPECIFICATIONS.

THE SIDE WALLS MAY BE BUILT AS PRECAST SEGMENTED SECTIONS.

ALL VOIDS AROUND PIPE ENTRANCE, BOTH INSIDE AND OUTSIDE, SHALL BE SEALED WITH MORTAR.

R-3295-2 DOUBLE UNIT STEPS SHALL BE OMITTED WHEN DEPTH OF "H" IS LESS THAN 5 FOOT.



SECTION B-B

DETAIL OF FRAME & GRATE

NOTES

REVISED - 10:13-11

SCALE

REVISED -


REVISED -

CLASS SI CONCRETE OR PRECAST CONCRETE SHALL BE USED THROUGHOUT, PRECAST CONCRETE SHALL BE IN ACCORDANCE WITH SECTION 504.01 THRU 504.05 OF THE STANDARD SPECIFICATIONS EXCEPT THAT CONCRETE STRENGTH SHALL BE 4,000 psi AFTER 28 DAYS. DOLIBLE

THE CONTRACT UNIT PRICE EACH FOR INLET SPECIAL SHALL INCLUDE THE COST OF CONSTRUCTING THE INLET BOX. FURNISHING AND INSTALLING THE FRAME AND CRATE. THE CAST IRON STEPS (IF USED), THE PRECAST FLOOR SLABS. SAND CUSHION (WHEN USED) AND REINFORCEMENT BARS.

REGION 2 / DISTRICT 2 STANDARD

SHEET NO. __ OF ___ SHEETS STA.



SECTION A-A

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE NOTED.

TOTAL SHEET SHEETS NO. COUNTY WINNEBAGO 327 321 CONTRACT NO. 64750 303

REVISED - 10-13-11

INLET SPECIAL

REVISED -OT DATE * Mon Dec 17 16:33:35 2012

or\pw.work\pwidpt\dosedd\dme67949\D26475@-eht-detaris-(pge311-327).dgr

DOUBLE INLET, SPECIAL