INDEX OF SHEETS

LIST OF STATE STANDARDS

SHEET	NO.	<u>DESCRIPTION</u> <u>STAN</u>	NDARD NO. DESCRIPTION
	1	COVER SHEET	
	2	INDEX OF SHEETS, STANDARDS, AND GENERAL NOTES	000001-06 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
	3-4	SUMMARY OF QUANTITIES	280001-05 TEMPORARY EROSION CONTROL SYSTEMS
	5	TYPICAL SECTIONS PLANS	424001-05 CURB RAMPS FOR SIDEWALKS
	6	ALIGNMENT, TIES & BENCHMARKS PLAN	601001-04 CONCRETE CURB TYPE B & COMBINATION CONCRETE CURB AND GUTTER
	. 7.	EXISTING & PROPOSED ROADWAY PLAN	601101-0/ SUB-SURFACE DRAINS
	8	EROSION CONTROL PLAN	602001-02 CATCH BASIN, TYPE A
	9	EXISTING & PROPOSED DRAINAGE PLAN	602011-02 CATCH BASIN, TYPE C
	10	EXISTING AND PROPOSED DRAINAGE PROFILES	604001-03 FRAME AND LIDS, TYPE 1
	11	SUE SURVEY PLAN	604091 <i>-02</i> FRAME AND GRATE, TYPE 24
	12	PLAT OF HIGHWAYS	701301-04 LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
	13	PROPOSED PAVEMENT MARKING PLAN & LANDSCAPING PLAN	701311-03 LANE CLOSURE, 2L, 2W SLOW, MOVING OPERATIONS- DAY ONLY,
	14-26	PROPOSED TRAFFIC SIGNAL PLANS	701326-04 LANE CLOSURE, 2L, 2W, PAVEMENT WIDENING, FOR SPEEDS > 45 MPH
* . *,	27	DRIVEWAY DETAILS DISTANCE BETWEEN R.O.W. AND FACE OF CURB & EDGE OF	701601-07 URBAN LANE CLOSURE, MULTILANE, 1W OR 2W WITH NONTRAVERSABLE MEDIAN
		SHOULDER >= 15' (4.5 m)	701701-07 URBAN LANE CLOSURE, MULTILANE INTERSECTION
	28	DRIVEWAY DETAILS DISTANCE BETWEEN R.O.W. AND FACE OF CURB < 15' (4.5 m)	701801-04 LANE CLOSURE, MULTILANE 1W OR 2W CROSSWALK OR SIDEWALK CLOSURE
	29	OUTLET FOR CONCRETE CURB & GUTTER	701901-01 TRAFFIC CONTROL DEVICES
	30	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING	886001-0/ DETECTOR LOOP INSTALLATION
	31	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT	886006-01 TYPICAL LAYOUT FOR DETECTOR LOOPS
	32	BUTT JOINT AND HMA TAPER DETAILS	
	33	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND, DRIVEWAYS	
	34	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT	
	35	DISTRICT ONE TYPICAL PAVEMENT MARKINGS	
	36	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)	
	37	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING	
	38",	ARTERIAL ROAD INFORMATION SIGN	
	39-41	CROSS SECTION PLANS	

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES. (48 HOUR NOTIFICATION IS REQUIRED).

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE VILLAGES OF STREAMWOOD AND HANOVER PARK

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES (40 MM) WHERE THE SPEED LIMIT IS 45 MPH (45 KM/H) OR LESS AND 1 INCH WHERE THE SPEED LIMIT IS GREATER THAN 45 MPH (45 KM/H). WITH WRITTEN APPROVAL FROM THE ENGINEER. A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MR. WALTER CZARNY AREA TRAFFIC FIELD ENGINEER AT (847) 715-8419 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

THE RESIDENT ENGINEER SHALL VERIFY ALL EXISTING PAVEMENT MARKINGS BEFORE MILLING

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS

THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847)705-4470
A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.

THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROPERTY AT ALL TIMES DURING THE CONSTRUCTION OF THIS PROJECT.

PRIOR TO EMBANKMENT PLACEMENT, ALL VEGETATION, LOOSE MATERIAL, AND UNSTABLE MATERIAL SHOUL BE REMOVED TO DEPTH ENCOUNTERED AND REPLACED WITH SUITABLE EMBANKMENT MATERIAL. ANY EMBANKMENT WIDENING ON EXISTING SLOPES SHOULD BE BENCHED IN ACCORDANCE WITH ARTICLE 205.04 OF THE STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.

ILE NAME =	USER NAME = guillaumefp	DESIGNED ~	REVISED -
:\pw_work\pwidot\guillaumefp\dms93544\R	133508-Design.dgn	DRAWN -	REVISED -
-	PLOT SCALE = 50.0000 '/ IN.	CHECKED -	REVISED ~
	PLOT DATE = 12/16/2010	DATE -	REVISED -