## TRAFFIC SIGNAL LEGEND

ITEM	REMOVAL	EXISTING	PROPOSED	<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	R			EMERGENCY VEHICLE LIGHT DETECTOR	R	<u>~</u>	•	ELECTRIC CABLE IN CONDUIT, TRACER,			
RAILROAD CONTROL CABINET		n n		CONFIRMATION BEACON	Ro-O	0()	•	NO. 14 1/C, UNLESS NOTED OTHERWISE			
COMMUNICATIONS CABINET	C C	ECC	cc	HANDHOLE	R □			COAXIAL CABLE			—c—
MASTER CONTROLLER		EMC	MC	HANDIOLL						~/	
MASTER MASTER CONTROLLER	R	EMMC	MMC	HEAVY DUTY HANDHOLE	R	H		VENDOR CABLE FOR CAMERA			
JNINTERRUPTIBLE POWER SUPPLY	UPS	EUPS	UPS	DOUBLE HANDHOLE	R O		0	COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED		<u> </u>	<u>—6</u> —
SERVICE INSTALLATION, P) POLE OR (G) GROUND MOUNT	-C-R	- <u></u> P	- <b>B</b>	JUNCTION BOX  GALVANIZED STEEL CONDUIT		W	Ų	FIBER OPTIC CABLE		—(2F)—	
ELEPHONE CONNECTION P) POLE OR (G) GROUND MOUNT	R	P	P	IN TRENCH (T) OR PUSHED (P)				NO. 62.5/125, MM12F  FIBER OPTIC CABLE		— <u>(24</u> F)—	
TEEL MAST ARM ASSEMBLY AND POLE	R <sub>O</sub>	0	•	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	_R			NO. 62.5/125, MM12F SM12F		— <u>(24</u> )—	—(24F)—
LUMINUM MAST ARM ASSEMBLY AND POLE	R			COMMON TRENCH			СТ	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE			——
TEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH LUMINAIRE	R <sub>O</sub> ->  →  —	O-X	•*	COILABLE NONMETALLIC CONDUIT (EMPTY)			CNC	NOTED ON PLANS)		<b>&gt;</b>	
TEEL COMBINATION MAST ARM	R	O	•	SYSTEM ITEM		S	S	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM,		C 11	C <sub>I</sub> II
SSEMBLY AND POLE WITH PTZ CAMERA	PIZH	PZ	PZ	INTERSECTION ITEM		I	ΙP	OR (S) SERVICE	5.05	·	·
IGNAL POST	R <sub>O</sub>	0	•	REMOVE ITEM RELOCATE ITEM	R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
EMPORARY WOOD POLE (CLASS 5 OR BETTER) 45 FOOT (13.7m) MINIMUM	$\overset{R}{\otimes}$	$\otimes$	•	ABANDON ITEM	Λ			STEEL MAST ARM POLE AND	RMF		
UY WIRE	R	>	>-	12" (300mm) TRAFFIC SIGNAL SECTION	7	(R)	R	FOUNDATION TO BE REMOVED	<u> </u>		
GNAL HEAD	R >	>	****	12// /700mm) PER WITH 0// /000			L	ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
GNAL HEAD CONSTRUCTION STAGES UMBERS INDICATE THE CONSTRUCTION STAGE)			2	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF		
GNAL HEAD WITH BACKPLATE	+C^R	+!>	+			(R)	R	FOUNDATION TO BE REMOVED	- / .		
GNAL HEAD OPTICALLY PROGRAMMED	-R ->"P"	-D''P''	- <b>▶</b> ′′P′′	SIGNAL FACE			G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF O		
ASHER INSTALLATION DENOTES SOLAR POWER)	R O-⊠"F"	O-t>″F″	•"F"			<b>₹</b> ?	<b>∢</b> Y <b>∢</b> G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		IS	IS
DESTRIAN SIGNAL HEAD	R -	-0	-			(R)	R	SAMPLING (SYSTEM) DETECTOR			S
EDESTRIAN PUSHBUTTON DETECTOR	R	<b>©</b>	<b>©</b>	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD			Y	EXISTING INTERSECTION LOOP DETECTOR		[F]	
CESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R APS	@APS				( Y )	<b>♦</b> Y <b>♦</b> G	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT(	DR .	L'_!	
LUMINATED SIGN NO LEFT TURN''	R	0	•			"P"	"P"	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT(	)R	PPI	
LUMINATED SIGN	D		٧	12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		(W)		PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		PIS	PIS
IO RIGHT TURN"		8		12" (300mm) PEDESTRIAN SIGNAL HEAD				PREFORMED SAMPLING (SYSTEM) DETECTOR		[PS]	PS
TECTOR LOOP, TYPE I				INTERNATIONAL SYMBOL, OUTLINED			·			1, -1	1 9
REFORMED DETECTOR LOOP		 	Р	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID		<b>(A)</b>	*	RAILROAD SYMBOLS			
CROWAVE VEHICLE SENSOR	R M)1		M	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		C C	<b>₽</b> C <b>*</b> D			EXISTING	PROPOSED
DEO DETECTION CAMERA	R Vþ		<b>V</b>	RADIO INTERCONNECT	<del>    R</del> O	##**	<del>   </del>  ••	RAILROAD CONTROL CABINET		R R	PAR
DEO DETECTION ZONE								RAILROAD CANTILEVER MAST ARM	Ž	XOX X	XOX X X
N, TILT, ZOOM CAMERA	R PTZ[1]	PZ)1	PTZ <b>M</b>	RADIO REPEATER  DENOTES NUMBER OF CONDUCTORS, ELECTRIC	R ERR	ERR	RR	FLASHING SIGNAL		<del>\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\</del>	<b>X</b> ⊕ <b>X</b>
IRELESS DETECTOR SENSOR	R(W)	(W)	(W)	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED				CROSSING GATE		<del>X0</del> <del>X</del> >	X-X-
IRELESS ACCESS POINT	R D			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		(1)		CROSSBUCK		*	*
NAME = USER NAME = kanthaphixay w_work\PWIDOT\KANTHAPHIXAYBC\ddil26 4\traffic_legend_v7.dgn		IGNED - DAG/BCK WN - BCK	REVISED REVISED	- STATE		,		DISTRICT 1	F.A. RTE.	SECTION	COUNTY TOTAL SHEETS