




MODEL: Default
FILE NAME: p:\3\hbmeng-pw-bentley.com\hbmeng-pw-01\Documents\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_NB\016-0161-62K53-017-WB-NorthAbutmentRepair.dgn

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Concrete Sealer	Sq Ft	471
Structural Repair Of Concrete (Depth Equal to or Less Than 5 Inches)	Sq Ft	13
Structural Repair Of Concrete (Depth Greater Than 5 Inches)	Sq Ft	9



NORTH ABUTMENT PLAN



NORTH ABUTMENT ELEVATION

(Looking North)

NOTES:

- Quantities and limits shown are estimated for bidding purpose only. The actual areas to be repaired and the type(s) of repairs to be used will be determined by the engineer in the field at the time of construction.
- For slope wall repairs, see sheet S05-20.
- Concrete Sealer is to be applied to the abutment seats and the bottom 2 feet of the abutment backwall.

LEGEND



Structural Repair of Concrete (Depth Equal to or Greater than 5 inches)



Structural Repair of Concrete (Depth Equal to or Less than 5 inches)

SF

Square Foot



USER NAME = imranh	DESIGNED - SUR	REVISED -
	DRAWN - ME	REVISED -
PLOT SCALE = 5/4" = 1/4"	CHECKED - JL	REVISED -
PLOT DATE = 12/9/2024	DATE - 12/6/2024	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

NORTH ABUTMENT REPAIRS
STRUCTURE NO. 016-0161 (WB)

SHEET S05-17 OF S05-27 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	601
CONTRACT NO. 62W87				
ILLINOIS		FED. AID PROJECT		


MODEL: Default
FILE NAME: pw:\bhmeng-pw.bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_NB\016-0161-62K53-018-WB-Pier1.dgn



BILL OF MATERIAL		
ITEM	UNIT	QUANTITY
Epoxy Crack Injection	Foot	15
Structural Repair Of Concrete (Depth Equal to or Less Than 5 Inches)	Sq Ft	17


LEGEND

 Structural Repair of Concrete
(Depth Equal to or Less than 5 inches)

 Epoxy Crack Injection

LF Linear Foot

SF Square Foot



- NOTE:**
- Quantities and limits shown are estimated for bidding purpose only. The actual areas to be repaired and the type(s) of repairs to be used will be determined by the engineer in the field at the time of construction.



USER NAME = imranh	DESIGNED - SUR	REVISED -
	DRAWN - ME	REVISED -
PLOT SCALE = 8:0.0000 " = 1 in.	CHECKED - JL	REVISED -
PLOT DATE = 12/9/2024	DATE - 12/6/2024	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PIER 1 REPAIRS
STRUCTURE NO. 016-0161 (WB)

SHEET S05-18 OF S05-27 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	602
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				


MODEL: Default
FILE NAME: pw:\bimeng-pw.bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_NB\016-0161-62K53-019-WB-Pier2.dgn



BILL OF MATERIAL		
ITEM	UNIT	QUANTITY
Epoxy Crack Injection	Foot	22
Structural Repair Of Concrete (Depth Equal to or Less Than 5 Inches)	Sq Ft	31


LEGEND

 Structural Repair of Concrete
(Depth Equal to or Less than 5 inches)

 Epoxy Crack Injection

LF Linear Foot

SF Square Foot



NOTE:

- Quantities and limits shown are estimated for bidding purpose only. The actual areas to be repaired and the type(s) of repairs to be used will be determined by the engineer in the field at the time of construction.



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	8:0.0000 " = 1 in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PIER 2 REPAIRS
STRUCTURE NO. 016-0161 (WB)


SHEET S05-19 OF S05-27 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	603
CONTRACT NO.				62W87
ILLINOIS		FED. AID PROJECT		

MODEL: Default
FILE NAME: p:\3\hbmeng-pw.bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_NB\016-0161-62K53-020-WB-SlopeWall.dgn



NORTH ABUTMENT SLOPE WALL PLAN



SOUTH ABUTMENT SLOPE WALL PLAN

BILL OF MATERIAL NORTH SLOPE WALL


ITEM	UNIT	QUANTITY
Slope Wall Crack Sealing	LF	42

BILL OF MATERIAL SOUTH SLOPE WALL

ITEM	UNIT	QUANTITY
Porous Granular Embankment	Cu Yd	10
Slope Wall Removal	Sq Yd	29
Slope Wall 4 Inch	Sq Yd	29
Slope Wall Crack Sealing	Foot	97

LEGEND

 Slope Wall Removal and Replacement with 4 inch Slope Wall

 Slope Wall Crack Sealing

LF Linear Foot

SF Square Foot

NOTES:

- Quantities and limits shown are estimated for bidding purposes only. The actual areas to be repaired, and the type(s) of repairs to be used, will be determined by the engineer in the field at the time of construction.
- Slope wall shall be reinforced with welded wire fabric, 6 in. x 6 in. W40 x W40, weighing 58 lbs. per 100 sq. ft.



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	14:8,0000 " = 1" / in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SLOPE WALL REPAIRS
STRUCTURE NO. 016-0161 (WB)

SHEET S05-20 OF S05-27 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	604
CONTRACT NO. 62W87				
		ILLINOIS	FED. AID PROJECT	

MODEL: Default
FILE NAME: p:\3\hbmeng-pw.bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_NB\016-0161-62K53-021-WB-BarSplicers.dgn




STANDARD BAR SPLICER ASSEMBLY PLAN

Only bar splicer assemblies as presented on the approved QPL list may be used.

Threaded splicer bar length = min. lap length + 1 1/2" + thread length

* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies required	Minimum lap length
N. Abut.	#5	10	3'-6"
N. Abut.	#6	6	4'-10"
S. Abut.	#5	10	3'-6"
S. Abut.	#6	6	4'-10"




INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.

"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required

NOTES:

- Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.
- All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.
- See approved list of bar splicer assemblies and mechanical splicers for alternatives.

BSD-1

05-15-2023



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	0:2,0000 " = 1" / in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BAR SPLICER ASSEMBLY & MECHANICAL SPLICER DETAILS
STRUCTURE NO. 016-0161 (WB)


SHEET S05-21 OF S05-27 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	605
CONTRACT NO. 62W87				
		ILLINOIS	FED. AID PROJECT	

Bench Mark:
Chiseled square cut in Northeast corner of concrete
end for steel guard rail in Southwest corner of
I-94 deck over Dalton Ave. El. 606.69
Existing Structure
I-beam bridge over Dalton Ave. 2 Spans @ 49.8' ±
1 Span @ 63.95'. Concrete deck and Steel Handrail
to be Removed in Stages. No Salvage.



PLAN



ELEVATION
(Looking East)

For Informational Purposes Only

APPROVED
FOR STRUCTURAL ADEQUACY ONLY

Robert E. Anderson
Engineer of Bridges and Structures



Sandor Ferenczi Date 8/16/90
Exp. Date 11/30/92

PROPOSED PROFILE I-94

PROPOSED PROFILE-DOLTON AVE.

016-0161

*42 (VB-10, 12, HB-14, B11) & 0707.1HB (R-3) 90

DATE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
1-94	*	COOK	318	255
SHT. 51 OF 525				

GENERAL NOTES:

DESIGN SPECIFICATIONS:
A.A.S.H.T.O. 1983 Standard Specifications for Highway
Bridges, and 1984 thru 1988 Interims.
1983 Guide specifications for Seismic Design of Highway
Bridges with 1985 and 1988 Interim Specifications.


DESIGN CRITERIA:
Service Load Design, Load Factor for Deck
Live Load: HS 20-44 & A1.

Allow 25 psf for Future Wearing Surface
DESIGN STRESSES
Existing Structural Steel
fs = 18,000 psi, ASTM A7 & fs = 20,000,
ASTM A36 (M183 Steel Beam 16 Repair)
Proposed Structural Steel
fs = 20,000 psi (M183 Steel)
Reinforced Concrete
fc = 3500 psi - Superstructure Composite Deck Slab
fc = 1400 psi - Substructure
fc = 1000 psi with earth pressure
n = 9


REINFORCEMENT:
fy = 60,000 psi - Superstructure
fs = 24,000 psi - Substructure

TRAFFIC:
All barricades, signs and other traffic control
devices and their placement installed for the
purpose of temporarily maintaining traffic during
construction shall be in full compliance with
the Illinois State Manual on Uniform Traffic
Control Devices otherwise noted.
The Contractor shall procure, install and remove
all temporary pavement markings as per the
traffic phasing shown on the plans or as directed
by the Engineer. See Roadway Plans.

Indicates Removal of Existing Concrete Deck Slab.
Indicates Boring Locations.
Note:
A. Limits of Porous Granular
Embankment (Typ. both Abutments).
Place at 45°.



LOCATION MAP



SECTION A-A

STATION 6+93.11
RE-BUILT BY
STATE OF ILLINOIS
PROJECT ACTM-PCBHI-94-
3 (307) 70
LOADING HS 20 & ALT.
STR. No. 016-0161

NAME PLATE
See Standard 2113

STAGE III - S.B. MAINLINE CONSTRUCTION				
STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION PLAN AND ELEVATION I-94 OVER DOLTON AVE. COOK COUNTY STA. 206+93.10 S.N. 016-0161 SCALE DATE: NOV. 1991 DRAWN BY KCB:IMG CHECKED BY LM S.B.M.-III-1 of 21				

MODEL: Default
FILE NAME: pw:\bentley-pw-bentley.com\hbmeng-pw-01\Documents\22002207-90904-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_NB\016-0161-62K53-022-WB-Existing Plans (Sheet 1 of 6).dgn
12/9/2024 2:53:19 PM




USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
DRAWN -	ME	REVISOR -		REVISOR -	
PLOT SCALE =	0:2,000" = 1 in.	CHECKED -	JL	REVISOR -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISOR -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


EXISTING PLANS (SHEET 1 OF 6)
STRUCTURE NO. 016-0161 (WB)

SHEET S05-22 OF S05-27 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	606
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				



MODEL: Default
FILE NAME: pw:\bentley-pw-bentley.com\hbmeng-pw-01\Documents\22002207-90904-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_NB\016-0161-62K53-024-WB-Existing Plans (Sheet 3 of 6).dgn
12/9/2024 2:53:38 PM



MODEL: Default
FILE NAME: pw:\bentley-pw-bentley.com\hbmeng-pw-01\Documents\22002207-90904-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_NB\016-0161-62K53-025-WB-Existing Plans (Sheet 4 of 6).dgn
12/9/2024 2:53:47 PM



For Informational Purposes Only



USER NAME	=	imranh
DESIGNED	-	SUR
DRAWN	-	ME
PLOT SCALE	=	0:2,000' = 1"
CHECKED	-	JL
PLOT DATE	=	12/9/2024
DATE	=	12/6/2024

REVISED	-
REVISED	-
REVISED	-
REVISED	-

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

EXISTING PLANS (SHEET 4 OF 6)
STRUCTURE NO. 016-0161 (WB)

SHEET S05-25 OF S05-27 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	609
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

For Informational Purposes Only

MODEL: Default
FILE NAME: pw:\bentley-pw-bentley.com\hbmeng-pw-01\Documents\22002207-90904-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_NB\016-0161-62K53-026-WB-Existing Plans (Sheet 5 of 6).dgn
12/9/2024 2:53:56 PM



USER NAME = imranh
DESIGNED - SUR
DRAWN - ME
PLOT SCALE = 0:2,000" = 1 in.
CHECKED - JL
PLOT DATE = 12/9/2024
DATE = 12/6/2024

REVISD -
REVISD -
REVISD -
REVISD -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


EXISTING PLANS (SHEET 5 OF 6)
STRUCTURE NO. 016-0161 (WB)

SHEET 505-26 OF 505-27 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	610

CONTRACT NO. 62W87

ILLINOIS FED. AID PROJECT



S.B.M.-III-14 of 21




For Informational Purposes Only


Existing Structure:

The bridge was constructed in 1948 under Section 0707.1-HB. It bridge was widened in 1990 under Section 42 (VB 10, 12) and 0707.1 HB (B-Y-I-86). In 1992, the bridge was reconstructed under Section 42 (VB 10, 12, HB 14, B-11) and 0707.1 HB (R-3)90. This structure carries eight 12' lanes (four westbound & four eastbound) of I-94 over Dolton Avenue. The outer shoulder is 6' wide, and the inner shoulder is 4'-4½". The bridge has three spans (49'-9⅞", 63'-10⅞", and 49'-9⅞") and a Skew of 12°-03'-45". The abutments are pile-supported stub abutments. The bridge has reinforced concrete column piers on pile foundations with an extension at each end.

Traffic is to be maintained utilizing stage construction.



ELEVATION
(Looking East)



PLAN

NOTE:

- All stations are to the I-94 EB P.G.L. and taken from existing plans.

LOADING HS 20-44

No future wearing surface is allowed.

DESIGN SPECIFICATION


2002 AASHTO Standard Specifications for Highway Bridges, 17th Edition

EXISTING DESIGN STRESSES
(1992 RECONSTRUCTION)

f'c = 3500 psi (Superstructure)
fy = 60,000 psi (Reinforcement Superstructure)
fs = 24,000 psi (Structural Steel)


PROPOSED DESIGN STRESSES

f'c = 4,000 psi (Superstructure)
fy = 60,000 psi (Reinforcement)



Exp: 11/30/2026

Date: 12/05/2024



GENERAL PLAN AND ELEVATION
EB I-94 OVER DOLTON AVE
F.A.I. ROUTE 94
SECTION 2019 180-RS & T
COOK COUNTY
STATION: 478+72.50
S.N. 016-0161



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	20:0'"/in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

STRUCTURE NO. 016-0161 (EB)

SHEET S06-01 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	612
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: p:\3\hbmeng-pw-bentley.com\hbmeng-pw-01\Documents\22002207-90904-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62KS3-001-EB-GPE.dgn
12/9/2024 3:14:05 PM

MODEL: Default
FILE NAME: p:\3\hbmeng-pw-bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62\K53-002-EB-GenNotes.dgn

GENERAL NOTES

1. Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.
2. During repair operations the contractor shall locate and protect any utilities or facilities including but not limited to the fiber optic and/or electrical conduits, conduits under the bridge deck, under lighting, traffic signals or signs attached to the structure. This work is to be performed to the satisfaction of the engineer and will not be paid for separately, but shall be included with the contract. It will be the contractor's responsibility to restore and replace any damage utilities or facilities to the satisfaction of the engineer and the department.
3. All exposed concrete edges shall have a ¾" x 45" chamfer except where shown otherwise.
4. Protective Coat shall be applied to the top and inside face of parapets.
5. Repairs shown are based upon inspection carried out at the time of plan preparation are for bidding purposes only. Actual area to be repaired and the type(s) of repairs to be used shall be determined by the engineer in the field at the time of construction.
6. The contractor shall take the necessary precautions for the protection of passing vehicles, bicycles, and pedestrians from falling objects and/or materials until completion of work.
7. Where underpass lighting is present on the structure, the Contractor shall adjust the Protective Shielding to ride above the existing lighting fixtures in order to maintain the existing level of lighting on the roadway underneath. Details shall be approved by the Engineer before installation.
8. Any adjustment done to the Protective Shield System must not change the load carrying capacity (or containment specifications) as indicated in the Standard Specifications, Cost of adjusting shielding is included in the cost of Protective Shield.
9. Concrete Sealer shall be applied to the designated areas of the abutments.
10. Prior to the application of the Concrete Sealer, the Contractor shall clean all existing debris from the abutment seats. The method of debris removal shall not damage the existing concrete and shall be approved by the Engineer. See Special provision for Debris Removal.
11. Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose detrimental foreign material shall be removed from the surfaces in contact with concrete (SSPCSP3 standards). Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel and the cost will be paid for according to Article 109.04 of the Standard Specifications. As directed by the Engineer, existing construction accessories welded to the top flange of beams and girders shall be removed. The weld areas shall be ground flush and inspected for cracks using magnetic particle testing (MT) or dye penetrant testing (PT) by qualified personnel approved by the Engineer. Any cracks that cannot be removed by grinding ¼ inch deep shall be identified and reported to the Bureau of Bridges and Structures for further disposition. The cost of removing welded accessories, grinding and inspecting weld areas and grinding cracks will be paid for according to Article 109.04 of the Standard Specifications.
12. Cost of removal and re-installation of all members necessary to complete the work as detailed on the plans and as specified in the Special Provisions shall be included with Structural Steel Repairs.
13. Existing reinforcement extended into the removal area shall be cleaned, straightened and incorporated into the new construction cost is included with concrete removal. Any reinforcement bars that are damaged during concrete removal operations shall be replaced using an approved bar splicer or anchorage system at the Contractor's expense.
14. Cleaning and field painting of structural steel shall be done under a separate painting contract.
15. The Contractor is responsible to remove, support and reinstall all existing electrical conduits interfering with the work. See special provision "Protection and Maintenance of Existing Underpass Luminaires".
16. Reinforcement bars designated (E) shall be epoxy coated.

17. The Contractor is responsible to protect the existing conduit and junction box embedded in the parapet during removal and construction. Any damage to the existing conduit and junction box shall be repaired by the Contractor at no additional cost to the Department.
18. No field welding is permitted except as specified in the contract documents.
19. The Engineer shall show actual locations and size of deck repairs on As-built Plans.
20. Bars indicated thus, 3x2-#5, indicates 3 lines of #5 bars with 2 lengths of bar per line.
21. Joint openings shall be adjusted according to Article 520.04 of the Standard Specification when the deck is poured at an ambient temperature other than 50° F.
22. Existing structural steel that will be in contact with new structural steel shall be cleaned and painted prior to erection as required by the Special Provision "Cleaning and Painting Contact Surface Areas of Existing Steel Structures", and the Standard Specifications. The color of the final finish coat shall be Gray, Munsell No. 5B 7/1. Cost included with Structural Steel Repair.
23. All new structural steel shall be hot-dip galvanized. See Special Provision for "Hot Dip Galvanizing for Structural Steel".
24. Fasteners shall be ASTM F 3125 Grade A325 Type 1, mechanically galvanized bolts in painted areas. Bolts ¾ in. diameter, holes 1⅝ in. diameter, unless otherwise noted.
25. The existing structural steel coating contains lead. The Contractor shall take appropriate precautions to deal with the presence of lead on this project.

INDEX OF SHEETS

- S06-01 General Plan and Elevation
- S06-02 General Notes, Index of Sheets & TBOM
- S06-03 Stage Construction (Sheet 1 of 2)
- S06-04 Stage Construction (Sheet 2 of 2)
- S06-05 Temporary Concrete Barrier
- S06-06 Deck Repair Plan
- S06-07 S. Abut. Joint Removal & Replacement (Sht. 1 of 3)
- S06-08 S. Abut. Joint Removal & Replacement (Sht. 2 of 3)
- S06-09 S. Abut. Joint Removal & Replacement (Sht. 3 of 3)
- S06-10 N. Abut. Joint Removal & Replacement (Sht. 1 of 3)
- S06-11 N. Abut. Joint Removal & Replacement (Sht. 2 of 3)
- S06-12 N. Abut. Joint Removal & Replacement (Sht. 3 of 3)
- S06-13 Preformed Joint Strip Seal
- S06-14 Framing Plan
- S06-15 Beam Straightening Details
- S06-16 Structural Steel Repair Details
- S06-17 South Abutment Repairs
- S06-18 North Abutment Repairs
- S06-19 Pier 1 Repairs
- S06-20 Pier 2 Repairs
- S06-21 Slope Wall Repairs
- S06-22 Bar Splicer Assembly & Mechanical Splicer Details
- S06-23 Existing Plans (Sheet 1 of 6)
- S06-24 Existing Plans (Sheet 2 of 6)
- S06-25 Existing Plans (Sheet 3 of 6)
- S06-26 Existing Plans (Sheet 4 of 6)
- S06-27 Existing Plans (Sheet 5 of 6)
- S06-28 Existing Plans (Sheet 6 of 6)

SCOPE OF WORK


1. Provide Protective Shield within limits indicated on the plans.
2. Scarify ¾" from the bridge deck slab.
3. Perform Deck Slab Repairs (Partial).
4. Remove and Reconstruct Expansion joints at North and South abutments and install new Preformed Joint Strip Seals.
5. Apply ¾" Thin Polymer Overlay on Bridge Deck.
6. Refer to Roadway plans for Approach Pavement Rehabilitation.
7. Apply Protective Coat to the top of reconstructed transverse joint areas, top and inside faces of parapets.
8. Perform structural concrete repairs to abutments and piers, as noted on plans.
9. Perform structural steel repairs to beams, as noted on plans.
10. Perform Slope Wall repairs.

TOTAL BILL OF MATERIAL

ITEM	UNIT	SUPER	SUB	TOTAL
Porous Granular Embankment	Cu Yd	-	1	1
Concrete Removal	Cu Yd	18.2	-	18.2
Slope Wall Removal	Sq Yd	-	2	2
Protective Shield	Sq Yd	529	-	529
Concrete Superstructure	Cu Yd	18.2	-	18.2
Protective Coat	Sq Yd	203	-	203
Reinforcement Bars, Epoxy Coated	Pound	3,150	-	3,150
Bar Splicers	Each	32	-	32
Slope Wall 4 Inch	Sq Yd	-	2	2
Preformed Joint Strip Seal	Foot	124	-	124
Anchor Bolt, 1"	Each	1	-	1
Concrete Sealer	Sq Ft	-	928	928
Epoxy Crack Injection	Foot	-	30	30
Slope Wall Crack Sealing	Foot	-	154	154
Structural Steel Repair	Pound	190	-	190
Beam Straightening	L Sum	0.33	-	0.33
Bridge Deck Scarification ¾"	Sq Yd	1,042	-	1,042
Bridge Deck Thin Polymer Overlay ¾"	Sq Yd	1,042	-	1,042
Structural Repair of Concrete (Depth Equal to or less than 5")	Sq Ft	-	93	93
Deck Slab Repair (Partial)	Sq Yd	46	-	46

	USER NAME = imranh	DESIGNED - SUR	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	GENERAL NOTES, INDEX OF SHEETS & TBOM STRUCTURE NO. 016-0161 (EB)	F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
		DRAWN - ME	REVISED -			94	(42-B-11-1) BR, BJR 24	COOK	761	613
	PLOT SCALE = 0:2,0000 " = 1 in.	CHECKED - JL	REVISED -			CONTRACT NO. 62W87				
	PLOT DATE = 12/9/2024	DATE - 12/6/2024	REVISED -			SHEET S06-02 OF S06-28 SHEETS				
						ILLINOIS	FED. AID PROJECT			


MODEL: Default
FILE NAME: pw:\hbmeng-pw.bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62KS3-003-EB-StageConst1.dgn



STAGE I REMOVAL
(Looking North)

STAGE I REMOVAL

1. Install temporary concrete barrier as shown to locate traffic on the West side of the existing structure.
2. Perform $\frac{3}{8}$ " bridge deck scarification.
3. Remove portions of bridge concrete deck/approach slab adjacent to expansion joints at the North and South Abutments.



STAGE I CONSTRUCTION
(Looking North)

STAGE I CONSTRUCTION

1. Perform bridge deck slab repairs.
2. Reconstruct transverse expansion joints and install new preformed joint strip steals within the limits of Stage I Construction.
3. Perform Structural repair of concrete and epoxy crack injection for the abutments and piers.
4. Apply $\frac{3}{8}$ " bridge deck thin polymer overlay.
5. Refer to Roadway plans for Approach Pavement Rehabilitation.
6. Apply protective coat to top and inside faces of East parapet, and reconstructed transverse expansion joints.
7. Perform Slope Wall repairs as shown on the plans.

*Match existing cross slopes




USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	8:0" = 1" / in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

STAGE CONSTRUCTION (SHEET 1 OF 2)
STRUCTURE NO. 016-0161 (EB)


SHEET S06-03 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	614
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				







NEW SLAB OR NEW DECK BEAM




EXISTING SLAB



EXISTING DECK BEAM




RESTRAINING PIN



DETAIL II



DETAIL III



BAR SPLICER FOR #4 BAR - DETAIL III


NOTES:

1. *Cost of retainer assembly is included with Temporary Concrete Barrier.*
2. *A retainer assembly shall be located at the approximate $\frac{1}{4}$ of each temporary concrete barrier.*
3. *The retainer plate shall not be removed until the concrete on the adjacent stage is ready to be poured. For Detail III applications the retainer plate shall not be removed until just prior to placing the adjacent beam.*
4. *When the 'A' dimension is less than $1\frac{1}{2}$ " , the wood block shall be omitted and the barrier shall be placed in direct contact with the steel retainer plate. For deck beam applications the minimum required 'A' distance is 6" to accommodate the shear key clamping device.*


Detail I - Installation for a new bridge deck or bridge slab.

Detail II - Installation for a new deck beam with an initial concrete wearing surface. Additional bar splicers shall be provided at 6'-0" centers and paired with the bar splicers of the concrete wearing surface reinforcement to accommodate the installation of the retainer assemblies. The cost of the additional bar splicers is included with the concrete wearing surface.

Detail III – Installation for a new deck beam with no initial wearing surface or with an initial hot-mix asphalt (HMA) wearing surface present. The deck beam directly beneath the temporary concrete barrier shall be fabricated with bar splicer inserts in the side of the beam, as detailed, to accommodate the installation of the retainer assemblies. A pair of bar splicers, 6" apart, shall be placed at 6'-0" centers along the length of the beam. The cost of the bar splicers is included with the deck beam.



STEEL RETAINER PL 1" x 8" x "W"
(Detail I and II)



STEEL RETAINER PL 1" x "H" x 10"
(Detail III)

RAILING CRITERIA

NCHRP 350 Test Level	3
Railing Weight (plf)	440

R-27

05-15-2023


USER NAME	=	imranh	DESIGNED	=	SUR	REVISED	=	
			DRAWN	=	ME	REVISED	=	
PLOT SCALE	=	0:2.0000 " = 1" / in.	CHECKED	=	JL	REVISED	=	
PLOT DATE	=	12/9/2024	DATE	=	12/6/2024	REVISED	=	

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

TEMPORARY CONCRETE BARRIER
STRUCTURE NO. 016-0161 (EB)

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	616
		CONTRACT NO. 62W87		
ILLINOIS		FED. AID PROJECT		

MODEL: Default
FILE NAME: p:\w\hbmeng-pw-bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62KS3-006-EB-DeckPlan.dgn



NOTES:

- Areas of deck repair shown are estimated. The Engineer shall show actual locations of deck repairs at the time of construction.
- For bridge deck final cross section, See Sheet S06-04.
- For North and South Joint Removal and Replacement, See Sheets S06-07 through S06-12.
- Protective Coat shall be applied to top and inside face of parapets, and the joint areas.
- Any reinforcement bars that are damaged during concrete removal operations shall be replaced using an approved bar splicer or anchorage system. Cost incidental to Concrete Removal.
- The Contractor shall exercise extreme caution during Concrete Removal to avoid damaging the steel beams and diaphragms to remain. Any damage to the existing steel beams and/or diaphragms to remain caused by the Contractor in the performance of his/her work shall be repaired by the Contractor, to the satisfaction of the Engineer, at no cost to the Department.

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Protective Coat	Sq Yd	149
Bridge Deck Thin Polymer Overlay 3/8"	Sq Yd	1042
Bridge Deck Scarification 3/8"	Sq Yd	1042
Deck Slab Repair (Partial)	Sq Yd	46

LEGEND



Deck Slab Repair (Partial Depth)



USER NAME =	imranh	DESIGNED -	ME	REVISED -	
		DRAWN -	SUR	REVISED -	
PLOT SCALE =	18:0.0000 " : " / in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	



STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

DECK REPAIR PLAN
STRUCTURE NO. 016-0161 (EB)

SHEET S06-06 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	617
CONTRACT NO.				62W87
ILLINOIS				FED. AID PROJECT

MODEL: Default
FILE NAME: p:\3\hbmeng-pw-bentley.com\hbmeng-pw-01\Documents\22002207-90904-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62K53-007-EB-SouthAbutJoint1.dgn
12/9/2024 3:14:22 PM



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	6'0" = 1" / in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

S. ABUT. JOINT REMOVAL & REPLACEMENT (SHT. 1 OF 3)
STRUCTURE NO. 016-0161 (EB)


SHEET S06-07 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	618
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				


MODEL: Default
FILE NAME: p:\3\hbmeng-pw.bentley.com\hbmeng-pw-01\Documents\22002207-90904-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62K53-008-EB-SouthAbutIn2.dgn




SECTION A-A




SECTION B-B




SECTION C-C



SECTION AA-AA



SECTION BB-BB



SECTION CC-CC

NOTES:

- For Legend, see Sheet S06-07.
- For Sections D-D, E-E, DD-DD and EE-EE, Bar diagrams, additional Notes and Bill of Material, see Sheet S06-09.
- Epoxy Grout v(E) bars in 9" min. holes in accordance with Section 584 of the Standard Specifications, drill to miss existing reinforcement. Cost included with Concrete Superstructure.



USER NAME	=	imranh	DESIGNED	-	SUR	REVISED	-
PLOT SCALE	=	2:0.0000 "/ in.	DRAWN	-	ME	REVISED	-
PLOT DATE	=	12/9/2024	CHECKED	-	JL	REVISED	-
			DATE	-	12/6/2024	REVISED	-


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

S. ABUT. JOINT REMOVAL & REPLACEMENT (SHT. 2 OF 3)
STRUCTURE NO. 016-0161 (EB)


SHEET S06-08 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	619
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				


MODEL: Default
FILE NAME: p:\3\hbmeng-pw-bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62K53-009-EB-SouthAbutJoint3.dgn




SECTION D-D



SECTION DD-DD




SECTION E-E




SECTION EE-EE

MIN BAR LAPS


#5	3'-6"
#6	4'-10"




BARS d(E) & d1(E)




BAR d4(E)




BAR d2(E)



BAR d5(E)



BAR d3(E)



BAR d7(E)

BILL OF MATERIAL

Bar	No.	Size	Length	Shape
a(E)	22	#5	17'-1"	---
a1(E)	22	#5	17'-10"	---
a2(E)	6	#6	6'-6"	---
d(E)	6	#5	3'-8"	L
d1(E)	6	#4	3'-8"	L
d2(E)	6	#5	2'-7"	~
d3(E)	3	#4	3'-5"	~
d4(E)	3	#4	2'-7"	~
d5(E)	2	#5	5'-8"	~
d6(E)	2	#5	5'-6"	~
d7(E)	2	#5	6'-1"	~
d8(E)	2	#5	5'-10"	---
h(E)	6	#6	28'-10"	---
h1(E)	6	#6	30'-6"	---
v(E)	60	#5	2'-0"	---
Concrete Removal			Cu Yd	8.9
Concrete Superstructure			Cu Yd	8.9
Protective Coat			Sq Yd	27
Reinforcement Bars, Epoxy Coated			Pound	1,640

NOTES:

- For Legend, see Sheet S06-07.
- For Preformed Joint Strip Seal Details, see Sheet S06-13.
- For Bar Splicer Assembly Details, see Sheet S06-22.
- Removal and disposal of the existing expansion joints is included with Concrete Removal.
- Epoxy grout d5(E), d6(E), d7(E) and d8(E) bars according to Article 584 of the Standard Specifications. Drill to miss existing reinforcement. Cost included with Concrete Superstructure.



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	2:0.0000 " / in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

S. ABUT. JOINT REMOVAL & REPLACEMENT (SHT. 3 OF 3)
STRUCTURE NO. 016-0161 (EB)

SHEET S06-09 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	620
CONTRACT NO.				62W87
ILLINOIS		FED. AID PROJECT		

59'-8 3/8" Face to face parapet, Measured along deck side of exp. Jt.

Exist. #5 vert. bars, O.F. to remain
Exist. #5 vert. bars, I.F. to remain
Both Sides, typ.

Exist. #4 bars, O.F. to be removed
Exist. #5 bars, I.F. to be removed
Both Sides, typ.

Exist. #6 bars at 12" cts., Top of Slab
to be removed, Both Sides, typ.

Exist. long. bars in bridge
parapet to remain, typ.

Exist. #5 vert. bars at 12" cts., E.F. to remain

Limits of Concrete Removal

1-Exist. #5 bar on Top, to be removed
2-Exist. #5 bars on Bot, to be removed

Exist. #6 bars at 12" cts.,
Top of Slab, to remain

Exist. #5 bars at 12" cts., Top of slab to remain
Exist. #5 bars at 12" cts., Bot of slab to remain

2-Exist. #6 bars, F.F. to be removed
3-Exist. #6 bars, B.F. to be removed

Exist. #5 bars at 6 1/2" cts., Top of slab to remain
Exist. #5 bars at 9" cts., Bot of slab to remain

Exist. long. bars in approach
parapet to remain, typ.

Exist. long. bars in bridge
parapet to remain, typ.

LEGEND

	Concrete Removal
E.F.	Each Face
I.F.	Inside Face
O.F.	Outside Face
F.F.	Front Face
B.F.	Back Face

NORTH ABUTMENT JOINT REMOVAL PLAN

*2-#5 d5(E) bars at 10" cts., I.F.
*2-#5 d6(E) bars at 10" cts., O.F.

Exist. #5 vert. bars, O.F. to remain
Exist. #5 vert. bars, I.F. to remain
Both Sides, typ.

3-#5 d(E) bars at 11" cts., I.F.
3-#5 d2(E) bars at 11" cts., I.F.
3-#4 d1(E) bars at 11" cts., O.F.
3-#4 d3(E) bars at 12" cts., O.F.

Exist. long. bars in bridge
parapet to remain, typ.

Exist. #5 vert. bars at 12" cts., E.F. to remain

Exist. #6 bars at 12" cts.,
Top of Slab, to remain

3-#6 h1(E) bars at 5" cts., E.F.
As shown in Section CC-CC

3-#6 a2(E) bar at 10" cts., Top
lap with alternate a1(E) bars

5x2 #5 a1(E) bars at 5" cts., Top
6x2-#5 a1(E) bars, Bot, as shown
in Section CC-CC

Exist. #5 bars at 12" cts., Top of slab to remain
Exist. #5 bars at 12" cts., Bot of slab to remain

3 Bar Splicers (E) for
#6 bars, E.F.

3-#6 h(E) bars at 5" cts., E.F.
As shown in Section CC-CC

5x2-#5 a(E) bars at 5" cts., Top
6x2-#5 a(E) bars, Bot as shown
in Section CC-CC

Exist. #5 bars at 6 1/2" cts., Top of slab to remain
Exist. #5 bars at 9" cts., Bot of slab to remain

Exist. #5 vert. bars, O.F. to remain
Exist. #5 vert. bars, I.F. to remain
Both Sides

*2-#5 d7(E) bars at 10" cts., I.F.
*2-#5 d8(E) bars at 10" cts., O.F.

3-#5 d(E) bars at 11" cts., I.F.
3-#5 d2(E) bars at 11" cts., I.F.
3-#4 d1(E) bars at 11" cts., O.F.
3-#4 d4(E) bars at 11" cts., O.F.

NOTES:

- Horizontal bars in approach parapets shall be cleaned, straightened, and reused in new construction.
- For Section A-A, B-B, C-C, AA-AA, BB-BB and CC-CC, see Sheet S06-11.
- For Sections D-D, E-E, DD-DD and EE-EE, additional Notes, Bar diagrams and Bill of Material, see Sheet S06-12.

NORTH ABUTMENT JOINT RECONSTRUCTION PLAN

*Field Drill and epoxy grout
in place accordingly to section 584
of the standard specifications.

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

N. ABUT. JOINT REMOVAL & REPLACEMENT (SHT. 1 OF 3)
STRUCTURE NO. 016-0161 (EB)


SHEET S06-10 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	621
CONTRACT NO. 62W87				


ILLINOIS FED. AID PROJECT




MODEL: Default
FILE NAME: p:\3\hbmeng-pw-bentley.com\hbmeng-pw-01\Documents\22002207-90904-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-EB-NorthAbutJoint2.dgn




SECTION A-A




SECTION B-B




SECTION C-C



SECTION AA-AA



SECTION BB-BB



SECTION CC-CC

NOTES:

- For Legend, see Sheet S06-10.
- For Bar diagrams, additional Notes and Bill of Material, see Sheet S06-12.



USER NAME	=	imranh	DESIGNED	-	SUR	REVISED	-
DRAWN	-	ME	REVIS	-		REVISED	-
PLOT SCALE	=	2:0'"/in.	CHECKED	-	JL	REVISED	-
PLOT DATE	=	12/9/2024	DATE	-	12/6/2024	REVISED	-


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

N. ABUT. JOINT REMOVAL & REPLACEMENT (SHT. 2 OF 3)
STRUCTURE NO. 016-0161 (EB)


SHEET S06-11 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	622
CONTRACT NO.				62W87
ILLINOIS FED. AID PROJECT				


MODEL: Default
FILE NAME: p:\3\hbmeng-pw-bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62KS3-012-EB-North\AbutJoint3.dgn




SECTION D-D



SECTION DD-DD



SECTION E-E




SECTION EE-EE

MIN BAR LAPS


#5	3'-6"
#6	4'-10"

BILL OF MATERIAL


Bar	No.	Size	Length	Shape
a(E)	22	#5	17'-1"	—
a1(E)	22	#5	17'-10"	—
a2(E)	6	#6	6'-6"	—
d(E)	6	#5	3'-8"	L
d1(E)	6	#4	3'-8"	L
d2(E)	6	#5	2'-7"	—
d3(E)	3	#4	3'-5"	—
d4(E)	3	#4	2'-7"	—
d5(E)	2	#5	5'-8"	—
d6(E)	2	#5	5'-6"	—
d7(E)	2	#5	6'-1"	—
d8(E)	2	#5	5'-10"	—
h(E)	6	#6	28'-10"	—
h1(E)	6	#6	30'-6"	—
Concrete Removal			Cu Yd	9.3
Concrete Superstructure			Cu Yd	9.3
Protective Coat			Sq Yd	27
Reinforcement Bars, Epoxy Coated			Pound	1,510




BARS d(E) & d1(E)




BAR d2(E)




BAR d3(E)



BAR d4(E)



BAR d5(E)



BAR d7(E)

NOTES:

- For Legend, see Sheet S06-10.
- For Preformed Joint Strip Seal Details, see Sheet S06-13.
- For Bar Splicer Assembly Details, see Sheet S06-21.
- Removal and disposal of the existing expansion joints is included with Concrete Removal.
- Epoxy grout d5(E), d6(E), d7(E), and d8(E) bars according to Article 584 of the Standard Specifications. Drill to miss existing reinforcement. Cost included with Concrete Superstructure.



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
PLOT SCALE =	2:0.0000 "/ in.	DRAWN -	ME	REVISED -	
PLOT DATE =	12/9/2024	CHECKED -	JL	REVISED -	
		DATE -	12/6/2024	REVISED -	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

N. ABUT. JOINT REMOVAL & REPLACEMENT (SHT. 3 OF 3)
STRUCTURE NO. 016-0161 (EB)

SHEET S06-12 OF S06-28 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	623
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: p:\3\hbmeng-pw-bentley.com\hbmeng-pw-01\Documents\22002207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62KS3-013-EB-PreformedJointStripSeal.dgn
12/9/2024 3:14:39 PM




FOR SKEWS $\leq 30^\circ$

PLAN AT PARAPET




ELEVATION AT PARAPET


(Skews $> 30^\circ$ shown. Skews $\leq 30^\circ$ similar except as shown in plan view.)



DETAIL A




SECTION B-B



TRIMETRIC VIEW

(Showing embedded plates only)




SHOWING ROLLED RAIL JOINT

* 5/8" ϕ x 6" studs @ 6" cts. (alternate angled/bent studs with horizontal studs)


3/8" ϕ threaded rods in 7/16" ϕ holes at $\pm 4'-0"$ cts. for holding the proper joint opening based on the temperature during the deck pour. Place to miss studs. All rods shall be burned, or sawed off flush with the plates after concrete is set.

SECTION A-A

* Granular or solid flux filled headed studs conforming to Article 1006.32 of the Std. Specs., automatically end welded.




SHOWING WELDED RAIL JOINT



LOCKING EDGE RAILS

** Back gouge not required if complete joint penetration is verified by mock-up.



LOCKING EDGE RAIL SPLICE

The inside of the locking edge rail groove shall be free of weld residue. Rolled rail shown, welded rail similar.

BILL OF MATERIAL

Item	Unit	Total
Preformed Joint Strip Seal	Foot	124



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	0:2,0000 "/in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PREFORMED JOINT STRIP SEAL
STRUCTURE NO. 016-0161 (EB)


SHEET S06-13 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	624
CONTRACT NO.				62W87
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: p:\3\hbmeng-pw.bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62KS3-01+EB-Framing Plan.dgn



FRAMING PLAN



BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Beam Straightening	L Sum	0.33
Anchor Bolts, 1"	Each	1

LEGEND



Straighten Damaged Beam Flange



Perform Beam Mid-Span Plating,
Paid for as Structural Steel Repair

NOTES:

- All work is to be performed utilizing stage construction, See Sheets S06-03 and S06-04 for details.
- Gouges caused by the impact should be ground to eliminate sharp or sudden irregularities in the beam surface. Grinding should be done in such a way as to provide a smooth transition with a maximum slope of 3:1 between the damaged and undamaged surfaces. Cost included in Structural Steel Repair.
- See Sheet S06-16 for Structural Steel Repair Details.



PHOTO 1: REPAIR ANCHOR
BOLT



PHOTO 2: BEAM FLANGE
REPAIR



USER NAME =	imranh	DESIGNED -	IH	REVISED -	
		DRAWN -	SUR	REVISED -	
PLOT SCALE =	16:0'"/ in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

FRAMING PLAN
STRUCTURE NO. 016-0161 (EB)

SHEET S06-14 OF S06-28 SHEETS




F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	625
CONTRACT NO. 62W87				
ILLINOIS		FED. AID PROJECT		

MODEL: Default
FILE NAME: pw:\bimeng-pw.bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62\K53-015-EB-Beam Straightening Details.dgn
12/9/2024 3:14:44 PM



PARTIAL PLAN
SUGGESTED BEAM STRAIGHTENING METHODS


NOTE: Straightening force shall be maintained on all load transfer blocking during beam straightening.




SUGGESTED VERTICAL STRAIGHTENING DETAIL
(To correct localized vertical flange deformations.)

* Edge of plate shall line up with edge of deformation.

NOTE:
Braces and jack assembly shall be placed on same side of web.
Bent bottom flange shall be straightened before starting any horizontal straightening operations.



VERTICAL STRAIGHTENING DETAIL




GRINDING DETAIL

Grind existing nicks, gouges and shallow cracks in the damaged beams as detailed. Grinding shall be done parallel to the longitudinal axis of the member. Ground surfaces shall be inspected for cracks using dye penetrant or magnetic particle testing prior to initiating any beam straightening operations. Any cracks that cannot be removed by grinding approximately 1/4" deep shall be identified and reported to the Bureau of Bridges and Structures for further disposition. Ground surfaces shall be spot cleaned and painted with an aluminum epoxy mastic primer followed by a finish coat to match the color of the existing beam. Cost of grinding, testing and spot painting is included with Beam Straightening.

Δ h: Measure in Field

Δ v: Measure in Field



EXISTING DEFORMATION TO BE STRAIGHTENED

(Looking North)
(Approximate max. deflections)
Deflected length of beam to be straightened is approximately 4'-0".






USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
DRAWN -	ME	REVIS			
PLOT SCALE =	0:2,0000 " / in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BEAM STRAIGHTENING DETAILS
STRUCTURE NO. 016-0161 (EB)

SHEET S06-15 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	626
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				



NOTES:


1. *For locations of Beam bottom flange Repairs, See Framing Plan on Sheet S06-14.*
2. *All Beam bottom flange repair plate and bottom flange repair angles shall conform to the requirements of AASHTO M270 Grade 36.*
3. *Beam bottom flange plate & bottom flange repair angles connection holes shall be $1\frac{5}{16}$ " \varnothing for $\frac{3}{4}$ " \varnothing bolts.*
4. *All proposed beam bottom flange repair plate, bottom flange repair angles, field drilling and associated bolts and fasteners shall be paid for as Structural Steel Repair.*
5. *Load carrying components designated "CVN" shall conform to the impact Testing Requirement, Zone 2.*
6. *Contractor to field verify hole locations before ordering material. Contractor can elect to field drill holes in repair plates.*

Direction of Travel I-94	Beam #	Span Number	Pier Reference	Distance from C/C Plate to C/C Pier
EB	20	2	1	39'-3 3/4" (L1)
EB	20	2	2	24'-7 3/8" (L2)


BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Steel Repair	Pound	190

MODEL: Default
FILE NAME: p:\3\hbmeng-pw-bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62KS3-017-EB-SouthAbutmentRepair.dgn



SOUTH ABUTMENT PLAN



SOUTH ABUTMENT ELEVATION
(Looking South)

NOTES:

- Quantities and limits shown are estimated for bidding purpose only. The actual areas to be repaired and the type(s) of repairs to be used will be determined by the engineer in the field at the time of construction.
- For slope wall repairs, see Sheet S06-21.
- Concrete Sealer is to be applied to the abutment seats, abutment backwall and abutment stem.

LEGEND



Structural Repair of Concrete (Depth Equal to or Less than 5 inches)




Epoxy Crack Injection

SF

Square Foot

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Concrete Sealer	Sq Ft	464
Epoxy Crack Injection	Foot	4
Structural Repair Of Concrete (Depth Equal to or Less Than 5 Inches)	Sq Ft	19



USER NAME = imranh	DESIGNED - SUR	REVISED -
	DRAWN - ME	REVISED -
PLOT SCALE = 5/4" = 1/4" / in.	CHECKED - JL	REVISED -
PLOT DATE = 12/9/2024	DATE - 12/6/2024	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SOUTH ABUTMENT REPAIRS
STRUCTURE NO. 016-0161 (EB)

SHEET S06-17 OF S06-28 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	628
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: p:\3\hbmeng-pw.bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-EB-NorthAbutmentRepair.dgn



Limits of North Abutment

NORTH ABUTMENT PLAN



Limits of North Abutment

NORTH ABUTMENT ELEVATION

(Looking North)

NOTES:

- Quantities and limits shown are estimated for bidding purpose only. The actual areas to be repaired and the type(s) of repairs to be used will be determined by the engineer in the field at the time of construction.
- For slope wall repairs, see sheet S06-21.
- Concrete Sealer is to be applied to the Abutment Seats, Abutment Backwall and Abutment Stem.

LEGEND




Structural Repair of Concrete (Depth Equal to or Less than 5 inches)

BILL OF MATERIAL


ITEM	UNIT	QUANTITY
Concrete Sealer	Sq Ft	464
Structural Repair Of Concrete (Depth Equal to or Less Than 5 Inches)	Sq Ft	14



MODEL: Default
FILE NAME: pw:\bimeng-pw.bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62KS3-019-EB-Pier1.dgn



PIER 1 ELEVATION
(Looking North)



PIER 1 ELEVATION
(Looking South)

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Epoxy Crack Injection	Foot	26
Structural Repair Of Concrete (Depth Equal to or Less Than 5 Inches)	Sq Ft	39

LEGEND

	Structural Repair of Concrete (Depth Equal to or Less than 5 inches)
	Epoxy Crack Injection
LF	Linear Foot
SF	Square Foot

NOTE:

- Quantities and limits shown are estimated for bidding purpose only. The actual areas to be repaired and the type(s) of repairs to be used will be determined by the engineer in the field at the time of construction.



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	8:0.0000 " = 1 in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION



PIER 1 REPAIRS
STRUCTURE NO. 016-0161 (EB)

SHEET S06-19 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	630
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Repair of Concrete (Depth Equal to or Less than 5 Inches)	Sq Ft	21




CRACKS ON PIER 2 (SF)
(Looking North)

NOTE:

- Quantities and limits shown are estimated for bidding purpose only. The actual areas to be repaired and the type(s) of repairs to be used will be determined by the engineer in the field at the time of construction.

LEGEND

-  Structural Repair of Concrete (Depth Equal to or less than 5")
- SF Square Foot



CRACKS ON PIER 2 (NF)
(Looking South)

MODEL: Default
FILE NAME: p:\3\hbmeng-pw.bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62KS3-02b-EB-Pier2.dgn



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	8:0.0000 " = 1' in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PIER 2 REPAIRS
STRUCTURE NO. 016-0161 (EB)


SHEET S06-20 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	631
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: p:\3\hbmeng-pw-bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62KS3-021-EB-SlopeWall.dgn



NORTH ABUTMENT SLOPE WALL PLAN



SOUTH ABUTMENT SLOPE WALL PLAN

BILL OF MATERIAL NORTH SLOPE WALL

ITEM	UNIT	QUANTITY
Porous Granular Embankment	Cu Yd	1
Slope Wall Removal	Sq Yd	2
Slope Wall 4 Inch	Sq Yd	2
Slope Wall Crack Sealing	Foot	101


BILL OF MATERIAL SOUTH SLOPE WALL


ITEM	UNIT	QUANTITY
Slope Wall Crack Sealing	Foot	53.0

NOTES:

- Quantities and limits shown are estimated for bidding purposes only. The actual areas to be repaired, and the type(s) of repairs to be used, will be determined by the engineer in the field at the time of construction.
- Slope wall shall be reinforced with welded wire fabric, 6 in. x 6 in. W40 x W40 weighing 58 lbs. per 100 sq. ft.

LEGEND

 Slope Wall Removal and Replacement with 4 inch Slope Wall

 Slope Wall Crack Sealing

LF Linear Foot

SF Square Foot



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	14:8,0000 " = 1" / in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SLOPE WALL REPAIRS
STRUCTURE NO. 016-0161 (EB)

SHEET S06-21 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	632
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: p:\w\hbmeng-pw.bentley.com\hbmeng-pw-01\Documents\2200\2207-909\04-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB\016-0161-62\K53-022-EB-BarSplicers.dgn




STANDARD BAR SPLICER ASSEMBLY PLAN

Only bar splicer assemblies as presented on the approved QPL list may be used.

Threaded splicer bar length = min. lap length + 1 1/2" + thread length

* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies required	Minimum lap length
N. Abut.	#5	10	3'-6"
N. Abut.	#6	6	4'-10"
S. Abut.	#5	10	3'-6"
S. Abut.	#6	6	4'-10"




INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.

"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required

NOTES:

- Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.
- All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.
- See approved list of bar splicer assemblies and mechanical splicers for alternatives.

BSD-1

05-15-2023



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
		DRAWN -	ME	REVISED -	
PLOT SCALE =	0:2,0000 " = 1 in.	CHECKED -	JL	REVISED -	
PLOT DATE =	12/9/2024	DATE -	12/6/2024	REVISED -	



STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BAR SPLICER ASSEMBLY & MECHANICAL SPLICER DETAILS
STRUCTURE NO. 016-0161 (EB)

SHEET S06-22 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	633
CONTRACT NO. 62W87				
ILLINOIS		FED. AID PROJECT		

Bench Mark:
Chiseled square cut in Northeast corner of concrete
end for steel guard rail in Southwest corner of
I-94 deck over Dalton Ave. El. 606.69
Existing Structure
I-beam bridge over Dalton Ave. 2 Spans @ 49.8' ±
1 Span @ 63.95'. Concrete deck and Steel Handrail
to be Removed in Stages. No Salvage.



For Informational Purposes Only

APPROVED
FOR STRUCTURAL ADEQUACY ONLY

Robert E. Anderson
Engineer of Bridges and Structures

Sander Ferenczi Date 8/16/90
Exp. Date 11/30/92

STATE OF ILLINOIS
SANDOR FERENCZI
81-3253
CHICAGO, ILLINOIS
REGISTERED PROFESSIONAL ENGINEER

PROPOSED PROFILE I-94

PROPOSED PROFILE DOLTON AVE.

016-0161

*42 (VB-10, 12, HB-14, B11) & 0707.1HB (R-3) 90

DATE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
1-94	*	COOK	318	255
SHT. 51 OF 525				

GENERAL NOTES:

DESIGN SPECIFICATIONS:
A.A.S.H.T.O. 1983 Standard Specifications for Highway
Bridges, and 1984 thru 1988 Interims.
1983 Guide specifications for Seismic Design of Highway
Bridges with 1985 and 1988 Interim Specifications.

DESIGN CRITERIA:
Service Load Design, Load Factor for Deck
Live Load: HS 20-44 & A1.

Allow 25 psf for Future Wearing Surface
DESIGN STRESSES
Existing Structural Steel
fs = 18,000 psi, ASTM A7 & fs = 20,000,
ASTM A36 (M183 Steel Beam 16 Repair)
Proposed Structural Steel
fs = 20,000 psi (M183 Steel)
Reinforced Concrete
fc = 3500 psi - Superstructure Composite Deck Slab
fc = 1400 psi - Substructure
fc = 1000 psi with earth pressure
n = 9



REINFORCEMENT:
fy = 60,000 psi - Superstructure
fs = 24,000 psi - Substructure

TRAFFIC:
All barricades, signs and other traffic control
devices and their placement installed for the
purpose of temporarily maintaining traffic during
construction shall be in full compliance with
the Illinois State Manual on Uniform Traffic
Control Devices unless otherwise noted.
The Contractor shall procure, install and remove
all temporary pavement markings as per the
traffic phasing shown on the plans or as directed
by the Engineer. See Roadway Plans.

Indicates Removal of Existing Concrete Deck Slab.

Indicates Boring Locations.

Note:
A. Limits of Porous Granular
Embankment (Typ. both Abutments).
Place at 45°.



SECTION A-A

STATION 6+93.11
RE-BUILT BY
STATE OF ILLINOIS
PROJECT ACTM-PCBHI-94-
3 (307) 70
LOADING HS 20 & ALT.
STR. No. 016-0161

NAME PLATE
See Standard 2113

STAGE III - S.B. MAINLINE CONSTRUCTION	
STATE OF ILLINOIS	
DEPARTMENT OF TRANSPORTATION	
PLAN AND ELEVATION	
I-94 OVER DOLTON AVE.	
COOK COUNTY	
STA. 206+93.10	S.N. 016-0161
SCALE	DRAWN BY KC&IMG
DATE: NOV. 1991	CHECKED BY L.M.
S.B.M.-III-1 of 21	

MODEL: Default
FILE NAME: pw:\bentley-pw-bentley.com\hbmeng-pw-01\Documents\22002207-90904-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161-62K53-023-EB-Existing Plans (Sheet 1 of 6).dgn
12/9/2024 3:15:15 PM



USER NAME =	imranh	DESIGNED -	SUR	REVISED -	
PLOT SCALE =	0:2,0000 "/in.	DRAWN -	ME	REVISED -	
PLOT DATE =	12/9/2024	CHECKED -	JL	REVISED -	
		DATE -	12/6/2024	REVISED -	

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


EXISTING PLANS (SHEET 1 OF 6)
STRUCTURE NO. 016-0161 (EB)

SHEET S06-23 OF S06-28 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	634
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				



MODEL: Default
FILE NAME: pw:\bentley-pw-bentley.com\hbmeng-pw-01\Documents\22002207-90904-SOUTH_CONTRACT\016-0161-62K53-026-EB-Existing Plans (Sheet 4 of 6).dgn
12/9/2024 3:15:42 PM



For Informational Purposes Only




USER NAME	=	imranh	DESIGNED	-	SUR	REVISED	-
PLOT SCALE	=	0:2,000" = 1"	DRAWN	-	ME	REVISED	-
PLOT DATE	=	12/9/2024	CHECKED	-	JL	REVISED	-
			DATE	=	12/6/2024	REVISED	-

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

EXISTING PLANS (SHEET 4 OF 6)
STRUCTURE NO. 016-0161 (EB)

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	637
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\bentley-pw-01\Documents\22002207-90904-SOUTH_CONTRACT\01-DGN\12-SHT\16-Structures\016-0161_SB016-0161-62K53-028-EB-Existing Plans (Sheet 6 of 6).dgn
12/9/2024 3:16:00 PM



Benchmark: Chiseled square cut in south end of west Pier
154th St. Bridge over I-94. Elev. 598.38

Existing Structure: Structure No. 016-0914 was originally constructed in 1946 as 4 Span steel wide flange bridge. Structure was repaired and rehabilitated in 1968, 1980, 1981 and 1988. In 1990 the existing deck was replaced, substructure was repaired and new bearings were placed at piers. Traffic to be maintained utilizing stage construction.

Salvage: Timber cribbing at abutments.

DESIGN SPECIFICATIONS

2002 AASHTO Standard Specifications
for Highway Bridges, 17th Edition

DESIGN STRESSES

FIELD UNITS




$f'_c = 3,500$ psi
 $f'_c = 4,000$ psi (Superstructure Concrete)
 $f_y = 60,000$ psi (Reinforcement)
 $f_y = 50,000$ psi (Structural Steel AASHTO M270 Gr. 50)

RECONSTRUCTION (1990)


$f'_c = 3,500$ psi (Superstructure)
 $f'_c = 1,400$ psi (Substructure)
 $f_y = 60,000$ psi (Reinforcement)
 $f_y = 36,000$ psi (Structual Steel AASHTO M 183)

ORIGINAL CONSTRUCTION (1946)

$f'_c = 3,000$ psi
 $f_y = 40,000$ psi (Reinforcement)



LOCATION SKETCH



12/05/2024
Exp. 11/30/2026

GENERAL PLAN AND ELEVATION
154TH STREET OVER I-94 BISHOP FORD
I-94 BRIDGES FROM 154TH TO US 6
COOK COUNTY
STATION 550+00.00
STRUCTURE NO. 016-0914

NOTE:
Dimensions shown are from existing drawings.



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

GENERAL PLAN AND ELEVATION
STRUCTURE NO. 016-0914

SHEET S07-01 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	640
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 2016-0914 - 154th over I-94\Sheets\01_016-0914-GPE.dgn

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com:wsp-us-pw-IL\Documents\Project_IDOT_District_1_VariousStructures\Work_Order_2016-0914 - 154th over I-94\Sheets\02_016-0914-GNdgn

GENERAL NOTES

No field welding is permitted except as specified in the contract documents.

Reinforcement bars designated (E) shall be epoxy coated.

Prior to pouring the new concrete deck, all heavy or loose rust, loose mill scale, and other loose detrimental foreign material shall be removed from the surfaces in contact with concrete (SSPC-SP3 standards). Tightly adhered paint may remain unless otherwise noted. Removal shall be accomplished by methods that will not damage the steel and the cost will be paid for according to Article 109.04 of the Standard Specifications.

As directed by the Engineer, existing construction accessories welded to the top flange of beams and girders shall be removed. The weld areas shall be ground flush and inspected for cracks using magnetic particle testing (MT) or dye penetrant testing (PT) by qualified personnel approved by the Engineer. Any cracks that cannot be removed by grinding ¼ inch deep shall be identified and reported to the Bureau of Bridges and Structures for further disposition. The cost of removing welded accessories, grinding and inspecting weld areas and grinding cracks will be paid for according to Article 109.04 of the Standard Specifications.

Plan dimensions and details relative to existing plans are subject to nominal construction variations. The Contractor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

Proposed elevations are based on the existing drawing profile and adjusted to account for the proposed overlay.

Fasteners shall be ASTM F 3125 Grade A325 Type 1. Fasteners shall be hot dip galvanized. See Special Provision for "Hot Dip Galvanizing for Structural Steel." Bolts ¾ in. Ø holes 1⅜ in. Ø, unless otherwise noted.

All new structural steel shall be galvanized. See Special Provision for "Hot Dip Galvanizing for Structural Steel."

Existing structural steel that will be in contact with new structural steel shall be cleaned and painted prior to erection as required by the Special Provision "Cleaning and Painting Contact Surface Areas of Existing Steel Structures."

The existing structural steel coating contains lead. The contractor shall take appropriate precautions to deal with the presence of lead on this project.

It is the Contractor's responsibility to temporarily support the existing signal interconnect and all other utilities interfering with proposed work, as required. Embedment in the south parapet shall be reestablished. Cost included in Concrete Superstructure.

The contractor shall exercise caution during removal and construction operations to avoid damaging the existing signal interconnect and all other utilities. Any damage to the signal interconnect or other utilities caused by the Contractor in the performance of their work shall be repaired by the Contractor, to the satisfaction of the Engineer, at no cost to the Department.

All exposed concrete edges shall have a ¾" x 45 degree chamfer except where shown otherwise.

The contractor shall salvage the wood cribbing supporting some of the abutment beam ends and diaphragms. The wood cribbing shall be transported, unloaded, and stacked by the Contractor to the District Bridge Yard in Elk Grove at 1101 Biesterfield Road during the week days of Monday-Friday, and between the hours of 8am and 2pm. The Contractor shall notify the District Bridge Office 48 hours in advance of the delivery at (847) 956-1443. Cost included in Structural Steel Removal.

Joint openings shall be adjusted according with Article 520.04 of the Standard Specs. when the joint concrete is poured at an ambient temperature other than 50° F.

Expansion joint shall be fabricated to conform to the existing cross-slopes of the bridge.

Bearing seat surfaces shall be constructed or adjusted to the designated elevations within a tolerance of ⅛ in. (0.01 ft.) Adjustment shall be made either by grinding the surface or by shimming the bearings.

Any reinforcement bars that are damaged during concrete removal operations shall be repaired or replaced using an approved bar splicer or anchorage system. Cost included to "Concrete Removal".

Cleaning and field painting of the structural steel shall be done under a separate painting contract.

Cost of removal and re-installation of all members necessary to complete the work as detailed on the plans and as specified in the Special Provisions shall be included with Furnishing and Erecting Structural Steel or Structural Steel Repairs.

The Engineer shall show actual locations and size of deck repairs on As-built Plans.

TOTAL BILL OF MATERIAL

ITEM	UNIT	SUPER	SUB	TOTAL
Porous Granular Embankment	CU YD	0	2	2
Concrete Removal	CU YD	17.0	0	17.0
Slope Wall Removal	SQ YD	0	3	3
Protective Shield	SQ YD	758	0	758
Concrete Structures	CU YD	0.0	1	1.0
Concrete Superstructure	CU YD	17.2	0	17.2
Protective Coat	SQ YD	1,443	0	1,443
Furnishing And Erecting Structural Steel	POUND	5,830	0	5,830
Reinforcement Bars, Epoxy Coated	POUND	2,630	0	2,630
Bar Splicers	EACH	26	0	26
Slope Wall 4 Inch	SQ YD	0	3	3
Preformed Joint Strip Seal	FOOT	124	0	124
Elastomeric Bearing Assembly, Type II	EACH	20	0	20
Anchor Bolts, 1"	EACH	80	0	80
Epoxy Crack Injection	FOOT	0	259	259
Jack and Remove Existing Bearings	EACH	0	20	20
Structural Steel Removal	POUND	5,430	0	5,430
Structural Steel Repair	POUND	10,650	0	10,650
Cleaning Drainage System	L SUM	0.34	0	0.34
Concrete Bridge Deck Scarification 3/8"	SQ YD	1,430	0	1,430
Bridge Deck Thin Polymer Overlay, 3/8"	SQ YD	1,430	0	1,430
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 Inches)	SQ FT	0	679	679
Structural Repair Of Concrete (Depth Greater Than 5 Inches)	SQ FT	0	46	46
Deck Slab Repair (Full Depth, Type I)	SQ YD	1	0	1
Deck Slab Repair (Partial)	SQ YD	4	0	4
Beam Straightening	L SUM	0.34	0	0.34
Temporary Shoring and Cribbing	EACH	0	23	23

SCOPE OF WORK

- Remove and replace the abutment bearings with elastomeric bearings.
- Remove and replace diaphragms at both abutments.
- Perform Structural Steel Beam End and Midspan Repairs at the locations shown in the drawings.
- Straighten impact damage on Beam 1 in Span 4.
- Perform Structural Repair of Concrete and Epoxy Crack Injection to the abutments and Piers as shown in the drawings.
- Perform ¾" Bridge Deck Scarification.
- Perform Deck slab repairs as required.
- Remove and replace deck expansion joints at the North and South Abutments. Install new Preformed Joint Strip Seals.
- Apply a ⅝" thin Polymer Deck Overlay on Bridge Deck.
- Apply Protective Coat.

- S07-01
S07-02
S07-03
S07-04
S07-05
S07-06
S07-07

S07-08

S07-09
S07-10
S07-11
S07-12
S07-13
S07-14
S07-15
S07-16
S07-17
S07-18
S07-19
S07-20
S07-21
S07-22
S07-23
S07-24
S07-25
- General Plan and Elevation
General Data
Removal and Construction Staging (1 of 2)
Removal and Construction Staging (2 of 2)
Temporary Concrete Barrier
Bridge Deck Repair Plan and Details
East and West Abutment Expansion Joint Removal and Replacement Plan
East and West Abutment Expansion Joint Removal and Replacement Details
Preformed Joint Strip Seal (1 of 3)
Preformed Joint Strip Seal (2 of 3)
Preformed Joint Strip Seal (3 of 3)
Framing Plan
Diaphragm Replacement Details
Beam End Plating Details
Beam Mid-Span Repair Details
Bearing Details
East Abutment Repairs
West Abutment Repairs
Pier 1 Repairs
Pier 2 Repairs
Pier 3 Repairs
Beam Straightening Details
Slope Wall Details
Bar Splicer Assembly Details
Existing General Plan and Elevation



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -




STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

GENERAL DATA
STRUCTURE NO. 016-0914

SHEET S07-02 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	641
CONTRACT NO. 62W87				
		ILLINOIS	FED. AID PROJECT	

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-IL\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 2016-0914 - 154th over I-94\Sheets\03_016-0914-Rem-Sig-1.dgn



NOTE:
Joint removal and reconstruction not shown but included in the removal and construction limits shown.

LEGEND
 Bridge Deck Scarification



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REMOVAL AND CONSTRUCTION STAGING (1 OF 2)
STRUCTURE NO. 016-0914


SHEET S07-03 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	642
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various\Structures\Work Order 2016-0914 - 154th over I-94\Sheets\04_016-0914-Rem-Stg-2.dgn



STAGE II CONSTRUCTION
(Looking East)



FINAL DECK CROSS SECTION
(Looking East)

NOTE:

Joint removal and reconstruction not shown
but included in the removal and construction
limits shown.



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -










STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

REMOVAL AND CONSTRUCTION STAGING (2 OF 2)
STRUCTURE NO. 016-0914

SHEET S07-04 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	643
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\3\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various\Structures\Work Order 2016-0914 - 154th over I-94\Sheets\05_016-0914-Tcb.dgn
12/06/24 3:07:12 PM



Notes:

Cost of retainer assembly is included with Temporary Concrete Barrier.

A retainer assembly shall be located at the approximate \bar{C} of each temporary concrete barrier.

The retainer plate shall not be removed until the concrete on the adjacent stage is ready to be poured. For Detail III applications the retainer plate shall not be removed until just prior to placing the adjacent beam.

When the 'A' dimension is less than 1 1/2", the wood block shall be omitted and the barrier shall be placed in direct contact with the steel retainer plate. For deck beam applications the minimum required 'A' distance is 6" to accommodate the shear key clamping device.

Detail I - Installation for a new bridge deck or bridge slab.

Detail II - Installation for a new deck beam with an initial concrete wearing surface. Additional bar splicers shall be provided at 6'-0" centers and paired with the bar splicers of the concrete wearing surface reinforcement to accommodate the installation of the retainer assemblies. The cost of the additional bar splicers is included with the concrete wearing surface.

Detail III - Installation for a new deck beam with no initial wearing surface or with an initial hot-mix asphalt (HMA) wearing surface present. The deck beam directly beneath the temporary concrete barrier shall be fabricated with bar splicer inserts in the side of the beam, as detailed, to accommodate the installation of the retainer assemblies. A pair of bar splicers, 6" apart, shall be placed at 6'-0" centers along the length of the beam. The cost of the bar splicers is included with the deck beam.

RAILING CRITERIA

NCHRP 350 Test Level	3
Railing Weight (plf)	440

R-27

5-15-2023



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

TEMPORARY CONCRETE BARRIER
STRUCTURE NO. 016-0914

SHEET S07-05 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	644
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\3\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various\Structures\Work Order 2016-0914 - 154th over I-94\Sheets\06_016-0914-DeckRepair.dgn



DECK PLAN

NOTES:

1. Areas of deck repair shown are estimated. The Engineer shall determine actual locations of deck repairs at the time of construction.
2. For West and East Abutment Expansion Joint Removal and Reconstruction, see Sheets S07-07 thru S07-08.
3. Protective coat shall be applied to top and inside face of reconstructed parapets, reconstructed sidewalks, reconstructed transverse joint areas and the surface of the new overlay. Protective coat need not be applied to existing exposed concrete surfaces.
4. Any reinforcement bars that are damaged during concrete removal operations shall be repaired or replaced using an approved bar splicer or anchorage system. Cost incidental to Concrete Removal.
5. The Contractor shall exercise extreme caution during Concrete Removal to avoid damaging the steel beams and diaphragms. Any damage to the existing steel beams and/or diaphragms caused by the Contractor in the performance of their work shall be repaired by the Contractor, to the satisfaction of the Engineer, at no cost to the Department.
6. Existing bridge fencing is to be protected during construction. Post location in the removal area for the joint replacement shall be temporarily shored during the concrete removal and replacement. Existing concrete anchor shall be replaced in kind and installed into the proposed parapet. Cost included in Concrete Removal.
7. Removal and disposal of the existing expansion joints will not be paid for separately, but are included in the cost of Concrete Removal.
8. The Contractor must exercise extreme care with the existing conduits in the sections of the parapets to be removed and to protect and support the conduit during construction. The Contractor will be required to repair any damage done to the conduit to the satisfaction of the Engineer. No splicing will be allowed to any cable damaged resulting from this work. The Contractor will be required to repair the entire span of any damaged cable at no additional cost to the Department.
9. If the existing name plate falls within the limits of Concrete Removal, it shall be removed and reinstalled in its original locations in accordance with IDOT Standard 515001. Cost included with Concrete Superstructure.
10. Adjust Deck Slab Repairs (Full Depth, Type I) limits as required to meet field conditions.

LEGEND:

-  Deck Slab Repair (Partial)
-  Deck Slab Repair (Full Depth, Type I)
-  Concrete Removal

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Protective Coat	Sq Yd	1,443
Bridge Deck Thin Polymer Overlay, 3/8"	Sq Yd	1,430
Concrete Bridge Deck Scarification 3/8"	Sq Yd	1,430
Protective Shield	Sq Yd	758
Jack and Remove Existing Bearings	Each	20
Deck Slab Repair (Full Depth, Type I)	Sq Yd	1
Deck Slab Repair (Partial)	Sq Yd	4







USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -



STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION











BRIDGE DECK REPAIR PLAN AND DETAILS
STRUCTURE NO. 016-0914


SHEET S07-06 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	645
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				






Bar	No.	Size	Length	Shape
a(E)	36	#5	31'-8"	
a1(E)	16	#5	6'-6"	
b(E)	130	#5	2'-2"	
c(E)	20	#5	2'-5"	
c1(E)	12	#5	5'-7"	
d(E)	12	#6	4'-4"	
d1(E)	12	#4	4'-8"	
d2(E)	8	#4	2'-1"	
h(E)	16	#6	30'-8"	
h1(E)	8	#6	4'-6"	
Concrete Removal			Cu. Yd.	17.0
Concrete Superstructure			Cu. Yd.	17.2
Reinforcement Bars, Epoxy Coated			Pound	2,630




NOTE:

1. Cut a1(E) bars to fit between girders 1 and 2 and 9 and 10.

LEGEND:

 Concrete Removal

 Bridge Deck Scarification $\frac{3}{8}$ "



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

E. & W. ABUT. EXP. JOINT REMOVAL & RECONSTRUCTION DETAILS STRUCTURE NO. 016-0914


SHEET S07-08 OF S07-25 SHEETS

S	F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
	94	(42-B-11-1) BR, BJR 24	COOK	761	647
			CONTRACT NO. 62W87		
		ILLINOIS	FED. AID PROJECT		

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 2016-0914 - 154th over I-94\Sheets\09_016-0914-PreformedJointStripSeal-1.dgn




PLAN AT PARAPET




SECTION AT PARAPET


(Skews $> 30^\circ$ shown. Skews $\leq 30^\circ$ similar except as shown in plan view.)



DETAIL A




SECTION B-B



TRIMETRIC VIEW

(Showing embedded plates only)




SHOWING ROLLED RAIL JOINT

* 5/8" \varnothing x 6" studs @ 6" cts. (alternate angled/bent studs with horizontal studs)


3/8" \varnothing threaded rods in 7/16" \varnothing holes at ± 4 '-0" cts. for holding the proper joint opening based on the temperature during the deck pour. Place to miss studs. All rods shall be burned, or sawed off flush with the plates after concrete is set.

SECTION A-A

* Granular or solid flux filled headed studs conforming to Article 1006.32 of the Std. Specs., automatically end welded.



SHOWING WELDED RAIL JOINT




ROLLED

(EXTRUDED) RAIL

WELDED RAIL

LOCKING EDGE RAILS

** Back gouge not required if complete joint penetration is verified by mock-up.



LOCKING EDGE RAIL SPLICE

The inside of the locking edge rail groove shall be free of weld residue. Rolled rail shown, welded rail similar.

BILL OF MATERIAL

Item	Unit	Total
Preformed Joint Strip Seal	Foot	124

(Sheet 1 of 3)

EJ-SS-S

11-1-2022



USER NAME =	DESIGNED - JS	REVISED -
PLOT SCALE =	CHECKED - RRD	REVISED -
PLOT DATE =	DRAWN - SVJ	REVISED -
	CHECKED - RRD	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PREFORMED JOINT STRIP SEAL - SIDEWALK (1 OF 3)
STRUCTURE NO. 016-0914


SHEET S07-09 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	648
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				


MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 2016-0914 - 154th over I-94\Sheets\10_016-0914-PreformedJointStripSeal-2.dgn



SECTION AT RAISED SIDEWALK




SECTION C-C



SECTION AT MEDIAN


For skews > 30°, chamfer acute corners 2" similar to sidewalk.




(FOR SKEWS $\leq 30^\circ$)

(FOR SKEWS $> 30^\circ$)

PLAN AT RAISED SIDEWALK



TRIMETRIC VIEW



SECTION D-D
(at Rt. L's)

(Sheet 2 of 3)

EJ-SS-S

11-1-2022



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVI	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PREFORMED JOINT STRIP SEAL - SIDEWALK (2 OF 3)
STRUCTURE NO. 016-0914

SHEET S07-10 OF S07-25 SHEETS


F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	649
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various\Structures\Work Order 2016-0914 - 154th over I-94\Sheets\11_016-0914-PreformedJointStripSeal-3.dgn




SECTION AT DECK LEVEL SIDEWALK


(Skews > 30° shown. Skews ≤ 30° similar except as shown in plan view.)




DETAIL B



SECTION E-E



SECTION F-F



PLAN AT DECK LEVEL SIDEWALK

(FOR SKEWS ≤ 30°)

(FOR SKEWS > 30°)

EJ-SS-S

11-1-2022

(Sheet 3 of 3)



USER NAME =	DESIGNED - JS	REVISED -
PLOT SCALE =	CHECKED - RRD	REVISED -
PLOT DATE =	DRAWN - SVJ	REVISED -
	CHECKED - RRD	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PREFORMED JOINT STRIP SEAL - SIDEWALK (3 OF 3)
STRUCTURE NO. 016-0914

SHEET S07-11 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	650
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 2016-0914 - 154th over I-94\Sheets\12_016-0914-FramingPlan.dgn



NOTES:

1. For Beam End and Mid-Span Repairs, Diaphragm Removal and Replacement Details and Bill of Materials, see Sheet S07-13 thru S07-15.
2. DE, DE1 and DE4 are W12x40 existing diaphragms. D, D1 and D4 are proposed W12x40 diaphragms.

LEGEND

- Perform Beam End Plating.
Paid for as Structural Steel Repair.
- Remove and Replace Existing Diaphragm.
Paid for as Structural Steel Removal and
Furnishing and Erecting Structural Steel.
- Perform Beam Mid-Span Plating.
Paid for as Structural Steel Repair.

Proposed Diaphragm Name Existing Diaphragm Name




USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


FRAMING PLAN
STRUCTURE NO. 016-0914

SHEET S07-12 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	651
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				



BEAMS 1 THRU 3 AND 5 THRU 10 EAST AND WEST ABUTMENTS




BEAMS 4 THRU 7 EAST AND WEST ABUTMENTS

* Distance from Top of Main Girder to Top of Proposed Diaphragm to be Field Verified prior to Ordering Material.
 ** Contractor to field verify diaphragm location and bolt hole locations before ordering material.




1. For Notes and Bill of Material see Sheet S07-13.
2. For Locations of Diaphragm Removal/Replacement and Beam End and Mid-Span Repairs, see Sheet S07-12.
3. See Sheet S07-13 for Clip Angle lengths.
4. Contractor to field verify hole locations before ordering material. Contractor can elect to field drill holes in repair plates.

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 2016-0914 - 154th over I-94\Sheets\15_016-0914-BeamMidSpanRepairDetails.dgn



PARTIAL ELEVATION
(Looking North)



SECTION E-E

Mid-Span Repair Detail Table					
Direction of Travel I-94	Beam #	Span Number	Pier Reference	Distance from CL Plate to CL Pier	
				L1	L2
Northbound	2	3	3		32'-0"
Northbound	4	3	3		32'-0"
Northbound	5	3	3		32'-0"
Northbound	6	3	3		32'-0"
Northbound	7	3	3		32'-0"
Northbound	8	3	3		32'-0"
Northbound	9	3	3		32'-0"
Southbound	1	2	1	27'-10"	
Southbound	2	2	1	31'-0"	
Southbound	3	2	1	31'-0"	
Southbound	4	2	1	31'-0"	
Southbound	5	2	1	29'-0"	
Southbound	6	2	1	29'-0"	
Southbound	7	2	1	31'-0"	
Southbound	8	2	1	25'-0"	
Southbound	9	2	1	25'-0"	
Southbound	10	2	1	28'-0"	

NOTES:

- For Notes and Bill of Material see Sheet S07-13.
- Contractor to field verify hole locations before ordering material.
Contractor can elect to field drill holes in repair plates.



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BEAM MID SPAN REPAIR DETAILS
STRUCTURE NO. 016-0914


SHEET S07-15 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	654
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 2016-0914 - 154th over I-94\Sheets\17_016-0914-EastAbutmentRepairs.dgn



ELEVATION
(Looking East)



PLAN

NOTES:

- Quantities and limits shown are estimates for bidding purposes only. The actual area to be repaired, and the type(s) of repairs to be used, will be determined by the engineer in the field at the time of construction.
- Removal and installation of drainage pipes, electrical cables conduits, or other items attached to the existing structure are included in the cost of Structural Repair of Concrete.
- Concrete repairs directly under Girders shall not start until the Temporary Shoring is installed.

GIRDER REACTION TABLE

East Abutment	Load (kips)
DL	23.9
LL	47.2
IM	13.9
TOTAL	85.0

Reactions are per girder

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 In)	Sq. Ft.	37
Epoxy Crack Injection	Foot	23
Temporary Shoring and Cribbing	Each	3

LEGEND:

- Structural Repair of Concrete
(Depth Equal to or Less Than 5 inches)
- Epoxy Crack Injection
- Temporary Shoring and Cribbing



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

EAST ABUTMENT REPAIRS
STRUCTURE NO. 016-0914


SHEET S07-17 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	656
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 2016-0914 - 154th over I-94\Sheets\18_016-0914-WestAbutmentRepairs.dgn



ELEVATION
(Looking West)



NOTES:

- Quantities and limits shown are estimates for bidding purposes only. The actual area to be repaired, and the type(s) of repairs to be used, will be determined by the engineer in the field at the time of construction.
- Removal and installation of drainage pipes, electrical cables conduits, or other items attached to the existing structure are included in the cost of Structural Repair of Concrete.
- Concrete repairs directly under Girders shall not start until the Temporary Shoring is installed.

PLAN

GIRDER REACTION TABLE

West Abutment	Load (kips)
DL	23.9
LL	47.2
IM	13.9
TOTAL	85.0

Reactions are per girder

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 In)	Sq. Ft.	42
Structural Repair Of Concrete (Depth Greater Than 5 In)	Sq. Ft.	25
Low Pressure Epoxy Crack Injection	Foot	33
Temporary Shoring and Cribbing	Each	5

LEGEND:

- Structural Repair of Concrete (Depth Equal to or Less Than 5 inches)
- Structural Repair of Concrete (Depth Greater than 5 inches)
- Epoxy Crack Injection
- Temporary Shoring and Cribbing



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

WEST ABUTMENT REPAIRS
STRUCTURE NO. 016-0914




SHEET S07-18 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	657
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 2016-0914 - 15th over I-94\Sheets\19_016-0914-Pier 1.dgn





MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-IL\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 2016-0914 - 154th over I-94\Sheets\20_016-0914-Pier 2.dgn
12/06/24 3:08:30 PM



BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 In)	Sq. Ft.	247
Epoxy Crack Injection	Foot	8
Temporary Shoring and Cribbing	Each	7



NOTES:

- Quantities and limits shown are estimates for bidding purposes only. The actual area to be repaired, and the type(s) of repairs to be used, will be determined by the engineer in the field at the time of construction.
- Removal and installation of drainage pipes, electrical cables conduits, or other items attached to the existing structure are included in the cost of Structural Repair of Concrete.
- Concrete repairs directly under Girders shall not start until the Temporary Shoring is installed.

LEGEND:

- Structural Repair of Concrete
(Depth Equal to or Less Than 5 inches)
- Epoxy Crack Injection
- Temporary Shoring and Cribbing

GIRDER REACTION TABLE

Pier 2	Load (kips)
DL	79.8
LL	53.0
IM	14.6
TOTAL	147.4

Reactions are per girder



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PIER 2 REPAIRS
STRUCTURE NO. 016-0914

SHEET S07-20 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	659
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-IL\Documents\Project IDOT 2050082201 - IDOT District 1 Various\Structures\Work Order 2016-0914 - 154th over I-94\Sheets\21_016-0914-Pier 3.dgn



SOUTH FACE

EAST FACE
(Looking West)

NORTH FACE


BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 In)	Sq. Ft.	139
Epoxy Crack Injection	Foot	53
Temporary Shoring and Cribbing	Each	4


GIRDER REACTION TABLE

Pier 3	Load (kips)
DL	79.4
LL	53.2
IM	15.6
TOTAL	148.2

Reactions are per girder




VIEW D-D




VIEW C-C



VIEW A-A



VIEW B-B



WEST FACE
(Looking East)

NOTES:

- Quantities and limits shown are estimates for bidding purposes only. The actual area to be repaired, and the type(s) of repairs to be used, will be determined by the engineer in the field at the time of construction.
- Removal and installation of drainage pipes, electrical cables conduits, or other items attached to the existing structure are included in the cost of Structural Repair of Concrete.
- Concrete repairs directly under Girders shall not start until the Temporary Shoring is installed.
- Existing Name Plate that interferes with Structural Repair of Concrete should be removed prior to repair and reinstalled after repair is completed. Cost included in Structural Repair of Concrete (Depth Equal to or less than 5 inches)

LEGEND:

- Structural Repair of Concrete (Depth Equal to or Less Than 5 inches)
- Epoxy Crack Injection
- Temporary Shoring and Cribbing



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PIER 3 REPAIRS
STRUCTURE NO. 016-0914

SHEET S07-21 OF S07-25 SHEETS




F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	660
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 2016-0914 - 154th over I-94\Sheets\22_016-0914-BeamStraighteningDetails.dgn
12/06/24 3:08:39 PM



PARTIAL PLAN
SUGGESTED BEAM STRAIGHTENING METHODS


NOTE: Straightening force shall be maintained on all load transfer blocking during beam straightening.



SUGGESTED VERTICAL STRAIGHTENING DETAIL
(To correct localized vertical flange deformations.)

* Edge of plate shall line up with edge of deformation.

NOTE:
Braces and jack assembly shall be placed on same side of web.
Bent bottom flange shall be straightened before starting any horizontal straightening operations.



EXISTING DEFORMATION TO BE STRAIGHTENED
(Looking North)
(Approximate max. deflections)
Deflected length of beam to be straightened is approximately 4'-0".




USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BEAM STRAIGHTENING DETAILS
STRUCTURE NO. 016-0914

SHEET S07-22 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	661
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				




Any voids found under the existing slopewall during the Slopewall Removal process are to be filled with Porous Granular Embankment.



1. Jacking shall be done after existing deck partial removal is completed.
2. The Contractor shall submit for approval by the Engineer plans for jacking, prior to commencing any work at the bearings. The maximum dead load reaction with the deck removed (per bearing) at the west and east abutments = 16 kips. The minimum jack capacity at each beam shall be 32 kips at the west and east abutments.
3. Top of beam elevations shall be measured prior to jacking and shall remain the same after bearings are in place.
4. There shall be at least one jack per bearing, and the jack shall be placed close to the bearing. The steel shall be raised a maximum of 1/8 inch and shall be blocked in position until after the completion of the installation of new bearings.
5. Burn the existing anchor bolts flush with the concrete surface, grind smooth, and seal with epoxy. The top and bottom plates shall be removed. The top plate shall be removed using the air-arc method. Grind smooth all weld material remaining on the bottom flange. Cost of removing anchor, bolts, top plates, and bottom plates shall be included with "Jack and Remove Existing Bearings".
6. The new elastomeric bearings shall be in place and the jacks lowered before the new concrete deck is poured.
7. See sheet S07-16 for bearing bill of materials.

ITEM	UNIT	QUANTITY
Porous Granular Embankment	Cu Yd	2
Slope Wall Removal	Sq Yd	3
Slope Wall 4 Inch	Sq Yd	3
Epoxy Crack Injection	Foot	106

MODEL: Default
FILE NAME: pw:\3\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various\Structures\Work Order 2016-0914 - 154th over I-94\Sheets\24_016-0914-BarSplicer Assembly.dgn




STANDARD BAR SPLICER ASSEMBLY PLAN

Only bar splicer assemblies as presented on the approved QPL list may be used.

Threaded splicer bar length = min. lap length + 1 1/2" + thread length

* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies required	Minimum lap length
W. Abutment	#5	9	3'-9"
W. Abutment	#6	4	4'-0"
E. Abutment	#5	9	3'-9"
E. Abutment	#6	4	4'-0"




INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.

"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required

Notes:
Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.
All reinforcement shall be lapped and tied to the splicer bars.
Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.
See approved list of bar splicer assemblies and mechanical splicers for alternatives.

BSD-1

5-15-2023



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BAR SPLICER ASSEMBLY DETAILS
STRUCTURE NO. 016-0914


SHEET S07-24 OF S07-25 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	663
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				


[illegible]

PLAN

STRUCTURAL STEEL:
 $f_s = 20,000$ psi A36 (M 183 Steel)
 Proposed
 $f_s = 18,000$ psi A33 Existing




James S. Rayburn
Professor of Biology and Zoology




STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION
GENERAL PLAN
154TH STREET OVER (I-94)
SECTION ~~FAI RTE 94~~ COOK COUNTY
STA. 550+00.00
S.N. 016-0914

DATE MAY 1989 CHECKED BY L. M.

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	664
		CONTRACT NO. 62W87		
ILLINOIS		FED. AID PROJECT		




ELEVATION




STATION 550 + 00.00
RE-BUILT 199 BY
STATE OF ILLINOIS
RT. 154 ST. SEC. 0905040606 DIB
F.A. PROJ. AC 11-94.3 (262)
LOADING HS20
STR. NO. 016-0914


NAME PLATE
See Std 2113



PROPOSED PROFILE - 154 TH. ST.



PROPOSED PROFILE I-94



See Std. 2344-1

DETAIL - A PLAN

SECTION E - E

GUARDRAIL MOUNTING DETAILS AT WINGWALLS

For Sections B, C & D see Traffic Barrier Terminal Type 7 Std. 2344-1.
For Standard 2344-1 Modification See Layout at N.E. Wingwall
& Section A-A. (#) TRAFFIC BARRIER TERMINAL TX 7 (Special)



USER NAME =	DESIGNED - JS	REVISED -
	CHECKED - RRD	REVISED -
PLOT SCALE =	DRAWN - SVJ	REVISED -
PLOT DATE =	CHECKED - RRD	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


**EXISTING GENERAL PLAN AND ELEVATION
STRUCTURE NO. 016-0914**

SHEET S07-25 OF S07-25 SHEETS


12/06/24 3:08:51 PM

Bench Mark: "X" scribed in chiseled box on top of concrete barrier wall at the southeast corner of bridge structure for Westbound FAI-94 over the Greenwood Avenue Elev. 627.12 (Assumed Local Datum)

Existing Structure: S.N. 016-0162 originally constructed in 1947 as a 4 span structure. In 1981, the structure was widened with a new deck and new beam lines on both sides of the superstructure. All superstructure was cleaned and painted. In 2009, the approach slabs, deck joints at abutments and deck overlay were replaced. The deck joint between the center parapets was resealed. Abutment bearings were replaced with elastomeric bearings. The steel beam ends and end diaphragms at abutments were cleaned and painted.



ELEVATION



PLAN

DESIGN SPECIFICATIONS
2002 AASHTO Standard Specifications
for Highway Bridges, 17th Edition

DESIGN STRESSES

FIELD UNITS (New Construction)

$f'_c = 4,000$ psi (Superstructure)

$f'_c = 3,500$ psi (Substructure)

$f_y = 60,000$ psi (Reinforcement)

$f_y = 50,000$ psi (M270 Grade 50)

FIELD UNITS (2009 Repairs)

$f'_c = 3,500$ psi (Concrete - Deck Slab)

$f_y = 60,000$ psi (Reinforcement - Deck Slab)

$f_s = 36,000$ psi (M270 Grade 36)

FIELD UNITS (1980 Rehab)

$f'_c = 3,500$ psi (Concrete - Deck Slab)

$f_c = 1,400$ psi (Substructure)

$f_y = 60,000$ psi (Reinforcement - Deck Slab)

$f_s = 20,000$ psi (Reinforcement- Substructure)

$f_s = 20,000$ psi (Structural Steel) (M183 Grade 36)

FIELD UNITS (1946 Original Construction)

$f_s = 18,000$ psi (A7 Struct. Steel)

$f'_c = 1,200$ psi (Superstructure)


$f_y = 20,000$ psi (Reinforcement)

$f'_c = 800$ psi (Concrete - Substructure)


LOADING HL-93

SCOPE OF WORK

1. Remove the existing bridge deck overlay.
2. Repair deck with partial and full depth patches.
3. Repair of bridge approach slabs.
4. Removal and replacement of expansion joints at the abutments.
5. Install a $\frac{3}{8}$ " thin polymer overlay.
6. Substructure and slopewall repairs.
7. Repair steel beams at corroded deck drain connections and beam ends.



EXISTING PROFILE GRADE FAI-94



LOCATION SKETCH

GENERAL PLAN AND ELEVATION
I-94 OVER GREENWOOD AVE
FAI 94 SEC. 1975-079-BR

COOK COUNTY

STATION 570+46.70

SN 016-0162



William P. Malinowski S.E.
Licensed Structural Engineer
State of Illinois No. 081-006059
Registration Expires 11/30/2026


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SHEET S08-01 OF S08-19 SHEETS

FAI RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	665
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

GENERAL NOTES

1. No field welding is permitted except as specified in the contract documents.
2. Reinforcement bars designated (E) shall be epoxy coated.
3. As directed by the Engineer, existing construction accessories welded to the top flange of beams and girders shall be removed. The weld areas shall be ground flush and inspected for cracks using magnetic particle testing (MT) or dye penetrant testing (PT) by qualified personnel approved by the Engineer. Any cracks that cannot be removed by grinding ¾ inch deep shall be identified and reported to the Bureau of Bridges and Structures for further disposition. The cost of removing welded accessories, grinding and inspecting weld areas and grinding cracks will be paid for according to Article 109.04 of the Standard Specifications.
4. Plan dimensions and details relative to the existing structure have been taken from existing plans are subject to nominal construction variations. The Contactor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.
5. Existing reinforcement shall be cleaned, straightened and incorporated into the new construction. Cost included with Concrete Removal.
6. Fasteners shall be ASTM F 3125 Grade A325 Type 1. Fastener shall be hot dip galvanized. See Special Provision for "Hot Dip Galvanizing for Structural Steel." Bolts ¾ in. Ø holes 1⅝ in. Ø, unless otherwise noted.
7. All new structural steel shall be galvanized. See Special Provision for "Hot Dip Galvanizing for Structural Steel."
8. Existing structural steel that will be in contact with new structural steel shall be cleaned and painted prior to erection as required by the Special Provision "Cleaning and Painting Contact Surface Areas of Existing Steel Structures."
9. The existing structural steel coating contains lead. The Contractor shall take appropriate precautions to address the presence of lead on this project.
10. Any reinforcement bars that are damaged during concrete removal operations shall be repaired or replaced using an approved bar splicer or anchorage system. Cost incidental to "Concrete Removal".
11. Calculated weight of Structural Steel = 2,008 lbs.
12. Cleaning and field painting of the existing structural steel shall be done under a separate painting contract.
13. Cost of removal and re-installation of all members necessary to complete the work as detailed on the plans and as specified in the Special Provisions shall be included with Structural Steel Repair.



EXISTING SLAB

SECTIONS THRU SLAB OR DECK BEAM

INDEX OF SHEETS

S08-01	General Plan and Elevation
S08-02	General Data
S08-03	Construction Staging - 1
S08-04	Construction Staging - 2
S08-05	Deck Repair Plan
S08-06	North Abutment Expansion Joint Reconstruction Plan
S08-07	South Abutment Expansion Joint Reconstruction Plan
S08-08	Abutment Expansion Joint Reconstruction Details - 1
S08-09	Abutment Expansion Joint Reconstruction Details - 2
S08-10	Preformed Joint Strip Seal
S08-11	Framing Plan
S08-12	Steel Beam Repair Details
S08-13	North Abutment Repairs
S08-14	South Abutment Repairs
S08-15	South Slopewall Repairs
S08-16	Pier 1 Repairs
S08-17	Pier 2 Repairs
S08-18	Pier 3 Repairs
S08-19	Bar Splicer Assembly Details

TOTAL BILL OF MATERIAL

ITEM	UNIT	SUPER- STRUCTURE	SUB- STRUCTURE	TOTAL
Porous Granular Embankment	Cu. Yd.	-	211	211
Concrete Removal	Cu. Yd.	23	9	32
Slope Wall Removal	Sq Yd.	-	159	159
Protective Shield	Sq Yd.	1,114	-	1,114
Concrete Structures	Cu. Yd.	-	9.0	9.0
Concrete Superstructure	Cu. Yd.	23.0	-	23.0
Protective Coat	Sq Yd.	10	-	10
Reinforcement Bars, Epoxy Coated	Pound	4,730	1,220	5,950
Bar Splicers	Each	52	12	64
Slope Wall 4 Inch	Sq Yd.	-	159	159
Preformed Joint Strip Seal	Foot	267	-	267
Epoxy Crack Injection	Foot	-	217	217
Approach Slab Repair (Full Depth)	Sq. Yd.	7	-	7
Structural Steel Repair	Pound	2,010	-	2,010
Cleaning Bridge Seats	Sq. Ft.	-	1,566	1,566
Concrete Bridge Deck Scarification 3/8"	Sq. Yd.	3,860	-	3,860
Bridge Deck Thin Polymer Overlay 3/8"	Sq. Yd.	3,860	-	3,860
Structural Repair of Concrete (Depth Equal to or Less Than 5 Inches)	Sq. Ft.	-	872	872
Deck Slab Repair (Full Depth - Type I)	Sq. Yd.	6	-	6
Deck Slab Repair (Full Depth - Type II)	Sq. Yd.	158	-	158
Deck Slab Repair (Partial)	Sq. Yd.	255	-	255
Expansion Joint (Special)	Foot	313	-	313

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various\Structures\Work Order 1\016-0162 - I-94 over Greenwood Ave\Sheets\02_016-0162 - General Data.dgn




USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

GENERAL DATA
STRUCTURE NO. 016-0162

SHEET S08-02 OF S08-19 SHEETS

F&I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	666
CONTRACT NO. 62W87				
		ILLINOIS	FED. AID PROJECT	




Concrete Removal for Joint
Replacement (see Sheets S08-07 to S08-10)




Approach Slab Repair (Full Depth)



Deck Slab Repair (Full Depth, Type I)




Deck Slab Repair (Full Depth, Type II)




Deck Slab Repair (Partial)

Notes:
Area of deck and approach slab repairs are estimated.
Actual type, location, and dimensions are to be
determined by the Engineer during construction and
documented on as-built plans.

ITEM	UNIT	SUPER	SUB	QUANTITY
Concrete Removal	Cu. Yd.	23	9	32
Approach Slab Repair (Full Depth)	Sq. Yd.	7	-	7
Deck Slab Repair (Full Depth, Type I)	Sq. Yd.	6	-	6
Deck Slab Repair (Full Depth, Type II)	Sq. Yd.	158	-	158
Deck Slab Repair (Partial Depth)	Sq. Yd.	255	-	255



PROPOSED PLAN AT NORTH ABUTMENT





*All reinforcement bars are to be evenly spaced unless otherwise noted.
Reinforcement bars designated (E) shall be epoxy coated.
O.F. denotes Outside Face. I.F. denotes Inside Face.
For Bill of Material and bar details see Sheet S08-10.
For additional abutment backwall demolition and reconstruction see Sheet S08-09.*

**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

SHEET S08-06 OF S08-19 SHEETS

ILLINOIS	FED. AID PROJECT
----------	------------------



NOTES

*All reinforcement bars are to be evenly spaced unless otherwise noted.
Reinforcement bars designated (E) shall be epoxy coated.
O.F. denotes Outside Face. I.F. denotes Inside Face.
For Bill of Material and bar details see Sheet S08-10.
For additional abutment backwall demolition and reconstruction see Sheet S08-09.*

USER NAME	=	DESIGNED	-	BJD	REVISED	-
		CHECKED	-	MGH	REVISED	-
PLOT SCALE	=	DRAWN	-	BJD	REVISED	-
PLOT DATE	=	CHECKED	-	MGH	REVISED	-


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

SOUTH ABUTMENT EXPANSION JOINT RECONSTRUCTION PLAN
STRUCTURE NO. 016-0162


SHEET S08-07 OF S08-19 SHEETS

F.A.I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	671
		CONTRACT NO. 62W87		
ILLINOIS		FED. AID PROJECT		


The Contractor shall exercise extreme care with the existing conduits in sections of the parapet to be removed and to protect and support the conduit. The Contractor will be required to repair any damage done to the conduit to the satisfaction of the Engineer. No splicing will be allowed to any cable damage resulting from this work, instead the Contractor will be required to repair the entire span of any damaged cable.




SECTION A-A




SECTION B-B




MEDIAN PARAPET
SECTION C-C




EB & WB PARPET
SECTION D-D




SECTION E-E




SECTION F-F



MEDIAN PARAPET
SECTION G-G




EB & WB PARPET
SECTION H-H






DETAIL A
(Typical entire length of bridge at median parapet)

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 1\016-0162 - I-94 over Greenwood Ave\Sheets\09_016-0162 - Abutment-Exp-JL-Details-2.dgn




INSIDE ELEVATION OF WEST PARAPET
(East Parapet Similar)



SUPERSTRUCTURE				
BILL OF MATERIAL				
Bar	No.	Size	Length	Shape
a(E)	12	#6	37'-5"	
a1(E)	52	#5	35'-0"	
a2(E)	12	#6	29'-10"	
a3(E)	52	#5	29'-10"	
d(E)	20	#4	5'-0"	
d1(E)	48	#5	4'-1"	
d2(E)	20	#4	4'-0"	
v(E)	8	#6	4'-0"	
v1(E)	8	#6	4'-1"	
x(E)	232	#5	3'-3"	
Concrete Structures		Cu. Yd.	9.0	
Concrete Superstructure		Cu. Yd.	23.0	
Protective Coat		Sq. Yd.	10.0	
Reinforcement Bars, Epoxy Coated		Pound	5,938	
Silicon Joint Sealer, 1"		Foot	313	

Reinforcement bars designated (E) shall be epoxy coated.



Note:
Protective Coat shall be applied to the front faces and tops of newly constructed parapets and medians.



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ABUTMENT EXPANSION JOINT RECONSTRUCTION DETAILS - 2
STRUCTURE NO. 016-0162


SHEET S08-09 OF S08-19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	673
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 1\016-0162 - I-94 over Greenwood Ave\Sheets\10_016-0162 - PreformedStripSeal.dgn
12/9/2024 7:17:46 AM




PLAN AT PARAPET



SECTION AT PARAPET

(Skews > 30° shown. Skews ≤ 30° similar except as shown in plan view.)




SHOWING ROLLED RAIL JOINT


* 5/8" Ø x 6" studs @ 6" cts. (alternate angled/bent studs with horizontal studs)
3/8" Ø threaded rods in 7/16" Ø holes at ±4'-0" cts. for holding the proper joint opening based on the temperature during the deck pour. Place to miss studs. All rods shall be burned, or sawed off flush with the plates after concrete is set.

SECTION A-A


* Granular or solid flux filled headed studs conforming to Article 1006.32 of the Std. Specs., automatically end welded.



SECTION B-B




DETAIL A




TRIMETRIC VIEW

(Showing embedded plates only)




SHOWING WELDED RAIL JOINT



LOCKING EDGE RAILS

** Back gouge not required if complete joint penetration is verified by mock-up.



LOCKING EDGE RAIL SPLICE

The inside of the locking edge rail groove shall be free of weld residue. Rolled rail shown, welded rail similar.

BILL OF MATERIAL

Item	Unit	Total
Preformed Joint Strip Seal	Foot	267



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PREFORMED JOINT STRIP SEAL
STRUCTURE NO. 016-0162

SHEET S08-10 OF S08-19 SHEETS

F.A.I. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	674
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com:wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various\Structures\Work Order 1\016-0162 - I-94 over Greenwood Ave\Sheets\11_016-0162 - FramingPlan.dgn



FRAMING PLAN

- (A)- Beam End Repairs, 40" (5 Locations).
See Sheet S08-12 for details.
- (B)- Beam End Repairs, 20" (2 Locations).
See Sheet S08-12 for details.
- (C)- Beam 8 Top and Bottom Flange Repairs.
See Sheet S08-12 for details.
- (D)- Beam 9 Top and Bottom Flange and Web Repairs (Includes repair to the web at corroded deck drain).
See Sheet S08-12 for details.



USER NAME	=	DESIGNED	-	BJD	REVISED	-	
		CHECKED	-	MGH	REVISED	-	
PLOT SCALE	=	DRAWN	-	BJD	REVISED	-	
PLOT DATE	=	CHECKED	-	MGH	REVISED	-	


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

FRAMING PLAN
STRUCTURE NO. 016-0162


SHEET S08-11 OF S08-19 SHEETS

F.A.I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	675
CONTRACT NO. 62W87				
		ILLINOIS	FED. AID PROJECT	


MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 1\016-0162 - I-94 over Greenwood Ave\Sheets\12_016-0162_Steel Beam Repair Details.dgn



DETAIL A




DETAIL B




DETAIL C

SECTION A-A



DETAIL D



SECTION B-B

SECTION C-C

SECTION D-D

NOTES:

- Distance from top of main girder to top of diaphragm to be field verified prior to ordering material.
- Contractor to field verify diaphragm location and bolt hole locations before ordering material.
- No welds are to be installed on the back/end of the beam. All welds are included in the cost of Structural Steel Repair.
- Contractor to field verify hole locations before ordering material. Contractor can elect to field drill holes in repair plates.

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Steel Repair	Pound	2,010

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

STEEL BEAM REPAIR DETAILS
STRUCTURE NO. 016-0162


SHEET S08-12 OF S08-19 SHEETS

FAI RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	676
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				




USER NAME =	DESIGNED - BJD	REVISED -
PLOT SCALE =	CHECKED - MGH	REVISED -
PLOT DATE =	DRAWN - BJD	REVISED -
	CHECKED - MGH	REVISED -


MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 1\016-0162 - I-94 over Greenwood Ave\Sheets\13_016-0162 - NorthAbutment.dgn



NORTH ABUTMENT ELEVATION




NORTH ABUTMENT ELEVATION




NORTH ABUTMENT ELEVATION

LEGEND:



Concrete Removal, for Information Only
(see Sheets S08-05 - S08-08)




Structural Repair Of Concrete
(Depth Equal To Or Less Than 5 In)

BILL OF MATERIAL


ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 In)	Sq. Ft.	115

	USER NAME =	DESIGNED - BJD	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	NORTH ABUTMENT REPAIRS STRUCTURE NO. 016-0162	SHEET S08-13 OF S08-19 SHEETS	FAI RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
		CHECKED - MGH	REVISED -				94	(42-B-11-1) BR, BJR 24	COOK	761	677
	PLOT SCALE =	DRAWN - BJD	REVISED -				CONTRACT NO. 62W87				
	PLOT DATE =	CHECKED - MGH	REVISED -				ILLINOIS FED. AID PROJECT				


MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-ll\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 1\016-0162 - I-94 over Greenwood Ave\Sheets\14_016-0162 - South Abutment.dgn



SOUTH ABUTMENT ELEVATION



SOUTH ABUTMENT ELEVATION



SOUTH ABUTMENT ELEVATION

BILL OF MATERIAL

LEGEND:



Concrete Removal, for Information Only
(see Sheets S08-05 - S08-08)



Structural Repair Of Concrete
(Depth Equal To Or Less Than 5 In)

Epoxy Crack Injection

ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 In)	Sq. Ft.	53
Epoxy Crack Injection	Foot	4



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SOUTH ABUTMENT REPAIRS
STRUCTURE NO. 016-0162

SHEET S08-14 OF S08-19 SHEETS


F.A.I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	678
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw\beniley.com:wsp-us-pw-ll\Documents\Project IDOT 2050082201 - IDOT District 1 Various\Structures\Work Order 1\016-0162 - I-94 over Greenwood Ave\Sheets\15_016-0162 - South SlopeWall.dgn



SOUTH SLOPEWALL

LEGEND:




Slope Wall Removal, Porous Granular Embankment and Slope Wall 4 Inch

BILL OF MATERIAL


ITEM	UNIT	QUANTITY
Porous Granular Embankment	Cu. Yd.	211
Slope Wall Removal	Sq. Yd.	159
Slope Wall 4 Inch	Sq. Yd.	159

12/9/2024 7:18:03 AM

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-ll\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 1\016-0162 - I-94 over Greenwood Ave\Sheets\16_016-0162 - Pier 1.dgn




PIER 1 NORTH FACE



PIER 1 SOUTH FACE

LEGEND:



Structural Repair Of Concrete
(Depth Equal To Or Less Than 5 In)

Epoxy Crack Injection

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 In)	Sq. Ft.	190.5
Epoxy Crack Injection	Foot	50.5



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PIER 1 REPAIRS
STRUCTURE NO. 016-0162


SHEET S08-16 OF S08-19 SHEETS

F&I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	680
CONTRACT NO. 62W87				
		ILLINOIS	FED. AID PROJECT	

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 1\016-0162 - I-94 over Greenwood Ave\Sheets\17_016-0162 - Pier 2.dgn




PIER 2 NORTH FACE



PIER 2 SOUTH FACE

LEGEND:



Structural Repair Of Concrete
(Depth Equal To Or Less Than 5 In)



Epoxy Crack Injection

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 In)	Sq. Ft.	190.5
Epoxy Crack Injection	Foot	77




USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION


PIER 2 REPAIRS
STRUCTURE NO. 016-0162

SHEET S08-17 OF S08-19 SHEETS

FAI RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	681
CONTRACT NO. 62W87				
ILLINOIS		FED. AID PROJECT		



PIER 3 NORTH FACE



PIER 3 SOUTH FACE

LEGEND:



Structural Repair Of Concrete (Depth Equal To Or Less Than 5 In)

Epoxy Crack Injection

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 In)	Sq. Ft.	322.5
Epoxy Crack Injection	Foot	85.5

USER NAME	=	DESIGNED	-	BJD	REVISED	-
		CHECKED	-	MGH	REVISED	-
PLOT SCALE	=	DRAWN	-	BJD	REVISED	-
PLOT DATE	=	CHECKED	-	MGH	REVISED	-


**STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION**

PIER 3 REPAIRS
STRUCTURE NO. 016-0162

SHEET S08-18 OF S08-19 SHEETS

F.A.J RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	682
CONTRACT NO. 62W87				
ILLINOIS		FED. AID PROJECT		

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various\Structures\Work Order 1\016-0162 - I-94 over Greenwood Ave\Sheets\19_016-0162 - BarSplicerAssemblyDetails.dgn




STANDARD BAR SPLICER ASSEMBLY PLAN

Only bar splicer assemblies as presented on the approved QPL list may be used.

Threaded splicer bar length = min. lap length + 1½" + thread length

* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies required	Minimum lap length
Abutment	#6	12	4'-5"
Deck	#5	52	3'-1"




INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.

"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required

Notes:
Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.
All reinforcement shall be lapped and tied to the splicer bars.
Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.
See approved list of bar splicer assemblies and mechanical splicers for alternatives.

BSD-1

2-1-2023



USER NAME =	DESIGNED -	BJD	REVISED -
	CHECKED -	MGH	REVISED -
	DRAWN -	BJD	REVISED -
	CHECKED -	MGH	REVISED -
PLOT SCALE =			
PLOT DATE =			

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS
STRUCTURE NO. 016-0162

SHEET S08-19 OF S08-19 SHEETS

F&I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	683
CONTRACT NO. 62W87				
		ILLINOIS	FED. AID PROJECT	

Bench Mark: "X" scribed in chiseled box on top of concrete barrier wall at the southeast corner of bridge structure for Westbound FAI-94 over the Little Calumet River Elev. 606.96 (Assumed Local Datum)

Existing Structure: S.N. 016-0163 originally constructed in 1947 as a 3 span structure. In 1981, the structure was widened with a new deck and new beam lines on both sides of the superstructure. All superstructure was cleaned and painted. In 2009, the approach slabs, deck joints at abutments and deck overlay were replaced. The deck joint between the center parapets was resealed. Abutment bearings were replaced with elastomeric bearings. The steel beam ends and end diaphragms at abutments were cleaned and painted.

Traffic to be maintained utilizing staged construction.

DESIGN SPECIFICATIONS
2002 AASHTO Standard Specifications
for Highway Bridges, 17th Edition

DESIGN STRESSES

FIELD UNITS (New Construction)

f'c = 4,000 psi (Superstructure)

f'c = 3,500 psi (Substructure)

fy = 60,000 psi (Reinforcement)

fy = 50,000 psi (M270 Grade 50)

FIELD UNITS (2009 Repairs)

f'c = 3,500 psi (Concrete - Deck Slab)

fy = 60,000 psi (Reinforcement - Deck Slab)

fs = 36,000 psi (M270 Grade 36)

FIELD UNITS (1980 Rehab)

f'c = 3,500 psi (Concrete - Deck Slab)

fc = 1,400 psi (Substructure)

fy = 60,000 psi (Reinforcement - Deck Slab)

fs = 20,000 psi (Reinforcement- Substructure)

fs = 20,000 psi (Structural Steel) (M183 Grade 36)

FIELD UNITS (1946 Original Construction)

fs = 18,000 psi (A7 Struct. Steel)

f'c = 1,200 psi (Superstructure)


fy = 20,000 psi (Reinforcement)

f'c = 800 psi (Concrete - Substructure)


LOADING HL-93

SCOPE OF WORK

- Scarify 2½" of the existing bridge deck.
- Repair deck with partial and full depth patches.
- Repair of bridge approach slabs.
- Removal and replacement of expansion joints at the abutments.
- Clean the existing floor drains and plug the floor drains within 10 feet of abutments.
- Install enclosed drainage system.
- Install a 2¾" latex concrete overlay.
- Perform ¼" Diamond Grinding to the top of bridge deck and abutment hatch block.
- Perform Bridge Deck Grooving (Longitudinal) on traffic lanes.
- Apply Protective Coat to the top of the reconstructed transverse joints, top of new Latex Concrete Overlay, and top and inside face of parapets.
- Repair steel beams at North Abutment.
- Perform Substructure repairs.




ELEVATION



2½" Deck Scarification and
2¾" Latex Concrete Overlay.
Perform ¼" Diamond Grinding
and apply Protective Coat.

PLAN




EXISTING PROFILE GRADE FAI-94

The Profile Grade shows the
final grade after grinding.



William P. Malinowski S.E.
Licensed Structural Engineer
State of Illinois No. 081-006059
Registration Expires 11/30/2026



LOCATION SKETCH

GENERAL PLAN AND ELEVATION
I-94 OVER LITTLE CALUMET RIVER
FAI 94 SEC. 1975-079-BR
COOK COUNTY
STATION 581+35.50
SN 016-0163

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\01_016-0163 - GPE.dgn
3/10/2025 1:14:07 PM



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SHEET S09-01 OF S09-15 SHEETS

FAI RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	684
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

GENERAL NOTES

1. No field welding is permitted except as specified in the contract documents.

2. Reinforcement bars designated (E) shall be epoxy coated.

3. Plan dimensions and details relative to the existing structure have been taken from existing plans are subject to nominal construction variations. The Contactor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.

4. Existing reinforcement shall be cleaned, straightened and incorporated into the new construction. Cost included with Concrete Removal.

5. The existing structural steel coating contains lead. The Contractor shall take appropriate precautions to address the presence of lead on this project.

6. Cleaning and painting of the existing structural steel shall be done under a separate painting contract.


7. Any reinforcement bars that are damaged during concrete removal operations shall be repaired or replaced using an approved bar splicer or anchorage system. Cost incidental to "Concrete Removal".

8. Joint openings shall be adjusted according to Article 520.04 of the Standard Specifications when the joint concrete is poured at an ambient temperature other than 50°F.

9. All exposed concrete edges shall have a ¾" x 45° chamfer except where shown otherwise.

10. As directed by the Engineer, existing construction accessories welded to the top flange of beams and girders shall be removed. The weld areas shall be ground flush and inspected for cracks using magnetic particle testing (MT) or dye penetrant testing (PT) by qualified personnel approved by the Engineer. Any cracks that cannot be removed by grinding ¾ inch deep shall be identified and reported to the Bureau of Bridges and Structures for further disposition. The cost of removing welded accessories, grinding and inspecting weld areas and grinding cracks will be paid for according to Article 109.04 of the Standard Specifications.

11. Up to ¼ inch to be ground off the bridge deck and the bridge approach slabs. The Profile Grade shows the final grade after grinding.



SECTIONS THRU SLAB OR DECK BEAM

INDEX OF SHEETS


S09-01	General Plan and Elevation
S09-02	General Data
S09-03	Construction Staging - 1
S09-04	Construction Staging - 2
S09-05	Deck Repair Plan
S09-06	North Abutment Expansion Joint Reconstruction Plan
S09-07	South Abutment Expansion Joint Reconstruction Plan
S09-08	Abutment Expansion Joint Reconstruction Details - 1
S09-09	Abutment Expansion Joint Reconstruction Details - 2
S09-10	Preformed Joint Strip Seal
S09-10A	Framing Plan
S09-10B	Steel Beam Repair Details
S09-11	Abutment Repairs
S09-12	Pier 1 Repairs
S09-13	Pier 2 Repairs
S09-14	Enclosed Drainage System
S09-15	Bar Splicer Assembly and Mechanical Splicer Details

TOTAL BILL OF MATERIAL


ITEM	UNIT	SUPER-STRUCTURE	SUB-STRUCTURE	TOTAL
Concrete Removal	Cu. Yd.	23	9	32
Protective Shield	Sq. Yd.	1,354		1,354
Concrete Structures	Cu. Yd.		9.0	9.0
Concrete Superstructure	Cu. Yd.	23.0		23.0
Protective Coat	Sq. Yd.	4,085		4,085
Reinforcement Bars, Epoxy Coated	Pound	4,460	1,130	5,590
Bar Splicers	Each	52	12	64
Preformed Joint Strip Seal	Foot	247		247
Epoxy Crack Injection	Foot		38	38
Plug Existing Floor Drains	Each	8		8
Bridge Deck Grooving (Longitudinal)	Sq. Yd.	2,972		2,972
Bridge Drainage System	Each	1		1
Approach Slab Repair (Full Depth)	Sq. Yd.	1		1
Approach Slab Repair (Partial Depth)	Sq. Yd.	53		53
Structural Steel Repair	Pound	300		300
Bridge Latex Concrete Overlay 2 3/4"	Sq. Yd.	3,333		3,333
Cleaning Bridge Seats	Sq. Ft.		1,346	1,346
Clean Existing Inlets	Each	40		40
Bridge Deck Scarification 2 1/2"	Sq. Yd.	3,333		3,333
Structural Repair of Concrete (Depth Equal to or Less Than 5 Inches)	Sq. Ft.		65	65
Deck Slab Repair (Full Depth - Type I)	Sq. Yd.	59		59
Deck Slab Repair (Full Depth - Type II)	Sq. Yd.	95		95
Expansion Joint (Special)	Foot	271		271
Diamond Grinding (Bridge Section)	Sq. Yd.	3,303		3,303

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various\Structures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\02_016-0163 - General Data.dgn

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\03_016-0163 - Construction Staging 1.dgn



STAGE I CONSTRUCTION
(Looking South)



STAGE II CONSTRUCTION
(Looking South)




USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

CONSTRUCTION STAGING - 1
STRUCTURE NO. 016-0163


SHEET S09-03 OF S09-15 SHEETS

F&I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	686
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				




FINAL CROSS SECTION
(Looking South)

	USER NAME =	DESIGNED - BJD	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION	CONSTRUCTION STAGING - 2 STRUCTURE NO. 016-0163	F&I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.	
		CHECKED - MGH	REVISED -			94	(42-B-11-1) BR, BJR 24	COOK	761	687	
	PLOT SCALE =	DRAWN - BJD	REVISED -					CONTRACT NO. 62W87			
	PLOT DATE =	CHECKED - MGH	REVISED -			SHEET S09-04 OF S09-15 SHEETS		ILLINOIS FED. AID PROJECT			




PROPOSED PLAN AT NORTH ABUTMENT




*All reinforcement bars are to be evenly spaced unless otherwise noted.
Reinforcement bars designated (E) shall be epoxy coated.
O.F. denotes Outside Face. I.F. denotes Inside Face.
For Bill of Material and bar details see Sheet S09-10.
For additional abutment backwall demolition and reconstruction see Sheet S09-09.*

12/9/2024 7:20:36 AM

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\07_016-0163 - Abutment-Exp-I-2.dgn



REMOVAL PLAN AT SOUTH ABUTMENT



PROPOSED PLAN AT SOUTH ABUTMENT

NOTES

All reinforcement bars are to be evenly spaced unless otherwise noted.
Reinforcement bars designated (E) shall be epoxy coated.
O.F. denotes Outside Face. I.F. denotes Inside Face.
For Bill of Material and bar details see Sheet S09-10.
For additional abutment backwall demolition and reconstruction see Sheet S09-09.



USER NAME	=	DESIGNED	-	BJD	REVISED	-
		CHECKED	-	MGH	REVISED	-
PLOT SCALE	=	DRAWN	-	BJD	REVISED	-
PLOT DATE	=	CHECKED	-	MGH	REVISED	-


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

SOUTH ABUTMENT EXPANSION JOINT RECONSTRUCTION PLAN
STRUCTURE NO. 016-0163


SHEET S09-07 OF S09-15 SHEETS

F.A.I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	690
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\08_016-0163 - I-94 over Little Calumet River\Exp-I-Details-1.dgn




SECTION A-A




SECTION B-B


The Contractor shall exercise extreme care with the existing conduits in sections of the parapet to be removed and to protect and support the conduit. The Contractor will be required to repair any damage done to the conduit to the satisfaction of the Engineer. No splicing will be allowed to any cable damage resulting from this work, instead the Contractor will be required to repair the entire span of any damaged cable.




MEDIAN PARAPET
SECTION C-C




EB & WB PARAPET
SECTION D-D




SECTION E-E




SECTION F-F



MEDIAN PARAPET
SECTION G-G



EB & WB PARAPET
SECTION H-H



DETAIL A
(Typical entire length of bridge)

* After 1/4" Diamond Grinding



USER NAME =	DESIGNED - BJD	REVISED -
PLOT SCALE =	CHECKED - MGH	REVISED -
PLOT DATE =	DRAWN - BJD	REVISED -
	CHECKED - MGH	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ABUTMENT EXPANSION JOINT RECONSTRUCTION DETAILS - 1
STRUCTURE NO. 016-0163




SHEET S09-08 OF S09-15 SHEETS

FAI RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BUR 24	COOK	761	691
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\09_016-0163 - Abutment-Exp-I-Details-2.dgn




INSIDE ELEVATION OF EAST PARAPET
(West Parapet Similar)



SUPERSTRUCTURE				
BILL OF MATERIAL				
Bar	No.	Size	Length	Shape
a(E)	12	#6	34'-8"	
a1(E)	52	#5	32'-4"	
a2(E)	12	#6	27'-7"	
a3(E)	52	#5	27'-7"	
d(E)	20	#4	5'-0"	
d1(E)	48	#5	4'-1"	
d2(E)	20	#4	4'-0"	
v(E)	8	#6	4'-0"	
v1(E)	8	#6	4'-1"	
x(E)	232	#5	3'-3"	
Concrete Structures		Cu. Yd.	9.0	
Concrete Superstructure		Cu. Yd.	23.0	
Protective Coat		Sq. Yd.	10	
Reinforcement Bars, Epoxy Coated		Pound	5,580	
Silicon Joint Sealer, 1"		Foot	271	


Reinforcement bars designated (E) shall be epoxy coated.

* After 1/4" Diamond Grinding




Note:
Protective Coat shall be applied to the front faces and tops of newly constructed parapets and medians.

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\10_016-0163 - PreformedStripSeal.dgn
12/9/2024 7:20:49 AM




PLAN AT PARAPET




SECTION AT PARAPET


(Skews > 30° shown. Skews ≤ 30° similar except as shown in plan view.)




DETAIL A



SECTION B-B



TRIMETRIC VIEW
(Showing embedded plates only)




SHOWING ROLLED RAIL JOINT


* 5/8" Ø x 6" studs @ 6" cts. (alternate angled/bent studs with horizontal studs)
3/8" Ø threaded rods in 7/16" Ø holes at ±4'-0" cts. for holding the proper joint opening based on the temperature during the deck pour. Place to miss studs. All rods shall be burned, or sawed off flush with the plates after concrete is set.

SECTION A-A

* Granular or solid flux filled headed studs conforming to Article 1006.32 of the Std. Specs., automatically end welded.
*** Before 1/4" Diamond Grinding




SHOWING WELDED RAIL JOINT



LOCKING EDGE RAILS

** Back gouge not required if complete joint penetration is verified by mock-up.



LOCKING EDGE RAIL SPLICE

The inside of the locking edge rail groove shall be free of weld residue.
Rolled rail shown, welded rail similar.

BILL OF MATERIAL

Item	Unit	Total
Preformed Joint Strip Seal	Foot	247

Notes:

The strip seal shall be made continuous and shall have a minimum thickness of 1/4". The configuration of the strip seal shall match the configuration of the locking edge rails. Open or "webbed" strip seal gland configurations are not permitted. The gland shall be sized for a maximum rated movement of 4 inches.

The locking edge rails depicted are configured for typical applications and are conceptual only. The actual configuration of the locking edge rails and matching strip seal may vary from manufacturer to manufacturer provided they fit the application and meet the minimum anchorage shown. Flanged edge rails, however, will not be allowed. Locking edge rails may exceed the 4 1/2" maximum depth provided the anchorage system is revised according to the manufacturer's recommendation.

The manufacturer's recommended installation methods shall be followed.

All steel components shall be galvanized after fabrication according to Article 520.03 of the Standard Specifications.

The Maximum space between locking edge rail segments shall be 3/16" and sealed with a suitable sealant; however, any rail joint within 10' measured perpendicular to the face of the curb or parapet shall be welded as shown in the locking edge rail splice detail.

Cost of parapet sliding plates, embedded plates, and anchorage studs included with Preformed Joint Strip Seal.

39" constant slope barrier shown, 44" constant slope barrier similar as noted.

The concrete opening below the strip seal will vary based on the locking edge rail chosen by the Contractor. Deck and parapet lengths shown elsewhere in the plans are dimensioned to the concrete opening, not the joint opening, and are based on the rolled locking edge rail. If the Contractor elects to use a different locking edge rail, dimensional adjustments may be required. One exception to this would be the strip seal joint at the end of the precast bridge approach slab. For these cases the pavement connector length shall be adjusted, not the length of the bridge approach slab.



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

MODIFIED PREFORMED JOINT STRIP SEAL
STRUCTURE NO. 016-0163

SHEET S09-10 OF S09-15 SHEETS

F&I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	693
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\10A_016-0163 - Framing Plan.dgn



FRAMING PLAN

- (A)- Beam End Repairs, 8"X24" (2 Locations).
See Sheet S09-10A for details.
- (B)- Beam End Repairs, 12"X24" (1 Location).
See Sheet S09-10A for details.




USER NAME	=	DESIGNED - BJD	REVISED -
		CHECKED - MGH	REVISED -
PLOT SCALE	=	DRAWN - BJD	REVISED -
PLOT DATE	=	CHECKED - MGH	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

FRAMING PLAN
STRUCTURE NO. 016-0163

SHEET S09-10A OF S09-15 SHEETS

F.A.I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	693A
CONTRACT NO. 62W87				
		ILLINOIS	FED. AID PROJECT	



ITEM	UNIT	QUANTITY
Structural Steel Repair	Pound	300


כ"ש

USER NAME	=	DESIGNED	-	BJD	REVISED	-
		CHECKED	-	MGH	REVISED	-
PLOT SCALE	=	DRAWN	-	BJD	REVISED	-
PLOT DATE	=	CHECKED	-	MGH	REVISED	-


SHEET S09-10B OF S09-15 SHEETS

F.A.I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	693B
		CONTRACT NO. 62W87		
		ILLINOIS	FED. AID PROJECT	


MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com:wsp-us-pw-IL\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\11_016-0163 - Abutment Repairs.dgn




ELEVATION
(South Abutment)



TOP PLAN



ELEVATION
(North Abutment)



TOP PLAN

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 in)	Sq. Ft.	11
Epoxy Crack Injection	Foot	38

LEGEND:



Concrete Removal for Joint Replacement
(see Sheets S09-07 to S09-10)



Structural Repair Of Concrete
(Depth Equal To Or Less Than 5 in)



Epoxy Crack Injection



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ABUTMENT REPAIRS
STRUCTURE NO. 016-0163


SHEET S09-11 OF S09-15 SHEETS

F&I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	694
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				


MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\12_016-0163 - Pier 1 Repairs.dgn




WEST FACE





TOP PLAN



SOUTH FACE



NORTH FACE



EAST FACE

LEGEND:

Structural Repair Of Concrete
(Depth Equal To Or Less Than 5 in)

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 in)	Sq. Ft.	8



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -


STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PIER 1 REPAIRS
STRUCTURE NO. 016-0163


SHEET S09-12 OF S09-15 SHEETS

F.A.I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	695
CONTRACT NO. 62W87				
		ILLINOIS	FED. AID PROJECT	


MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-IL\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\13_016-0163 - Pier 2 Repairs.dgn




TOP PLAN




WEST FACE



SOUTH FACE



EAST FACE



NORTH FACE

LEGEND:

 Structural Repair Of Concrete
(Depth Equal To Or Less Than 5 in)

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Structural Repair Of Concrete (Depth Equal To Or Less Than 5 In)	Sq. Ft.	46



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -



STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

PIER 2 REPAIRS
STRUCTURE NO. 016-0163

SHEET S09-13 OF S09-15 SHEETS

F.A.I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BJR 24	COOK	761	696
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-IL\Documents\Project IDOT 2050082201 - IDOT District 1 Various Structures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\14_016-0163 - Drainage System for Structures.dgn



SCUPPER LOCATIONS

Station	Offset
580+79.48	57.00' Rt.
581+05.10	57.00' Rt.
581+29.85	57.00' Rt.
581+55.00	57.00' Rt.
580+98.36	1.50' Rt.
581+23.31	1.50' Rt.
581+49.27	1.50' Rt.
581+74.26	1.50' Rt.
581+02.94	1.50' Lt.
581+27.36	1.50' Lt.
581+52.23	1.50' Lt.
581+75.09	1.50' Lt.
581+17.39	57.00' Lt.
581+42.41	57.00' Lt.
581+67.68	57.00' Lt.
581+92.40	57.00' Lt.

- Notes:
- All drain pipes and fittings shall be 8" \odot Reinforced Thermosetting Resin Pipe (RTRP) in accordance with Article 523.02 of the Standard Specifications.
 - All pipe hangers, supports and hardware shall be galvanized by the hot-dip process. The zinc coatings shall conform to the requirements of AASHTO M2332.
 - Pipe hangers/supports shall be provided on all horizontal/vertical pipes at each tee, elbow or change in direction and at intermediate spacings not to exceed those recommended by the manufacturer.
 - Hanger dimensions shall be adjusted in the field by the Engineer to fit existing conditions and to maximize slope.
 - Details shown are schematic only. Contractor to determine required fittings, provisions for expansion/contraction and routing of piping as required to pass diaphragms and maintain minimum slopes.
 - All cost for the components and work required for the drainage system will be included in the pay item Drainage System for Structures (L. Sum.).

BILL OF MATERIAL

ITEM	UNIT	QUANTITY
Drainage System For Structures	L. Sum	1

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

ENCLOSED DRAINAGE SYSTEM
STRUCTURE NO. 016-0163


SHEET S09-14 OF S09-15 SHEETS

F&I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR. BUR 24	COOK	761	697
CONTRACT NO. 62W87				
ILLINOIS		FED. AID PROJECT		



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -

MODEL: Default
FILE NAME: pw:\wsp-us-pw.bentley.com\wsp-us-pw-l\Documents\Project IDOT 2050082201 - IDOT District 1 VariousStructures\Work Order 1\016-0163 - I-94 over Little Calumet River\Sheets\15_016-0163 - BarSplicerAssemblyDetails.dgn




STANDARD BAR SPLICER ASSEMBLY PLAN

Only bar splicer assemblies as presented on the approved QPL list may be used.

Threaded splicer bar length = min. lap length + 1 1/2" + thread length

* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies required	Minimum lap length
Abutment	#6	12	4'-5"
Deck	#5	52	3'-1"




INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.

"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.

(E) : Indicates epoxy coating.



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required

Notes:

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.
All reinforcement shall be lapped and tied to the splicer bars.
Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications.
See approved list of bar splicer assemblies and mechanical splicers for alternatives.

BSD-1

2-1-2023



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - BJD	REVISED -
PLOT DATE =	CHECKED - MGH	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS
STRUCTURE NO. 016-0163


SHEET S09-15 OF S09-15 SHEETS

F&I RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
94	(42-B-11-1) BR, BJR 24	COOK	761	698
CONTRACT NO. 62W87				
		ILLINOIS	FED. AID PROJECT	

3/11/2025 12:45:10 PM

GENERAL NOTES

1. Fasteners shall be ASTM F 3125 Grade A325 Type 1, hot dip galvanized bolts in metallized areas. Bolts $\frac{7}{8}$ in. diameter, holes $\frac{15}{16}$ in. diameter, unless otherwise noted. See Special Provision for "Metallizing of Structural Steel"
2. Calculated weight of Structural Steel = 36,610 (Grade 36)
Calculated weight of Structural Steel = 623,700 (Grade 50)
3. All structural steel shall be metalized. See Special Provision for "Metallizing of Structural Steel."
4. Reinforcement bars designated (E) shall be epoxy coated.
5. The finishing machine rails shall be placed on the top of the top flange of the exterior beams within the deck. Beam blocks shall be placed between beams at all tie locations in each bay for the full width of the deck pour.
6. Slipforming of the parapets is not allowed.
7. Bearing seat surfaces shall be constructed or adjusted to the designated elevations within a tolerance of $\frac{1}{8}$ in. (0.01 ft.). Adjustment shall be made either by grinding the surface or by shimming the bearings.
8. Plan dimensions and details relative to the existing structure have been taken from existing plans are subject to nominal construction variations. The Contactor shall field verify existing dimensions and details affecting new construction and make necessary approved adjustments prior to construction or ordering of materials. Such variations shall not be cause for additional compensation for a change in scope of the work, however, the Contractor will be paid for the quantity actually furnished at the unit price bid for the work.
9. The existing structural steel coating contains lead. The Contractor shall take appropriate precautions to address the presence of lead on this project.
10. All steel rail elements of the Bridge Fence Railing shall be galvanized. See Sht. S10-19 of S10-37.



SECTION THRU ABUTMENT

STA. 344+75.42
RE-BUILT 202X BY
STATE OF ILLINOIS
F.A.P. Rt. 581
Sec. (42-B-11-1) BR, BJR 24
LOADING HL-93
STR. NO. 016-0388

NAME PLATE


See Std. 515001. Existing Name Plate shall be cleaned and relocated next to new Name Plate. Cost included in Name Plates.

INDEX OF SHEETS


- S10-01 General Plan and Elevation
S10-02 General Data
S10-03 Stage Construction Details - 1
S10-04 Stage Construction Details - 2
S10-05 Temporary Concrete Barrier For Stage Construction
S10-06 Top of Deck Slab Elevation Layout
S10-07 Top of Deck Slab Elevations - 1
S10-08 Top of Deck Slab Elevations - 2
S10-09 Top of Deck Slab Elevations - 3
S10-10 Top of West Approach Slab Elevations
S10-11 Top of East Approach Slab Elevations
S10-12 Superstructure - 1
S10-13 Superstructure - 2
S10-14 Superstructure Details
S10-15 Superstructure Details
S10-16 Bridge Approach Slab Details - 1
S10-17 Bridge Approach Slab Details - 2
S10-18 Bridge Fence Railing
S10-19 Bridge Fence Railing
S10-20 Preformed Joint Strip Seal
S10-21 Preformed Joint Strip Seal - Sidewalk
S10-22 Drainage Scupper Details
S10-23 Framing Plan
S10-24 Structural Steel
S10-25 Structural Steel Details
S10-26 Bearing Details
S10-27 West Abutment Removal and Repairs
S10-28 East Abutment Removal and Repairs
S10-29 West Abutment Modifications
S10-30 East Abutment Modifications
S10-30A Abutment Modifications Details - 1
S10-30B Abutment Modifications Details - 2
S10-31 Pier 1 Removal and Repairs
S10-32 Pier 2 Removal and Repairs
S10-33 Pier 3 Removal and Repairs
S10-34 Pier 1 Modifications
S10-35 Pier 2 Modifications
S10-36 Pier 3 Modifications
S10-37 Bar Splicer Assembly and Mechanical Splicer Details

TOTAL BILL OF MATERIAL


ITEM	UNIT	SUPER- STRUCTURE	SUB- STRUCTURE	TOTAL
Removal of Existing Superstructures	Each	1	-	1
Concrete Removal	Cu Yd	-	20.7	20.7
Protective Shield	Sq Yd	1,288	-	1,288
Concrete Structures	Cu Yd	-	127.6	127.6
Concrete Superstructure	Cu Yd	952.6	-	952.6
Bridge Deck Grooving	Sq Yd	2,368	-	2,368
Protective Coat	Sq Yd	3,184	-	3,184
Concrete Superstructure (Approach Slab)	Cu Yd	253.8	-	253.8
Furnishing and Erecting Structural Steel	L Sum	1	-	1
Stud Shear Connectors	Each	14,574	-	14,574
Reinforcement Bars, Epoxy Coated	Pound	361,430	29,920	391,350
Bar Splicers	Each	896	154	1,050
Bridge Fence Railing	Foot	524	-	524
Name Plates	Each	2	-	2
Preformed Joint Strip Seal	Foot	184	-	184
Elastomeric Bearing Assembly, Type I	Each	56	-	56
Anchor Bolts, 1"	Each	112	-	112
Anchor Bolts, 1 1/4"	Each	28	-	28
Concrete Sealer	Sq Ft	-	1,625	1,625
Epoxy Crack Injection	Foot	-	147	147
Bar Terminators	Each	156	-	156
Structural Repair of Concrete (Depth Equal To or Less Than 5 Inches)	Sq Ft	-	207	207
Drainage Scuppers, DS-12	Each	8	-	8




PROFILE GRADE - WB 159TH ST (US 6)



PROFILE GRADE - EB 159TH ST (US 6)



PROFILE GRADE -
I-94 NB (BISHOP FORD)



PROFILE GRADE -
I-94 SB (BISHOP FORD)

MODEL: Default
FILE NAME: pw:\wsp-us-pw-bentley.com\wsp-us-pw-l\Documents\Project IDOT District 1 Various\Structures\Work Order 1\016-0388 - 159th over I-94\Sheets\02_016-0388-General Data.dgn



USER NAME =	DESIGNED - BJD	REVISED -
	CHECKED - MGH	REVISED -
PLOT SCALE =	DRAWN - GM	REVISED -
PLOT DATE =	CHECKED - BJD	REVISED -

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION

GENERAL DATA
STRUCTURE NO. 016-0388

SHEET S10-02 OF S10-37 SHEETS

FAP RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
581	(42-B-11-1) BR, BJR 24	COOK	761	700
CONTRACT NO. 62W87				
ILLINOIS FED. AID PROJECT				