INDEX OF SHEETS

SHEET NO.	DESCRIPTION	STD. NO.	DESCRIPTION
1	COVER SHEET	000001-06	STANDARD SYMBOLS, ABBREVIATIO
2	INDEX OF SHEETS, LIST OF STATE STANDARDS, AND PLAN NOTES	424001 - 07	PERPENDICULAR CURB RAMPS FOR
3-5	SUMMARY OF QUANTITIES	442201 - 03	CLASS C & D PATCHES
6-8	EXISTING AND PROPOSED TYPICAL SECTIONS	606001-04	CONCRETE CURB AND COMBINATION
9-17	EXISTING AND PROPOSED ROADWAY AND PAVEMENT MARKING PLANS	701301 - 04	LANE CLOSURE, 2L. 2W, SHORT TI
18-22	DETECTOR LOOP REPLACEMENT PLANS	701311-03	LANE CLOSURE, 21, 2W, MOVING O
23		- 701501 - 06	LANE CLOSURE. 2L. 2W, UNDIVIDED
24		701606- <i>08</i>	URBAN LANE CLOSURE, MULTILANE
	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT (D8-22)	701701- <i>08</i>	URBAN LANE CLOSURE, MULTILANE
25	CURB OR CURB & GUTTER REMOVAL & REPLACEMENT (08-24)	701901 - 02	TRAFFIC CONTROL DEVICES
26	BUTT JOINT AND HMA TAPER DETAIL (OB-32)	886001-01	DETECTOR LOOP INSTALLATIONS
27	HMA TAPER AT EDGE OF PCC PAVEMENT (DB-33)	701336-06	
28	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS (TC-10)		
29	TYPICAL APPLICATION RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT) (TC-11)		alfort af
30	DISTRICT ONE TYPICAL PAVEMENT MARKINGS (TC-13)		
31	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC) (TC-14)		
32	PAYEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING (TC-16)		
33	ARTERIAL ROAD INFORMATION SIGN (TC-22)		
34	DISTRICT ONE DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING (TS-OS SHEET 1)		

STANDARDS

SCRIPTION NDARD SYMBOLS. ABBREVIATIONS AND PATTERNS PENDICULAR CURB RAMPS FOR SIDEWALKS SS C & D PATCHES CRETE CURB AND COMBINATION CONCRETE CURB AND GUTTER CLOSURE, 2L. 2W, SHORT TIME OPERATIONS. CLOSURE, 2L, 2W, MOVING OPERATIONS, DAY ONLY CLOSURE. 2L. 2W. UNDIVIDED FOR SPEED (45 MPH AN LANE CLOSURE, MULTILANE, 2W. WITH MOUUNTABLE MEDIN AN LANE CLOSURE, MULTILANE INTERSECTION

PLAN NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT (800) 892-0123 OR 811 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS UTILITIES. 48 HOUR NOTIFICATION IS REQUIRED.

TEN (10) FOOT TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURBS AND GUTTER AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN, THE TRANSITIONS SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES, AND THE VILLAGE OF DOLTON, SOUTH HOLLAND, AND THORNTON.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT,

ANY PAVEMENT MARKINGS AND RAISED REFLECTIVE PAVEMENT MARKERS OBLITERATED BY MILLING AND RESURFACING OPERATIONS ON SIDE STREETS AND ENTRANCES SHALL BE REPLACED AND PAID FOR IN KIND.

BEFORE BEGINNING ANY WORK, THE CONTRACTOR SHALL RETAIN AND RECORD FOR FUTURE REFERENCE, ALL EXISTING PAVEMENT MARKING LINES (AND RAISED REFLECTIVE PAVEMENT MARKERS) IN ORDER THAT THESE LOCATIONS CAN BE RE-ESTABLISHED FOR STRIPING. EXACT LOCATIONS OF ALL PAVEMENT MARKINGS SHALL BE AS DIRECTED BY THE ENGINEER.

ALL PAVEMENT PATCHING LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

LOCATION OF COMBINATION CONCRETE CURB AND GUTTER REMOVAL AND REPLACEMENT, WILL BE DETERMINED IN THE FIELD BY THE ENGINEER,

DRAINAGE ADJUSTMENT OR RECONSTRUCTION LOCATIONS WILL BE DETERMINED IN THE FIELD BY THE ENGINEER.

IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.

THE CONTRACTOR SHALL CONTACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS IN ADVANCE OF BEGINNING WORK.

THE ENGINEER SHALL CONTACT MS. PATRICE HARRIS. AREA TRAFFIC FIELD ENGINEER AT (708)-597-9800 A MINIMUM OF TWO WEEKS PRIOR TO THE PLACEMENT OF PERMANENT PAVEMENT MARKINGS.

THESE PLANS HAVE BEEN PREPARED FROM NOTES RECEIVED FROM THE BUREAU OF CONSTRUCTION.

THE THICKNESS OF THE HMA MIXTURE SHOWN ON THE PLANS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HMA MIXTURE IS PLACED.

THE CONTRACTOR SHALL BE REQUIRED TO PROVIDE ACCESS TO ABUTTING PROPERTY AT ALL TIMES DURING THE CONSTRUCTION OF THIS PROJECT.

THE CONTRACTOR WILL BE REQUIRED TO KEEP A RECORD OF THE LOCATIONS OF PLATED STRUCTURES BY STATION AND OFFSET LEFT OR RIGHT OF THE CENTERLINE OF PAVEMENT.

EXISTING BROKEN FRAMES AND LIDS SHALL BE REMOVED AND DISPOSED OF BY THE CONTRACTOR AND SALL BE REPLACED AS DIRECTED BY THE ENGINEER, REPLACEMENT FRAMES AND LIDS WILL BE PAID FOR ACCORDING TO ARTICLE 109.04 OF THE STANDARD SPECIFICATIONS UNLESS A SEPARATE PAY ITEM HAS BEEN PROVIDED.

DO NOT SCALE PLANS FOR CONSTRUCTION DIMENSIONS.

DOUBLE LANE MARKERS ARE TO BE USED AS SHOWN ON THE DISTRICT ONE DETAIL "TYPICAL APPLICATIONS" RAISED REFLECTIVE PAVEMENT MARKERS ISNOW-PLOW RESISTANT!" SHOWN IN THE PLANS.

PAVEMENT MARKING TAPE, TYPE III SHALL BE USED FOR SHORT TERM PAVEMENT MARKINGS ON ALL FINAL SURFACES. THE COST OF THE PAVEMENT MARKING TAPE, TYPE III AND ITS REMOVAL SHALL BE INCLUDED IN THE COST OF SHORT TERM PAVEMENT MARKING.

WHEN THE MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 11/2 INCHES (40 mm) WHERE THE SPEED LIMIT IS 40 MPH (80 Km/h) OR LESS AND 1 INCH (25 mm) WHERE THE SPEED LIMIT IS GREATER THAN 40 MPH (80 Km/h), WITH WRITTEN APPROVAL OF THE ENGINEER, A MAXIMUM GRADE DIFFERENTAL OF 3 INCHES (75 mm) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H).

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING WHERE RESURFACING MEETS EXISTING PAVEMENT) ACCORDING TO THE "BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE ENGINEER WILL CONTACT FOBIOLA OUIROZ OF THE ROADSIDE DEVELOPMENT UNIT AT (847) 705-4596 AT LEAST 7 DAYS PRIOR TO PLANTING FOR APPROVAL OF LAYOUT OF THE TREES WHICH IS TO BE DONE BY THE CONTRACTOR.

į	FILE NAME 2	USER NAME : goglianobt	DESIGNED .	REVISED -
	ci\ps_work\p=idos\gegicenobs\d8295786\0	36986-eht-plon.dgn	DRAWN -	REVISED
		PLOT SCALE : 188,8006 1/ In.	CHECKED -	REVISEO -
		PLOT DATE * 1/8/2013	DATE -	REVISED -

STATE	OF	ILLINOIS
DEPARTMENT (OF '	TRANSPORTATION

SCALE: 1"=50"

CHICAGO RD. (LINCOLN AVE. TO WATER ST.)	F.A.U. RTE.	SECTION	COUNTY	TOTAL	Ţ
INDEX, STANDARDS & GENERAL NOTES	2921	(S.8&R) RS-8	COOK	34	Τ
Letter 12 and Automatical Control of the Control of			CONTRACT	NO, E	60
SHEEL NO. 1 OF L SHEETS STA. TO STA.	EEG 00	NO DICT NO THE WOLF FED A	10 000 668		