


DIAGONAL LINE SPACING: 50' (15 m) C-C (LESS THAN 30MPH (50 km/h)) 75' (25 m) C-C 30MPH (50 km/h; TO 45MPH (70 km/h)) 150' (45 m) C-C (MORE THAN 45NPH (70 km/h))

MEDIANS OVER 4' (1.2 m) WIDE




A WINIMUM OF TWO PAIRS OF TURN ARROWS SHALL BE USED, WHITE IN COLOR. ADDITIONAL PAIRS SHALL BE PLACED AT 200' (60 m) TO 300' (90 m) INTERVALS.



MEDIAN WITH TWO-WAY LEFT TURN LANE

TYPICAL PAINTED MEDIAN MARKING




FULL SIZE LETTERS 8' (2.4 m) AND ARROWS SHALL BE USED. \P AREA = 15.6 SQ. FT. (1.5 m²) \P AREA = 20.8 SQ. FT. (1.9 m²)

* TURN LANES IN EXCESS OF 400' (120 m) IN LENGTH MAY HAVE AN ADDITIONAL SET OF ARROW - "ONLY" INSTALLED MIDWAY BETWEEN THE OTHER TWO SETS OF ARROW - "ONLY".

TYPICAL LEFT (OR RIGHT) TURN LANE

TYPICAL TURN LANE MARKING



TYPICAL ISLAND MARKING

TYPE OF MARKING	WIDTH OF LINE	PATTERN	COLOR	SPACING / REMARKS			
CENTERLINE ON 2 LANE PAVEMENT	4 (100)	SKIP-DASH	YELLOW	10' (3 m) LINE WITH 30' (9 m) SPACE			
CENTERLINE ON MILITI-LANE UNDIVIDED 2 @ 4 (100)		SOLID	YELLOW	11 (280) C-C 51/2 (140) C-C FROM SKIP-DASH CENTERLINE 11 (280) C-C OMIT SKIP-DASH CENTERLINE BEIWEEN			
NO PASSING ZONE LINES: FOR ONE DIRECTION FOR BOTH DIRECTIONS	IRECTION 4 (100)		YELLOW YELLOW				
LANE LINES	4 (100) 5 (125) ON FREEWAYS	SKIP-DASH SKIP-DASH	WHITE WHITE	10' (3 m) LINE WITH 30' (9 m) SPACE			
DOTTED LINES (EXTENSIONS OF CINTER, LANE OR TURN LANE MARKINGS) SAME AS LINE BEING EXTENDED		SKIP-DASH	SAME AS LINE BEING EXTENDED	2' (600) LINE WITH 6' (1.8 m) SPACE			
EDGE LINES	S 4 (100)		YELLOW-LEFT WHITE-RIGHT	OUTLINE MOUNTABLE MEDIANS IN YELLOW: EDGE LINES ARE NOT USED NEXT TO BARRIER CURB			
TURN LANE MARKINGS 6 (150) LINE; FULL SIZE LETTERS & SYMBOLS (8' (2.4m))		SOLID	WHITE	SEE TYPICAL TURN LANE MARKING DETAIL			
TWO WAY LEFT TURN MARKING	2 m 4 (100) EACH DIRECTION	SKIP-DASH AND SOLID	YELLOW	10' (3 m) LINE WITH 30' (9 m) SPACE FOR SKIP-DASH; 51/2 (140) C-C BETWEEN SOLID LINE AND SKIP-DASH LINE			
	8' (2.4m) LEFT ARROW	IN PAIRS	WHITE	SEE TYPICAL TWO-WAY LEFT TURN MARKING DETAIL			
CROSSWALK LINES (PEDESTRIAN) A. DIAGONALS (BIK: & EQUESTRIAN) B. LONGITUDINAL FARS (SCHOOL) 2 © 6 (150) 12 (300) © 45° 12 (300) © 90°		SOLID SOLID SOLID	WHITE WHITE WHITE	NOT LESS THAN 6' (1.8 m) APART 2' (600) APART 2' (600) APART 5' (600) APART 5' (700) APART 5' (700) APART 5' (700) APART 5' (700) APART 6' (700) APART 6' (700) APART 7' (700) APART 8' (7			
STOP LINES 24 (600)		SOLID	WHITE	PLACE 4' 11.2 m) IN ADVANCE OF AND PARALLEL TO CROSSWALK, IF PRESENT. OTHERWIST, PLACE AT DESIRED STOPPING POINT. PARALLEL TO CROSSROAD CENTERLINE, WHERE POSSIBLE			
PAINTED MEDIANS 2 © 4 (100) WITH 12 (300) DIAGONALS © 45° NO DIAGONALS USED FOR 4' (1.2 m) WIDE MEDIANS		SOL10	YELLOW: TWO WAY TRAFFIC WHITE: ONE WAY TRAFFIC	11 (280) C-C FOR THE DOUBLE LINE SEE TYPICAL PAINTED MEDIAN MARKING.			
DRE MARKING ANE 8 (200) WITH 12 (300) HANNELIZING LINES DIAGONALS @ 45°		SOLID	WHITE	DIAGONA.S: 15' (4.5 m) C-C (LESS THAN 30MPH (50 km/h)) 20' (6 m) C-C 30MPH (50 km/h) TO 45MPH (70 km/h)) 30' (9 m) C-C (OVER 45MPH (70 km/h))			
AILROAD CROSSING 24 (600) TRANSVERSE .INES; "RR" IS 6' (1.8 ml .ETTERS; 16 (400) .INE FOR "X"		SOLID	WHITE	SEE STATE STANDARD 780001 AREA OF: "R"-3.6 SQ. FT. (0.33 m²) EACH "X"-54.0 SQ. FT. (5.0 m²)			
SHOULDER DIAGONALS 12 (300) e 45°		SOLID	WHITE - RIGHT YELLOW - LEFT	50' (15 m) C-C (LESS THAN 30MPH (50 km/h)) 75' (25 m) C-C (30 MPH (50 km/h) T0 45MPH (70 km/h) 150' (45 m) C-C (0VER 45MPH (70 km/h))			

FOR FURTHER DETAILS ON PAVEMENT MARKING REFER TO STANDARD SPECIFICATIONS FOR ROAD AND ERIDGE CONSTRUCTION AND STATE STANDARD 7800CL.

All dimensions are in irches (millimeters) unless otherwise shown.

HRGreen.com **HRGreen**

_	HEED MANE - 1	DECIONED EVEDS	DEVICED T DANSHOUSE 10 07 0
	USER NAME = drivakosgn	DESIGNED - EVERS	REVISED -T. RAMMACHER 10-27-9
		DRAWN -	REVISED - C. JUCIUS 09-09-0
	PLOT SCALE = 50.000 '/ IN.	CHECKED -	REVISED -
	PLOT DATE = 9/9/2009	DATE - 03-19-90	REVISED -

STATE OF	ILLINOIS
DEPARTMENT OF	TRANSPORTATION

DISTRICT ONE				F.A RTE.	SECTION	COUNTY	TOTAL	SHEET NO.		
ı	TYPICAL PAVEMENT MARKINGS				334	TR-RS-3	LAKE	52	47	
ITFICAL PAVENIENT MANNINGS				TC-13		CONTRACT	NO.	60N25		
	SCALE: NONE	SHEET NO. 1 OF 1	SHEETS	STA.	TO STA.	FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT				