



SHEET NO. ${\it 1}$ TOTAL SHEETS SHEET NO. FAP 505 335 145 WINNEBAGO 3 SHEETS

**111RS-4, 111BR-1, Ya-15d-RS-1,& (W-15d)T-1 Contract # 64970



TOP ANCHOR PLATE



(4" Wide)

NOTCH DETAIL

DETAIL "A"

STATION 11025+71 BUILT 20 BY STATE OF ILLINOIS F.A.P. RT. 505 SEC 109RS-2, Ya-15d-RS-1 LOADING HS20 STR. NO. 101-2049

NAME PLATE

See Std. 515001 Located on the SE Headwall. Locate to miss pipe grating.



GENERAL NOTES

Reinforcement bars shall conform to the requirements of A.S.T.M. A 706 Gr 60. See Special Provisions.

The distance from the top of headwall or wingwall to the adjacent ground surface shall be 3 inches (nominal), but in no case greater than 4 inches.

Grating shall include pipes, plates, expansion bolts, and all other hardware as shown and shall be included with the contract unit price per Cu, Yd. for Concrete Structures.

Bolts, Nuts, and Washers shall be in accordance with Article 1006.08 of the Standard Specifications and shall be galvanized.

Steel Plates shall conform to AASHTO M-183 and shall be galvanized conforming to AASHTO M-111.

Steel Pipes shall conform to A.S.T.M. A-53 (Type E or S) Grade B, Schedule 40, and shall be galvanized conforming to A.S.T.M. A-120. Contractor shall field verify pipe length.

See Plan and Profile Sheet 76 of 335 for more information.

See Sheet 159 of 335 for details of Breaker Run Crushed Stone.

If the Contractor elects to use precast construction, the Precaster shall provide complete details in the shop drawings for review by the Engineer.



200 West Front Street Wheaton, Il 60187

ILLINOIS DEPARTMENT OF TRANSPORTATION GRATED CULVERT EXTENSION NO. 11 IL-75 OVER TRIBUTARY TO PECATONICA RIVER FAP RTE 505 - SECTION *111RS-4, 111BR-1, Ya-15d-RS-1,& (W-15d)T-1 WINNEBAGO COUNTY STATION 11025+71

STRUCTURE NO. 101-2049

DATE: 3/03/2009

DRAWN BY BLB CHECKED BY WJV