ELE	CTRICAL LEGEND - ONE-LINE DIAGRAM						
	CABLE TERMINATOR/LUG						
***	TRANSFORMER						
	DISCONNECT SWITCH						
->-	FUSIBLE DISCONNECT SWITCH						
	CIRCUIT BREAKER						
~~~	THERMAL MAGNETIC CIRCUIT BREAKER						
	FUSE						
<b>‡</b>	TRANSIENT VOLTAGE SURGE SUPPRESSOR OR SURGE PROTECTOR DEVICE						
*	GROUND - GROUND ROD, GROUNDING ELECTRODE, OR AT EARTH POTENTIAL						
Ø	INDICATING LIGHT						
•	MOTOR						
•	LOAD, MOTOR, # = HORSEPOWER						
0	ELECTRIC UTILITY METER BASE						
	JUNCTION BOX WITH SPLICE						
XXX	EQUIPMENT, XXX = DEVICE DESCRIPTION						
CND	GROUND BUS OR TERMINAL						
S/N	NEUTRAL BUS						
#	Panelboard with main lugs						
  -  -  -	Panelboard with main Breaker						
## <b></b>	fuse panel with main fuse pullout						
	DUPLEX RECEPTACLE 120V SINGLE PHASE GROUNDING TYPE						
	CONTROL STATION						
N EM	TRANSFER SWITCH						
	ENGINE GENERATOR SET						

ſ	ELECTRICAL LEGEND - SCHEMATIC
	<u> </u>
<u>+</u>	NORMALLY OPEN (N.O.) CONTACT
<del>  *</del>	NORMALLY CLOSED (N.C.) CONTACT
(S)	STARTER COIL, * = STARTER NUMBER
-¥F	OVERLOAD RELAY CONTACT
<b>®</b>	CONTROL RELAY, * = CONTROL RELAY NUMBER
(€)	RELAY, • = RELAY NUMBER
<u>، ~ °</u>	TOGGLE SWITCH / 2 POSITION SWITCH
OFF AUTO	2—POSITION SELECTOR SWITCH
HAND T AUTO	3POSITION SELECTOR SWITCH (H-O-A SHOWN)
H	2 POLE DISCONNECT SWITCH
1111	3 POLE DISCONNECT SWITCH
<u>~</u>	PHOTOCELL
0	TERMINAL BLOCK, * = TERMINAL NUMBER
	DEVICE TERMINAL, * = DEVICE TERMINAL NUMBER
	INTERNAL PANEL WIRING
	FIELD WIRING
	FUSE
GND	GROUND BUS OR TERMINAL
S/N	NEUTRAL BUS
<u>+</u>	GROUND, GROUND ROD, GROUND BUS
	INDUSTRIAL CONTROL RELAY OR LIGHTING CONTACTOR
	S1 CUTOUT HANDLE REMOVED
### ###	S1 CUTOUT HANDLE INSERTED
¹ 2-6	N.O. THERMAL SWITCH
ۍ. ا	N.C. THERMAL SWITCH
(#)	L-830 SERIES ISOLATION TRANSFORMER

	ELECTRICAL ABBREVIATIONS
A.F.F.	ABOVE FINSHED FLOOR
A, AMP	AMPERES
ATS	AUTOMATIC TRANSFER SWITCH
AWG	AMERICAN WIRE GAUGE
BKR	BREAKER
С	CONDUIT
C8	CIRCUIT BREAKER
CKT	CIRCUIT
CR	CONTROL RELAY
a	COPPER
DPOT	DOUBLE POLE DOUBLE THROW
DPST	DOUBLE POLE SINGLE THROW
EM	EMERGENCY
EMT	ELECTRICAL METALLIC TUBING
ENCL.	ENCLOSURE
EP	EXPLOSION PROOF
ES	EMERGENCY STOP
ETL	INTERTEK - ELECTRICAL TESTING LABS
ETM	ELAPSE TIME METER
GFCI	GROUND FAULT CIRCUIT INTERRUPTER
GF1	GROUND FAULT INTERRUPTER
GND	GROUND .
GRSC	GALVANIZED RIGID STEEL CONDUIT
HID	HIGH INTENSITY DISCHARGE
HOA	HAND OFF AUTOMATIC
HP	HORSEPOWER
HPS	HIGH PRESSURE SODIUM
J	JUNCTION BOX
KVA	KILOVOLT AMPERE(S)
KW	KILOWATTS
rc	LIGHTING CONTACTOR
LTFMC	LIQUID TIGHT FLEXIBLE NETAL CONDUIT (UL LISTED)
LTG	LIGHTING
LP	LIGHTING PANEL
MAX	MAXIMUM
MCB	MAIN CIRCUIT BREAKER
MCM	THOUSAND CIRCLUAR MIL.
MOP	MAIN DISTRIBUTION PANEL
MFR	MANUFACTURER
MH	METAL HALIDE
Min	MINIMUM
MLO	MAIN LUGS ONLY
NEC	NATIONAL ELECTRICAL CODE (NFPA 70)
NC	NORMALLY CLOSED
NO	NORMALLY OPEN
NTS	NOT TO SCALE
OHE	OVERHEAD ELECTRIC

OL

OVERLOAD

	LECTRICAL ABBREVIATIONS (CONTINUED)
PB	PULL BOX
PC	PHOTO CELL
PDB	POWER DISTRIBUTION BLOCK
PNL	PANEL.
RCPT	RECEPTACLE
R	RELAY
s	STARTER
SP0	SURGE PROTECTION DEVICE
SPST	SINGLE POLE SINGLE THROW
TVSS	TRANSIENT VOLTAGE SURGE SUPPRESSOR
MP	TYPICAL
UG	UNDERGROUND
UGE	UNDERGROUND ELECTRIC
UL	UNDERWRITER'S LABORATORIES
٧	VOLTS
W/	WITH
W/0	wпноuт
WP	WEATHER PROOF
XFER	Transfer
XFMR	TRANSFORMER

XFMR	TRANSFORMER
AIRP	ORT EQUIPMENT/FACILITY ABBREVIATIONS
ASOS	AUTOMATED SURFACE OBSERVING SYSTEM
ATCT	AIR TRAFFIC CONTROL TOWER
AWOS	AUTOMATED WEATHER OBSERVING SYSTEM
CCR	CONSTANT CURRENT REGULATOR
DNE	DISTANCE MEASURING EQUIPMENT
FAR	FEDERAL AWATION REGULATION
CS CS	GLIDE SLOPE FACILITY
HIRL	HIGH INTENSITY RUNWAY LIGHT
ILS	INSTRUMENT LANDING SYSTEM
IM	INNER MARKER
UR	LOW IMPACT-RESISTANT
roc	LOCALIZER FACILITY
NALS	MEDIUM INTENSITY APPROACH LIGHTING SYSTEM
MALSR	MEDIUM INTENSITY APPROACH LIGHTING SYSTEM WITH RUNWAY ALIGNMENT INDICATING LIGHTS
MIRL.	MEDIUM INTENSITY RUNWAY LIGHT
MITL.	MEDIUM INTENSITY TAXIWAY LIGHT
NDB	NON-DIRECTIONAL BEACON
PAPI	PRECISION APPROACH PATH INDICATOR
PLASI	PULSE UGHT APPROACH SLOPE INDICATOR
RAIL	RUNWAY ALIGNMENT INDICATING LIGHTS
REIL.	RUNWAY END IDENTIFIER LIGHT
RVR	RUNWAY VISUAL RANGE
VADI	VISUAL APPROACH DESCENT INDICATOR
VASI	VISUAL APPROACH SLOPE INDICATOR
VOR	VERY HIGH FREQUENCY OMNIDIRECTIONAL RANGE FACILITY
WC	WIND CONE

- ALL ELECTRICAL EQUIPMENT SHALL BE INSTALLED IN CONFORMANCE WITH NFPA 70-NATIONAL ELECTRIC CODE (NEC) MOST CURRENT ISSUE IN FORCE, THE RESPECTIVE EQUIPMENT MANUFACTURER'S DIRECTIONS AND ALL OTHER APPLICABLE LOCAL CODES, LAWS, ORDINANCES, AND REQUIREMENTS IN FORCE. ANY INSTALLATIONS WHICH VOID THE U.L. LISTING, ETL LISTING (OR OTHER THIRD PARTY LISTING) AND/OR THE MANUFACTURER'S WARRANTY OF A DEVICE WILL NOT BE PERMITTED.
- CONTRACTOR SHALL COORDINATE WORK AND ANY POWER OUTAGES WITH THE RESPECTIVE FACILITY OWNER PERSONNEL AND THE AIRPORT MANAGER.
- 3. COLOR CODE PHASE AND NEUTRAL CONDUCTOR INSULATION FOR NO. 6 AWG OR SMALLER. PROVIDE COLORED INSULATION OR COLORED MARKING TAPE FOR PHASE AND NEUTRAL CONDUCTORS FOR NO. 4 AWG AND LARGER. INSULATED GROUND CONDUCTORS SHALL HAVE GREEN COLORED INSULATION FOR ALL CONDUCTOR AWG AND/OR KCMIL TO COMPLY WITH NEC 250.119. NEUTRAL CONDUCTORS SHALL HAVE WHITE COLORED INSULATION FOR NO. 6 AWG AND SMALLER TO MEET THE REQUIREMENTS OF NEC 200.6. STANDARD COLORS FOR POWER WIRING AND BRANCH CIRCUITS SHALL BE AS FOLLOWS:

120/240 VAC. 1 PHASE. 3 WIRE PHASE A BLACK PHASE B RED NEUTRAL WHITE GREEN GROUND

- 4. SEE RESPECTIVE SITE PLANS FOR SITE LEGEND INFORMATION.
- 5. LIFMC DENOTES LIQUID TIGHT FLEXIBLE METAL CONDUIT ULLISTED, SUNLIGHT RESISTANT, & SUITABLE FOR GROUNDING. LIQUID TIGHT FLEXIBLE METAL CONDUIT AND ASSOCIATED FITTINGS SHALL BE U.L. LISTED TO MEET THE REQUIREMENTS OF NEC 350.6. LIQUID TIGHT FLEXIBLE METAL CONDUIT THAT IS USED FOR FLEXIBILITY (INCLUDING CONNECTIONS TO CCR'S & TRANSFORMERS) SHALL REQUIRE AN EXTERNAL BONDING JUMPER OR INTERNAL EQUIPMENT GROUNDING CONDUCTOR PER NEC 350.60. EXTERNAL BONDING JUMPERS USED WITH CCR INSTALLATIONS SHALL BE #6 AWG COPPER (MINIMUM).
  DO NOT INSTALL LITEMC THAT IS NOT UL LISTED.
- 6. ALL ELECTRICAL INSTALLATIONS AT OR ASSOCIATED WITH THE FUEL FACILITY IN CLASSIFIED HAZARDOUS LOCATIONS (CLASS I, DIV. 1 OR 2, GROUP D) SHALL BE SUITABLE FOR THE RESPECTIVE ENVIRONMENT AND SHALL CONFORM TO THE APPLICABLE SECTIONS OF NEC (MOST CURRENT ISSUE) INCLUDING, BUT NOT LIMITED TO, ARTICLES 500, 501, 514 AND 515 AS WELL AS ALL MANUFACTURER REQUIREMENTS, AND ALL LOCAL CODES, LAWS, ORDINANCES, AND REQUIREMENTS IN FORCE.

	8				
	REVISION				
	DATE				

TRI-TOWNSHIP AIRPORT SAVANNA, CARROLL COUNTY ILLINOIS

HANSON

ELECTRICAL LEGEND AND ABBREVIATIONS CONSTRUCT NEW VAULT

4 of 24 sheets