

STANDARD BAR SPLICER ASSEMBLY

Minimum Lap Lengths							
Bar size to be spliced	Table 1	Table 2	Table 3	Table 4	Table 5	Table 6	
3, 4	1'-5''	1'-11''	2'-1''	2'-4''	2'-7''	2'-11''	
5	1'-9''	2'-5''	2'-7''	2'-11''	3'-3''	3'-8''	
6	2'-1''	2'-11''	3'-1''	3′-6″	3′-10′′	4'-5''	
7	2'-9''	3′-10′′	4'-2''	4'-8''	5'-2''	5′-10′′	
8	3′-8′′	5′-1′′	5′-5′′	6'-2''	6′-9′′	7'-8''	
9	4'-7''	6'-5''	6′-10′′	7'-9''	8'-7''	9′-8′′	

Table 1: Black bar, 0.8 Class C

- Table 2: Black bar, Top bar lap, 0.8 Class C
- Table 3: Epoxy bar, 0.8 Class C
- Table 4: Epoxy bar, Top bar lap, 0.8 Class C
- Table 5: Epoxy bar, Class C
- Table 6: Epoxy bar, Top bar top, Class C

Threaded splicer bar length = min. lap length + 1_2^{\prime} + thread length

* Epoxy not required on Bar Splicer Assembly components used in conjunction with black bars.

Location	Bar size	No. assemblies required	Table for minimum lap length
025-0070	#5	20	Table 3
025-0070	#6	8	Table 3



INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt. "B" : Set bar splicer assembly by nailing to wood forms or

cementing to steel forms. (E) : Indicates epoxy coating.





1-2

BSD-1	1-27-12								• EFFINGHAM & CLAY	
FILE NAME =	USER NAME = teasleyck	DESIGNED - KLB	REVISED -		BAB SP	LICER ASSEMBLY AND MI	CHANICAL SPLICER DE	F.A.I.	SECTION	COUNTY TOTAL SHEET
c:\pw_work\pwidot\teasleyck\d0181558\D7	4450-sht-brdetails-0250070.dgn	DRAWN - KLB	REVISED -	STATE OF ILLINOIS				57		•• 84 76
	PLOT SCALE = 40.0000 ' / in.	CHECKED - MEA	REVISED -	DEPARTMENT OF TRANSPORTATION	STRUCTURE NO. 025-0070 (SB)					CONTRACT NO. 74450
	PLOT DATE = 10/18/2012	DATE - 05/31/12	REVISED -		SCALE:	SHEET NO. 20 OF 22 SHEETS	STA. TO STA.		ILLINOIS	FED. AID PROJECT



STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required

<u>NOTES</u>

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications. See approved list of bar splicer assemblies and mechanical splicers for alternatives.

· /25 C 1)DC 0 0 /17 1)DC 2