





Burn exist. 1" anchor bolts flush with concrete surface. Grind smooth and seal with epoxy. Cost included with Concrete Structures.



Section A-A

GENERAL NOTES

All edges shall have standard (3/4") chamfers.

Bolt holes for connection of type 6 end shoe shal drilled or formed. Wood blockouts and extra length will be required for flared wingwalls

Reinforcement bars designated (E) shall be epoxy coated.

Modification shall be made to the NE, NW and SW wingwalls of the SB structure SN 025-0068 and to the SW, SE, NW and NE wingwalls of structures 025-0043 and 0073.

Epoxy grout d2(E) & d3(E) bars in 9" deep holes in accordance with Section 584 of the Standard Specifications.

Concrete removal shall be considered included in the cost of Concrete Structures.

									•• EFFINGHAM, CLAT		
Ī	FILE NAME =	USER NAME = teasleyck	DESIGNED -	REVISED -			WING WALL MODIFICATION DETAILS	F.A.I. BIE	SECTION	COUNTY TOTAL SHEET	
	c:\pw_work\pwidot\teasleyck\d0181558\d77	4450-sht-details.dgn	DRAWN -	REVISED -	STATE OF ILLINOIS		WING WALL MODIFICATION DETAILS		•	•• 84 83	
		PLOT SCALE = 100.0000 '/ in.	CHECKED -	REVISED -	DEPARTMENT OF TRANSPORTATION					CONTRACT NO. 74450	
		PLOT DATE = 10/18/2012	DATE -	REVISED -		SCALE: NA	SHEET NO. 1 OF 1 SHEETS STA. TO STA	۹.	ILLINOIS FE	D. AID PROJECT	

	be	
th	bol	ts

s(E)

d3(E)

d2(E)

8′′

41/-

(25-6-1)RS-8 & (13-1)RS-2 FFFINGHAM, CLAY