
ENTRANCE APPROACHES – URBAN AREA


COUNTY TOTAL SHEET SECTION (4MFT)R WINNEBAGO 353 283 FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT

TYPICAL APPLICATION OF ENTRANCES




WHEN THE ISLAND BETWEEN DRIVES IS LESS THAN 7.5m (25') LONG OR LESS THAN 10 FEET WIDE, IT SHALL BE DEFINED BY CURBS,

* 45° MIN. ANGLE PERMITTED ONLY FOR ONE-WAY DRIVEWAYS. 60° MIN. ANGLE FOR TWO-WAY DRIVEWAYS.




15m (49') DEPRESSED CURB FOR COMMERCIAL ENTRANCE 8m (26') DEPRESSED CURB FOR PRIVATE ENTRANCE EDGE OF PAVEMENT





EXISTING SIDEWALK


NO SIDEWALK

NONCOMMERCIAL - URBAN RIGHT-OF-WAY -- EDGE OF PAVEMENT STATE HIGHWAY











ASCENDING APPROACH



DESCENDING APPROACH

* IN CASES WHERE GRADE EXCEEDS 12%, THE RESIDENT ENGINEER SHALL CHECK WITH DISTRICT DESIGN OFFICE TO DETERMINE NEW APPROACH GRADE, PARTICULAR ATTENTION SHALL BE PAID TO THE NEGATIVE GRADE TO PREVENT DRAINAGE FROM OVER FLOWING INTO THE PRIVATE ENTRANCE.



THE VARIABLE HEIGHT INTEGRAL CURB AND PREMOULDED JOINT FILLER WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE OF DRIVEWAY PAVEMENT OF THE THICKNESS SPECIFIED.

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE NOTED.