TRAFFIC SIGNAL LEGEND

ITEM .	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	<u>ITEM</u>	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET				EMERGENCY VEHICLE LIGHT DETECTOR	e exti		w-44	ELECTRICAL CABLE IN CONDUIT, TRACER,		alle si sinana anno 1	
RAILROAD CONTROL CABINET		8><6	EXE	CONFIRMATION BEACON		0-6	w d	NO. 14 1/C. UNLESS NOTED OTHERWISE		ă	
COMMUNICATIONS CABINET	(CC)	ECC	СС	HANDHOLE	R _E			COAXIAL CABLE			— <u>C</u> —
MASTER CONTROLLER		EMC	MC	HEAVY DUTY HANDHOLD	A	2	H	VENDOR CABLE FOR CAMERA		- Ø-	V)
MASTER MASTER CONTROLLER		EMAC	MMC	DOUBLE HANDHOLE	F	SIJ	in la	COPPER INTERCONNECT CABLE,		-6	-6-
UNINTERRUPTIBLE POWER SUPPLY	R UPS	ELP'S	UPS	JUNCTION BOX		<u>ā</u>		NO. 18 3 PAIR TWISTED, SHIELDED			-6-
SERVICE INSTALLATION, (P) POLE OR (G) GROUND MOUNT	-Comp	P		GALVANIZED STEEL CONDUIT IN TRENCH (T) OR PUSHED (P)		The second secon		FIBER OPTIC CABLE NO. 62.5/125, MM12F		- (12b-	
TELEPHONE CONNECTION (P) POLE OF (G) GOUND MOUNT	R		P	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	Ř			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		- 245-	(4F)
STEEL MAST ARM ASSEMBLY AND POLE	R	. One of the second sec		COMMONTRENCH			СТ	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE			
ALUMINUM MAST ARM ASSEMBLY AND POLE	And the second control of the second control	And the second Appendix of the second		COILABLE NONMETALLIC CONDUIT (EMPTY)			. CNC	NOTED ON PLANS			
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE	R	<u></u>	₩	SYSTEM ITEM		> -	S IP	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE		C _{ull} -o	$C_{i i }$
STEEL COMBINATION MAST ARM	R	<u> </u>		INTERSECTION ITEM				CONTROLLER CABINET AND	RCF		
ASSEMBLY AND POLE WITH PTZ CAMERA	PTZ)		PTZ	REMOVE ITEM				FOUNDATION TO BE REMOVE			
SIGNAL POST	R _O	0	*	ABANDON ITEM				STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVE	RMF · · · · · · · · · · · · · · · · · · ·		
TEMPORARY WOOD POLE (CLASS 5 OR BETTER) 45 FOOT (13.7m) MINIMUM	R	8	③	12" (300mm) TRAFFIC SIGNAL SECTION		Ei.	R	ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVE	RMF		
GUY WIRE	<u></u>	>	>	12" (300mm) RED WITH 6" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE		5		STEEL COMBINATION MAST ARM ASSEMBLY			
SIGNAL HEAD	R	->	— <u> </u>				R	AND POLE WITH LUMINAIRE AND FOUNDATION TO BE REMOVE	RMF Ont Commission		
SIGNAL HEAD CONSTRUCTION STAGES (NUMBERS INDICATE THE CONSTRUCTION STAGE)			2	SIGNAL FACE			Y	SIGNAL POST AND FOUNDATION	RME		
SIGNAL HEAD WITH BACKPLATE	HL.R	₽	+	SIGNAL PAGE			47	TO BE REMOVE	RMF	i rei	Ic
SIGNAL HEAD OPTICALLY PROGRAMMED	-R *P*	-i> "P"	"p"			53	[46]	INTERSECTION & SAMPLING (SYSTEM) DETECTOR			IS
FLASHER INSTALLATION (S DENOTES SOLAR POWER)	OB alta	OF,	*F"	SIGNAL FACE WITH BACKPLATE "P" INDICATES PROGRAMMED HEAD			R Y	SAMPLING SYSTEM DETECTOR		S	S
PEDESTRIAN SIGNAL HEAD	R						G	EXISTING INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETEC	TOR	P	
PEDESTRIAN PUSHBUTTON DETECTOR	R (*)	@	©				[→ G]	EXISTING PREFORMED INTERSECTION LOOP DETECTOR			
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R	⊕APS	⊚APS			E2	"	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETEC	IOR		
ILLUMINATED SIGN	R			12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL	- -			PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		PIS	PIS
"NO LEFT TURN" ILLUMINATED SIGN	R			12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED		783 1		PREFORMED SAMPLING (SYSTEM) DETECTOR		[PS]	PS
"NO RIGHT TURN"			\bigcirc	12" (300mm) PEDESTRIAN SIGNAL HEAD				Paris at the factor of the fac	all of the parties and address other	b 480.	
DETECTOR LOOP, TYPE I		· ·		INTERNATIONAL SYMBOL, SOLID			×	RAILROAD SYMBOLS			
PREFORMED DETECTOR LOOP		P	P	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER			№ C ※ D				
MICROWAVE VEHICLE SENSOR	R		M	RADIO INTERCONNECT	en e						R R
VIDEO DETECTION CAMERA	R		[V]N	RADIO REPEATER	₩ [®] o	-		RAILROAD CONTROL CABINET		And of the control of the	
VIDEO DETECTION ZONE	R			DENOTES NUMBER OF CONDUCTORS, ELECTRIC	RICHAI		[RR]	RAILROAD CANTILEVER MAST ARM	2		XeX
PAN, TILT, ZOOM CAMERA	च्या	PIZN	PTZ	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED		784		FLASHING SIGNAL			X - X
WIRELESS DETECTOR SENSOR	R	W	W	GROUND CABLE IN CONDUIT			(5)	CROSSING GATE		X-0-X	XOX
WIRELESS ACCESS POINT		-		NO. 6 SOLID COPPER (GREEN)		(1)		CROSSBUCK		75	><
LE NAME = USER NAME = \$USER\$	DES	IGNED - DAD	REVISED		e core, y a estado cabado de los adribados do contratacio	on come a mora en manamenta a como en como e manos			F.A.P.	A Re	COUNTY TOTAL SHE
ILEL\$	DRA		REVISED -	STA	TË OF ILLINO	155	and the second	DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN DETAILS	F.A.P. RTE. 2578	532B	DuPage 781 4