

PROP. PAY LIMIT OF BIT. SURF. REMOVAL FULL THICKNESS OF MILLING TEMP. RAMP (NOTE "C") (NOTE "E") PROP. BIT. SURFACE REMOVAL EXIST. BIT. SURFACE EXIST, PAVEMENT MILLED TEMPORARY RAMP

(FOR BUTT JOINT AND BIT. TAPER SEE DETAIL BELOW) OPTION 1




OPTION 2 TYPICAL TEMPORARY RAMP


(FOR BUTT JOINT AND BIT. TAPER SEE DETAIL BELOW)



TYPICAL BUTT JOINT AND BITUMINOUS TAPER FOR MILLING AND RESURFACING

TOTAL SHEETS 588 ILLINOIS





TYPICAL BUTT JOINT AND BITUMINOUS TAPER FOR RESURFACING ONLY

* * PC CONCRETE, BITUMINOUS OR BITUMINOUS RESURFACED PAVEMENT.

A: MAINLINE ROADWAYS AND MAJOR SIDE ROADS.

B: MINOR SIDE ROADS.

C: THE TEMP. RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING BITUMINOUS SURFACE.

D: THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED BITUMINOUS COURSES.

E: TAPER THE TEMP. RAMP AT A RATE OF 900 (3 ft.) PER INCH OF MILLING THICKNESS.

F: INSTALLATION AND REMOVAL OF THE 1.35 m (4.5') TEMP, BIT, RAMP WILL BE PAID AS "BITUMINOUS SURFACE REMOVAL - BUTT JOINT".

G: SEE ARTICLE 406.18 AND 406.24 OF THE STANDARD SPECIFICATIONS FOR "BITUMINOUS AND PCC SURFACE REMOVAL, BUTT JOINT".

* SEE TYPICAL SECTIONS FOR MILLING THICKNESS.

* * * * 6.1 m (20') PER 25 (1) RESURFACING (NOTE "A") 3.0 m (10') PER 25 (1) RESURFACING (NOTE "B") ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE SHOWN.

ILLINOIS DEPARTMENT OF TRANSPORTATION

BUTT JOINT AND BITUMINOUS TAPER

DETAILS

SCALE: NONE

09/09/94

NAME

M. DE YONG R. SHAH

CHECKED BY BD400-05 (VI=BD32)

REVISION DATE: 04/06/01

THE BUTT JOINT WILL BE PAID FOR PER SQUARE METER (SQUARE YARD.) AS "BITUMINOUS SURFACE REMOVAL - BUTT JOINT" OR AS "PORTLAND CEMENT CONCRETE SURFACE REMOVAL - BUTT JOINT".