



Illinois Department of Transportation

2300 South Dirksen Parkway / Springfield, Illinois / 62764

September 11, 2025

SUBJECT: FAP 336 (Randall Road)
Section 19-00514-00-WR
Kane County
Contract No. 61L28
Item 091
September 19, 2025 Letting
Addendum (A)

NOTICE TO PROSPECTIVE BIDDERS:

Attached is an addendum to the plans or proposal. This addendum involves revised and/or added material.

- 1. Revised the Schedule of Prices**
- 2. Revised Plan Sheets 9, 22, 36, & 73**
- 3. Revised Special Provision Index**
- 4. Added page 247A to the Special Provisions**

Prime contractors must utilize the enclosed material when preparing their bid and must include any changes to the Schedule of Prices in their bid.

Very truly yours,

A handwritten signature in black ink, appearing to read 'Jack A. Elston'.

Jack A. Elston, P.E.
Bureau Chief, Design and Environment

| | |
|--|------|
| REMOVE EXISTING DOUBLE HANDHOLE | 200 |
| PERENNIAL PLANTS, WETLAND TYPE, 2" DIAMETER BY 4" DEEP PLUG | 201 |
| SEDIMENT BASIN | 204 |
| REMOVE EXISTING RIPRAP | 205 |
| WASHOUT BASIN | 206 |
| RELOCATE EXISTING MAILBOX..... | 208 |
| SEEDING, CLASS 5B (MODIFIED)..... | 209 |
| DEWATERING | 212 |
| REMOVE EXISTING FLARED END SECTION | 215 |
| MANHOLES TYPE A 6'-DIA, WITH 2 TYPE 1 FRAME, CLOSED LID RESTRICTOR PLATE | 216 |
| FENCE REMOVAL | 217 |
| TEMPORARY WOOD POLE, INSTALL ONLY D1..... | 218 |
| SEDIMENT CONTROL, STABILIZED CONSTRUCTION ENTRANCE | 219 |
| PIPE UNDERDRAIN REMOVAL | 220 |
| PROTECTION OF EXISTING TREES..... | 221 |
| FAILURE TO COMPLETE PLANT CARE AND ESTABLISHMENT WORK ON TIME | 224 |
| REMOVAL AND DISPOSAL OF REGULATED SUBSTANCES (PROJECT SPECIFIC) | 225 |
| REMOVAL OF TEMPORARY LIGHTING UNIT (D1)..... | 228 |
| TEMPORARY PAVEMENT (VARIABLE DEPTH)..... | 229 |
| SANITARY MANHOLES TO BE ADJUSTED | 230 |
| FRAMES AND LIDS TO BE ADJUSTED (SPECIAL)..... | 232 |
| PERVIOUS HOT-MIX ASPHALT | 233 |
| PLANTING SOIL MIX FURNISH AND PLACE..... | 239 |
| TEMPORARY FLASHING BEACON INSTALLATION | 243 |
| ANTI-GRAFFITI COATING | 244 |
| FIRE HYDRANT TO BE RELOCATED..... | 246 |
| ROD AND CLEAN EXISTING CONDUIT | 247 |
| BICYCLE RAILING (GROUND MOUNTED) | 247A |
| IDOT TRAINING PROGRAM GRADUATE ON-THE-JOB TRAINING SPECIAL PROVISION | 248 |
| LR107-4 | 250 |
| LR1030-2 | 251 |
| STORMWATER POLLUTION PREVENTION PLAN (BDE 2342) | 253 |
| CONTRACTOR CERTIFICATION STATEMENT (BDE 2342A) | 267 |
| NOTICE OF INTENT (ILR 10) | 268 |
| UNITED STATES ARMY CORPS PERMIT | 271 |
| KANE DUPAGE SOIL AND WATER CONSERVATION DISTRICT PERMIT | 274 |
| LPC 663 (IL ROUTE 72)..... | 276 |
| LPC 663 (RANDALL ROAD) | 278 |
| KANE COUNTY STORMWATER PERMIT..... | 287 |

BICYCLE RAILING (GROUND MOUNTED)

Description: This item shall consist of fabricating, furnishing, and erecting a bicycle railing to match the bicycle railing detailed on the structural plans and in accordance with the applicable requirements of Section 509 of the Standard Specifications except as modified herein.

The bicycle railing shall be installed onto the on 12" circular foundations. The foundations shall be a depth of 4 foot deep.

Shop Drawings: The Contractor shall submit detailed shop drawings in accordance with Article 509.04 of the Standard Specification to the Engineer for approval before fabrication is begun.

Fabrication: Fabrication of the bicycle railing shall conform to Article 509.05 of the Standard Specification the handrail shall be hot-dipped galvanized conforming to the requirements of ASTM A123, Coating Grade 50 after fabrication.

Installation: The fence shall be installed in accordance with the following:

- Concrete Set Posts. Drill hole in firm, undisturbed, or compacted soil. Holes shall have a diameter of at least 12 inches and depths approximately 4 foot deep Excavate deeper as required for adequate support in soft and loose soils and for posts with heavy lateral loads. Set post bottom 48" below surface when in firm, undisturbed soil. Place concrete around post in a continuous pour. Trowel finish around posts and slope to direct water away from posts. Concrete shall be Class SI.
- Check each post for vertical and top alignment and maintain in position during placement and finish operation.

Basis of Payment: This work will be paid for at the contract unit price per Foot for BICYCLE RAILING (GROUND MOUNTED), which price shall include all materials, mounting, foundation, excavation, fabrication, transportation, and erection.