TRAFFIC SIGNAL LEGEND

ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	\bowtie R	\bowtie		EMERGENCY VEHICLE LIGHT DETECTOR	R≪	∞ <	•	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE			
RAILROAD CONTROL CABINET		B B	B►◆R	CONFIRMATION BEACON	R ₀ -(]	$\circ \!\!\!\!- \!\!\!\!\! \bigcirc$	•-			~	
OMMUNICATIONS CABINET	C C	E C C	СС	HANDHOLE	R			COAXIAL CABLE		<u>—(c)</u>	<u> </u>
ASTER CONTROLLER		EMC	MC		R	H	_	VENDOR CABLE FOR CAMERA			
ASTER MASTER CONTROLLER	R	EMMC	MMC	HEAVY DUTY HANDHOLE	D			COPPER INTERCONNECT CABLE,			
NINTERRUPTIBLE POWER SUPPLY	UPS	EUPS	UPS	DOUBLE HANDHOLE JUNCTION BOX	* <u> </u>			NO. 18 3 PAIR TWISTED, SHIELDED		<u></u>	-6-
RVICE INSTALLATION,) POLE OR (G) GROUND MOUNT	-□- ^R	-□ ⁻	- ■	GALVANIZED STEEL CONDUIT		<u> </u>		FIBER OPTIC CABLE NO. 62.5/125, MM12F		— <u>12</u> F—	
LEPHONE CONNECTION) POLE OR (G) GROUND MOUNT	R T	P	P	IN TRENCH (T) OR PUSHED (P) TEMPORARY SPAN WIRE, TETHER WIRE,	R			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		— <u>24</u> F—	—(24F)—
EEL MAST ARM ASSEMBLY AND POLE	R _O	0	•——	AND CABLE				FIBER OPTIC CABLE NO. 62.5/125,		,	
UMINUM MAST ARM ASSEMBLY AND POLE	R	0		COMMON TRENCH			СТ	(NUMBER OF FIBERS & TYPE TO BE NOTED ON PLANS)		-	
EEL COMBINATION MAST ARM SEMBLY AND POLE WITH LUMINAIRE	^R O–¤——	O-X	• ×	COILABLE NONMETALLIC CONDUIT (EMPTY) SYSTEM ITEM		S	CNC S	GROUND ROD AT (C) CONTROLLER,		Cu	Ca
EEL COMBINATION MAST ARM SEMBLY AND POLE WITH PTZ CAMERA	R PTZ]]	Q	PTZ	INTERSECTION ITEM		I	ΙP	(H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE		" ⊪⊸	⁻ ∥ ├ •
SNAL POST	R	0	•	REMOVE ITEM	R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
EMPORARY WOOD POLE (CLASS 5 OR	° R⊗	⊗	•	RELOCATE ITEM	RL						
TTER) 45 FOOT (13.7m) MINIMUM				ABANDON ITEM	Α			STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	ORMF		
Y WIRE SNAL HEAD	R	> -⊳	<i>></i> ─	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
	>			12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE		R					
NAL HEAD CONSTRUCTION STAGES MBERS INDICATE THE CONSTRUCTION STAGE:			-	TELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND FOUNDATION TO BE DEMONSTOR	RMF O-⊐⊄		
NAL HEAD WITH BACKPLATE	+DR	+->	+-			(R)	R	FOUNDATION TO BE REMOVED			
SNAL HEAD OPTICALLY PROGRAMMED	R →>′′P′′	- >′′P′′	→ "P"	SIGNAL FACE			G ∢ Y	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF O		
ASHER INSTALLATION DENOTES SOLAR POWER)	O>''F''	O- ⊳ "F"	●→ "F"			40	◆ G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		[IS]	IS
DESTRIAN SIGNAL HEAD	R -∐	-0	-1			R	R	SAMPLING (SYSTEM) DETECTOR		[5]	S
DESTRIAN PUSHBUTTON DETECTOR	R	©	•	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD			Y	EXISTING INTERSECTION LOOP DETECTOR		[<u>P</u>]	
CESSIBLE PEDESTRIAN PUSHBUTTON DETECTO	R R (©) APS	(@) APS	APS			4 9	4 Y	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT	OR	נייי	
UMINATED SIGN	R	<u> </u>	C			"P"	4 G (*P''	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT	OR	IPPI LPPI	
O LEFT TURN''		(5)	⑤	12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		OW W		PREFORMED INTERSECTION AND SAMPLING		PIS	PIS
LUMINATED SIGN O RIGHT TURN''	R			12" (300mm) PEDESTRIAN SIGNAL HEAD				(SYSTEM) DETECTOR			
TECTOR LOOP, TYPE I		r-;		INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		PS ₁	PS
		} j	□ P	12" (300mm) PEDESTRIAN SIGNAL HEAD		(•	DAILDOAD	CVMDC	NI C	
REFORMED DETECTOR LOOP		7 – Ý	P	INTERNATIONAL SYMBOL, SOLID			*	RAILROAD	21MDC)L9	
CROWAVE VEHICLE SENSOR	R M D	MI	M	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		(€) C ((€) D	₽ C ★ D			<u>EXISTING</u>	PROPOSED
DEO DETECTION CAMERA	R V M	(V)	$\widehat{\mathbb{V}}$	RADIO INTERCONNECT	## * O		 •	RAILROAD CONTROL CABINET			▶ ∢
DEO DETECTION ZONE				RADIO REPEATER	R ERR	ERR	RR	RAILROAD CANTILEVER MAST ARM	Σ	XOX X	XeX
N, TILT, ZOOM CAMERA	R [PTZ]1	PTZÍ	₽ĭZ¶	DENOTES NUMBER OF CONDUCTORS, ELECTRIC	List	~/		FLASHING SIGNAL		$\boxtimes \ominus \boxtimes$	X O X
RELESS DETECTOR SENSOR	R(W)	(W)	(W)	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED				CROSSING GATE		X0X>	X 0 X
RELESS ACCESS POINT	R		<u> </u>	GROUND CABLE IN CONDUIT		(1)	(1)	CROSSBUCK		≥ ≤	*
NAME = USER NAME = konthop	nixeybc DE	ESIGNED - DAG/BCK	REVISED	NO. 6 SOLID COPPER (GREEN)		~		DISTRICT 4	F.A. RTE.	SECTION	COUNTY TOTA
v_work\PWIDOT\KANTHAPHIXAYBC\d01126 4\traffic_legend_v7.dgr		RAWN - BCK	REVISED	CTATE	OF ILLINOIS	•		DISTRICT 1	RTE.	320.1011	SHEE 577