## TYPICAL BENCHING DETAIL FOR EMBANKMENT

(12'-0")

PROP. EMBANKMENT

WIDENING (VARIES)

SEE GENERAL NOTES 6

## NOTES:

- ONSTRUCT SUCCEEDING BENCH CUTS AND EMBANKMENT PLACEMENT AND COMPACTION FROM BOTTOM TO TOP IN STAIRSTEP FASHION.
- 2 EXISTING FORESLOPE PREPARED IN ACCORDANCE WITH ARTICLE 205.04 OF THE STANDARD SPECIFICATIONS.
- BENCH CUT EXISTING SLOPE TYPICAL FOR EACH STEP.

CUARDRAIL OR

CONCRETE BARRIER

- TRIM TO FINAL SLOPE.
- 5 EQUAL 200 (8-INCH) LIFTS OF EMBANKMENT COMPACTED IN ACCORDANCE WITH ARTICLE 205.06 OF THE STANDARD SPECIFICATIONS.
- EXCAVATION OF BENCH CUTS WITHIN EXISTING EMBANKMENT WILL BE
  PAID FOR AT THE CONTRACT UNIT PRICE PER CUBIC METER OR CUBIC
  YARD FOR "EARTH EXCAVATION (SPECIAL". THIS PRICE WILL INCLUDE
  ALL LABOR AND MATERIAL NO ADDITIONAL COMPENSATION WILL BE ALLOWED.

ALL DIMENSIONS ARE IN MILLIMETERS (INCHES) UNLESS OTHERWISE SHOWN.

ILLINOIS DEPARTMENT OF TRANSPORTATION

BENCHING DETAIL FOR EMBANKMENT WIDENING

SCALE: NONE

ORAWN BY: CADD CHECKED BY: S.E.B. RD-51

00-31

-DATE-TIN -DGH-SPE VHRDN