

Number

END ELEVATION

5 mm carbon steel. Hot dip 10 Ga. stainless steel or hot galvanized after fabrication. dip galvanized carbon steel. 19 mm Ø stainless steel U-bolt 140 Provide two washers and two hexagon locknuts. 4 At € pipe 21 mm x 51 mm slots on @ DN 250 pipe. (4 slots required per pipe) 38 mm ¢ pipe coupling and plug, and 38 mm ∮ hole Detail cap plate in cover for geometry UPPER LOWER HANDHOLE COVERS **€** Upper Handhole (See Detail D) <u>D</u>etail C (See Base -W200x423 Sheet OS-A-6A(M).) DETAIL A **€** of frame within DN 80 pipe (3) (TVD.) 6 b 25 mm of plumb Drill & tap for 4-12 mm ¢ 6 mm screws. Galv. Bolts ______ ⟨*Typ*. Chase thread (ASTM A307M) 95 after galvanizing. 75 6 mm galv. cap plate Structure with 4-16 mm ϕ holes at 90° intervals. Install after S057I055R164.7 S057I055R164.7 <u>DN</u> 250 pipe ③ galvanizing frame. 20 mm x 50 mm mm (For wall thickness S057I055L165.8 flat bar frame(1) see table.) 4-12 mm hex nuts S057I055L165.8 at 90° intervals welded to pipe. Chase threads after 25 R galvanizing frame. Provide 165 mm x 115 mm cover. SECTION A-A Provide 4-8 mm & holes in cover for 6 mm round head hot dip galvanized As an alternate to bolts, may use galvanized or stainless steel machine screws. drive-fit caps installed after galvanizing frame. (See cover details) DETAIL D 75 mm wide - 10 Ga. bent stainless steel Lower Handhole cover plate with two (See Detail D) 21 mm ϕ holes Backfill shall be placed Detail B (See Base prior to erection of "D" = Outside Sheet OS-A-6A(M).) support frame Chord Diameter

> OS-F3(M) (Spread Footing) or OS4-F3(M) (Drilled Shaft). SIDE ELEVATION

FOR FOUNDATION DETAILS SEE BASE SHEET

DN 250 PIPE TRUSS SUPPORT FRAME

Conduit @ leg

with handhole

Truss Type	Dimensions								
	R (m)	S (m)	(m)	(m)	(m)	(mm)	(mm)	Y (m)	Z (m)
<i>I-A</i>	1.37	1.66	1.22	1.68	1.96	100	230	2.52	3.28
II-A (5)	1.60	1.91	1.37	1.85	2.13	120	240	2.52	3.28

OS-A-6(M)

SECTION B-B

11/1/2002