Fill slot with weld *J L UMINUM TUBE* 





6... Aluminum Tube alloy 6061-T6 or 6... \$ Fiberglass Pipe TOP PLAN

(Showing Aluminum Tube)

## FLOOR DRAIN DETAILS

## Notes:

Flberglass pipe shall conform to ASTM D2996, with short-time rupture strength hoop tensile stress of 30,000 p.s.i. minimum. The surface of the Fiberglass pipe shall be free of bond inhibiting agents.

The exterior surfaces of the Fiberglass Floor Drains shall be cleaned and given a washcoat pretreatment in accordance with Steel Structures Painting Council's Spec. SSPC-SPI & SSPC-Paint 27 prior to painting with a vinyl enamel coat. The color shall be light grey Munsell No. 10Y 7/1. Painting of the Fiberglass Floor Drains will not be required when the exterior surfaces of the furnished drains are coated by the manufacturer with a pigment that matches the color of the concrete slab.

ESSCA CONSULTANTS, INC. DESIGNED BY: ELH 12/04 DRAWN BY: HAG 12/04 CHECKED BY: ELH 04/06 APPROVED BY: RDP 04/06



SECTION A-A



SECTION B-B

ROUTE NO.	SECTION	COUNTY		TOTAL SHEETS	SHEET NO.
FAS 338	34BR	IROQUOIS		49	31
STA			TO STA		
FED. ROAD DIST. NO. 3		ILLINOIS	FED. AID PROJECT-		
		DWG. I	VO. 8	OF 13	
		CONT	RACT N	10. 666.	10

## STRUCTURE INDEX OF SHEETS

General Plan	Dwg. No. 1 of 13
General Data	Dwg. No. 2 of 13
Stage Construction Details	Dwg. No. 3 of 13
Temporary Concrete Barrier	Dwg. No. 4 of 13
Top of Slab Elevations	Dwg. No. 5 of 13
Superstructure	Dwg. No. 6 of 13
Superstructure Details	Dwg. No. 7-8 of 13
Abutments	Dwg. No. 9 of 13
Piers	Dwg. No. 10 of 13
Metal Shell Pile Details	Dwg. No. 11 of 13
Bar Splicer Assembly Details	Dwg. No. 12 of 13
Soil Borings	Dwg. No. 13 of 13

## DIMENSION "A"

	Pier 1	Pier 2
West edge of superstructure	2"	2"
West edge of roadway	3 <sup>3</sup> 8"	33 <sub>8</sub> "
€ Roadway & P.G.	5 <sup>5</sup> 8"	5 <sup>5</sup> 8"
East edge of roadway	3 <sup>3</sup> 8"	3 <sup>3</sup> 8"
East edge of superstructure	2"	2"

