



PORTABLE CHANGEABLE MESSAGE SIGN

TYPE II BARRICADE, DRUM, OR VERTICAL BARRICADE WITH MONODIRECTIONAL FLASHING LIGHT

LANE DROP ARROW - SEE STANDARD 780001

TEMPORARY THERMOPLASTIC RUMBLE STRIPS

- 1 THE ROAD CONSTRUCTION AHEAD SIGN SHALL BE LOCATED 3 MILES IN ADVANCE OF THE PROJECT LIMITS.
- THE MESSAGE AND SIZE OF THE WORK ZONE PUBLIC INFORMATION SIGN SHALL BE AS SPECIFIED BY THE DEPARTMENT.
- 3 TO BE PLACED IN THE MEDIAN WHEN FEASABLE. THE MESSAGE THE PROJECT. THE PRIMARY MESSAGES SHALL BE:

 "RIGHT LANE CLOSED" / " x MILES AHEAD"

 "LEFT LANE CLOSED" / " x MILES AHEAD" "ALL LANES OPEN"
- THREE, TYPE II BARRICADES, DRUMS, OR VERTICAL BARRICADES AT 50' CENTERS.
- (5) THIS SIGN SHALL BE USED WHEN 2 LANES ARE CLOSED.
- (6) WHEN THE LEFT LANE IS CLOSED, SWITCH THESE TWO SIGNS AND THE DIRECTION OF THE MERGE ARROW.
- 48"x48" FLUORESCENT ORANGE SIGN WITH 7" HIGH BLACK LETTERS.

GENERAL NOTE:

THIS STANDARD IS USED WHERE AT ANY TIME A LANE IS CLOSED ON A FREEWAY/EXPRESSWAY.

WHEN THE LEFT LANE IS CLOSED, LEFT LANE CLOSED SIGNS SHALL BE SUBSTITUTED FOR THE RIGHT LANE CLOSED SIGNS.

ALL SIGNS, MESSAGE BOARDS AND OTHER TRAFFIC CONTROL DEVICES UP TO AND INCLUDING THE FIRST ARROW BOARD ARE STATIONARY. THE OTHER SIGNS AND OTHER ARROWBOARD SHALL BE MOVED AS NECESSARY TO MAINTAIN THE REQUIRED DISTANCE FROM THE START OF THE LANE CLOSURE TAPER(S).

SEE SPECIAL PROVISIONS.

ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SHOWN.

FILE NAME =	USER NAME = braboypo	DESIGNED	REV	VISED -	
c:\pw_work\pwidot\braboypc\dms32763\det	ails.dgn	DRAWN	REV	VISED -	
	PLOT SCALE = 20.0911 ' / IN.	CHECKED	REV	VISED -	
	PLOT DATE = Sep 04, 2008 - 08:21:43 AM	DATE	REV	VISED -	

STATE	: OF	ILLINOIS
DEPARTMENT	OF 1	TRANSPORTATION

	DETAIL			SECTION	COUNTY	TOTAL	SHEET NO.
			80	(06-1,2)RS-3, I	BUREAU	116	114
CONTRACT NO. 6662	7				CONTRACT	NO. E	6623
SCALE: SHEET NO OF SHEETS STA TO STA FED. ROAD DIST. NO ILLINOIS FED. AID PROJECT	SCALE: SHEET NO OF SH	TS STA TO STA	FED. RO	DAD DIST. NO ILLINOIS FED. A	ID PROJECT		