

INDEX OF SHEETS

For Index of Sheets See page 2

LIST OF STANDARDS

280001-02 609006-02 635011-01 701321-08
 420401-05 630001-06 666001 701326-02
 482011-01 630301-03 701006-02 702001-06
 515001-02 631031-05 701011-01 704001-02
 542401 635001 701301-02 780001-01
 601101 635006-02 701311-02 781001-02
 701201-02


DESIGN DESIGNATION

ADT = 2850 (2001)
MU 14% SU 5%


STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION

DIVISION OF HIGHWAYS

PLANS FOR PROPOSED
FEDERAL AID HIGHWAYFAP ROUTE 310 (US 67)
SECTION (41-A)BR
McDONOUGH COUNTY
C-94-103-99PROJECT BRF - 0310 (095)
R2W of the 4th PMCarter Creek
SN 055-0007 (exist.)
SN 055-0048 (prop.)

OCAA BITUMINOUS CONCRETE SUPERPAVE
 OCAA CONCRETE
 NPDES PERMIT REQUIRED
 404/401 PERMIT REQUIRED



FULL SIZE PLANS HAVE BEEN PREPARED USING STANDARD
 ENGINEERING SCALES. REDUCED SIZED PLANS WILL NOT
 CONFORM TO STANDARD SCALES. IN MAKING MEASUREMENTS
 ON REDUCED PLANS, THE ABOVE SCALES MAY BE USED.

J.U.L.I.E.
 JOINT UTILITY LOCATION INFORMATION FOR EXCAVATION
 1-800-892-0123

CONTRACT NO. 88939
 CATALOG NO. 031050-00D

GROSS LENGTH OF IMPROVEMENT = 645 FEET = 0.12 MILES
 NET LENGTH OF IMPROVEMENT = 585 FEET = 0.11 MILES



FRED M. LIN, PE
 IL REGISTERED ENGINEER
 REGISTRATION NO. 062-056704
 REGISTRATION EXP. 11-30-2007

STATE OF ILLINOIS
DEPARTMENT OF TRANSPORTATION
DIVISION OF HIGHWAYS
SUBMITTED <i>Aug 16 2006</i>
<i>John Doe</i>
DEPUTY DIRECTOR OF HIGHWAYS, REGION ENGINEER
<i>October 13, 2006</i>
<i>Mike Henry</i>
ENGINEER OF DESIGN AND ENVIRONMENT
<i>October 13, 2006</i>
<i>Milton R. Sees, P.E.</i>
DIRECTOR OF HIGHWAYS, CHIEF ENGINEER

PRINTED BY THE AUTHORITY
 OF THE STATE OF ILLINOIS

GENERAL NOTES

BITUMINOUS CONCRETE MIXTURE REQUIREMENTS

Mixture Use(s):	BIT. CONCRETE SURFACE CSE.	BIT. CONCRETE LVL. BINDER	BIT. CONCRETE BINDER CSE. & BITUMINOUS SHLD. (BOTTOM LIFT)	BITUMINOUS SHLD. (TOP LIFT)
RAP % (Max)**:	15%	0%	25%	30%
ACPC:	PG 64-22	SBR or SBS PG 70-22	PG 64-22	PG 64-22
Design Air Voids:	4.0% @ N=50	4.0% @ N=50	4.0% @ N=50	4.0% @ N=50
Mixture Composition: (Gradation Mixture)	IL 9.5 OR 12.5	IL 4.75	IL 19.0	IL 9.5L
Friction Aggregate	MIXTURE D	N/A	N/A	MIXTURE C

**** If the RAP option is selected, the asphalt cement grade may need to be adjusted; this will be determined by the Engineer.**

PAVING SURFACE COURSES

Continuous paving operations on the main roadway shall be maintained at all times during the construction of the bituminous surface. No interruptions for side roads, entrances, turn lanes etc. will be allowed.

ORDERING LENGTH CONFIRMATION – DRAINAGE ITEM

The Contractor shall consult with the Engineer in regard to the exact length of the box/pvc culverts, storm sewers, and/or pipe drains required prior to ordering these items.

ENGINEERS FIELD OFFICE

Add the following sentence to the end of paragraph 670.02 (i) and 670.04 (i):
All of the telephone lines provided shall have unpublished numbers.

PAVEMENT STATIONING NUMBERS & PLACEMENT

The Contractor shall provide labor and materials required to imprint pavement station numbers in the finished surface of the pavement and/or overlay. The numbers shall be approximately 2 mm (3/4 inch) wide, 125 mm (5 inches) high and 15 mm (5/8 inch) deep.

The pavement station numbers shall be installed as specified herein.

Interval = 100 meters (metric stationing) or 200 feet (English stationing)

Bottom of Numbers 150 mm (6 inches) from the Inside edge of the pavement marking.

Lectures

- * **2, 3, & 5 Lane Pavements** – right edge of pavement in direction of increasing stationing
 - * **Multi-Lane Divided Roadways** – outside edge of pavement in both directions
 - * **Ramps** – along baseline edge of pavement

Position – stations shall be placed so they can be read from the adjacent shoulder.

Format – Metric (English) pavement stations shall use this format (XX + X00" (XXX")) where X represents the pavement station.

This work will not be paid for separately, but will be considered included in the cost of the associated pavement and/or overlay pay items.

Company	Offset	Location	Type of Utility	Type of Conflict	Disposition
AmerenCIPS (Electric)	30' RT	565 + 60	Power Pole	Fill	Relocate
AmerenCIPS (Electric)	30' RT	568 + 53	Power Pole	Fill	Relocate
McDonough Telephone	30' LT	564 + 15 to 565 + 30	Buried Telephone	Cut	Relocate
McDonough Telephone	28' LT	565 + 50 to 569 + 00	Buried Telephone	Benching	Caution
McDonough Telephone	32' LT	569 + 20 to 570 + 75	Buried Telephone	Cut	Relocate

STATUS OF UTILITIES TO BE ADJUSTED

ILLINOIS DEPARTMENT OF TRANSPORTATION

SUMMARY OF QUANTITIES

SECTION	COUNTY	TOTAL SHEETS	HEET NO
310	141-AISB	MCDONOUGH	58
STA.	TO STA.		
REG. ROAD DIST. NO. Y	ILLINOIS	FED-AID PROJECT	

SUMMARY OF QUANTITIES			TOTAL QUANTITIES	CONSTRUCTION TYPE CODE		
CODE NO	ITEM	UNIT		FED-STATE 80%-20% X020-2A MCDONOUGH	FED-STATE 80%-20% SFTY-3N MCDONOUGH	
20100110	TREE REMOVAL (6 TO 15 UNITS DIAMETER)	UNIT	650	650		
20100210	TREE REMOVAL (OVER 15 UNITS DIAMETER)	UNIT	119	119		
20200100	EARTH EXCAVATION	CU YD	5300	5300		
20300100	CHANNEL EXCAVATION	CU YD	100	100		
20700400	POROUS GRANULAR EMBANKMENT, SPECIAL	CU YD	45	45		
21101615	TOP SOIL FURNISH AND PLACE, 4"	SQ YD	4840	4840		
25000300	SEEDING, CLASS 3	ACRE	1	1		
25000400	NITROGEN FERTILIZER NUTRIENT	POUND	90	90		
25000500	PHOSPHORUS FERTILIZER NUTRIENT	POUND	90	90		
25000600	POTASSIUM FERTILIZER NUTRIENT	POUND	90	90		
25000700	AGRICULTURAL GROUND LIMESTONE	TON	2	2		
25002300	TEMPORARY SEEDING	ACRE	1	1		
25100115	MULCH, METHOD 2	ACRE	1	1		
25100630	EROSION CONTROL BLANKET	SQ YD	1000	1000		
28000300	TEMPORARY DITCH CHECKS	EACH	5	5		
28000400	PERIMETER EROSION BARRIER	FOOT	825	825		
28000500	INLET AND PIPE PROTECTION	EACH	1	1		
28100105	STONE RIPRAP, CLASS A3	SQ YD	1223	1223		
28100107	STONE RIPRAP, CLASS A4	SQ YD	1015	1015		
28200200	FILTER FABRIC	SQ YD	2238	2238		
40200800	AGGREGATE SURFACE COURSE, TYPE B	TON	20.5	20.5		
40600100	BITUMINOUS MATERIALS (PRIME COAT)	GALLON	500	500		
40600300	AGGREGATE (PRIME COAT)	TON	1.2	1.2		
40600980	BITUMINOUS SURFACE REMOVAL - BUTT JOINT	SQ YD	274	274	*	
40600990	TEMPORARY RAMP	SQ YD	862.2	862.2	*	
42001165	BRIDGE APPROACH PAVEMENT	SQ YD	236	236	*	
42001300	PROTECTIVE COAT	SQ YD	354	354	*	
42001430	BRIDGE APPROACH PAVEMENT CONNECTOR (FLEXIBLE)	SQ YD	50.7	50.7	*	
44000006	BITUMINOUS SURFACE REMOVAL 1 1/2"	SQ YD	440	440		
44000100	PAVEMENT REMOVAL	SQ YD	292	292		
44000920	BITUMINOUS CONCRETE SHOULDER REMOVAL	SQ YD	96.2	96.2		
48202600	BITUMINOUS SHOULDERS SUPERPAVE 8"	SQ YD	14.7	14.7		
48202800	BITUMINOUS SHOULDERS SUPERPAVE 10"	SQ YD	444.9	444.9		

SUMMARY OF QUANTITIES			TOTAL QUANTITIES	CONSTRUCTION TYPE CODE		
CODE NO	ITEM	UNIT		FED-STATE 80%-20% X020-2A MCDONOUGH	FED-STATE 80%-20% SFTY-3N MCDONOUGH	
48202900	BITUMINOUS SHOULDERS SUPERPAVE (VARIABLE DEPTH)	SQ YD	222.2	222.2		
50100100	REMOVAL OF EXISTING STRUCTURES	EACH	1	1		
50105220	PIPE CULVERT REMOVAL	FOOT	34	34		
50200100	STRUCTURE EXCAVATION	CU YD	124	124		
50300100	FLOOR DRAINS	EACH	6	6		
50300225	CONCRETE STRUCTURES	CU YD	103.9	103.9		
50300255	CONCRETE SUPER STRUCTURES	CU YD	156.2	156.2		
50300260	BRIDGE DECK GROOVING	SQ YD	270	270		
50300300	PROTECTIVE COAT	SQ YD	354	354		
50800205	REINFORCEMENT BARS, EPOXY COATED	POUND	37040	37040		
51201100	FURNISHING METAL PILE SHELLS 14"	FOOT	1821	1821		
51202600	DRIVING AND FILLING SHELLS	FOOT	1821	1821		
51203200	TEST PILE METAL SHELLS	EACH	2	2		
51205200	TEMPORARY SHEET PILING	SQ FT	1334	1334		
51500100	NAME PLATES	EACH	1	1		
54200223	PIPE CULVERTS, CLASS D, TYPE 1 18"	FOOT	34	34		
54215547	METAL END SECTIONS 12"	EACH	4	4		
54215553	METAL END SECTIONS 18"	EACH	2	2		
59100100	GEOCOMPOSITE WALL DRAIN	SQ YD	31	31		
60100945	PIPE DRAINS 12"	FOOT	116	116		
60109580	PIPE UNDERDRAINS FOR STRUCTURES 4"	FOOT	97	97		
60600095	CLASS SI CONCRETE (OUTLET)	CU YD	3.5	3.5		
60900240	TYPE C INLET BOX, STANDARD 609006	EACH	4	4		
60900515	CONCRETE THRUST BLOCKS	EACH	4	4		
* 63000000	STEEL PLATE BEAM GUARD RAIL, TYPE A	FOOT	525	525		
* 63100085	TRAFFIC BARRIER TERMINAL, TYPE 6	EACH	4	4		
* 63100169	TRAFFIC BARRIER TERMINAL TYPE 1 SPECIAL (FLARED)	EACH	4	4		
66502300	WOVEN WIRE FENCE REMOVAL	FOOT	1040.5	1040.5		
66600105	FURNISHING AND ERECTING RIGHT-OF-WAY MARKERS	EACH	16	16		
66700205	PERMANENT SURVEY MARKERS, TYPE I	EACH	1	1		
67000400	ENGINEER'S FIELD OFFICE, TYPE A	CAL MO	3	3		
67100100	MOBILIZATION	L SUM	1	1		

ILLINOIS DEPARTMENT OF TRANSPORTATION

SUMMARY OF QUANTITIES

F. A. P. ITE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
310	(41-AIBR	MCDONOUGH	58	5
STA.	TO STA.			
FEED ROAD DIST. NO. 7	ILLINOIS	PUB. AID PROJECT		

SUMMARY OF QUANTITIES			TOTAL QUANTITIES	CONSTRUCTION TYPE CODE		
CODE NO	ITEM	UNIT		FED-STATE 80%-20% X020-2A MCDONOUGH	FED-STATE 80%-20% SFTY-3N MCDONOUGH	
70100405	TRAFFIC CONTROL AND PROTECTION, STANDARD 701321	EACH	1	1		
70100450	TRAFFIC CONTROL AND PROTECTION, STANDARD 701201	L SUM	1	1		
70100500	TRAFFIC CONTROL AND PROTECTION, STANDARD 701326	L SUM	1	1		
70106500	TEMPORARY BRIDGE TRAFFIC SIGNALS	EACH	1	1		
70106700	TEMPORARY RUMBLE STRIP	EACH	6	6		
70300520	PAVEMENT MARKING TAPE, TYPE III 4"	FOOT	8428	8428		
70300625	TEMPORARY PAINT PAVEMENT MARKING LINE 4"	FOOT	2580	2580		
70301000	WORK ZONE PAVEMENT MARKING REMOVAL	SQ FT	2810	2810		
70400100	TEMPORARY CONCRETE BARRIER	FOOT	587.5	587.5		
70400200	RELOCATE TEMPORARY CONCRETE BARRIER	FOOT	487.5	487.5		
* 78005110	EPOXY PAVEMENT MARKING - LINE 4"	FOOT	2580	2580		
78200410	GUARDRAIL MARKERS, TYPE A	EACH	16	16		
78200520	BARRIER WALL MARKERS, TYPE B	EACH	2	2		
78201000	TERMINAL MARKER - DIRECT APPLIED	EACH	4	4		
78300100	PAVEMENT MARKING REMOVAL	SQ FT	582	582		
Z0002600	BAR SPLICERS	EACH	196	196		
Z0013798	CONSTRUCTION LAYOUT	L SUM	1	1		
Z0020800	EROSION CONTROL CURB	FOOT	648	648		
Z0030250	IMPACT ATTENUATORS, TEMPORARY (NON-REDIRECTIVE), TEST LEVEL 3"	EACH	4	4		
Z0030350	IMPACT ATTENUATORS, RELOCATE (NON-REDIRECTIVE), TEST LEVEL 3"	EACH	2	2		
X0301512	GUARDRAIL AGGREGATE EROSION CONTROL	TON	197	197		
X0321475	PIPE ELBOW, 12"	EACH	8	8		
X4066424	BITUMINOUS CONCRETE SURFACE COURSE, SUPER PAVE, MIX "D", N50	TON	239	239		
X4066614	BITUMINOUS CONCRETE BINDER COURSE, SUPER PAVE, IL-19.0 N50	TONS	517.6	517.6		
X5020501	UNDERWATER STRUCTURE EXCAVATION PROTECTION - LOCATION 1	EACH	1	1		
X5020502	UNDERWATER STRUCTURE EXCAVATION PROTECTION - LOCATION 2	EACH	1	1		

SUMMARY OF QUANTITIES			TOTAL QUANTITIES	CONSTRUCTION TYPE CODE		
CODE NO	ITEM	UNIT		FED-STATE 80%-20% X020-2A MCDONOUGH		
A2002014	TREE AESCULUS GLABRA (OHIO BUCKEYE) 1-3/4" CALIPER, BALLED AND BURLAPPED	EACH	3	3		
A2002914	TREE, CELTIS OCCIDENTALIS (COMMON HACKBERRY), 1-3/4" CALIPER, BALLED AND BURLAPPED	EACH	7	7		
A2005014	TREE, GYMNOCLADUS DIOICUS (KENTUCKY COFFEE TREE). 1-3/4" CALIPER, BALLED AND BURLAPPED	EACH	5	5		
A2006514	TREE, QUERCUS BICOLOR (SWAMP WHITE OAK), 1-3/4" CALIPER, BALLED AND BURLAPPED	EACH	7	7		
A2006708	TREE, QUERCUS MACROCARPA (BUR OAK), 1" CALIPER, BALLED AND BURLAPPED	EACH	5	5		
B2001164	TREE, CERCIS CANADENSIS(EASTERN REBUD) 5' HEIGHT, CLUMP FORM, BALLED AND BURLAP PED	EACH	5	5		
B2006214	TREE, SYRINGA RETICULATA (JAPANESE TREE LILAC). 1-3/4" CALIPER, TREE FORM, BALLED AND BURLAPPED	EACH	15	15		

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	sheet NO.
310	(4L-AIBR	MCDONOUGH	58	6
STA.	TO STA.			
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		

D-94-025-99

SCHEDULE OF QUANTITIES

20100110 TREE REMOVAL (6 TO 15 UNITS DIAMETER)

LOCATION	QUANTITY (UNIT)
STATION	
RIGHT SIDE NORTH OF CREEK	72
LEFT SIDE NORTH OF CREEK	26
RIGHT SIDE SOUTH OF CREEK	261
LEFT SIDE SOUTH OF CREEK	291
TOTAL =	650

20100210 TREE REMOVAL (OVER 15 UNITS DIAMETER)

LOCATION	QUANTITY (UNIT)
STATION	
RIGHT SIDE NORTH OF CREEK	0
LEFT SIDE NORTH OF CREEK	0
RIGHT SIDE SOUTH OF CREEK	101
LEFT SIDE SOUTH OF CREEK	18
TOTAL =	119

20200100 EARTH EXCAVATION

LOCATION	EARTH EXCAVATION CU. YD.	EARTH EXCAVATION ADJUSTED FOR SHRINKAGE CU. YD.	EMBANKMENT CU. YD.	EARTHWORK BALANCE WASTE (+) OR SHORTAGE (-) CU. YD.
STATION				
NORTH OF BRIDGE	1682.1	1345.7	1300.2	+45.6
SOUTH OF BRIDGE	3610.8	2888.7	2701.3	+187.4
TOTAL =	5292.9	4234.3	4001.5	+232.8

28000300 TEMPORARY DITCH CHECKS

LOCATION	QUANTITY (EACH)
STATION	
RIGHT SIDE STA. 566+75	1
STA. 568+25	1
LEFT SIDE STA. 566+75	1
STA. 568+25	1
STA. 569+25	1
TOTAL =	5

28000500 INLET AND PIPE PROTECTION

LOCATION	QUANTITY (EACH)
STATION	
STA. 564+48.9 OFF. 33.4, LT.	1
TOTAL =	1

29100105 STONE RIPRAP, CLASS A3

LOCATION	QUANTITY (SQ. YD.)
STATION	
STA. 564+00 TO STA. 566+50, RT.	382
STA. 564+00 TO STA. 566+00, LT.	260
STA. 569+50 TO STA. 571+00, RT.	347
STA. 568+75 TO STA. 571+00, LT.	234
TOTAL =	1223

40200800 AGGREGATE SURFACE COURSE, TYPE B

LOCATION	QUANTITY (TON)
STATION	
STA. 564+65.5, LT.	20.5
TOTAL =	20.5

40600100 BITUMINOUS MATERIALS (PRIME COAT)

LOCATION	QUANTITY (GALLON)
STATION	
STA. 564+45 TO 568+73.5	250.0
STA. 568+09.5 TO 570+30	250.0
TOTAL =	500.0

40600980 BITUMINOUS SURFACE REMOVAL - BUTT JOINT

LOCATION	QUANTITY (SQ. YD.)
STATION	
STA. 564+15 TO 564+45	80.0
STA. 570+30 TO 570+60	80.0
STA. 566+58.5 TO 568+73.5	56.7
STA. 568+09.5 TO 568+24.5	56.7
TOTAL =	273.4

40600990 TEMPORARY RAMP

LOCATION	QUANTITY (SQ. YD.)
STATION	
STA. 564+15	13.3
STA. 566+13	40.0
STA. 565+73.5 TO 566+73.5	377.8
STA. 565+73.5 TO 566+73.5	377.8
STA. 568+75	40.0
STA. 570+60	13.3
TOTAL =	862.2

42001165 BRIDGE APPROACH PAVEMENT

LOCATION	QUANTITY (SQ. YD.)
STATION	
STA. 566+73.5 TO 567+03.5	117.8
STA. 567+79.5 TO 568+09.5	117.8
TOTAL =	235.6

42001430 BRIDGE APPROACH PAVEMENT CONNECTOR (FLEXIBLE)

LOCATION	QUANTITY (SQ. YD.)
STATION	
STA. 568+67.5 TO 566+73.5, RT.	26.3
STA. 568+09.5 TO 568+15.5, RT.	26.3
TOTAL =	50.7

44000006 BITUMINOUS SURFACE REMOVAL 1 1/2"

LOCATION	QUANTITY (SQ. YD.)
STATION	
STA. 564+45 TO STA. 565+30	228.7
STA. 569+50 TO STA. 570+30	213.3
TOTAL =	440.0

44000100 PAVEMENT REMOVAL

LOCATION	QUANTITY (SQ. YD.)
STATION	
STA. 566+70.5 TO STA. 567+18.8	128.8
STA. 567+51.3 TO STA. 568+12.5	163.2
TOTAL =	292.0

60600095 CLASS SI CONCRETE (OUTLET)

LOCATION	QUANTITY (CU. YD.)
STATION	
STA. 563+62, LT.	3.5
TOTAL =	3.5

44000920 BITUMINOUS CONCRETE SHOULDER REMOVAL

LOCATION	QUANTITY (SQ. YD.)
STATION	
STA. 564+34.2 TO STA. 565+35.0, LT.	76.5
STA. 565+92 TO STA. 567+19, LT.	9.0
STA. 567+68 TO STA. 568+0	

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	(41-A)BR	McDONOUGH	58
STA.	TO STA.		
		FED. ROAD DIST. NO.	ILLINOIS
		FED. AID PROJECT	
D-94-025-99			

SCHEDULE OF QUANTITIES

54215553 METAL END SECTION 18"

LOCATION	QUANTITY (EACH)
STATION, OFFSET	
STA. 564+48.9 OFF. 33.4 LT.	1
STA. 564+82.4 OFF. 32.8 LT.	1
TOTAL =	2

60100945 PIPE DRAINS 12"

LOCATION	QUANTITY (FOOT)
STATION	
STA. 566+90.0, RT.	30.0
STA. 566+90.0, LT.	28.0
STA. 567+93.0, RT.	30.0
STA. 567+93.0, LT.	28.0
TOTAL =	116.0

60900240 TYPE C INLET BOX, STANDARD 609006

LOCATION	QUANTITY (EACH)
STATION	
STA. 566+90.0, BOTH LT. AND RT.	2
STA. 567+93.0, BOTH LT. AND RT.	2
TOTAL =	4

60900515 CONCRETE THRUST BLOCKS

LOCATION	QUANTITY (EACH)
STATION	
STA. 566+90.0, BOTH LT. AND RT.	2
STA. 567+93.0, BOTH LT. AND RT.	2
TOTAL =	4

63000000 STEEL PLATE BEAM GUARD RAIL, TYPE A

LOCATION	QUANTITY (FOOT)
STATION	
STA. 565+85.35 TO STA. 566+72.85, LT	87.5
STA. 564+97.85 TO STA. 566+72.85, RT	175.0
STA. 568+10.15 TO STA. 569+85.15, LT	175.0
STA. 568+10.15 TO STA. 568+97.65, RT	87.5
TOTAL =	625.0

63100085 TRAFFIC BARRIER TERMINAL TYPE 6

LOCATION	QUANTITY (EACH)
STATION	
STA. 568+72.85 TO PARAPET, LEFT & RIGHT	2
PARAPET TO STA. 568+10.15, LEFT & RIGHT	2
TOTAL =	4

63100169 TRAFFIC BARRIER TERMINAL TYPE 1, SPECIAL (FLARED)

LOCATION	QUANTITY (EACH)
STATION	
STA. 565+35.35 TO STA. 565+85.35, LT	1
STA. 564+47.85 TO STA. 564+97.85, RT	1
STA. 569+35.15 TO STA. 570+35.15, LT	1
STA. 568+97.65 TO STA. 569+47.65, RT	1
TOTAL =	4

66502300 WOVEN WIRE FENCE REMOVAL

LOCATION	QUANTITY (FOOT)
STATION	
STA. 564+00 TO WING WALL, RT.	313.5
WING WALL TO STA. 571+25, RT.	188.0
STA. 565+59.5 TO WING WALL, LT.	375.5
WING WALL TO STA. 568+89.8, LT.	163.5
TOTAL =	1040.5

70301000 WORK ZONE PAVEMENT MARKING REMOVAL

LOCATION	QUANTITY (SQ. FT.)
STAGE 1	
STA. 565+23.5 TO STA. 569+59.5	290.7
STOP BARS	48.0
STAGE 2	
STA. 565+23.5 TO STA. 569+59.5	290.7
STAGE 3	
Estimated	2180.0
TOTAL =	2809.3

70400100 TEMPORARY CONCRETE BARRIER

LOCATION	QUANTITY (FOOT)
STATION	
STA. 565+23.5 TO STA. 569+09.5	487.5
STA. 568+92 TO STA. 567+68	50.0
STA. 567+51 TO STA. 567+68	50.0
TOTAL =	587.5

70400200 RELOCATE TEMPORARY CONCRETE BARRIER

LOCATION	QUANTITY (FOOT)
STATION	
STA. 565+23.5 TO STA. 570+09.5	487.5
TOTAL =	487.5

70300625 TEMPORARY PAINT PAVEMENT MARKING - LINE 4"
78005110 EPOXY PAVEMENT MARKING - LINE 4"

LOCATION	QUANTITY (FOOT)
STATION	
STA. 564+15.0 TO STA. 570+60.0, RT.	645.0
STA. 564+15.0 TO STA. 570+60.0, LT.	645.0
STA. 564+15.0 TO STA. 570+60.0, CENTER	1290.0
TOTAL =	2580.0

78200410 GUARDRAIL MARKERS, TYPE A

LOCATION	QUANTITY (EACH)
STATION	
RIGHT SIDE	
STA. 564+97.85	1
STA. 565+47.85	1
STA. 565+97.85	1
STA. 566+47.85	1
STA. 566+97.85	1
STA. 567+97.85	1
STA. 568+47.85	1
STA. 568+97.85	1
STA. 569+47.85	1
LEFT SIDE	
STA. 569+85.15	1
STA. 569+35.15	1
STA. 568+85.15	1
STA. 568+35.15	1
STA. 567+85.15	1
STA. 566+85.15	1
STA. 565+85.15	1
STA. 564+85.15	1
TOTAL =	16

70300520 PAVEMENT MARKING TAPE, TYPE III 4"

LOCATION	QUANTITY (FOOT)
STATION	
JOB SITE	6
TOTAL =	6
STAGE 1	
STA. 565+23.5 TO STA. 569+59.5	872.0
STOP BARS	144.0
STAGE 2	
STA. 565+23.5 TO STA. 569+59.5	872.0
STAGE 3	
Estimated	6540.0
TOTAL =	8428.0

REVISIONS	DATE	ILLINOIS DEPARTMENT OF TRANSPORTATION
NAME	DATE	ILLINOIS DEPARTMENT OF TRANSPORTATION
		SN 055-0048
		SUMMARY OF QUANTITIES
		SCALE: VERT. / HORIZ.
		DRAWN BY
		CHECKED BY

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
310	I41-ABR	MCDONOUGH	58	8
STA.	TO STA.			
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		

D-94-025-99

SCHEDULE OF QUANTITIES

78200520 BARRIER WALL MARKERS, TYPE B

LOCATION	QUANTITY (EACH)
STATION	
RIGHT SIDE	
STA. 567+47.85	1
LEFT SIDE	
STA. 567+35.15	1
TOTAL =	2

X0301512 GUARDRAIL AGGREGATE EROSION CONTROL

LOCATION	QUANTITY (TON)
STATION	
STA. 564+25.35 TO STA. 567+03.50, RT	55.4
STA. 565+12.85 TO STA. 567+03.50, LT	42.5
STA. 567+79.50 TO STA. 569+70.15, RT	42.5
STA. 567+79.50 TO STA. 570+60.00, LT	56.4
TOTAL =	196.8

78201000 TERMINAL MARKER - DIRECT APPLIED

LOCATION	QUANTITY (EACH)
STATION	
STA. 565+35.35, LT	1
STA. 564+47.85, RT	1
STA. 570+35.15, LT	1
STA. 569+47.65, RT	1
TOTAL =	4

X0321475 PIPE ELBOW, 12"

LOCATION	QUANTITY (EACH)
STATION	
STA. 568+90.0, RT	2
STA. 568+90.0, LT	2
STA. 567+93.0, RT	2
STA. 567+93.0, LT	2
TOTAL =	8

78300100 PAVEMENT MARKING REMOVAL

LOCATION	QUANTITY (SQ. FT.)
STAGE 1	
STA. 565+23.5 TO 569+59.5 (CENTER AND LEFT)	438.0
STAGE 2	
STA. 565+23.5 TO 569+59.5 (RIGHT)	145.3
TOTAL =	583.3

X4066424 BITUMINOUS CONCRETE SURFACE COURSE, SUPERPAVE, MIX 'D', N50

LOCATION	QUANTITY (TON)
STATION	
STA. 564+15.0 TO STA. 566+73.5	91.9
STA. 568+09.5 TO STA. 570+60.0	89.1
TEMPORARY SHOULDER PAVEMENT	
STA. 565+23.5 TO STA. 567+67.5, RT	6.7
STA. 568+65.5 TO STA. 569+59.5, RT	6.7
TEMPORARY RAMP	
STA. 565+73.5 TO STA. 566+73.5	22.2
STA. 568+09.5 TO STA. 569+09.5	22.2
TOTAL =	239.0

Z0020800 EROSION CONTROL CURB

LOCATION	QUANTITY (FOOT)
STATION	
STA. 565+85.35 TO STA. 567+03.50, LT	118.16
STA. 564+97.85 TO STA. 567+03.50, RT	205.65
STA. 567+79.50 TO STA. 569+59.5, LT	205.65
STA. 567+79.50 TO STA. 568+97.65, RT	118.15
TOTAL =	647.6

X4066614 BITUMINOUS CONCRETE BINDER COURSE, SUPERPAVE, IL-19.0, N50

LOCATION	QUANTITY (TON)
STATION	
STA. 565+30.0 TO STA. 566+73.5	191.4
STA. 568+09.5 TO STA. 569+50.0	187.4
TEMPORARY SHOULDER PAVEMENT	
STA. 565+23.5 TO STA. 567+67.5, RT	87.3
STA. 568+65.5 TO STA. 569+59.5, RT	51.5
TOTAL =	517.6



Z0030250 IMPACT ATTENUATORS, TEMPORARY (NON-REDIRECTIVE), TEST LEVEL 3

LOCATION	QUANTITY (EACH)
STATION	
STA. 565+23.5, RT.	1
STA. 566+92.0, LT.	1
STA. 569+59.5, RT.	1
STA. 567+68.0, LT.	1
TOTAL =	4

Z0030350 IMPACT ATTENUATORS, RELOCATE (NON-REDIRECTIVE), TEST LEVEL 3


LOCATION	QUANTITY (EACH)
STATION	
STA. 565+23.5	1
STA. 570+09.5	1
TOTAL =	2

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEET SHEETS NO.
310	(41)-AIBR	MCDONOUGH	58 9
STA.	TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	



RIPRAP DITCH


STA. 564+00.0 TO STA. 566+50.0, RT.
STA. 564+00.0 TO STA. 566+00.0, LT.
STA. 569+50.0 TO STA. 571+00.0, RT.
STA. 568+75.0 TO STA. 571+00.0, LT.



PROPOSED TYPICAL SECTION

STA. 564+45.0 TO STA. 565+73.5
STA. 569+09.5 TO STA. 570+30.0

BUTT JOINT:
STA. 564+15.0 TO STA. 564+45.0
STA. 570+30.0 TO STA. 570+60.0



TEMP. SHLD. PAVT. DETAILS

STA. 565+23.5 TO STA. 566+73.5, RT.
STA. 568+09.5 TO STA. 570+09.5, RT.
(SEE MORE DETAILS ON TRAFFIC CONTROL PLAN)


EROSION CONTROL CURB SCHEDULES:

STA. 565+85.35 TO STA. 567+03.50, LEFT
STA. 564+97.85 TO STA. 567+03.50, RIGHT

STA. 567+79.50 TO STA. 569+85.15, LEFT
STA. 567+79.50 TO STA. 568+97.65, RIGHT

REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION	
NAME	DATE	SN 055-0048	TYPICAL SECTIONS
		U.S. 67	
		SECTION (41A)BR	
		MCDONOUGH	DRAWN BY
SCALE: VERT. HORIZ.	DATE		CHECKED BY

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
310	(41-A)BR	MCDONOUGH	58	10
STA.	TO STA.			
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		




*BRIDGE CONE TRANSITION
TRANSITION FORESLOPE FROM 3:1 TO 2:1 FROM STA. 566+73.5 TO STA. 566+93.5 AND FROM STA. 568+09.5 TO STA. 567+89.5.

**EROSION CONTROL CURB SCHEDULES:
STA. 565+85.35 TO STA. 567+03.50, LEFT
STA. 564+97.85 TO STA. 567+03.50, RIGHT
STA. 567+79.50 TO STA. 569+85.15, LEFT
STA. 567+79.50 TO STA. 568+97.65, RIGHT


CONTRACT NO. 88939

F.A.P. ATE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
310	(41-A)BR	MCDONOUGH	58	11
STA.	TO STA.			
ED. ROAD DIST. NO.		ILLINOIS	FED. AID PROJECT	



BENCH MARK:

A CHISELED SQUARE ON THE SOUTHWEST WINGWALL OF EXISTING
S.N. 055-0007, ELEVATION 620.90.





- \$ U.S. 67

LOT DATE = 8/8/2006
FILE NAME = c:\pro\jbooks\9550018\sheetpcin.dgn
LOT SCALE = 186.0105' / in.
GER NAME = hudscons

ILLINOIS DEPARTMENT OF TRANSPORTATION
SN 055-0048
HORIZONTAL ALIGNMENT &
LOCAL TIES
VERT.
HORIZ.
DRAWN BY
CHECKED BY

A scale bar and a north arrow are located in the bottom right corner of the map. The scale bar shows distances of 20', 0, 20', and 40'. The north arrow is a diamond shape with a vertical line extending from its top.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
310	(41-A)BR	MCDONOUGH	58	12
STA.	TO STA.	FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT		



SEC 26, TWP4N, R2W, 4TH P.M.

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
310	I41-ABR	MCDONOUGH	58	13
STA. 563+00.0	TO STA. 567+20.0			
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		

CONTRACT NO. 88939

PLAN SURVEYED
PLOTTED
GRADES CHECKED
STRUCTURE NOTATNS
NOTE BOOK NO.

GUARDRAIL SCHEDULES NORTH OF PR. BRIDGE:

TRAFFIC BARRIER TERMINAL, TYPE 1, SPECIAL (FLARED)
50' - STA. 565+35.35 TO STA. 565+85.35, LEFT
50' - STA. 564+47.85 TO STA. 564+97.85, RIGHT

STEEL PLATE BEAM GUARD RAIL, TYPE A
87.5' - 7 SECTIONS, STA. 565+85.35 TO STA. 566+72.85, LEFT
175' - 14 SECTIONS, STA. 564+97.85 TO STA. 566+72.85, RIGHT

TRAFFIC BARRIER TERMINAL, TYPE 6
STA. 566+72.85 TO BRIDGE PARAPET, BOTH LEFT & RIGHT


EROSION CONTROL CURB SCHEDULES:

STA. 565+85.35 TO STA. 567+03.50, LEFT
STA. 564+97.85 TO STA. 567+03.50, RIGHT

STA. 567+79.50 TO STA. 569+85.15, LEFT
STA. 567+79.50 TO STA. 568+97.65, RIGHT

NOTES:


1. BENCH MARK:
A CHISELED SQUARE ON THE SOUTHWEST WINGWALL OF EXISTING S.N. 055-0007, ELEVATION 620.90.
2. TRANSITION FORESLOPE FROM 3:1 TO 2:1 FROM STA. 566+73.5 TO STA. 566+93.5. SEE CROSS SECTION SHEETS FOR MORE DETAILS.
3. SEE EROSION CONTROL SHEET, TYPICAL & CROSS SECTION SHEETS AND STRUCTURE GENERAL PLAN AND ELEVATION SHEET FOR DETAILS OF STONE RIPRAP NOT SHOWN.



MATCH LINE STA. 567+20.00

*TYPE C INLET BOX
STD. 609006, TYP.
STA. 566+90.0

PROFILE SURVEYED
PLOTTED
GRADES CHECKED
STRUCTURE NOTATNS
NOTE BOOK NO.




F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
310	(41-AIBR	McDONOUGH	58	14
STA. 567+20.0	TO STA. 572+00.0			


FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT

CONTRACT NO. 88939

SEC 26, TWP4N, R2W, 4TH P.M.



SEC 27, TWP4N, R2W, 4TH P.M.



PROFILE SURVEYED BY DATE

PLOTTED DRAWN CHECKED SIGNATURE DATE

NOTE BOOK ISM. NOTED STRUCTURE NOTES C.H.R.D. NO.

PLOTTED DRAWN CHECKED SIGNATURE DATE

NOTE BOOK ISM. NOTED STRUCTURE NOTES C.H.R.D. NO.

635 630 625 620 615 610 605 600 595

SCALE: 1" = 20'


CONTRACT NO. 88939

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	HEET NO.
310	41-AIBR	MCDONOUGH	58	15
STA.	TO STA.			
FED. ROAD DIST. NO. ILLINOIS		FED. AID PROJECT		


MAINTENANCE OF TRAFFIC - STAGE I

SEQUENCE OF OPERATIONS							
PHASE	A	B	P/B	1	2	3	4
INTERVAL	1	2	3	4	5	6	1
NORTHBOUND	G	Y	R	R	R	R	R
SOUTHBOUND	R	R	R	C	Y	R	R
ENTRANCE	R	R	R	R	R	R	G

NOTE: PUSH BUTTON PHASE 1 STARTS AT THE END OF EITHER PHASE 3 OR PHASE 6.



MAINTENANCE OF TRAFFIC - STAGE 2



STAGE II CONSTRUCTION:

- CLOSE EAST HALF OF U.S. 67 AS SHOWN IN ACCORDANCE WITH STANDARD 701321. APPLY TEMPORARY PAVEMENT MARKING TAPES.
- REMOVE EAST HALF OF EXISTING U.S. 67 PAVEMENT AND REMAINING EX. STRUCTURE.
- ROUGH GRADE EAST SIDE EMBANKMENT, FINISH EAST SIDE DITCHES. FINISH EAST HALF OF THE PROPOSED BRIDGE AND DRAINAGE ITEMS. CONSTRUCT TEMPORARY RAMP AND SHOULDERS.
- CONSTRUCT ENTRANCE CULVERT AND GUTTER OUTLET. APPLY EROSION CONTROLS ON THE EAST SIDE.

REVISIONS	
NAME	DATE


ILLINOIS DEPARTMENT OF TRANSPORTATION

SN 055-0048
TRAFFIC CONTROL PLANSCALE: VERT.
HORIZ.
DRAWN BY
CHECKED BY

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	41-A1BR	MCDONOUGH	58 16
STA.	TO STA.		

FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT


MAINTENANCE OF TRAFFIC - STAGE III

STAGE III CONSTRUCTION:

1. CONSTRUCT BINDER, SURFACE COURSES AND BIT. SHOULDERS UNDER STD. 701201.
2. CONSTRUCT PR. ENTRANCE AND MAIL BOX TURNOUT.
3. INSTALL PROPOSED GUARDRAIL.
4. APPLY PERMANENT PAVEMENT MARKINGS UNDER STD. 701311 OR OTHERWISE AS DIRECTED BY THE ENGINEER. COST OF M.O.T. FOR APPLICATION OF P.M. WILL NOT BE PAID FOR SEPARATELY, BUT SHALL BE CONSIDERED AS INCLUDED IN THE UNIT PRICE OF EPOXY PAVEMENT MARKING.


STAGE III NOTES:

1. AFTER COMPLETION OF A COMPLETE BITUMINOUS LIFT THE EMBANKMENT ADJACENT TO THE ROADWAY WILL BE PLACED TO MAINTAIN DROPOFFS OF 4" OR LESS AND SLOPES NO STEEPER THAN 1:3.
2. DURING PAVING LAYERS, SMOOTH TRANSITIONS SHALL BE PROVIDED FOR U.S. 67. LONGITUDINAL LANE DROPS SHALL BE LESS THAN 4".
3. DURING PAVING OPERATIONS, APPLY SHORT TERM PAVEMENT MARKINGS PRIOR TO OPENING TO TRAFFIC AT THE END OF EACH DAY.
4. BUTT JOINTS SHALL BE CONSTRUCTED DURING THE FINAL SURFACING LAYER OF STAGE III.
5. AT LEAST ONE LANE SHALL BE OPEN TO VEHICLES AT ALL TIMES.
6. PRIOR TO THE INSTALLATION OF GUARDRAIL, TYPE II BARRICADES SHOULD BE PLACED AT LOCATIONS AS DIRECTED BY THE ENGINEER.







20' 0" 20' 40"
SCALE: 1" = 40'

100' TEMPORARY RAMP

A-A, STAGE I

100' TEMPORARY RAMP

TEMPORARY RAMP DETAILS (STAGE I)B-B, STAGE IA-A, STAGE IIIB-B, STAGE III

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

SN 055-0048
TRAFFIC CONTROL PLANSCALE: VERT.
HORIZ.
DATEDRAWN BY
CHECKED BY

CONTRACT NO. 88939

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
310	14L-A1BR	MCDONOUGH	58	17
STA.	TO STA.			

FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT

SEC 26, TWP4N, R2W, 4TH P.M.

EROSION CONTROL LEGEND

- INLET & PIPE PROTECTION
- TEMPORARY DITCH CHECK
- PROP. SEEDING, CLASS 3 & MULCH METHOD 2 WITHIN CONSTRUCTION LIMITS (TYP.)
- STONE RIPRAP WITH FILTER FABRIC
- EXISTING DITCH FLOW
- PROPOSED DITCH FLOW
- PERIMETER EROSION BARRIER

POT Sta 561+70.00

34' PIPE CULVERTS, CLASS D, TY. 1 18"
 WITH METAL END SECTIONS, 2.2%
 U.S. R STA. 564+48.9 OFF. 33.4' LT. EL. 625.56
 D.S. E STA. 564+82.4 OFF. 32.8' LT. EL. 624.83

PR. R.O.W.

PR. CONST. LIMIT

EX. R.O.W.

562

U.S. 67

563

12±


564

565+00

566

567

NOTE:
 EROSION CONTROL BLANKET SHALL BE INSTALLED ON SLOPES STEEPER
 THAN 1:3 AND AT LOCATIONS AS DIRECTED BY THE ENGINEER.



10' 0 10' 20'
 SCALE: 1" = 20'

SEC 27, TWP4N, R2W, 4TH P.M.

MATCH LINE STA. 567+20.00

STONE RIPRAP CLASS A3 WITH FILTER FABRIC
 FOR DITCH EROSION CONTROL
 SEE TYPICAL SECTION SHEET FOR MORE DETAILS.

SEC 26, TWP4N, R2W, 4TH P.M.

MATCH LINE STA. 567+20.00

TOP OF CHANNEL
BANK (TYPICAL)

PR. R.O.W.

10'

(TYPICAL)

STONE RIPRAP CLASS A3 WITH FILTER FABRIC

FOR DITCH EROSION CONTROL

SEE TYPICAL SECTION SHEET FOR MORE DETAILS.

EX. R.O.W.

12±

571

0

U.S. 67

1

572

POT Sta 572+70.00

STONE RIPRAP CLASS A4 WITH FILTER FABRIC
 SEE STRUCTURE GENERAL PLAN AND ELEVATION SHEET

10' 0 10' 20'
 SCALE: 1" = 20'

SEC 27, TWP4N, R2W, 4TH P.M.

REVISIONS	NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION

SN 055-0048
 EROSION CONTROL SHEET

SCALE: VERT.
 HORIZ.
 DRAWN BY
 CHECKED BY


Bench Mark:
A chiseled square on the Southwest wingwall of existing S.N. 055-0007. Elevation 620.90

Existing Structure:
The existing Structure No. 055-0007, Constructed in 1924, is a single span reinforced concrete tee beam bridge on closed abutments with wingwalls. Back to back abutments length is 33'-0" and out to out deck width is 32'-8". The existing structure was rehabilitated in 1997, which added two longitudinal WF beams in each bay between the existing concrete tee beams. The Contractor shall remove and replace the existing structure. Staged Construction will be utilized to maintain one lane of traffic during construction. No Salvage.


ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
F.A.P. 310 U.S. 67	(41-A)BR	McDonough	58	18

PED. ROAD DIST. NO. 4
HOUDI PROJECT
Contract #88939

SHEET NO. 1
16 SHEETS





ELEVATION




SECTION A-A

INDEX OF SHEETS


1. General Plan and Elevation
2. Stage Construction Details
3. Slab Elevations
4. Superstructure
5. Superstructure Details
6. North Abutment
7. South Abutment
8. Piers
9. Temporary Concrete Barrier
10. Bar Splicer Assembly Details
11. Pile Details
- 12-16. Soil Borings



PLAN



PROFILE GRADE
(US 67 Along Q Roadway)



LOCATION SKETCH

APPROVED
For Structural Adequacy Only




Ralph E. Anderson
Engineer of Bridges & Structures

Michael J. Koenig 6-28-06

Michael T. Haley
Licensed Structural Engineer
State of Illinois No. 81-5991

Date



GENERAL NOTES

1. Reinforcement bars shall conform to the requirements of AASHTO M31 or M322 Grade 60.
2. Placement of slope protection system may be varied in the field to suit ground conditions as directed by the Engineer.
3. The Contractor shall make allowance for the deflection of forms, shrinkage and settlement of falsework, in addition to allowance for dead load deflection.
4. The Contractor shall drive one Metal Shell test pile in a permanent location at each the North Abutment and at Pier 2 as directed by the Engineer before ordering the remainder of piles.
5. All construction joints shall be bonded.
6. Excavation behind existing abutment walls shall be done before removing the existing superstructure. The Contractor shall sawcut the existing abutments at the stage removal line before Stage 1 removal.
7. Bridge approach slab shall be poured after removal of concrete slab forms.

DESIGN SPECIFICATIONS

2002 AASHTO Specifications

DESIGN STRESSES

f'c = 3,500 psi
fy = 60,000 psi (Reinforcement)

LOADING HS20-44

Allow 50 lb/sq. ft for future wearing surface

SEISMIC DATA

Seismic Performance Category (SPC) = A
Bedrock Acceleration Coefficient (A) = 0.041g
Site Coefficient (S) = 1.5

STATION 567+41.50
BUILT 20... BY
STATE OF ILLINOIS
F.A.P. RTE. 310 SEC (41A)BR
LOADING HS20
STRUCTURE NO. 055-0048

NAME PLATE
(See Std. 515001)

WATERWAY INFORMATION

Drainage Area = 10.0 Sq. Mi. Low Grade Elev. 621.0 At Sta. 567+41						
Flood	Freq. Yr.	Q C.F.S.	Opening Sq. Ft.	Nat. Exist. Prop.	Head-Ft. Exist. Prop.	Headwater El. Exist. Prop.
-	10	1217	249	359	616.1	0.3 0.0 616.4 616.1
Design	50	1917	283	425	617.3	0.9 0.4 618.2 617.7
Base	100	2219	295	451	617.7	1.1 0.5 618.8 618.2
Max. Calc.	500	2952	303	509	618.6	1.9 0.8 620.5 619.4

ILLINOIS DEPARTMENT OF TRANSPORTATION

GENERAL PLAN AND ELEVATION

F.A.P. ROUTE 310 (US 67)

OVER CARTER CREEK

SECTION (41A)BR


MCDONOUGH COUNTY

STA. 567+41.50

S.N. 055-0048


ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
F.A.P. 310 U.S. 67	(41-A)BR	McDonough	58	19
FED. RD. DIST. NO. +		FED. AID PROJECT -		

Contract #88939

SHEET NO. 2
16 SHEETS


STAGE I REMOVAL & CONSTRUCTION

(Looking South)




STAGE II REMOVAL & CONSTRUCTION

(Looking South)



PROPOSED CROSS SECTION




SECTION THRU INTEGRAL ABUTMENT

* Included in the cost of Pipe Underdrains for Structures.

Note:

All drainage system components shall extend to 2'-0" from the end of each wingwall except an outlet pipe shall extend until intersecting with the side slopes. The pipes shall drain into concrete headwalls. (See Article 601.05 of the Standard Specifications and Highway Standard 60110).

ITEM	UNIT	SUPER	SUB	TOTAL
Removal of Existing Structures	Each	1	1	1
Structure Excavation	Cu. Yd.		124	124
Underwater Structure Excavation	Each		1	1
Underwater Structure Excavation Protection - Location 1	Each		1	1
Underwater Structure Excavation Protection - Location 2	Each		1	1
Temporary Sheet Piling	Sq. Ft.	1334	1334	
Porous Granular Embankment (Special)	Cu. Yd.	45	45	
Pipe Underdrains for Structures 4"	Foot	97	97	
Geocomposite Wall Drain	Sq. Yd.	31	31	
Concrete Structures	Cu. Yd.	103.9	103.9	
Concrete Superstructure	Cu. Yd.	156.2	156.2	
Bridge Deck Grooving	Sq. Yd.	270	270	
Reinforcement Bars, Epoxy Coated	Pound	26,310	10,730	37,040
Bar Splicers	Each	118	78	196
Protective Coat	Sq. Yd.	351	3	354
Floor Drains	Each	6	6	
Furnishing Metal Pile Shells 14"	Foot	1821	1821	
Driving and Filling Shells	Foot	1821	1821	
Test Pile Metal Shells	Each	2	2	
Name Plates	Each	1	1	
Stone Riprap Class A4	Sq. Yd.	1015	1015	
Filter Fabric	Sq. Yd.	1015	1015	
Permanent Survey Marker T1	Each	1	1	




NORTH ABUTMENT

SOUTH ABUTMENT

If the contractor chooses to alter the temporary cantilevered sheet piling design requirements shown on the plans, a design submittal including plan details and calculations will be required for review and acceptance by the Engineer. Minimum Section modulus of temporary sheet piling shall be 49 in³/ft. The Contractor shall connect the first sheet to the existing abutment wall to ensure stability of sheets driven to the top of the existing footing. This connection shall be reviewed and accepted by the Engineer and included in the cost for Temporary Sheet Piling.

TEMPORARY SHEET PILING




ILLINOIS DEPARTMENT OF TRANSPORTATION
STAGE CONSTRUCTION DETAILS
F.A.P. ROUTE 310 (US 67)
OVER CARTER CREEK
SECTION (41A)BR
MCDONOUGH COUNTY
STA. 567+41.50
S.N. 055-0048

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
F.A.P. 310 U.S. 67	(41-A)BR	McDonough	58	20

SHEET NO. 3
16 SHEETS

Contract #88939



FACE OF EAST CURB


Location	Station	Offset (ft)	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
E N. Abut.	567+04.25	-17.00	621.95	621.95
A	567+14.25	-17.00	621.90	621.90
E Pier 1	567+26.75	-17.00	621.85	621.85
B	567+36.75	-17.00	621.84	621.84
C	567+46.75	-17.00	621.84	621.84
E Pier 2	567+56.25	-17.00	621.86	621.86
D	567+66.25	-17.00	621.91	621.91
E S. Abut.	567+78.75	-17.00	621.99	621.99

EDGE OF N.B. LANE

Location	Station	Offset (ft)	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
E N. Abut.	567+04.25	-12.00	622.05	622.05
A	567+14.25	-12.00	622.00	622.00
E Pier 1	567+26.75	-12.00	621.95	621.95
B	567+36.75	-12.00	621.94	621.94
C	567+46.75	-12.00	621.94	621.94
E Pier 2	567+56.25	-12.00	621.96	621.96
D	567+66.25	-12.00	622.01	622.01
E S. Abut.	567+78.75	-12.00	622.09	622.09

STAGE CONSTRUCTION LINE

Location	Station	Offset (ft)	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
E N. Abut.	567+04.25	2.50	622.20	622.20
A	567+14.25	2.50	622.15	622.15
E Pier 1	567+26.75	2.50	622.10	622.10
B	567+36.75	2.50	622.09	622.09
C	567+46.75	2.50	622.09	622.09
E Pier 2	567+56.25	2.50	622.11	622.11
D	567+66.25	2.50	622.16	622.16
E S. Abut.	567+78.75	2.50	622.24	622.24



EDGE OF S.B. LANE

Location	Station	Offset (ft)	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
E N. Abut.	567+04.25	12.00	622.05	622.05
A	567+14.25	12.00	622.00	622.00
E Pier 1	567+26.75	12.00	621.95	621.95
B	567+36.75	12.00	621.94	621.94
C	567+46.75	12.00	621.94	621.94
E Pier 2	567+56.25	12.00	621.96	621.96
D	567+66.25	12.00	622.01	622.01
E S. Abut.	567+78.75	12.00	622.09	622.09

FACE OF WEST CURB

Location	Station	Offset (ft)	Theoretical Grade Elevations	Theoretical Grade Elevations Adjusted For Dead Load Deflection
E N. Abut.	567+04.25	17.00	621.95	621.95
A	567+14.25	17.00	621.90	621.90
E Pier 1	567+26.75	17.00	621.85	621.85
B	567+36.75	17.00	621.84	621.84
C	567+46.75	17.00	621.84	621.84
E Pier 2	567+56.25	17.00	621.86	621.86
D	567+66.25	17.00	621.91	621.91
E S. Abut.	567+78.75	17.00	621.99	621.99


ILLINOIS DEPARTMENT OF TRANSPORTATION
SLAB ELEVATIONS
F.A.P. ROUTE 310 (US 67)
OVER CARTER CREEK
SECTION (41A)BR
MCDONOUGH COUNTY
STA. 567+41.50
S.N. 055-0048

REVISIONS	
NAME	DATE

RD. W. Chastain Chastain, Illinois 62629
(217) 453-4628 FAX (217) 453-4706
Designed By: DLS Checked By: MTH Drawn By: ADB
Date: 01/06 File: 0550048.DWG

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	HEET NO.
F.A.P. 310 U.S. 67	(41-A)BR	McDonough	58	22


Contract #88939




SUPERSTRUCTURE BILL OF MATERIAL

Bar	No.	Size	Length	Shape
a(E)	51	#5	20'-7"	-
a ₁ (E)	67	#5	20'-7"	-
a ₂ (E)	51	#5	15'-7"	-
a ₃ (E)	67	#5	15'-7"	-
b(E)	56	#9	13'-0"	-
b ₁ (E)	52	#9	23'-0"	-
b ₂ (E)	58	#7	18'-6"	-
b ₃ (E)	56	#7	25'-0"	-
b ₄ (E)	29	#7	18'-4"	-
b ₅ (E)	28	#7	31'-7"	-
b ₆ (E)	56	#5	7'-9"	-
b ₇ (E)	78	#5	12'-10"	-
b ₈ (E)	12	#8	39'-7"	-
b ₉ (E)	18	#8	27'-6"	-
b ₁₀ (E)	12	#5	26'-4"	-
d(E)	154	#5	3'-11"	-
d ₁ (E)	152	#4	3'-6"	-
d ₂ (E)	12	#5	2'-2"	-
e(E)	48	#4	11'-4"	-
e ₁ (E)	24	#4	14'-6"	-
s ₂ (E)	76	#4	8'-0"	-
s ₃ (E)	148	#4	5'-11"	-
s ₄ (E)	58	#5	5'-9"	-
Reinforcement Bars, Epoxy Coated		Pound	26310	
Concrete Superstructure		Cu. Yds.	156.2	




Reinforcement bars designated (E) shall be epoxy coated.




INSIDE ELEVATION OF PARAPET (East Parapet Shown)



PARAPET JOINT DETAILS



SECTION A-A



SECTION B-B



REVISIONS	NAME	DATE

LIN ENGINEERING, LTD.
20 W. Chestnut Chicago, Illinois 60629
(312) 483-4669 FAX (312) 483-4705
Designed By DLS Checked By MTF Drawn By ADB
Date: 01/06 File: 0550048.DGN

ILLINOIS DEPARTMENT OF TRANSPORTATION
SUPERSTRUCTURE DETAILS
F.A.P. ROUTE 310 (US 67)
OVER CARTER CREEK
SECTION (41A)BR
MCDONOUGH COUNTY
STA. 567+41.50
S.N. 055-0048



ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
F.A.P. 310 U.S. 67	(41-A)BR	McDonough	58	23
FED. ROAD DIST. NO. 4		FED. AD. PROJECT		
Contract #88939				

SHEET NO. 6
16 SHEETS



PILE DATA

Type: 14"φ Metal Shell
Capacity: 35 Ton
Est. Length: 45 Ft.
No. Required: 6+1 Test Pile



Order $v_1(E)$ full length. Cut as shown and use remainder of bars in opposite face.


REVISIONS	
NAME	DATE

LIN ENGINEERING LTD.
DD W. CHESTNUT
C201-403-3065
Chattom Woods 62529
P.O. Box 403-4065
Designed By DLS Checked By MTH Drawn By ADB
Date: 07/06 File: 05500403.Dwg

BILL OF MATERIAL

Bar No.	Size	Length	Shape
h(E)	#6	8'-6"	
p(E)	#7	15'-10"	
p1(E)	#7	20'-10"	
s(E)	#5	11'-7"	□
u(E)	#6	7'-3"	■
v(E)	#5	3'-5"	—
v1(E)	#5	7'-7"	—
Concrete Structures Cu. Yd. 13.1			
Reinforcement Bars, Epoxy Coated Pound 1760			
Structure Excavation Cu. Yd. 27.0			
Furnishing Metal Foot 270			
Pile Shells 14" Foot 270			
Driving and Filling Shells Foot 270			
Test Pile Metal Shells Each 1			




Reinforcement bars designated (E) shall be epoxy coated. For details of Bar Splicers, see sheet 10 of 16.



ILLINOIS DEPARTMENT OF TRANSPORTATION
NORTH ABUTMENT
F.A.P. ROUTE 310 (US 67)
OVER CARTER CREEK
SECTION (41A)BR
MCDONOUGH COUNTY
STA. 567+41.50
S.N. 055-0048

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHRINKAGE
F.A.P. 310 U.S. 67	(41-A)BR	McDonough	58	24

SHEET NO. 7
16 SHEETS





BILL OF MATERIAL

Bar	No.	Size	Length	Shape
h(E)	24	#6	8'-6"	—
p(E)	6	#7	15'-10"	—
p1(E)	6	#7	20'-10"	—
s(E)	35	#5	11'-7"	□
u(E)	8	#6	7'-3"	—
v(E)	11	#5	3'-5"	—
v1(E)	12	#5	7'-7"	—
Concrete Structures	Cu. Yd.	13.1		
Reinforcement Bars, Epoxy Coated	Pound	1760		
Structure Excavation	Cu. Yd.	27.1		
Furnishing Metal Pile Shells 14"	Foot	315		
Driving and Filling Shells	Foot	315		

Reinforcement bars designated (E) shall be epoxy coated. For details of Bar Splicers, see sheet 10 of 16.

PILE DATA

Type: 14"φ Metal Shell
Capacity: 35 Ton
Est. Length: 45 Ft.
No. Required: 7




REVISIONS	
NAME	DATE


ILLINOIS DEPARTMENT OF TRANSPORTATION
SOUTH ABUTMENT
F.A.P. ROUTE 310 (US 67)
OVER CARTER CREEK
SECTION (41A)BR
MCDONOUGH COUNTY
STA. 567+41.50
S.N. 055-0048

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
F.A.P. 310 U.S. 67	(41-A)BR	McDonough	58	25


SHEET NO. 8
16 SHEETS



TOP PLAN




END VIEW





SECTION B-B

PILE DATA
Type: 14" Metal Shell
Capacity: 50 Ton
Est. Length: 68 Ft. (Pier 1), 78 Ft. (Pier 2)
No. Req'd: 9 (Pier 1), 8+1 Test Pile (Pier 2)

REVISIONS	NAME	DATE



SECTION A-A
PILE ENCASEMENT DETAIL



BAR $s_1(E)$

BILL OF MATERIAL (Two Piers)


Bar No.	Size	Length	Shape
$h_1(E)$ 52	#5	21'-0"	—
$h_2(E)$ 52	#5	16'-0"	—
$p_2(E)$ 14	#7	16'-0"	—
$p_3(E)$ 14	#7	21'-0"	—
$s_1(E)$ 74	#5	9'-7"	□
$u_1(E)$ 12	#6	9'-5"	U
$u_2(E)$ 52	#5	7'-8"	U
$v_2(E)$ 152	#5	3'-5"	—
$v_3(E)$ 156	#5	14'-0"	—
Concrete Structures	Cu. Yd.	77.7	
Reinforcement Bars, Epoxy Coated	Pound	7210	
Structure Excavation	Cu. Yd.	69.9	
Furnishing Metal Pile Shells 14"	Foot	1236	
Driving and Filling Shells	Foot	1236	
Test Pile Metal Shells	Each	1	
Underwater Structure Excavation Protection Location 1	Each	1	
Underwater Structure Excavation Protection Location 2	Each	1	

Reinforcement bars designated (E) shall be epoxy coated.

ILLINOIS DEPARTMENT OF TRANSPORTATION
PIERS
F.A.P. ROUTE 310 (US 67)
OVER CARTER CREEK
SECTION (41A)BR
MCDONOUGH COUNTY
STA. 567+41.50
S.N. 055-0048

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	PAGE NO.
F.A.P. 310 U.S. 67	(41-A)BR	McDonough	58	26
FED-HIGH DIST-NR-4				FED-HIGH PROJECT-
Contract #88939				

SHEET NO. 9
16 SHEETS



NEW SLAB


EXISTING SLAB

NOTES

Detail I - With Bar Splicer or Couplers:
Connect one (1) 1"x7"x10" steel \bar{P} to the top layer of couplers with 2- $5/8$ " ϕ bolts screwed to coupler at approximate ℓ of each barrier panel.

Detail II - With Extended Reinforcement Bars:
Connect one (1) 1"x7"x10" steel \bar{P} to the concrete slab with 2- $5/8$ " ϕ Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate ℓ of each barrier panel.
Cost of anchorage is included with Temporary Concrete Barrier.

SECTIONS THRU SLAB




DETAIL I

The 1"x7"x10" Plate shall not be removed until Stage II Construction forms and reinforcement bars are in place.

DETAIL II

The 1"x7"x10" Plate shall not be removed until Stage II Construction forms and all reinforcement bars are in place and the concrete is ready to be placed.



\bar{P} 1"x7"x10"

* Required only with Detail II

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
TEMPORARY CONCRETE BARRIER
F.A.P. ROUTE 310 (US 67)
OVER CARTER CREEK
SECTION (41A)BR
MCDONOUGH COUNTY
STA. 567+41.50
S.N. 055-0048

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
F.A.P. 310 U.S. 67	(41-A)BR	McDonough	58	27

SHEET NO. 10
16 SHEETS

Contract #88939

NOTES

Bar splicer assemblies shall be of an approved type and shall develop in tension at least 125 percent of the yield strength of the lapped reinforcement bars.

Splicer rods shall be of minimum 60 ksi yield strength, threaded or coiled full length.

All reinforcement bars shall be lapped and tied to the splicer rods or dowel bars.


Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars.

Other systems of similar design may be submitted to the Engineer for approval. Approval shall be based on certified test results from an approved testing laboratory that the proposed bar splicer assembly satisfies the following requirements:

① Minimum Capacity = $1.25 \times f_y \times A_t$
Minimum *Pull-out Strength = $1.25 \times f_{s,allow} \times A_t$


Where f_y = Yield strength of lapped reinforcement bars in ksi.
 $f_{s,allow}$ = Allowable tensile stress in lapped reinforcement bars in ksi (Service Load)

A_t = Tensile stress area of lapped reinforcement bars.
* = 28 day concrete




BAR SPlicer ASSEMBLY ALTERNATIVES

** Heavy Hex Nuts conforming to ASTM A 563, Grade C, D or DH may be used.



ONE PIECE




WELDED SECTIONS

INSTALLATION AND SETTING METHODS

"A" : Set bar splicer assembly by means of a template bolt.
"B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms.
(E) : Indicates epoxy coating.


BAR SPlicer ASSEMBLIES			
Bar Size to be Spliced	Splicer Rod or Dowel Bar Length	Strength Requirements	
		Min. Capacity kips - tension	Min. Pull-out Strength kips - tension
#4	1'-8"	14.7	5.9
#5	2'-0"	23.0	9.2
#6	2'-7"	33.1	13.3
#7	3'-5"	45.1	18.0
#8	4'-6"	58.9	23.6
#9	5'-9"	75.0	30.0
#10	7'-3"	95.0	38.0
#11	9'-0"	117.4	46.8

Bar splicer assemblies shall be according to Section 508 of the Standard Specifications, except as noted. The furnishing and installation of bar splicer assemblies will be measured and paid for at the contract unit price each for "BAR SPICERS."




FOR INTEGRAL OR SEMI-INTEGRAL ABUTMENTS

Bar Splicer for #5 bar
Min. Capacity = 23.0 kips - tension
Min. Pull-out Strength = 9.2 kips - tension
No. Required =



FOR PILE BENT ABUTMENTS

Bar Splicer for #5 bar
Min. Capacity = 23.0 kips - tension
Min. Pull-out Strength = 9.2 kips - tension
No. Required =



STANDARD

Bar Size	No. Assemblies Required	Location
#5	118	Slab
#7	12	Abutments
#5	52	Piers
#7	14	Piers


ILLINOIS DEPARTMENT OF TRANSPORTATION
BAR SPlicer ASSEMBLY DETAILS
F.A.P. ROUTE 310 (US 67)
OVER CARTER CREEK
SECTION (41A)BR
MCDONOUGH COUNTY
STA. 567+41.50
S.N. 055-0048

REVISIONS	
NAME	DATE


ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
F.A.P. 310 U.S. 67	(41-A)BR	McDonough	58	28
FED. AID DIST. NO. 4				FED. AID PROJECT

SHEET NO. 11
16 SHEETS

Contract #88939




SECTION A-A
FOR PILES UNDER
45' LONG



SECTION A-A
FOR PILES 45'
OR MORE


Handling: For Pile lengths up to 45' use two slings placed at a distance of 0.21L from each end. For Piles longer than 45', use three slings placed at a distance of 0.12L from each end and at mid point of pile.

DETAIL OF PRECAST
CONCRETE PILES





Notes:
Driving and bearing ends of pipe shall be cut square. The thickness of the shell shall be 0.250 inches with a tolerance of 5 %. The shell shall be according to Article 1006.05(a) of the Standard Specifications.



DETAIL OF CYLINDRICAL
STEEL SHELL FOR CAST IN
PLACE CONCRETE PILES



OPTIONAL
FLAT END



DETAIL OF REINFORCEMENT FOR
METAL SHELLS AT ABUTMENTS



The cost of Reinforcement, concrete, and excavation for forms is included with Concrete Encasement.

DETAIL OF PROTECTION
FOR METAL SHELLS AT PIERS

REVISIONS	
NAME	DATE

ILLINOIS DEPARTMENT OF TRANSPORTATION
PILE DETAILS
F.A.P. ROUTE 310 (US 67)
OVER CARTER CREEK
SECTION (41A)BR
MCDONOUGH COUNTY
STA. 567+41.50
S.N. 055-0048

ROUTE NO.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
F.A.P. 310 U.S. 67	(41-A)BR	McDonough	58	29
P.D. NO. 4 DIST. NO. 4				FED. AID PROJECT

SHEET NO. 12

16 SHEETS

Contract #88939

Illinois Department
of Transportation
Division of Highways
DOOT**SOIL BORING LOG**Page 1 of 2
Date 5/19/85

ROUTE	US 67 (FAP 310)	DESCRIPTION	US 67 Over Carter Creek	LOGGED BY T. Schepke
SECTION	(41-A) BR	LOCATION	SEC. TWP. 4N RNG. 2W. 4 th PM	
COUNTY	McDonough	DRILLING METHOD	Hollow Stem Auger	HAMMER TYPE
STRUCT. NO.	Existing 055-0007	Surface Water Elev.	607.24 ft	AUTO
Station	Prop. 567+37.85	Stream Bed Elev.	ft	
BORING NO.	1	Groundwater Elev:		
Station	567+24	First Encounter	None ft	
Offset	20.00ft RT of CL	Upon Completion	Not Taken ft	
Ground Surface Elev.	620.40 ft	After 24 Hrs.	Not Taken ft	
	(ft)	(ft)	(ft)	(%)
Brown SILTY CLAY LOAM	-	Brown & Gray SANDY CLAY LOAM (continued)		
			14° 10.0	
			15°	
	5' 0.8 B	24.0		
614.80		594.90		
Brown & Gray CLAY LOAM	-	Gray CLAY LOAM w/ trace of sand & gravel		
			20° 2.3 B 10.0	
	7' 1.0			
			12° 2.0	
	16' 1.4 B	23.0		
609.80				
Brown - Green CLAY LOAM	-			
			13° 2.1	
	4' 0.5 B			
607.40				
Dark Gray SILTY CLAY LOAM	-			
			12°	
	18' 0.8 B	23.0		
604.90				
Brown & Gray SANDY CLAY LOAM	-	Gray CLAY w/ trace of sand & gravel		
			15° 1.3 10.0 B	
	3' 2.1	21.0		
			13° 1.0	
	20' 2"			
			13° 1.0	

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)
BBS, from 137 (Rev. B-99)

Illinois Department
of Transportation
Division of Highways
DOOT**SOIL BORING LOG**Page 2 of 2
Date 5/19/85

ROUTE	US 67 (FAP 310)	DESCRIPTION	US 67 Over Carter Creek	LOGGED BY T. Schepke
SECTION	(41-A) BR	LOCATION	SEC. TWP. 4N RNG. 2W. 4 th PM	
COUNTY	McDonough	DRILLING METHOD	Hollow Stem Auger	HAMMER TYPE
STRUCT. NO.	Existing 055-0007	Surface Water Elev.	607.24 ft	AUTO
Station	Prop. 567+37.85	Stream Bed Elev.	ft	
BORING NO.	1	Groundwater Elev:		
Station	567+24	First Encounter	None ft	
Offset	20.00ft RT of CL	Upon Completion	Not Taken ft	
Ground Surface Elev.	620.40 ft	After 24 Hrs.	Not Taken ft	
	(ft)	(ft)	(ft)	(%)
Brown SILTY CLAY LOAM	-	Gray CLAY w/ trace of sand & gravel (continued)		
			11° 1.6 B	
			12° 1.0	
	13' 1.3 B			
554.90				
Gray CLAY w/ trace of sand & gravel	-			
			13° 1.6 B	
			12° 1.5	
	10' 1.5			
			11°	
	12' 1.5			
			13°	
	11' 1.6			
			12° 1.2	
	12' 1.0			
			13°	
	12' 0.8			
			14°	

The Unconfined Compressive Strength (UCS) Failure Mode is indicated by (B-Bulge, S-Shear, P-Penetrometer)
The SPT (N value) is the sum of the last two blow values in each sampling zone (AASHTO T206)
BBS, from 137 (Rev. B-99)

REVISIONS	
NAME	DATE


LIN ENGINEERING, LTD.
210 W. Chestnut
Canton, Illinois 61229
(309) 433-1663
FAX: (309) 433-4105
Designed By DLS Checked By MTH Drawn By ADB
Date: 01/06 File: 0550048.DCN

ILLINOIS DEPARTMENT OF TRANSPORTATION
SOIL BORINGS
F.A.P. ROUTE 310 (US 67)
OVER CARTER CREEK
SECTION (41A)BR
MCDONOUGH COUNTY
STA. 567+41.50
S.N. 055-0048


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEET NO.
310	(41-A)BR	MCDONOUGH	58 34
STA. 563+50 TO STA. 564+15			
FED. ROAD DIST. NO.		ILLINOIS	FED. AID PROJECT

FINAL SURVEYED	DATE
PLOTTED	
NOTE BOOK	
NO. 15	LAST PAGE
AREAS CHECKED	


ORIGINAL SURVEY	DATE
SURVEYED	
PLOTTED	
NOTE BOOK	
NO. 15	LAST PAGE
AREAS CHECKED	



F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	(4)-A1BR	MCDONOUGH	58 35
STA. 564+45		TO STA. 565+00	
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	




F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	(41-A)BR	MCDONOUGH	58 36
STA. 565+50 TO STA. 566+50			
FED. ROAD DIST. NO.		ILLINOIS	FED. AID PROJECT



F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	(41-AIBR	McDONOUGH	58
	STA. 567+00	TO STA. 568+00	


FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT



FINAL SURVEY	BY	DATE
SUBDIVIDED		
PLOTTED		
NOTE BOOK		
TEMPLATE		
AREAS CHECKED		
NO.		


ORIGINAL SURVEY	BY	DATE
SUBDIVIDED		
PLOTTED		
NOTE BOOK		
TEMPLATE		
AREAS CHECKED		
NO.		

F.A.P. RT.C.	SECTION	COUNTY	TOTAL SHEETS	HEET NO.
310	(41-AIBR	McDONOUGH	58	38
STA. 568+50 TO STA. 569+50				
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT				




CONTRACT NO. 88939


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEET NO.
310	141-AIBR	MCDONOUGH	58 39
STA. 570+00 TO STA. 570+30			
FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT			



F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEET NO.
310 (41-A)BR		McDONOUGH	58 40
STA. 570+60	TO STA. 571+50		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	



F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	(41-AIBR	MCDONOUGH	58 41
STA.	TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	


SLOPE STEPS DETAILTYPICAL CROSS-SECTION EMBANKMENT
CONSTRUCTION ON SIDEHILL

DESIGNER NOTE:

1. EACH PROJECT SHOULD BE REVIEWED INDEPENDENTLY FOR TREATMENT REQUIRED.
2. REFER TO THIS DETAIL WITH NOTE ON APPLICABLE TYPICAL SECTIONS.

\$DATE\$

REPLACEMENT MATERIAL:

STANDARD EMBANKMENT
(IN ACCORDANCE WITH
205 OF THE STANDARD SPECIFICATION).All dimensions are in millimeters
(Inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION


DISTRICT CADD STANDARD

DATE	REVISIONS	BY
1-1-97	RENUM. L-5.03, NEW REVISION BOX, REVISED TITLE BOX, REVISED GENERAL NOTES.	T.P.

SLOPE STEPS
DETAILCADD STD. NO. 205001-D4
SCALE: NOT DRAWN TO SCALEDRAWN BY CADD
CHECKED BY


205001-D4

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEET NO.
310	(41-AIBR)	MCDONOUGH	58 42
STA.	TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	

CASE 1
(DITCH)


(*)				
LOCATION	WIDTH (1) m (in ft)	LENGTH m (in ft)	RIPRAP m tons (tons)	FABRIC m^2 (sq yds)
STA TO STA				
TOTAL				

(1) WIDTH = $W_1 + W_2 + W_D$

CASE 2
(CULVERT & SLOPE)

(*)				
LOCATION	WIDTH (1) m (in ft)	LENGTH m (in ft)	RIPRAP m tons (tons)	FABRIC m^2 (sq yds)
STA TO STA				
TOTAL				

(1) WIDTH = $W_2 + W_D$

CASE 3
(CULVERT)

(*)				
LOCATION	WIDTH (1) m (in ft)	LENGTH m (in ft)	RIPRAP m tons (tons)	FABRIC m^2 (sq yds)
STA TO STA				
TOTAL				

(1) WIDTH = W_D

All slope ratios are expressed as units of vertical displacement to units of horizontal displacement (V:H).

All dimensions are in millimeters (inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION

SPECIAL DETAIL SHEET

RIPRAP DITCH FOR
EROSION PROTECTION

CADD DETAIL 281001-D4
DRAWN BY CADD
SCALE: NOT DRAWN TO SCALE

CHECKED BY

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	(41-ABR)	MCDONOUGH	58 43
STA.	TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	





TABLE A
(LENGTHS AND TAPER RATES)

SPECIAL NOTE NUMBER	ELEMENT	MAINLINE INTERSTATES & 4-LANE EXPRESSWAYS	ALL OTHERS
①	LENGTH OF BUTT JOINT	18.0 m(60')	9.0 m(30')
②	PERMANENT TAPER RATE	1:480	1:240
③	TEMPORARY RAMP TAPER RATE	1:80	1:40
④	TEMPORARY RAMP LENGTH	3.0 m(10')	1.5 m(5')
⑤	LENGTH OF BUTT JOINT	3.0 m(10')	3.0 m(10')

GENERAL NOTES

1. The work shall be done in accordance with Article 406.18 and the Special Provision for Butt Joints.
2. The pavement surface to be removed may be either bituminous or P.C. concrete. The work shall be performed in accordance with Article 440.03 and the Special Provisions for Butt Joints.
3. The saw cut joints shall be primed just prior to the placing of bituminous material. The work will be in accordance with the applicable portions of Article 406.06.



All dimensions are in millimeters (inches) unless otherwise noted.

CASE 2 : NO BITUMINOUS SURFACE REMOVAL (COLD MILLING)

DATES

DATE	REVISIONS	BY
1-1-97	RENUM. C-23.01, NEW REVISION BOX	T.P.
4-1-97	CORRECTION TO DEPTH	J.A.
9-15-05	REVISED DESIGNER NOTE	M.M.A.

ILLINOIS DEPARTMENT OF TRANSPORTATION

DISTRICT CADD STANDARD


BUTT JOINTS

CADD STD NO. 406101-D4 SHEET 1 OF 3


SCALE: NOT DRAWN TO SCALE DRAWN BY CADD

DATE **DATES** CHECKED BY


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	141-ABR	MCDONOUGH	58 44
STA.	TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	



CASE 3 : WITH BITUMINOUS SURFACE REMOVAL (COLD MILLING)
TIE-IN TO EXISTING BITUMINOUS TAPER



CASE 4 : NO BITUMINOUS SURFACE REMOVAL (COLD MILLING)
TIE-IN TO EXISTING BITUMINOUS TAPER



All dimensions are in millimeters (inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION


DISTRICT CADD STANDARD

BUTT JOINTS

CADD STD NO. 406101-D4 SHEET 2 OF 3
SCALE: NOT DRAWN TO SCALE
DRAWN BY CADD
CHECKED BY

DETAIL TEMPORARY RAMP

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	HEET NO.
310	(41-ABR)	MCDONOUGH	58	45
STA.	TO STA.			
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		



CASE 5 : WITH BITUMINOUS SURFACE REMOVAL (COLD MILLING)
TIE-IN TO EXISTING BITUMINOUS TAPER

All dimensions are in millimeters
(inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT CADD STANDARD
BUTT JOINTS
CADD STD NO. 406101-D4 SHEET 3 OF 3
SCALE: NOT DRAWN TO SCALE DRAWN BY CADD
CHECKED BY

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	HEET NO.
310	41-AIBR	MCDONOUGH	58	46
STA.	TO STA.			
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		





TABLE A

ELBOW DESIGN CONTROLS

PIPE DIAMETER	L = Pay limits of Pipe Elbow and minimum length of pipe required for fabrication	
	DEGREE OF ELBOW $\leq 45^\circ$	DEGREE OF ELBOW $> 46^\circ$
300(12)	600(24)	1.22M(4')
375(15)	600(24)	1.22M(4')
450(18)	600(24)	1.22M(4')
525(21)	600(24)	1.22M(4')
600(24)	1.22M(4')	1.22M(4')
750(30)	1.22M(4')	1.83M(6')
900(36)	1.22M(4')	1.83M(6')

TABLE B	
ELBOW DESIGN CONTROLS	
EARTH SLOPE (V:H)	DEGREE OF ELBOW *
1:6	9°
1:4	14°
1:3	18°
1:2	26°
1:1½	33°

* Approximate - based upon 0.5% inlet and outlet flowlines.



All dimensions are in millimeters (inches) unless otherwise noted.

DATE	REVISIONS	BY
1-1-97	RENUM. J-11.05, NEW REVISION BOX, REVISED TITLE BOX	T.P.

ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT CADD STANDARD



PIPE ELBOW

CADD STD. NO. 601301-D4
SCALE: NOT DRAWN TO SCALE


DRAWN BY CADD
CHECKED BY

601301-D4


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	(41-ABR)	MCDONOUGH	58 47
STA.	TO STA.		
FED. ROAD DIST. NO.	ILLINOIS FED. AID PROJECT		





TYPE A GUTTER (MODIFIED)



Edge of pavement or paved shoulder



QUANTITY
Section C-C to A-A
m³ (cu. yd.) concrete.



INLET

DESIGNER NOTE:
1. INCLUDE STATE STANDARD 420001.
2. INCLUDE DISTRICT SPECIAL PROVISION.

QUANTITIES	
CALC. BY:	DATE:
CHECKED BY:	DATE:
QUANTITY CALCULATIONS ARE ON FILE AT THE DISTRICT 4 OFFICE; BUREAU OF PROJECT IMPLEMENTATION; DOCUMENTATION SECTION	


DGN-ONLY

All dimensions are in millimeters (inches) unless otherwise noted.


ILLINOIS DEPARTMENT OF TRANSPORTATION		
DISTRICT CADD STANDARD		
TYPE A GUTTER, (MODIFIED) (INLET, OUTLET & ENTRANCE)		
DATE	REVISIONS	BY
1-1-97	RENUM. A-102, NEW REVISION BOX, ELIMINATED EXPANSION ANCHOR TIES.	T.P.
2-28-02	ENTRANCE TYPICALS REVISED	M.A.

CADD STANDARD 606101-D4 SHEET 1 OF 3
DRAWN BY CADD
CHECKED BY


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	(41-ABR)	MCDONOUGH	58 4B
STA.	TO STA.		
FED. ROAD DIST. NO.	ILLINOIS FED. AID PROJECT		



SECTION A-A



SECTION B-B




SECTION C-C

QUANTITIES	
CALC. BY:	DATE:
CHECKED BY:	DATE:

##DRAFT##




QUANTITY CALCULATIONS ARE ON FILE AT THE DISTRICT 4 OFFICE; BUREAU OF PROJECT IMPLEMENTATION DOCUMENTATION SECTION




If the average grade of pavement for the distance from section A-A to section D-D exceeds 2%, this distance shall be increased 1.8 m (6 ft.) for each 1% increase in grade. A quantity adjustment is required.

QUANTITY
Section A-A to E-E = m³ (cu. yd.) concrete.
Section F-F = m³/m (cu. yd./ft.) concrete.


SECTION D-D

SECTIONS AT END OF OUTLET
(CURTAIN WALL)

QUANTITY
Curtain Wall m³ (cu. yd.) concrete.



SECTION G-G



SECTION H-H

All dimensions are in millimeters (Inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION


DISTRICT CADD STANDARD

TYPE A GUTTER, (MODIFIED)
(INLET, OUTLET & ENTRANCE)

CADD STANDARD 606101-D4 SHEET 2 OF 3
SCALE: NOT DRAWN TO SCALE DRAWN BY CADD
CHECKED BY

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEET NO.
3101	(41-WBR	MCDONOUGH	58 49
STA.	TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	


Pay Limits of Type A Gutter (Modified) Entrance




TYPICAL URBAN ENTRANCE

QUANTITY CALCULATION


LOCATION	LENGTH	NON-COMMERCIAL 150 (6)	COMMERCIAL ENTRANCE 200 (8)
Entrance Flare	2.15 m (7 Ft) Urban 4.30 m (14 Ft) Rural	0.37 Cu M / M (0.15 Cu Yd / Ft)	0.45 Cu M / M (0.18 Cu Yd / Ft)
Section B-B	See Plans	0.57 Cu M / M (0.23 Cu Yd / Ft)	0.70 Cu M / M (0.28 Cu Yd / Ft)



Pay Limits of Type A Gutter (Modified) Entrance



TYPICAL RURAL ENTRANCE



GENERAL NOTES

- 1.J Slope may be increased from 4% (min.) to 6% (max.) in order to match the existing.
- 2.J The cross-slope is to be constructed as given in the plans from back turnout to where driveway matches existing.
- 3.J For Non-Commercial Entrances the driveway thickness shall be 150 (6). For Commercial Entrances the driveway thickness shall be 200 (8).

All dimensions are in millimeters (Inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION

DISTRICT CADD STANDARD

TYPE A GUTTER, (MODIFIED)
(INLET, OUTLET & ENTRANCE)

SHEET 3 OF 3
CADD STANDARD 606101-D4
DRAWN BY CADD
CHECKED BY

CALC. BY: _____ DATE: _____
CHECKED BY: _____ DATE: _____


QUANTITY CALCULATIONS ARE ON
FILE AT THE DISTRICT 4 OFFICE;
BUREAU OF PROJECT IMPLEMENTATION;
DOCUMENTATION SECTION

ENTRANCE

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	41-AIR	MCDONOUGH	58
STA.	TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	

CONCRETE THRUST BLOCK
BILL OF MATERIALS

PIPE SIZE	X	Y	CLASS SI CONCRETE m ³ (cu. yd.)
300(12)	600(24)	600(24)	0.2(0.2)
375(15)	675(27)	675(27)	0.2(0.3)
450(18)	750(30)	750(30)	0.2(0.3)
600(24)	900(36)	900(36)	0.3(0.4)
750(30)	1.07m (3'-6")	1.07m (3'-6")	0.6(0.8)



The contract unit price each for CONCRETE THRUST BLOCK shall include the cost of excavation, CLASS SI CONCRETE and compacted backfill.


QUANTITIES	
CALC. BY:	DATE:
CHECKED BY:	DATE:
QUANTITY CALCULATIONS ARE ON FILE AT THE DISTRICT 4 OFFICE; BUREAU OF PROJECT IMPLEMENTATION DOCUMENTATION SECTION	

All dimensions are in millimeters (inches) unless otherwise noted.


DATE	REVISIONS	BY
1-1-97	RENUM. J-10-04, NEW REVISION BOX,	T.P.
	ADDED QUANTITY CALCULATION BOX.	

ILLINOIS DEPARTMENT OF TRANSPORTATION	
DISTRICT CADD STANDARD	
CONCRETE THRUST BLOCKS	
CADD STD. NO. 609001-D4	
DRAWN BY CADD CHECKED BY	

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
310	41-AIBR	MCDONOUGH	58	51
STA.	TO STA.			
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		



TYPICAL SECTION WITH EROSION CONTROL CURB



TYPICAL SECTION WITHOUT EROSION CONTROL CURB

GENERAL NOTES: EROSION CONTROL CURB

1. This work shall consist of grading as needed, installing hardware and treated timber boards, furnishing and placing mastic material and incidental bituminous surfacing in front of Steel Plate Beam Guardrail in accordance with Plan Details.
2. Timber shall be treated in accordance with Article 1007.12. All preservatives specified in the article will be allowed. Waterborne preservatives "asa" and "cca" shall have a minimum retention of 6.4 kg/m³ (0.40 lbs./cu. ft.)

GENERAL NOTES: GUARDRAIL AGGREGATE EROSION CONTROL

1. This work shall consist of grading as needed, furnishing and installing geotextile fabric and staples, and furnishing, placing and shaping crushed aggregate around and behind Steel Plate Beam Guardrail posts in accordance with Plan Details.
2. Before placing the aggregate and the Geotextile Fabric, weeds and grass shall be removed from the area to be covered.
3. After the area has been prepared, and in a dry condition, the Geotextile fabric shall be placed with a 300(12) minimum overlap. A knife cut for guardrail post installation is necessary.
4. The aggregate shall be deposited, compacted and shaped by either mechanical or hand methods, in a manner reasonably true to line and grade.
5. The Contractor shall have the option of placing the guardrail before or after the Geotextile Fabric and Aggregate are in place. If the guardrail is placed after the Geotextile Fabric and Aggregate, then any voids must be filled and the aggregate returned to line and grade.
6. Materials shall meet the following requirements:
 - A. The crushed aggregate shall be CA1 gradation in accordance with Article 1004.01(c) of the Standard Specifications.
 - B. The Geotextile Fabric shall be nonwoven fabric in accordance with Article 1080.02 of the Standard Specifications.

All dimensions are in millimeters (inches) unless otherwise noted.


ILLINOIS DEPARTMENT OF TRANSPORTATION			
DISTRICT CADD STANDARD			
DATE	REVISIONS	BY	
1-1-97	RENUM. C-22.01, NEW REVISION BOX	T.P.	
3-1-97	CORRECT STD. NUMBERS IN NOTES PG. 2	J.A.	
11-3-00	CORRECTION TO NOTES	M.A.	

GUARDRAIL EROSION CONTROL TREATMENTS


SHEET 1 OF 2
DRAWN BY CADD
CHECKED BY

CADD STD NO. 630101-D40
SCALE: NOT DRAWN TO SCALE

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	141-AIBR	MCDONOUGH	58
STA.	TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	




DETAIL A
(Typical Treated Timber Splices)




PLAN VIEW

APPROACH SLAB OR BRIDGE APPROACH SHOULDER
(STANDARD 609001 or 609006)



TYPICAL SECTION WITH EROSION CONTROL CURB
AT INLETS TYPE E & F (STANDARD 610001)



SECTION A-A
TYPICAL SECTION WITH EROSION CONTROL CURB
AT BRIDGE APPROACH CURB
(STANDARD 609001 OR 609006)

All dimensions are in millimeters
(inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION


DISTRICT CADD STANDARD

GUARDRAIL EROSION
CONTROL TREATMENTS

CADD STD NO. 630101-D4(2)
DRAWN BY CADD
SCALE: NOT DRAWN TO SCALE

SHEET 2 OF 2
DRAWN BY CADD
CHECKED BY


F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	sheet NO.
310	(41-AIBR)	MCDONOUGH	58	53
STA.	TO STA.			
FED. ROAD DIST. NO.	ILLINOIS FED. AID PROJECT			



① Spacing 24 m (80 ft.) max. for first 122 m (400 ft.) or curve spacing shown in Standard 635001, whichever is less (min. 4 reflectors regardless of length).

② After 122 m (400 ft.), transition to normal delineator spacing shown in Standard 635001, and continue as required.

ONE-WAY TRAFFIC




③ Bidirectional silver/silver should be used in lieu of monodirectional silver on both sides of two-lane bridges where the bridge pavement is less than 610 (24') wider than the pavement approaching the bridge.

TWO-WAY TRAFFIC

GUARDRAIL / BARRIER WALL / BRIDGE RAIL REFLECTORS

LEGEND


- ◀ Monodirectional silver
- ◀ Monodirectional amber
- ▲ Terminal Marker - Black/Yellow
Left or Right as appropriate



NOTE: Omit terminal marker when terminal over 3 m (10') from edge of paved shoulder or break point of unpaved shoulder, or when terminal buried in backslope.


Traffic Barrier Terminal Type(*) and/or Turned-Down Terminal

[Terminal over 3 m (10') from edge of shoulder]
*See Plans for Type




Traffic Barrier Terminal Type(*) and/or Turned-Down Terminal

[Terminal over 3 m (10') or less from edge of shoulder]
*See Plans for Type



NOTE: Omit terminal marker when terminal over 3 m (10') from edge of paved shoulder or break point of unpaved shoulder.

Traffic Barrier Terminal Type 1 (Special) [Terminal over 3 m (10') from edge of shoulder]



Traffic Barrier Terminal Type 1(Special) [Terminal 3 m (10') or less from edge of shoulder]

All dimensions are in millimeters (inches) unless otherwise noted.


ILLINOIS DEPARTMENT OF TRANSPORTATION

DISTRICT CADD STANDARD





GUARDRAIL AND BARRIER WALL DELINEATION		
CADD STD. NO. 635101-D4	REVISIONS	BY
1-1-97	RENUM. E-10.02, NEW REVISION BOX	T.P.
3-1-97	CORRECT STD. SPEC. *	J.A.

SHEET 1 OF 3
DRAWN BY CADD
CHECKED BY



F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	HEET NO.
310	141-AIBR	MCDONOUGH	58	54
STA.	TO STA.			
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		



For Traffic Barrier Terminal Type 1 (Special)


Standard Treatment - Direct Applied Sheeting
Traffic Barrier Terminal Type 1 (Special)For Traffic Barrier Terminal Type (*)
and Post Mount
* See Plans for TypeSheeting Position for
Traffic Barrier Terminal Type (*)
* See Plans for TypeStandard Treatment - Direct Applied Sheeting
Traffic Barrier Terminal Type (*)
* See Plans for TypeTERMINAL MARKER DETAILS

Color: Black / Yellow reflectorized
OM - I100 (L or R) Direct applied reflective sheeting
OM - I200 (L or R) Post mounted



DETAIL OF MOUNTING TERMINAL MARKER TO POST

STANDARD TERMINAL MARKER

POST MOUNTED TERMINAL MARKER ASSEMBLYALTERNATE TREATMENT - POST MOUNTED
(For turned-down terminal where sheeting cannot be direct applied)TERMINAL MARKER TREATMENTSGENERAL NOTES

All dimensions are in millimeters (Inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION


DISTRICT CADD STANDARD

GUARDRAIL AND
BARRIER WALL DELINEATION

CADD STD. NO. 635101-D4
SCALE: NOT DRAWN TO SCALE



SHEET 2 OF 3
DRAWN BY CADD
CHECKED BY

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
310	(41-A)BR	MCDONOUGH	58	55
STA.		TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		




TYPICAL MOUNTING DETAIL
FOR BRIDGE RAIL REFLECTOR

REFLECTOR MOUNTING





REFLECTOR MARKER TYPE B




REFLECTOR MARKER TYPE A

Min. reflective area 4,194 mm² (6 1/2 Sq. In.)
each side. May be rectangular or slight trapezoid.



REFLECTORS



3 min. adhesive weep
holes or slots each side,
variable spacing.

REFLECTOR MARKER TYPE C

All dimensions are in millimeters
(inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION
DISTRICT CADD STANDARD

GUARDRAIL AND
BARRIER WALL DELINEATION

CADD STD. NO. 635101-D4

SCALE: NOT DRAWN TO SCALE


DRAWN BY CADD

CHECKED BY



F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	HEET NO.
310	41-AIBR	MCDONOUGH	56	56
STA.	TO STA.			
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT		

PERMANENT SURVEY TIES


- Permanent Survey Tie
- Section Corner, $\frac{1}{4}$ Corner, or other land corner.

TYPICAL APPLICATIONGENERAL NOTES

- The marker shall be cast in place of Class SI Concrete.
- Tie marker shall be installed after the final seeding has been completed unless otherwise specified by the Engineer.
- The tie distances to the section corner shall be measured and recorded by the IDOT Chief of Surveys.

SECTIONPERMANENT SURVEY MARKERSBRONZE TABLET - No Scale
TYPE IGENERAL NOTES

- All type II markers shall be cast in place, and precast markers will not be allowed.
- Two permanent magnets, each having a diameter of 19 3/4 and a thickness of 6 1/4, or equivalent, shall be attached to the underside of the tablet with an approved epoxy bonding agent.
- The location of the markers shall be in accordance with the plans in general, the markers will be placed at the P.T.'s and P.C.'s of horizontal curves and spaces along the tangents in a way that a minimum of two markers are always inter-visible, and not to exceed 300m(1000').
- The markers shall be placed under the direction of the Engineer and shall be installed in a workmanlike manner in order that there will be no further settlement or horizontal shifting. The monuments shall be placed in a way that the survey point will fall within the portion of the plaque provided for that purpose.
- The project designation, the centerline station, the survey point, and the elevation shall be permanently marked by the use of metal dies after marker has been installed.

MARKER CAST IN PLACE
TYPE II

All dimensions are in millimeters (inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION

DISTRICT CADD STANDARD


DATE	REVISIONS	BY
1-1-97	RENUM. D-3.01, NEW REVISION BOX	T.P.
	ADD DESIGNER NOTE, REVISED TITLE BOX	
7-7-98	ADD DESIGNER NOTE	J.A.
5-24-06	REMOVED GEN. NOTE UNDER TIES	M.A.

PERMANENT SURVEY TIE
&
PERMANENT SURVEY MARKERS TY.I - TY.II

CADD STD. NO. 667101-D4
SCALE: NOT DRAWN TO SCALE

DRAWN BY CADD
CHECKED BY

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
310	(41-A)BR	McDONOUGH	58	57
STA.	TO STA.	FED. ROAD DIST. NO. ILLINOIS FED. AID PROJECT		



FLUSH PAVED MEDIAN: TWO-WAY LEFT TURN LANE WITH ONE-WAY LEFT TURN LANE AT SIGNALIZED INTERSECTION

TYPICAL PAVEMENT MARKING LEGEND

(Note: This is a District Standard Legend.
Some elements may not apply to specific project.)

- (1) 100(4) Solid (Yellow)
- (2) 100(4) Solid (White)
- (3) 2-150(6) Crosswalk @ 2m (6'-6")min C.-C. (White)
- (4) 2-200(8) Crosswalk @ 2m (6'-6")min C.-C. (White) (When traffic signals are present)
- (4) 150(6) Skip-Dash (White) (See Special Note 1)
- (5) 200(8) Solid (White)
- (6) 300(12) Diagonal (White) (Item (6) is shown on Std. 780001)
- (7) 600(24) Stop Bar (White)
- (8) Letters & Arrows (See Std. 780001 and Special Notes 2 & 3)
- (9) 100(4) Skip-Dash (Yellow) (See Special Note 1)
- (10) 300(12) Diagonal (Yellow) (See Table A)
- (11) 100(4) Double Solid (Yellow)

SPECIAL NOTES

1. Skip-Dash markings will be centered between both ends of city blocks and shall be placed in alignment transversely across the pavement.
2. The following shall apply to arrows located in one-way left turn lanes:
 - A. A minimum of two (2) arrows is required.
 - B. The maximum spacing between arrows is 24 m (80').
 - C. Arrows shall be evenly spaced if three (3) or more are required.
3. The following shall apply to arrow pairs located in two-way left turn lanes:
 - A. A minimum of two (2) arrow pairs is required.
 - B. The maximum spacing between arrow pairs is 61 m (200').
 - C. Arrow pairs shall be evenly spaced if three (3) or more are required.
 - D. The spacing between Bi Directional Left Turn Arrows is 10 m (33').

GENERAL NOTES

1. Refer to State Standard 780001 for additional Pavement Markings including letters & arrows.
2. See Plans for Pavement Markings adjacent to curbed islands and medians, and through lane reductions.

All dimensions are in millimeters
(inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION

DISTRICT CADD STANDARD


TYPICAL PAVEMENT MARKINGS

DATE	REVISIONS	BY
1-1-97	RENUM. F-8-03, NEW REVISION BOX	T.P.
2-7-97	ADD BI DIRECTIONAL DIMENSION	J.A.
10-97	CORRECT BI DIRECTIONAL DIMENSION	J.A.
8-02	ADD CROSSWALK DMNS. WITH T.S.	M.A.

CADD STANDARD 780001-D4
DRAWN BY CADD
CHECKED BY

SCALE: NOT DRAWN TO SCALE
SHEET 1 OF 2

F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEETS NO.
310	(41-A)BR	MCDONOUGH	58
STA.	TO STA.		
FED. ROAD DIST. NO.	ILLINOIS	FED. AID PROJECT	




FLUSH PAVED MEDIAN: RESTRICTED LEFT TURN LANE

TABLE A

RECOMMENDED SPACING BETWEEN DIAGONAL LINES

INTERSECTION CHANNELIZATION
(Includes Width Transitions for
Median and Left Turn Lane
Introductions)

SPEED LIMIT RANGE	CONTINUOUS	
Less Than 50 km/h (30 mph)	15m (50')	5m (15')
50 - 70 km/h (30 - 45 mph)	23m (75')	6m (20')
Over 70 km/h (45 mph)	46m (150')	9m (30')



All dimensions are in millimeters (inches) unless otherwise noted.

ILLINOIS DEPARTMENT OF TRANSPORTATION

DISTRICT CADD STANDARD

TYPICAL PAVEMENT
MARKINGS

CADD STANDARD 780001-D4 SHEET 2 OF 2
DRAWN BY CADD
SCALE: NOT DRAWN TO SCALE
CHECKED BY