

CHECKED .

- RJC

DRAWN

CHECKED

PLOT SCALE =

PLOT DATE =



"A" : Set bar splicer assembly by means of a template bolt. "B" : Set bar splicer assembly by nailing to wood forms or cementing to steel forms. (E) : Indicates epoxy coating.

STATE OF ILLINOIS

DEPARTMENT OF TRANSPORTATION

6'-0"



REVISED

REVISED -

REVISED

Mechanical coupler (E) ******* Reinforcement bar Reinforcement bar

STANDARD MECHANICAL SPLICER

Location	Bar size	No. assemblies required		

NOTES

Splicer bars shall be deformed with threaded ends and have a minimum 60 ksi yield strength.

All reinforcement shall be lapped and tied to the splicer bars. Bar splicer assemblies shall be epoxy coated according to the requirements for reinforcement bars. See Section 508 of the Standard Specifications. See special provision for Mechanical Splicers. See approved list of bar splicer assemblies and mechanical splicers for

alternatives.

BAR SPLICER ASSEMBLY AND MECHANICAL SPLICER DETAILS	F.A.P. RTE.	SECTION	COUNTY	TOTAL SHEET SHEETS NO.	
STRUCTURE NO. 023-0034		14BR	EDGAR	115 56	
		CONTRACT NO. 70618			
SHEET NO. 16 OF 21 SHEETS		ILLINOIS FED. AID PROJECT			