

NOTES:

1. DETECTABLE WARNINGS ARE TO BE INSTALLED AT LOCATIONS OF SIDEWALK REMOVAL AND REPLACEMENT. CONTRACTOR TO POSITION AND PLACE DETECTABLE WARNINGS AT THE DIRECTION OF THE ENGINEER.

LEGEND


BITUMINOUS PAVEMENT REPAIR

HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT (10' UNLESS OTHERWISE INDICATED)



CONCRETE SIDEWALK REMOVAL AND REPLACEMENT

CONCRETE CURB, CONCRETE CURB AND GUTTER REMOVAL AND REPLACEMENT



HOT-MIX ASPHALT SURFACE REMOVAL, 2"
LEVELING BINDER (MACHINE METHOD), N50 3/4"
HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50 1 1/2"

STRUCTURE TO BE ADJUSTED

STRUCTURE TO BE RECONSTRUCTED

FILE	E NAME = 09326-PLAN-01 - P02	USER NAME =	DESIGNED PKB	REVISED		139TH STREET RESURFACING CRAWFORD AVENUE TO COOPERS GROVE ROAD PAVEMENT PLAN		SECTION	COUNTY	TOTAL S	NO
- 1			CHECKED PKB	REVISED	STATE OF ILLINOIS			09-00024-00-RS	COOK	15	5
- 1		PLOT SCALE = 1"=50"	DRAWN AG/PS	REVISED	DEPARTMENT OF TRANSPORTATION					CONTRACT NO. 63304	
		PLOT DATE = 09-18-09	CHECKED — AG	REVISED —		SCALE: 1"=50' SHEET NO. 5 OF 15 SHEETS STA. 26+00 TO STA. 48+00	FED. ROAD DIS		D PROJECT ARA-		