	SUMMARY OF QUANTITIES				PAVEMENT MARKINGS LANDSCAPE  CONSTRUCTION TYPE CODE			
	CODE NO.	PAY ITEM	UNIT	QUAN	1000	SFTY-1D	Y003	
T	40600100	BITUMINOUS MATERIALS (PRIME COAT)	GALLON	1800	1800			
1	40600895	CONSTRUCTING TEST STRIP	EACH	1	1			
1	40600982	HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT	SQ YD	400	400			
	40603335	HOT-MIX ASPHALT SURFACE COURSE, MIX "D", N50	TON	1500	1500			
1	42400200	PORTLAND CEMENT CONCRETE SIDEWALK 5 INCH	SQ FT	3000	3000			
	42400800	DETECTABLE WARNINGS	SQ FT	232	232			
	44000157	HOT-MIX ASPHALT SURFACE REMOVAL, 2" INCH	SQ YD	14000	14000			
1	44000600	SIDEWALK REMOVAL	SQ FT	3000	3000			
	44001700	COMBINATION CONCRETE CURB AND GUTTER REMOVAL AND REPLACEMENT	FOOT	1640	1640			
1	44201749	CLASS D PATCHES, TYPE I, 9 INCH	SQ YD	50	50			
1	44201753	CLASS D PATCHES, TYPE II, 9 INCH	SQ YD	100	100			
1	44201757	CLASS D PATCHES, TYPE III, 9 INCH	SQ YD	100	100			
1	44201759	CLASS D PATCHES, TYPE IV, 9 INCH	SQ YD	250	250			
1	60200105	CATCH BASINS, TYPE A, 4'- DIAMETER FRAME, TYPE 1 FRAME, OPEN LID	EACH	1	1			
1	60250200	CATCH BASINS TO BE ADJUSTED	EACH	46	46			
1	60253000	CATCH BASINS TO BE RECONSTRUCTED WITH NEW TYPE 1 FRAME, OPEN LID	EACH	2	2			
1	60255500	MANHOLES TO BE ADJUSTED	EACH	39	39		-	
1	60266600	VALVE BOXES TO BE ADJUSTED	EACH	6	6			
- 1	60500050	REMOVING CATCH BASINS	EACH	1	1			
1	67100100	MOBILIZATION	L SUM	1	1			
1	70102625	TRAFFIC CONTROL AND PROTECTION, STANDARD 701606	L SUM	1	1		l	
1	70102635	TRAFFIC CONTROL AND PROTECTION, STANDARD 701701	L SUM	1	1			
	70102640	TRAFFIC CONTROL AND PROTECTION, STANDARD 701801	L SUM	1	1			
1	70300100	SHORT-TERM PAVEMENT MARKING	FOOT	910	9/0			
*	78000200	THERMOPLASTIC PAVEMENT MARKING - LINE 4"	FOOT	7600	7600			
*	78000650	THERMOPLASTIC PAVEMENT MARKING - LINE 24"	FOOT	310	310			
$ \mathbf{x} $	88600600	DETECTOR LOOP REPLACEMENT	FOOT	40	40			
1	X4067107	POLYMERIZED LEVELING BINDER (MACHINE METHOD), IL-4.75, N50	TON	1000	1000			
1	XX006947	HOT-MIX ASPHALT DRIVEWAY REMOVAL AND REPLACEMENT	SQ YD	50	50			
1								
1								
1				1				
1				<u> </u>				
1								
1								
1			-					
		THE CONTROL OF THE PROPERTY OF			<b>i</b>			
			1	1	-			
-1								
-1								
	-,,							
			1		<u> </u>			
			1	<del> </del>	l			
			<del>                                     </del>	<b>.</b>				
1			-					

## \* - INDICATES SPECIALTY ITEMS

FILE NAME = 09325-QUAN-01 - P01	USER NAME =	DESIGNED RES	REVISED	
		CHECKED — JMN	REVISED	l
	PLOT SCALE =	DRAWN — MJD	REVISED —	DE
	PLOT DATE = 10-13-09	CHECKED — RES	REVISED —	l

## STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

							,
WOODLAWN AVENUE	F.A.U SECTION				COUNTY	TOTAL SHEETS	SHEET NO.
STREET RESURFACING		09-00012-00-RS			COOK	13	2
SUMMARY OF QUANTITIES AND GENERAL NOTES	CONTRACT NO. 63305						
SCALE: N/A SHEET NO. 2 OF 13 SHEETS STA. N/A TO STA. N/A	FED. RO.	AD DIST. NO. 1	ILLINOIS	FED. Al	D PROJECT ARA-	3003 (429)	

## **GENERAL NOTES**

- BEFORE STARTING ANY EXCAVATION THE CONTRACTOR SHALL CALL "J.U.L.I.E."
  AT (800) 892-0123 AND (312) 744-7000 FOR FIELD LOCATIONS OF BURIED
  ELECTRIC, TELEPHONE AND GAS UTILITIES. (48 HOUR NOTIFICATION REQUIRED)
- 2. UTILITIES INDICATED ON THE PLANS ARE PROVIDED FOR THE CONTRACTORS USE AND ARE BASED UPON INFORMATION AVAILABLE AT THE TIME OF THE ADVERTISEMENT FOR BIDS. THE OWNER AND ENGINEER DO NOT GUARANTEE THE ACCURACY OF UTILITY INFORMATION.
- IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO VERIFY ALL DIMENSIONS AND CONDITIONS EXISTING IN THE FIELD PRIOR TO CONSTRUCTION AND ORDERING OF MATERIALS.
- 4. SCHEDULES INCLUDED IN THE PLANS HAVE BEEN PREPARED FROM FIELD NOTES. EXACT LOCATIONS FOR PATCHING SHALL BE DETERMINED IN THE FIELD BY THE ENGINEER.
- ANY REFERENCE TO STANDARDS THROUGHOUT THE PLANS OR SPECIAL PROVISIONS SHALL BE INTERPRETED TO BE THE LATEST STANDARDS OF THE ILLINOIS DEPARTMENT OF TRANSPORTATION.
- 6. THE THICKNESS OF HMA MIXTURE STATED IN THE SPECIFICATIONS IS THE NOMINAL THICKNESS. DEVIATIONS FROM THE NOMINAL THICKNESS WILL BE PERMITTED WHEN SUCH DEVIATIONS OCCUR DUE TO IRREGULARITIES IN THE EXISTING SURFACE OR BASE ON WHICH THE HMA SURFACE IS PLACED.
- ACCESS TO DRIVEWAYS SHALL BE MAINTAINED AT ALL TIMES BY LIMITING CURB AND GUTTER REPAIR TO ONE—HALF THE DRIVEWAY WIDTH AT ONE TIME AS WELL AS TEMPORARY AGGREGATE.