



(FOR BUTT JOINT AND HMA TAPER SEE DETAIL BELOW)

OPTION 1



OPTION 2 TYPICAL TEMPORARY RAMP



TYPICAL BUTT JOINT AND HMA TAPER FOR MILLING AND RESURFACING

DESIGNED - M. DE YONG USER NAME = gaglianobt REVISED - R. SHAH 10-25-94 DRAWN REVISED - A. ABBAS 03-21-97 PLOT SCALE = 50.2000 '/ IN. CHECKED -REVISED - M. GOMEZ 04-06-01 PLOT DATE = 1/4/2208 DATE - 06-13-90 REVISED - R. BORO 01-01-07

FILE NAME =

\disastd\22x34\bd32 dgn

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION**


| 1251 09 - DOI 08 - OO - RS LAKE | 12 9 | FED. ROAD DIES | DO | CONTRACT NO | CONTRAC **BUTT JOINT AND** HMA TAPER DETAILS SHEET NO. 1 OF 1 SHEETS STA. TO STA.

ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN,

CONTRACT NO. 45388

13/4 (45) FOR E AND F MIX

1/2 (40) FOR C AND D MIX



TYPICAL BUTT JOINT AND HMA TAPER FOR RESURFACING ONLY

HMA TAPER DETAIL

* * PC CONCRETE, HMA OR HMA RESURFACED PAVEMENT.

* * EXIST. PAVEMENT

NOTES

- A: MAINLINE ROADWAYS AND MAJOR SIDE ROADS.
- B: MINOR SIDE ROADS.

PROP. HMA SURF. CRSE.

PROP. HMA BINDER CRSE.

- C: THE TEMP. RAMP SHALL BE CONSTRUCTED IMMEDIATELY UPON REMOVAL OF THE EXISTING HMA SURFACE.
- D: THE BUTT JOINT SHALL BE CONSTRUCTED IMMEDIATELY PRIOR TO PLACING THE PROPOSED HMA COURSES.
- E: TAPER THE TEMP. RAMP AT A RATE OF 3'-0" (900 mm) PER 1 INCH (25 mm) OF MILLING THICKNESS.

VARIES

- F: INSTALLATION AND REMOVAL OF THE 4'-6" (1.35 m) TEMP, RAMP IS INCLUDED IN COST OF HMA SURFACE REMOVAL - BUTT JOINT
- G: SEE ARTICLE 406.08 AND 406.14 OF THE STANDARD SPECIFICATIONS FOR "HMA AND/OR PCC SURFACE REMOVAL, BUTT JOINT".
- * SEE TYPICAL SECTIONS FOR MILLING THICKNESS.
- ** ** 20'-0" (6.1 m) PER 1 (25) RESURFACING (NOTE "A") 10'-0" (3.0 m) PER 1 (25) RESURFACING (NOTE "B")

BASIS OF PAYMENT:

THE BUTT JOINT WILL BE PAID FOR AT THE CONTRACT UNIT PRICE PER SOUARE YARD (SOUARE METER)
FOR "HOT-MIX ASPHALT SURFACE REMOVAL - BUTT JOINT" OR FOR "PORTLAND CEMENT CONCRETE SURFACE REMOVAL- BUTT JOINT".

SCALE: NONE