



SECTION (Showing reinforcement clearances for slip forming and additional reinforcement bars)



GFRP REBAR STIFFENING DETAIL

(Place as shown in parapet section at each parapet joint location.)

USER NAME:	DESIGNED - RTM	REVISED -					SECTION	COUNTY	TÓTAL SHEETS	SHEET NO.
	DRAWN - MSD	REVISED -	STATE OF ILLINOIS	CONCRETE PARAPET SLIPFORMING OPTION		717	109B-3	LOGAN	73	48
PLOT SCALE:	CHECKED - KEB	REVISED -	DEPARTMENT OF TRANSPORTATION						CONTRACT NO. 72A88	
PLOT DATE:	DATE -	DATE - REVISED -		SCALE;	SHEET NO. 13 OF 27 SHEETS STA. TO STA.	FED. ROAD DIS	T. NO. ILLINOIS	FED. AID PR		

SODEMANN AND ASSOCIATES, INC.

GENERAL NOTES

All dimensions shall remain the same as shown on contract plans, except dimensions A and B which are to be revised as shown to provide additional clearance. Additional concrete needed to revise dimension A and B= 0.0165 cu. yds./ft. of parapet. Place aluminum sheet in curb portion at and near piers. Full thickness saw cut at all joint locations in lieu of cork joint filler.



<u>#3 (E) BAR</u>

CONCRETE PARAPET SLIPFORMING OPTION STRUCTURE NO. 054-0514

07100