

## **If you plan to submit a bid directly to the Department of Transportation**

### **PREQUALIFICATION**

Any contractor who desires to become pre-qualified to bid on work advertised by IDOT must submit the properly completed pre-qualification forms to the Bureau of Construction no later than 4:30 p.m. prevailing time twenty-one days prior to the letting of interest. This pre-qualification requirement applies to first time contractors, contractors renewing expired ratings, contractors maintaining continuous pre-qualification or contractors requesting revised ratings. To be eligible to bid, existing pre-qualification ratings must be effective through the date of letting.

### **REQUESTS FOR AUTHORIZATION TO BID**

Contractors wanting to bid on items included in a particular letting must submit the properly completed "Request for Authorization to Bid/or Not For Bid Status" (BDE 124INT) and the ORIGINAL "Affidavit of Availability" (BC 57) to the proper office no later than 4:30 p.m. prevailing time, three (3) days prior to the letting date.

### **WHO CAN BID ?**

Bids will be accepted from only those companies that request and receive written **Authorization to Bid** from IDOT's Central Bureau of Construction.

**WHAT CONSTITUTES WRITTEN AUTHORIZATION TO BID?:** When a prospective prime bidder submits a "Request for Authorization to Bid/or Not For Bid Status" (BDE 124INT) he/she must indicate at that time which items are being requested For Bidding purposes. Only those items requested For Bidding will be analyzed. After the request has been analyzed, the bidder will be issued an **Authorization to Bid or Not for Bid Report**, approved by the Central Bureau of Construction that indicates which items have been approved For Bidding. If **Authorization to Bid** cannot be approved, the **Authorization to Bid or Not for Bid Report** will indicate the reason for denial.

**ABOUT AUTHORIZATION TO BID:** Firms that have not received an authorization form within a reasonable time of complete and correct original document submittal should contact the department as to status. This is critical in the week before the letting. These documents must be received three days before the letting date. Firms unsure as to authorization status should call the Prequalification Section of the Bureau of Construction at the number listed at the end of these instructions.

**ADDENDA AND REVISIONS:** It is the contractor's responsibility to determine which, if any, addenda or revisions pertain to any project they may be bidding. Failure to incorporate all relevant addenda or revisions may cause the bid to be declared unacceptable.

Each addendum will be placed with the contract number. Addenda and revisions will also be placed on the Addendum/Revision Checklist and each subscription service subscriber will be notified by e-mail of each addendum and revision issued.

The Internet is the Department's primary way of doing business. The subscription server e-mails are an added courtesy the Department provides. It is suggested that bidders check IDOT's website at <http://www.dot.il.gov/desenv/delett.html> before submitting final bid information.

### ***IDOT IS NOT RESPONSIBLE FOR ANY E-MAIL FAILURES.***

Addenda Questions may be directed to the Contracts Office at (217)782-7806 or [D&Econtracts@dot.il.gov](mailto:D&Econtracts@dot.il.gov)

Technical Questions about downloading these files may be directed to Tim Garman (217)524-1642 or [Timothy.Garman@illinois.gov](mailto:Timothy.Garman@illinois.gov).

**WHAT MUST BE INCLUDED WHEN BIDS ARE SUBMITTED?:** Bidders need not return the entire proposal when bids are submitted. That portion of the proposal that must be returned includes the following:

1. All documents from the Proposal Cover Sheet through the Proposal Bid Bond
2. Other special documentation and/or information that may be required by the contract special provisions

All proposal documents, including Proposal Guaranty Checks or Proposal Bid Bonds, should be stapled together to prevent loss when bids are processed by IDOT personnel.

**ABOUT SUBMITTING BIDS:** It is recommended that bidders deliver bids in person to insure they arrive at the proper location prior to the time specified for the receipt of bids. Any bid received at the place of letting after the time specified will not be accepted.

**WHO SHOULD BE CALLED IF ASSISTANCE IS NEEDED?**

<b>Questions Regarding</b>	<b>Call</b>
Prequalification and/or Authorization to Bid	217/782-3413
Preparation and submittal of bids	217/782-7806
Mailing of plans and proposals	217/782-7806

**ADDENDUMS AND REVISIONS TO THE PROPOSAL FORMS**

Planholders should verify that they have received and incorporated any addendum and/or revision prior to submitting their bid. Failure by the bidder to include an addendum or revision could result in a bid being rejected as irregular.

RETURN WITH BID

19

Proposal Submitted By
Name
Address
City

Letting January 15, 2010

BIDDERS NEED NOT RETURN THE ENTIRE PROPOSAL  
(See instructions inside front cover)

**NOTICE TO PROSPECTIVE BIDDERS**

This proposal can be used for bidding purposes by only those companies that request and receive written AUTHORIZATION TO BID from IDOT's Central Bureau of Construction.

(SEE INSTRUCTIONS ON THE INSIDE OF COVER)

**Notice To Bidders,  
Specifications,  
Proposal, Contract  
and Contract Bond**



**Illinois Department  
of Transportation**

Springfield, Illinois 62764

Contract No. 76C64  
ST CLAIR County  
Section DIST 8 ITS 2010-3  
Route FAI 64  
Project ACHSIP-064-1(124)001  
District 8 Construction Funds

PLEASE MARK THE APPROPRIATE BOX BELOW:

- A Bid Bond is included.
- A Cashier's Check or a Certified Check is included

Prepared by

Checked by

F

(Printed by authority of the State of Illinois)

---

---

## INSTRUCTIONS

**ABOUT IDOT PROPOSALS:** All proposals issued by IDOT are potential bidding proposals. Each proposal contains all Certifications and Affidavits, a Proposal Signature Sheet and a Proposal Bid Bond required for Prime Contractors to submit a bid after written **Authorization to Bid** has been issued by IDOT's Central Bureau of Construction.

**WHO CAN BID?:** Bids will be accepted from only those companies that request and receive written **Authorization to Bid** from IDOT's Central Bureau of Construction. To request authorization, a potential bidder must complete and submit Part B of the Request for Authorization to Bid/or Not For Bid Status form (BDE 124 INT) and submit an original Affidavit of Availability (BC 57).

**WHAT CONSTITUTES WRITTEN AUTHORIZATION TO BID?:** When a prospective prime bidder submits a "Request for Authorization to Bid/or Not For Bid" form, he/she must indicate at that time which items are being requested For Bidding purposes. Only those items requested For Bidding will be analyzed. After the request has been analyzed, the bidder will be issued an **Authorization to Bid or Not for Bid Report**, approved by the Central Bureau of Construction that indicates which items have been approved For Bidding. If **Authorization to Bid** cannot be approved, the **Authorization to Bid or Not for Bid Report** will indicate the reason for denial. If a contractor has requested to bid but has not received a **Authorization to Bid or Not for Bid Report**, they should contact the Central Bureau of Construction in advance of the letting date.

**WHAT MUST BE INCLUDED WHEN BIDS ARE SUBMITTED?:** Bidders need not return the entire proposal when bids are submitted. That portion of the proposal that must be returned includes the following:

1. All documents from the Proposal Cover Sheet through the Proposal Bid Bond
2. Other special documentation and/or information that may be required by the contract special provisions

All proposal documents, including Proposal Guaranty Checks or Proposal Bid Bonds, should be stapled together to prevent loss when bids are processed by IDOT personnel.

**ABOUT SUBMITTING BIDS:** It is recommended that bidders deliver bids in person to insure they arrive at the proper location prior to the time specified for the receipt of bids. Any bid received at the place of letting after the time specified will not be accepted.

### WHO SHOULD BE CALLED IF ASSISTANCE IS NEEDED?

Questions Regarding	Call
Prequalification and/or Authorization to Bid	217/782-3413
Preparation and submittal of bids	217/782-7806
Mailing of CD-ROMS	217/782-7806

RETURN WITH BID



PROPOSAL

TO THE DEPARTMENT OF TRANSPORTATION

1. Proposal of \_\_\_\_\_  
\_\_\_\_\_

Taxpayer Identification Number (Mandatory) \_\_\_\_\_

for the improvement identified and advertised for bids in the Invitation for Bids as:

**Contract No. 76C64  
ST CLAIR County  
Section DIST 8 ITS 2010-3  
Project ACHSIP-064-1(124)001  
Route FAI 64  
District 8 Construction Funds**

**ITS-Dynamic Message Board-HSIP at westbound I-64 northeast of 37th Street Bridge in East St. Louis.**

2. The undersigned bidder will furnish all labor, material and equipment to complete the above described project in a good and workmanlike manner as provided in the contract documents provided by the Department of Transportation. This proposal will become part of the contract and the terms and conditions contained in the contract documents shall govern performance and payments.



**RETURN WITH BID**

6. **COMBINATION BIDS.** The undersigned further agrees that if awarded the contract for the sections contained in the following combination, he/she will perform the work in accordance with the requirements of each individual proposal comprising the combination bid specified in the schedule below, and that the combination bid shall be prorated against each section in proportion to the bid submitted for the same. If an error is found to exist in the gross sum bid for one or more of the individual sections included in a combination, the combination bid shall be corrected as provided in the specifications.

**When a combination bid is submitted, the schedule below must be completed in each proposal comprising the combination.**

**If alternate bids are submitted for one or more of the sections comprising the combination, a combination bid must be submitted for each alternate.**

**Schedule of Combination Bids**

Combination No.	Sections Included in Combination	Combination Bid	
		Dollars	Cents

7. **SCHEDULE OF PRICES.** The undersigned bidder submits herewith, in accordance with the rules and instructions, a schedule of prices for the items of work for which bids are sought. The unit prices bid are in U.S. dollars and cents, and all extensions and summations have been made. The bidder understands that the quantities appearing in the bid schedule are approximate and are provided for the purpose of obtaining a gross sum for the comparison of bids. If there is an error in the extension of the unit prices, the unit prices shall govern. Payment to the contractor awarded the contract will be made only for actual quantities of work performed and accepted or materials furnished according to the contract. The scheduled quantities of work to be done and materials to be furnished may be increased, decreased or omitted as provided elsewhere in the contract.

8. **CERTIFICATE OF AUTHORITY.** The undersigned bidder, if a business organized under the laws of another State, assures the Department that it will furnish a copy of its certificate of authority to do business in the State of Illinois with the return of the executed contract and bond. Failure to furnish the certificate within the time provided for execution of an awarded contract may be cause for cancellation of the award and forfeiture of the proposal guaranty to the State.

ILLINOIS DEPARTMENT OF TRANSPORTATION  
 SCHEDULE OF PRICES  
 CONTRACT  
 NUMBER - 76C64

State Job # - C-98-008-09  
 PPS NBR - 8-08800-2803  
 County Name - ST CLAIR - -  
 Code - 163 - -  
 District - 8 - -  
 Section Number - DIST 8 ITS 2010-3

Project Number  
 ACHSIP-0641/124/001

Route  
 FAI 64

Item Number	Pay Item Description	Unit of Measure	Quantity	x	Unit Price	=	Total Price
X0323228	F & I TRUSS DAMPER	EACH	1.000				
X0325470	CON AT ST 3 ALUM	FOOT	120.000				
X0325922	CELLULAR MODEM	EACH	1.000				
X7010600	TC-PROT 701406 SPL	L SUM	1.000				
X7015015	TRUSS MTD CHG MSG SGN	EACH	1.000				
X8100065	CON T 4 PVC TY C	FOOT	15.000				
67000400	ENGR FIELD OFFICE A	CAL MO	6.000				
67100100	MOBILIZATION	L SUM	1.000				
70100815	TRAF CONT-PROT 701446	L SUM	1.000				
73300300	OVHD SIN STR-SPAN T3A	FOOT	70.000				
73305000	OVHD SIN STR WALKWAY	FOOT	36.000				
73400200	DRILL SHAFT CONC FDN	CU YD	21.700				
80300100	LOCATE UNDERGR CABLE	FOOT	100.000				
80500100	SERV INSTALL TY A	EACH	1.000				
81012500	CON T 1 1/2 PVC	FOOT	80.000				



ILLINOIS DEPARTMENT OF TRANSPORTATION  
 SCHEDULE OF PRICES  
 CONTRACT  
 NUMBER - 76C64

State Job # - C-98-008-09  
 PPS NBR - 8-08800-2803  
 County Name - ST CLAIR- -  
 Code - 163 - -  
 District - 8 - -  
 Section Number - DIST 8 ITS 2010-3

Project Number  
 ACHSIP-0641/124/001

Route  
 FAI 64

Item Number	Pay Item Description	Unit of Measure	Quantity	x	Unit Price	=	Total Price
81012800	CON T 3 PVC	FOOT	115.000				
81400720	DBL HANDHOLE PCC	EACH	1.000				
81702500	EC C XLP USE 4C 6	FOOT	110.000				
81900200	TR & BKFIL F ELECT WK	FOOT	110.000				
86300305	CONT CAB TYPE III SPL	EACH	1.000				
87800210	CONC FDN TY D SPL	FOOT	3.500				

**CONTRACT NUMBER**

**76C64**

**THIS IS THE TOTAL BID**

**\$ \_\_\_\_\_**

**NOTES:**

- 1. Each PAY ITEM should have a UNIT PRICE and a TOTAL PRICE.**
- 2. The UNIT PRICE shall govern if no TOTAL PRICE is shown or if there is a discrepancy between the product of the UNIT PRICE multiplied by the QUANTITY.**
- 3. If a UNIT PRICE is omitted, the TOTAL PRICE will be divided by the QUANTITY in order to establish a UNIT PRICE.**
- 4. A bid may be declared UNACCEPTABLE if neither a unit price nor a total price is shown.**

## RETURN WITH BID

### **STATE REQUIRED ETHICAL STANDARDS GOVERNING CONTRACT PROCUREMENT: ASSURANCES, CERTIFICATIONS AND DISCLOSURES**

#### **I. GENERAL**

**A.** Article 50 of the Illinois Procurement Code establishes the duty of all State chief procurement officers, State purchasing officers, and their designees to maximize the value of the expenditure of public moneys in procuring goods, services, and contracts for the State of Illinois and to act in a manner that maintains the integrity and public trust of State government. In discharging this duty, they are charged by law to use all available information, reasonable efforts, and reasonable actions to protect, safeguard, and maintain the procurement process of the State of Illinois.

**B.** In order to comply with the provisions of Article 50 and to carry out the duty established therein, all bidders are to adhere to ethical standards established for the procurement process, and to make such assurances, disclosures and certifications required by law. By execution of the Proposal Signature Sheet, the bidder indicates that each of the mandated assurances has been read and understood, that each certification is made and understood, and that each disclosure requirement has been understood and completed.

**C.** In addition to all other remedies provided by law, failure to comply with any assurance, failure to make any disclosure or the making of a false certification shall be grounds for termination of the contract and the suspension or debarment of the bidder.

#### **II. ASSURANCES**

**A.** The assurances hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder. The Department may terminate the contract if it is later determined that the bidder rendered a false or erroneous assurance, and the surety providing the performance bond shall be responsible for the completion of the contract.

##### **B. Felons**

1. The Illinois Procurement Code provides:

Section 50-10. Felons. Unless otherwise provided, no person or business convicted of a felony shall do business with the State of Illinois or any state agency from the date of conviction until 5 years after the date of completion of the sentence for that felony, unless no person held responsible by a prosecutorial office for the facts upon which the conviction was based continues to have any involvement with the business.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-10.

##### **C. Conflicts of Interest**

1. The Illinois Procurement Code provides in pertinent part:

Section 50-13. Conflicts of Interest.

(a) Prohibition. It is unlawful for any person holding an elective office in this State, holding a seat in the General Assembly, or appointed to or employed in any of the offices or agencies of state government and who receives compensation for such employment in excess of 60% of the salary of the Governor of the State of Illinois, or who is an officer or employee of the Capital Development Board or the Illinois Toll Highway Authority, or who is the spouse or minor child of any such person to have or acquire any contract, or any direct pecuniary interest in any contract therein, whether for stationery, printing, paper, or any services, materials, or supplies, that will be wholly or partially satisfied by the payment of funds appropriated by the General Assembly of the State of Illinois or in any contract of the Capital Development Board or the Illinois Toll Highway authority.

(b) Interests. It is unlawful for any firm, partnership, association or corporation, in which any person listed in subsection (a) is entitled to receive (i) more than 7 1/2% of the total distributable income or (ii) an amount in excess of the salary of the Governor, to have or acquire any such contract or direct pecuniary interest therein.

(c) Combined interests. It is unlawful for any firm, partnership, association, or corporation, in which any person listed in subsection (a) together with his or her spouse or minor children is entitled to receive (i) more than 15%, in the aggregate, of the total distributable income or (ii) an amount in excess of 2 times the salary of the Governor, to have or acquire any such contract or direct pecuniary interest therein.

(d) Securities. Nothing in this Section invalidates the provisions of any bond or other security previously offered or to be offered for sale or sold by or for the State of Illinois.

(e) Prior interests. This Section does not affect the validity of any contract made between the State and an officer or employee of the State or member of the General Assembly, his or her spouse, minor child or any combination of those persons if that contract was in existence before his or her election or employment as an officer, member, or employee. The contract is voidable, however, if it cannot be completed within 365 days after the officer, member, or employee takes office or is employed.

The current salary of the Governor is \$177,412.00. Sixty percent of the salary is \$106,447.20.

## RETURN WITH BID

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-13, or that an effective exemption has been issued by the Board of Ethics to any individual subject to the Section 50-13 prohibitions pursuant to the provisions of Section 50-20 of the Code and Executive Order Number 3 (1998). Information concerning the exemption process is available from the Department upon request.

### **D. Negotiations**

1. The Illinois Procurement Code provides in pertinent part:

Section 50-15. Negotiations.

(a) It is unlawful for any person employed in or on a continual contractual relationship with any of the offices or agencies of State government to participate in contract negotiations on behalf of that office or agency with any firm, partnership, association, or corporation with whom that person has a contract for future employment or is negotiating concerning possible future employment.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-15, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

### **E. Inducements**

1. The Illinois Procurement Code provides:

Section 50-25. Inducement. Any person who offers or pays any money or other valuable thing to any person to induce him or her not to bid for a State contract or as recompense for not having bid on a State contract is guilty of a Class 4 felony. Any person who accepts any money or other valuable thing for not bidding for a State contract or who withholds a bid in consideration of the promise for the payment of money or other valuable thing is guilty of a Class 4 felony.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-25, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

### **F. Revolving Door Prohibition**

1. The Illinois Procurement Code provides:

Section 50-30. Revolving door prohibition. Chief procurement officers, associate procurement officers, State purchasing officers, their designees whose principal duties are directly related to State procurement, and executive officers confirmed by the Senate are expressly prohibited for a period of 2 years after terminating an affected position from engaging in any procurement activity relating to the State agency most recently employing them in an affected position for a period of at least 6 months. The prohibition includes, but is not limited to: lobbying the procurement process; specifying; bidding; proposing bid, proposal, or contract documents; on their own behalf or on behalf of any firm, partnership, association, or corporation. This Section applies only to persons who terminate an affected position on or after January 15, 1999.

2. The bidder assures the Department that the award and execution of the contract would not cause a violation of Section 50-30, and that the bidder has no knowledge of any facts relevant to the kinds of acts prohibited therein.

### **G. Reporting Anticompetitive Practices**

1. The Illinois Procurement Code provides:

Section 50-40. Reporting anticompetitive practices. When, for any reason, any vendor, bidder, contractor, chief procurement officer, State purchasing officer, designee, elected official, or State employee suspects collusion or other anticompetitive practice among any bidders, offerors, contractors, proposers, or employees of the State, a notice of the relevant facts shall be transmitted to the Attorney General and the chief procurement officer.

2. The bidder assures the Department that it has not failed to report any relevant facts concerning the practices addressed in Section 50-40 which may involve the contract for which the bid is submitted.

### **H. Confidentiality**

1. The Illinois Procurement Code provides:

Section 50-45. Confidentiality. Any chief procurement officer, State purchasing officer, designee, or executive officer who willfully uses or allows the use of specifications, competitive bid documents, proprietary competitive information, proposals, contracts, or selection information to compromise the fairness or integrity of the procurement, bidding, or contract process shall be subject to immediate dismissal, regardless of the Personnel code, any contract, or any collective bargaining agreement, and may in addition be subject to criminal prosecution.

2. The bidder assures the Department that it has no knowledge of any fact relevant to the practices addressed in Section 50-45 which may involve the contract for which the bid is submitted.

## RETURN WITH BID

### **I. Insider Information**

1. The Illinois Procurement Act provides:

Section 50-50. Insider information. It is unlawful for any current or former elected or appointed State official or State employee to knowingly use confidential information available only by virtue of that office or employment for actual or anticipated gain for themselves or another person.

2. The bidder assures the Department that it has no knowledge of any facts relevant to the practices addressed in Section 50-50 which may involve the contract for which the bid is submitted.

### **III. CERTIFICATIONS**

**A.** The certifications hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder. The Department may terminate the contract if it is later determined that the bidder rendered a false or erroneous certification, and the surety providing the performance bond shall be responsible for completion of the contract.

#### **B. Bribery**

1. The Illinois Procurement Code provides:

Section 50-5. Bribery.

- (a) Prohibition. No person or business shall be awarded a contract or subcontract under this Code who:

- (1) has been convicted under the laws of Illinois or any other state of bribery or attempting to bribe an officer or employee of the State of Illinois or any other state in that officer's or employee's official capacity; or

- (2) has made an admission of guilt of that conduct that is a matter of record but has not been prosecuted for that conduct.

- (b) Businesses. No business shall be barred from contracting with any unit of State or local government as a result of a conviction under this Section of any employee or agent of the business if the employee or agent is no longer employed by the business and:

- (1) the business has been finally adjudicated not guilty; or

- (2) the business demonstrates to the governmental entity with which it seeks to contract, and that entity finds that the commission of the offense was not authorized, requested, commanded, or performed by a director, officer, or high managerial agent on behalf of the business as provided in paragraph (2) of subsection (a) of Section 5-4 of the Criminal Code of 1961.

- (c) Conduct on behalf of business. For purposes of this Section, when an official, agent, or employee of a business committed the bribery or attempted bribery on behalf of the business and in accordance with the direction or authorization of a responsible official of the business, the business shall be chargeable with the conduct.

- (d) Certification. Every bid submitted to and contract executed by the State shall contain a certification by the contractor that the contractor is not barred from being awarded a contract or subcontract under this Section. A contractor who makes a false statement, material to the certification, commits a Class 3 felony.

2. The bidder certifies that it is not barred from being awarded a contract under Section 50.5.

#### **C. Educational Loan**

1. Section 3 of the Educational Loan Default Act provides:

§ 3. No State agency shall contract with an individual for goods or services if that individual is in default, as defined in Section 2 of this Act, on an educational loan. Any contract used by any State agency shall include a statement certifying that the individual is not in default on an educational loan as provided in this Section.

2. The bidder, if an individual as opposed to a corporation, partnership or other form of business organization, certifies that the bidder is not in default on an educational loan as provided in Section 3 of the Act.

#### **D. Bid-Rigging/Bid Rotating**

1. Section 33E-11 of the Criminal Code of 1961 provides:

§ 33E-11. (a) Every bid submitted to and public contract executed pursuant to such bid by the State or a unit of local government shall contain a certification by the prime contractor that the prime contractor is not barred from contracting with any unit of State or local government as a result of a violation of either Section 33E-3 or 33E-4 of this Article. The State and units of local government shall provide the appropriate forms for such certification.

## RETURN WITH BID

(b) A contractor who makes a false statement, material to the certification, commits a Class 3 felony.

A violation of Section 33E-3 would be represented by a conviction of the crime of bid-rigging which, in addition to Class 3 felony sentencing, provides that any person convicted of this offense or any similar offense of any state or the United States which contains the same elements as this offense shall be barred for 5 years from the date of conviction from contracting with any unit of State or local government. No corporation shall be barred from contracting with any unit of State or local government as a result of a conviction under this Section of any employee or agent of such corporation if the employee so convicted is no longer employed by the corporation and: (1) it has been finally adjudicated not guilty or (2) if it demonstrates to the governmental entity with which it seeks to contract and that entity finds that the commission of the offense was neither authorized, requested, commanded, nor performed by a director, officer or a high managerial agent in behalf of the corporation.

A violation of Section 33E-4 would be represented by a conviction of the crime of bid-rotating which, in addition to Class 2 felony sentencing, provides that any person convicted of this offense or any similar offense of any state or the United States which contains the same elements as this offense shall be permanently barred from contracting with any unit of State or local government. No corporation shall be barred from contracting with any unit of State or local government as a result of a conviction under this Section of any employee or agent of such corporation if the employee so convicted is no longer employed by the corporation and: (1) it has been finally adjudicated not guilty or (2) if it demonstrates to the governmental entity with which it seeks to contract and that entity finds that the commission of the offense was neither authorized, requested, commanded, nor performed by a director, officer or a high managerial agent in behalf of the corporation.

2. The bidder certifies that it is not barred from contracting with the Department by reason of a violation of either Section 33E-3 or Section 33E-4.

### **E. International Anti-Boycott**

1. Section 5 of the International Anti-Boycott Certification Act provides:

§ 5. State contracts. Every contract entered into by the State of Illinois for the manufacture, furnishing, or purchasing of supplies, material, or equipment or for the furnishing of work, labor, or services, in an amount exceeding the threshold for small purchases according to the purchasing laws of this State or \$10,000.00, whichever is less, shall contain certification, as a material condition of the contract, by which the contractor agrees that neither the contractor nor any substantially-owned affiliated company is participating or shall participate in an international boycott in violation of the provisions of the U.S. Export Administration Act of 1979 or the regulations of the U.S. Department of Commerce promulgated under that Act.

2. The bidder makes the certification set forth in Section 5 of the Act.

### **F. Drug Free Workplace**

1. The Illinois "Drug Free Workplace Act" applies to this contract and it is necessary to comply with the provisions of the "Act" if the contractor is a corporation, partnership, or other entity (including a sole proprietorship) which has 25 or more employees.

2. The bidder certifies that if awarded a contract in excess of \$5,000 it will provide a drug free workplace by:

(a) Publishing a statement notifying employees that the unlawful manufacture, distribution, dispensation, possession or use of a controlled substance, including cannabis, is prohibited in the contractor's workplace; specifying the actions that will be taken against employees for violations of such prohibition; and notifying the employee that, as a condition of employment on such contract, the employee shall abide by the terms of the statement, and notify the employer of any criminal drug statute conviction for a violation occurring in the workplace no later than five (5) days after such conviction.

(b) Establishing a drug free awareness program to inform employees about the dangers of drug abuse in the workplace; the contractor's policy of maintaining a drug free workplace; any available drug counseling, rehabilitation, and employee assistance programs; and the penalties that may be imposed upon employees for drug violations.

(c) Providing a copy of the statement required by subparagraph (1) to each employee engaged in the performance of the contract and to post the statement in a prominent place in the workplace.

(d) Notifying the Department within ten (10) days after receiving notice from an employee or otherwise receiving actual notice of the conviction of an employee for a violation of any criminal drug statute occurring in the workplace.

(e) Imposing or requiring, within 30 days after receiving notice from an employee of a conviction or actual notice of such a conviction, an appropriate personnel action, up to and including termination, or the satisfactory participation in a drug abuse assistance or rehabilitation program approved by a federal, state or local health, law enforcement or other appropriate agency.

(f) Assisting employees in selecting a course of action in the event drug counseling, treatment, and rehabilitation is required and indicating that a trained referral team is in place.

(g) Making a good faith effort to continue to maintain a drug free workplace through implementation of the actions and efforts stated in this certification.

## RETURN WITH BID

### **G. Debt Delinquency**

1. The Illinois Procurement Code provides:

Section 50-11 and 50-12. Debt Delinquency.

The contractor or bidder certifies that it, or any affiliate, is not barred from being awarded a contract under 30 ILCS 500. Section 50-11 prohibits a person from entering into a contract with a State agency if it knows or should know that it, or any affiliate, is delinquent in the payment of any debt to the State as defined by the Debt Collection Board. Section 50-12 prohibits a person from entering into a contract with a State agency if it, or any affiliate, has failed to collect and remit Illinois Use Tax on all sales of tangible personal property into the State of Illinois in accordance with the provisions of the Illinois Use Tax Act. The contractor further acknowledges that the contracting State agency may declare the contract void if this certification is false or if the contractor, or any affiliate, is determined to be delinquent in the payment of any debt to the State during the term of the contract.

### **H. Sarbanes-Oxley Act of 2002**

1. The Illinois Procurement Code, Section 50-60(c), provides:

The contractor certifies in accordance with 30 ILCS 500/50-10.5 that no officer, director, partner or other managerial agent of the contracting business has been convicted of a felony under the Sarbanes-Oxley Act of 2002 or a Class 3 or Class 2 felony under the Illinois Securities Law of 1953 for a period of five years prior to the date of the bid or contract. The contractor acknowledges that the contracting agency shall declare the contract void if this certification is false.

### **I. Addenda**

The contractor or bidder certifies that all relevant addenda have been incorporated in to this contract. Failure to do so may cause the bid to be declared unacceptable.

### **J. Section 42 of the Environmental Protection Act**

The contractor certifies in accordance with 30 ILCS 500/50-12 that the bidder or contractor is not barred from being awarded a contract under this Section which prohibits the bidding on or entering into contracts with the State of Illinois or a State agency by a person or business found by a court or the Pollution Control Board to have committed a willful or knowing violation of Section 42 of the Environmental Protection Act for a period of five years from the date of the order. The contractor acknowledges that the contracting agency may declare the contract void if this certification is false.

### **K. Apprenticeship and Training Certification (Does not apply to federal aid projects)**

In accordance with the provisions of Section 30-22 (6) of the Illinois Procurement Code, the bidder certifies that it is a participant, either as an individual or as part of a group program, in the approved apprenticeship and training programs applicable to each type of work or craft that the bidder will perform with its own forces. The bidder further certifies for work that will be performed by subcontract that each of its subcontractors submitted for approval either (a) is, at the time of such bid, participating in an approved, applicable apprenticeship and training program; or (b) will, prior to commencement of performance of work pursuant to this contract, begin participation in an approved apprenticeship and training program applicable to the work of the subcontract. The Department, at any time before or after award, may require the production of a copy of each applicable Certificate of Registration issued by the United States Department of Labor evidencing such participation by the contractor and any or all of its subcontractors. Applicable apprenticeship and training programs are those that have been approved and registered with the United States Department of Labor. The bidder shall list in the space below, the official name of the program sponsor holding the Certificate of Registration for all of the types of work or crafts in which the bidder is a participant and that will be performed with the bidder's forces. Types of work or craft work that will be subcontracted shall be included and listed as subcontract work. The list shall also indicate any type of work or craft job category that does not have an applicable apprenticeship or training program. **The bidder is responsible for making a complete report and shall make certain that each type of work or craft job category that will be utilized on the project as reported on the Construction Employee Workforce Projection (Form BC-1256) and returned with the bid is accounted for and listed.**

**NA - FEDERAL**

---

---

The requirements of this certification and disclosure are a material part of the contract, and the contractor shall require this certification provision to be included in all approved subcontracts. In order to fulfill this requirement, it shall not be necessary that an applicable program sponsor be currently taking or that it will take applications for apprenticeship, training or employment during the performance of the work of this contract.

### **L. Executive Order Number 1 (2007) Regarding Lobbying on Government Procurements**

The bidder hereby warrants and certifies that they have complied and will comply with the requirements set forth in this Order. The requirements of this warrant and certification are a material part of the contract, and the contractor shall require this warrant and certification provision to be included in all approved subcontracts.

## RETURN WITH BID

### **M. Disclosure of Business Operations in Iran**

Section 50-36 of the Illinois Procurement Code, 30ILCS 500/50-36 provides that each bid, offer, or proposal submitted for a State contract shall include a disclosure of whether or not the Company acting as the bidder, offer or, or proposing entity, or any of its corporate parents or subsidiaries, within the 24 months before submission of the bid, offer, or proposal had business operations that involved contracts with or provision of supplies or services to the Government of Iran, companies in which the Government of Iran has any direct or indirect equity share, consortiums or projects commissioned by the Government of Iran, or companies involved in consortiums or projects commissioned by the Government of Iran and either of the following conditions apply:

- (1) More than 10% of the Company's revenues produced in or assets located in Iran involve oil-related activities or mineral-extraction activities; less than 75% of the Company's revenues produced in or assets located in Iran involve contracts with or provision of oil-related or mineral-extraction products or services to the Government of Iran or a project or consortium created exclusively by that government; and the Company has failed to take substantial action.
- (2) The Company has, on or after August 5, 1996, made an investment of \$20 million or more, or any combination of investments of at least \$10 million each that in the aggregate equals or exceeds \$20 million in any 12-month period, which directly or significantly contributes to the enhancement of Iran's ability to develop petroleum resources of Iran.

The terms "Business operations", "Company", "Mineral-extraction activities", "Oil-related activities", "Petroleum resources", and "Substantial action" are all defined in the Code.

Failure to make the disclosure required by the Code shall cause the bid, offer or proposal to be considered not responsive. The disclosure will be considered when evaluating the bid, offer, or proposal or awarding the contract. The name of each Company disclosed as doing business or having done business in Iran will be provided to the State Comptroller.

Check the appropriate statement:

Company has no business operations in Iran to disclose.

Company has business operations in Iran as disclosed the attached document.

### **N. Political Contributions and Registration with the State Board of Elections**

Sections 20-160 and 50-37 of the Illinois Procurement Code regulate political contributions from business entities and any affiliated entities or affiliated persons bidding on or contracting with the state. Generally under Section 50-37, any business entity, and any affiliated entity or affiliated person of the business entity, whose current year contracts with all state agencies exceed an awarded value of \$50,000, are prohibited from making any contributions to any political committees established to promote the candidacy of the officeholder responsible for the awarding of the contracts or any other declared candidate for that office for the duration of the term of office of the incumbent officeholder or a period 2 years after the termination of the contract, whichever is longer. Any business entity and affiliated entities or affiliated persons whose state contracts in the current year do not exceed an awarded value of \$50,000, but whose aggregate pending bids and proposals on state contracts exceed \$50,000, either alone or in combination with contracts not exceeding \$50,000, are prohibited from making any political contributions to any political committee established to promote the candidacy of the officeholder responsible for awarding the pending contract during the period beginning on the date the invitation for bids or request for proposals is issued and ending on the day after the date of award or selection if the entity was not awarded or selected. Section 20-160 requires certification of registration of affected business entities in accordance with procedures found in Section 9-35 of The Election Code.

By submission of a bid, the contractor business entity acknowledges and agrees that it has read and understands Sections 20-160 and 50-37 of the Illinois Procurement Code, and that it makes the following certification:

**The undersigned business entity certifies that it has registered as a business with the State Board of Elections and acknowledges a continuing duty to update the registration in accordance with the above referenced statutes. A copy of the certificate of registration shall be submitted with the bid. The bidder is cautioned that the Department will not award a contract without submission of the certificate of registration.**

These requirements and compliance with the above referenced statutory sections are a material part of the contract, and any breach thereof shall be cause to void the contract under Section 50-60 of the Illinois Procurement Code. This provision does not apply to Federal-aid contracts.



## TO BE RETURNED WITH BID

### IV. DISCLOSURES

A. The disclosures hereinafter made by the bidder are each a material representation of fact upon which reliance is placed should the Department enter into the contract with the bidder. The Department may terminate the contract if it is later determined that the bidder rendered a false or erroneous disclosure, and the surety providing the performance bond shall be responsible for completion of the contract.

#### B. Financial Interests and Conflicts of Interest

1. Section 50-35 of the Illinois Procurement Code provides that all bids of more than \$10,000 shall be accompanied by disclosure of the financial interests of the bidder. This disclosed information for the successful bidder, will be maintained as public information subject to release by request pursuant to the Freedom of Information Act.

The financial interests to be disclosed shall include ownership or distributive income share that is in excess of 5%, or an amount greater than 60% of the annual salary of the Governor, of the bidding entity or its parent entity, whichever is less, unless the contractor or bidder is a publicly traded entity subject to Federal 10K reporting, in which case it may submit its 10K disclosure in place of the prescribed disclosure. If a bidder is a privately held entity that is exempt from Federal 10K reporting, but has more than 400 shareholders, it may submit the information that Federal 10K companies are required to report, and list the names of any person or entity holding any ownership share that is in excess of 5%. The disclosure shall include the names, addresses, and dollar or proportionate share of ownership of each person making the disclosure, their instrument of ownership or beneficial relationship, and notice of any potential conflict of interest resulting from the current ownership or beneficial interest of each person making the disclosure having any of the relationships identified in Section 50-35 and on the disclosure form.

In addition, all disclosures shall indicate any other current or pending contracts, proposals, leases, or other ongoing procurement relationships the bidding entity has with any other unit of state government and shall clearly identify the unit and the contract, proposal, lease, or other relationship.

2. Disclosure Forms. Disclosure Form A is attached for use concerning the individuals meeting the above ownership or distributive share requirements. Subject individuals should be covered each by one form. In addition, a second form (Disclosure Form B) provides for the disclosure of current or pending procurement relationships with other (non-IDOT) state agencies. **The forms must be included with each bid or incorporated by reference.**

#### C. Disclosure Form Instructions

##### Form A: For bidders that have previously submitted the information requested in Form A

The Department has retained the Form A disclosures submitted by all bidders responding to these requirements for the April 24, 1998 or any subsequent letting conducted by the Department. The bidder has the option of submitting the information again or the bidder may check the following certification statement indicating that the information previously submitted by the bidder is, as of the date of submission, current and accurate. Before checking this certification, the bidder should carefully review its prior submissions to ensure the Certification is correct. If the Bidder checks the Certification, the Bidder should proceed to Form B instructions.

### CERTIFICATION STATEMENT

**I have determined that the Form A disclosure information previously submitted is current and accurate, and all forms are hereby incorporated by reference in this bid. Any necessary additional forms or amendments to previously submitted forms are attached to this bid.**

\_\_\_\_\_  
(Bidding Company)



\_\_\_\_\_  
Signature of Authorized Representative

\_\_\_\_\_  
Date

**Form A: For bidders who have NOT previously submitted the information requested in Form A**

If the bidder is a publicly traded entity subject to Federal 10K reporting, the 10K Report may be submitted to meet the requirements of Form A. If a bidder is a privately held entity that is exempt from Federal 10K reporting, but has more than 400 shareholders, it may submit the information that Federal 10K companies are required to report, and list the names of any person or entity holding any ownership share that is in excess of 5%. If a bidder is not subject to Federal 10K reporting, the bidder must determine if any individuals are required by law to complete a financial disclosure form. To do this, the bidder should answer each of the following questions. A "YES" answer indicates Form A must be completed. If the answer to each of the following questions is "NO", then the NOT APPLICABLE STATEMENT on the second page of Form A must be signed and dated by a person that is authorized to execute contracts for the bidding company. Note: These questions are for assistance only and are not required to be completed.

1. Does anyone in your organization have a direct or beneficial ownership share of greater than 5% of the bidding entity or parent entity? YES \_\_\_ NO \_\_\_
2. Does anyone in your organization have a direct or beneficial ownership share of less than 5%, but which has a value greater than \$102,600.00? YES \_\_\_ NO \_\_\_
3. Does anyone in your organization receive more than \$106,447.20 of the bidding entity's or parent entity's distributive income? (Note: Distributive income is, for these purposes, any type of distribution of profits. An annual salary is not distributive income.) YES \_\_\_ NO \_\_\_
4. Does anyone in your organization receive greater than 5% of the bidding entity's or parent entity's total distributive income, but which is less than \$106,447.20? YES \_\_\_ NO \_\_\_  
(Note: Only one set of forms needs to be completed per person per bid even if a specific individual would require a yes answer to more than one question.)

A "YES" answer to any of these questions requires the completion of Form A. The bidder must determine each individual in the bidding entity or the bidding entity's parent company that would cause the questions to be answered "Yes". Each form must be signed and dated by a person that is authorized to execute contracts for your organization. **Photocopied or stamped signatures are not acceptable.** The person signing can be, but does not have to be, the person for which the form is being completed. The bidder is responsible for the accuracy of any information provided.

If the answer to each of the above questions is "NO", then the NOT APPLICABLE STATEMENT on page 2 of Form A must be signed and dated by a person that is authorized to execute contracts for your company.

**Form B: Identifying Other Contracts & Procurement Related Information** Disclosure Form B must be completed for each bid submitted by the bidding entity. Note: *Checking the NOT APPLICABLE STATEMENT on Form A does not allow the bidder to ignore Form B. Form B must be completed, checked, and dated or the bidder may be considered nonresponsive and the bid will not be accepted.*

The Bidder shall identify, by checking Yes or No on Form B, whether it has any pending contracts (including leases), bids, proposals, or other ongoing procurement relationship with any other (non-IDOT) State of Illinois agency. If "No" is checked, the bidder only needs to complete the check box on the bottom of Form B. If "Yes" is checked, the bidder must do one of the following:

Option I: If the bidder did not submit an Affidavit of Availability to obtain authorization to bid, the bidder must list all non-IDOT State of Illinois agency pending contracts, leases, bids, proposals, and other ongoing procurement relationships. These items may be listed on Form B or on an attached sheet(s). Do not include IDOT contracts. Contracts with cities, counties, villages, etc. are not considered State of Illinois agency contracts and are not to be included. Contracts with other State of Illinois agencies such as the Department of Natural Resources or the Capital Development Board must be included. Bidders who submit Affidavits of Availability are suggested to use Option II.

Option II: If the bidder is required and has submitted an Affidavit of Availability in order to obtain authorization to bid, the bidder may write or type "See Affidavit of Availability" which indicates that the Affidavit of Availability is incorporated by reference and includes all non-IDOT State of Illinois agency pending contracts, leases, bids, proposals, and other ongoing procurement relationships. For any contracts that are not covered by the Affidavit of Availability, the bidder must identify them on Form B or on an attached sheet(s). These might be such things as leases.

**D. Bidders Submitting More Than One Bid**

Bidders submitting multiple bids may submit one set of forms consisting of all required Form A disclosures and one Form B for use with all bids. Please indicate in the space provided below the bid item that contains the original disclosure forms and the bid items which incorporate the forms by reference.

- The bid submitted for letting item \_\_\_\_\_ contains the Form A disclosures or Certification Statement and the Form B disclosures. The following letting items incorporate the said forms by reference:

---



---

RETURN WITH BID/OFFER

ILLINOIS DEPARTMENT OF TRANSPORTATION

Form A Financial Information & Potential Conflicts of Interest Disclosure

Contractor Name, Legal Address, City, State, Zip, Telephone Number, Email Address, Fax Number (if available)

Disclosure of the information contained in this Form is required by the Section 50-35 of the Illinois Procurement Code (30 ILCS 500). Vendors desiring to enter into a contract with the State of Illinois must disclose the financial information and potential conflict of interest information as specified in this Disclosure Form. This information shall become part of the publicly available contract file. This Form A must be completed for bids in excess of \$10,000, and for all open-ended contracts. A publicly traded company may submit a 10K disclosure (or equivalent if applicable) in satisfaction of the requirements set forth in Form A. See Disclosure Form Instructions.

DISCLOSURE OF FINANCIAL INFORMATION

1. Disclosure of Financial Information. The individual named below has an interest in the BIDDER (or its parent) in terms of ownership or distributive income share in excess of 5%, or an interest which has a value of more than \$106,447.20 (60% of the Governor's salary as of 3/1/09). (Make copies of this form as necessary and attach a separate Disclosure Form A for each individual meeting these requirements)

FOR INDIVIDUAL (type or print information)

NAME:

ADDRESS

Type of ownership/distributable income share:

stock sole proprietorship Partnership other: (explain on separate sheet): % or \$ value of ownership/distributable income share:

2. Disclosure of Potential Conflicts of Interest. Check "Yes" or "No" to indicate which, if any, of the following potential conflict of interest relationships apply. If the answer to any question is "Yes", please attach additional pages and describe.

(a) State employment, currently or in the previous 3 years, including contractual employment of services. Yes \_\_\_ No \_\_\_

If your answer is yes, please answer each of the following questions.

1. Are you currently an officer or employee of either the Capitol Development Board or the Illinois Toll Highway Authority? Yes \_\_\_ No \_\_\_

2. Are you currently appointed to or employed by any agency of the State of Illinois? If you are currently appointed to or employed by any agency of the State of Illinois, and your annual salary exceeds \$106,447.20, (60% of the Governor's salary as of 3/1/09) provide the name the State agency for which you are employed and your annual salary.

**RETURN WITH BID/OFFER**

- 3. If you are currently appointed to or employed by any agency of the State of Illinois, and your annual salary exceeds \$106,447.20, (60% of the Governor's salary as of 3/1/09) are you entitled to receive (i) more than 7 1/2% of the total distributable income of your firm, partnership, association or corporation, or (ii) an amount in excess of the salary of the Governor? Yes \_\_\_ No \_\_\_
  
- 4. If you are currently appointed to or employed by any agency of the State of Illinois, and your annual salary exceeds \$106,447.20, (60% of the Governor's salary as of 3/1/09) are you and your spouse or minor children entitled to receive (i) more than 15% in aggregate of the total distributable income of your firm, partnership, association or corporation, or (ii) an amount in excess of 2 times the salary of the Governor? Yes \_\_\_ No \_\_\_

---

(b) State employment of spouse, father, mother, son, or daughter, including contractual employment for services in the previous 2 years.

Yes \_\_\_ No \_\_\_

If your answer is yes, please answer each of the following questions.

- 1. Is your spouse or any minor children currently an officer or employee of the Capitol Development Board or the Illinois Toll Highway Authority? Yes \_\_\_ No \_\_\_
  
- 2. Is your spouse or any minor children currently appointed to or employed by any agency of the State of Illinois? If your spouse or minor children is/are currently appointed to or employed by any agency of the State of Illinois, and his/her annual salary exceeds \$106,447.20, (60% of the Governor's salary as of 3/1/09) provide the name of the spouse and/or minor children, the name of the State agency for which he/she is employed and his/her annual salary. \_\_\_\_\_
  
- 3. If your spouse or any minor children is/are currently appointed to or employed by any agency of the State of Illinois, and his/her annual salary exceeds \$106,447.20.00, (60% of the salary of the Governor as of 3/1/09) are you entitled to receive (i) more than 7 1/2% of the total distributable income of your firm, partnership, association or corporation, or (ii) an amount in excess of the salary of the Governor? Yes \_\_\_ No \_\_\_
  
- 4. If your spouse or any minor children are currently appointed to or employed by any agency of the State of Illinois, and his/her annual salary exceeds \$106,447.20, (60% of the Governor's salary as of 3/1/09) are you and your spouse or any minor children entitled to receive (i) more than 15% in the aggregate of the total distributable income from your firm, partnership, association or corporation, or (ii) an amount in excess of 2 times the salary of the Governor? Yes \_\_\_ No \_\_\_

---

(c) Elective status; the holding of elective office of the State of Illinois, the government of the United States, any unit of local government authorized by the Constitution of the State of Illinois or the statutes of the State of Illinois currently or in the previous 3 years.

Yes \_\_\_ No \_\_\_

---

(d) Relationship to anyone holding elective office currently or in the previous 2 years; spouse, father, mother, son, or daughter.

Yes \_\_\_ No \_\_\_

---

(e) Appointive office; the holding of any appointive government office of the State of Illinois, the United State of America, or any unit of local government authorized by the Constitution of the State of Illinois or the statutes of the State of Illinois, which office entitles the holder to compensation in excess of the expenses incurred in the discharge of that office currently or in the previous 3 years.

Yes \_\_\_ No \_\_\_

---

(f) Relationship to anyone holding appointive office currently or in the previous 2 years; spouse, father, mother, son, or daughter.

Yes \_\_\_ No \_\_\_

---

(g) Employment, currently or in the previous 3 years, as or by any registered lobbyist of the State government.

Yes \_\_\_ No \_\_\_

---

**RETURN WITH BID/OFFER**

(h) Relationship to anyone who is or was a registered lobbyist in the previous 2 years; spouse, father, mother, son, or daughter. Yes \_\_\_ No \_\_\_

(i) Compensated employment, currently or in the previous 3 years, by any registered election or reelection committee registered with the Secretary of State or any county clerk of the State of Illinois, or any political action committee registered with either the Secretary of State or the Federal Board of Elections. Yes \_\_\_ No \_\_\_

(j) Relationship to anyone; spouse, father, mother, son, or daughter; who was a compensated employee in the last 2 years by any registered election or re-election committee registered with the Secretary of State or any county clerk of the State of Illinois, or any political action committee registered with either the Secretary of State or the Federal Board of Elections. Yes \_\_\_ No \_\_\_

**APPLICABLE STATEMENT**

**This Disclosure Form A is submitted on behalf of the INDIVIDUAL named on previous page.**

Completed by:  \_\_\_\_\_ Date \_\_\_\_\_  
Signature of Individual or Authorized Representative

**NOT APPLICABLE STATEMENT**

**I have determined that no individuals associated with this organization meet the criteria that would require the completion of this Form A.**

**This Disclosure Form A is submitted on behalf of the CONTRACTOR listed on the previous page.**

\_\_\_\_\_ Date \_\_\_\_\_  
Signature of Authorized Representative

RETURN WITH BID/OFFER

ILLINOIS DEPARTMENT  
OF TRANSPORTATION

Form B  
Other Contracts &  
Procurement Related Information  
Disclosure

Contractor Name		
Legal Address		
City, State, Zip		
Telephone Number	Email Address	Fax Number (if available)

Disclosure of the information contained in this Form is required by the Section 50-35 of the Illinois Procurement Act (30 ILCS 500). This information shall become part of the publicly available contract file. This Form B must be completed for bids in excess of \$10,000, and for all open-ended contracts.

**DISCLOSURE OF OTHER CONTRACTS AND PROCUREMENT RELATED INFORMATION**

**1. Identifying Other Contracts & Procurement Related Information.** The BIDDER shall identify whether it has any pending contracts (including leases), bids, proposals, or other ongoing procurement relationship with any other State of Illinois agency: Yes \_\_\_ No \_\_\_

If **“No” is checked**, the bidder only needs to complete the signature box on the bottom of this page.

**2. If “Yes” is checked.** Identify each such relationship by showing State of Illinois agency name and other descriptive information such as bid or project number (attach additional pages as necessary). SEE DISCLOSURE FORM INSTRUCTIONS:

**THE FOLLOWING STATEMENT MUST BE CHECKED**

<input type="checkbox"/>	_____	_____
	Signature of Authorized Representative	Date

## **RETURN WITH BID**

### **SPECIAL NOTICE TO CONTRACTORS**

The following requirements of the Illinois Department of Human Rights' Rules and Regulations are applicable to bidders on all construction contracts advertised by the Illinois Department of Transportation:

#### **CONSTRUCTION EMPLOYEE UTILIZATION PROJECTION**

- (a) All bidders on construction contracts shall complete and submit, along with and as part of their bids, a Bidder's Employee Utilization Form (Form BC-1256) setting forth a projection and breakdown of the total workforce intended to be hired and/or allocated to such contract work by the bidder including a projection of minority and female employee utilization in all job classifications on the contract project.
- (b) The Department of Transportation shall review the Employee Utilization Form, and workforce projections contained therein, of the contract awardee to determine if such projections reflect an underutilization of minority persons and/or women in any job classification in accordance with the Equal Employment Opportunity Clause and Section 7.2 of the Illinois Department of Human Rights' Rules and Regulations for Public Contracts adopted as amended on September 17, 1980. If it is determined that the contract awardee's projections reflect an underutilization of minority persons and/or women in any job classification, it shall be advised in writing of the manner in which it is underutilizing and such awardee shall be considered to be in breach of the contract unless, prior to commencement of work on the contract project, it submits revised satisfactory projections or an acceptable written affirmative action plan to correct such underutilization including a specific timetable geared to the completion stages of the contract.
- (c) The Department of Transportation shall provide to the Department of Human Rights a copy of the contract awardee's Employee Utilization Form, a copy of any required written affirmative action plan, and any written correspondence related thereto. The Department of Human Rights may review and revise any action taken by the Department of Transportation with respect to these requirements.





**RETURN WITH BID**

**Contract No. 76C64  
ST CLAIR County  
Section DIST 8 ITS 2010-3  
Project ACHSIP-064-1(124)001  
Route FAI 64  
District 8 Construction Funds**

**PART II. WORKFORCE PROJECTION - continued**

- B. Included in "Total Employees" under Table A is the total number of **new hires** that would be employed in the event the undersigned bidder is awarded this contract.

The undersigned bidder projects that: (number) \_\_\_\_\_ new hires would be recruited from the area in which the contract project is located; and/or (number) \_\_\_\_\_ new hires would be recruited from the area in which the bidder's principal office or base of operation is located.

- C. Included in "Total Employees" under Table A is a projection of numbers of persons to be employed directly by the undersigned bidder as well as a projection of numbers of persons to be employed by subcontractors.

The undersigned bidder estimates that (number) \_\_\_\_\_ persons will be directly employed by the prime contractor and that (number) \_\_\_\_\_ persons will be employed by subcontractors.

**PART III. AFFIRMATIVE ACTION PLAN**

- A. The undersigned bidder understands and agrees that in the event the foregoing minority and female employee utilization projection included under **PART II** is determined to be an underutilization of minority persons or women in any job category, and in the event that the undersigned bidder is awarded this contract, he/she will, prior to commencement of work, develop and submit a written Affirmative Action Plan including a specific timetable (geared to the completion stages of the contract) whereby deficiencies in minority and/or female employee utilization are corrected. Such Affirmative Action Plan will be subject to approval by the contracting agency and the **Department of Human Rights**.
- B. The undersigned bidder understands and agrees that the minority and female employee utilization projection submitted herein, and the goals and timetable included under an Affirmative Action Plan if required, are deemed to be part of the contract specifications.

Company \_\_\_\_\_ Telephone Number \_\_\_\_\_

Address \_\_\_\_\_

**NOTICE REGARDING SIGNATURE**

The Bidder's signature on the Proposal Signature Sheet will constitute the signing of this form. The following signature block needs to be completed only if revisions are required.

Signature:  \_\_\_\_\_ Title: \_\_\_\_\_ Date: \_\_\_\_\_

- Instructions: All tables must include subcontractor personnel in addition to prime contractor personnel.
- Table A - Include both the number of employees that would be hired to perform the contract work and the total number currently employed (Table B) that will be allocated to contract work, and include all apprentices and on-the-job trainees. The "Total Employees" column should include all employees including all minorities, apprentices and on-the-job trainees to be employed on the contract work.
- Table B - Include all employees currently employed that will be allocated to the contract work including any apprentices and on-the-job trainees currently employed.
- Table C - Indicate the racial breakdown of the total apprentices and on-the-job trainees shown in Table A.

## RETURN WITH BID

### ADDITIONAL FEDERAL REQUIREMENTS

In addition to the Required Contract Provisions for Federal-Aid Construction Contracts (FHWA 1273), all bidders make the following certifications.

- A. By the execution of this proposal, the signing bidder certifies that the bidding entity has not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action, in restraint of free competitive bidding in connection with the submitted bid. This statement made by the undersigned bidder is true and correct under penalty of perjury under the laws of the United States.
- B. CERTIFICATION, EQUAL EMPLOYMENT OPPORTUNITY:
1. Have you participated in any previous contracts or subcontracts subject to the equal opportunity clause. YES \_\_\_\_\_ NO \_\_\_\_\_
  2. If answer to #1 is yes, have you filed with the Joint Reporting Committee, the Director of OFCC, any Federal agency, or the former President's Committee on Equal Employment Opportunity, all reports due under the applicable filing requirements of those organizations?  
YES \_\_\_\_\_ NO \_\_\_\_\_

**RETURN WITH BID**

**Contract No. 76C64  
ST CLAIR County  
Section DIST 8 ITS 2010-3  
Project ACHSIP-064-1(124)001  
Route FAI 64  
District 8 Construction Funds**

PROPOSAL SIGNATURE SHEET

The undersigned bidder hereby makes and submits this bid on the subject Proposal, thereby assuring the Department that all requirements of the Invitation for Bids and rules of the Department have been met, that there is no misunderstanding of the requirements of paragraph 3 of this Proposal, and that the contract will be executed in accordance with the rules of the Department if an award is made on this bid.

(IF AN INDIVIDUAL) Firm Name \_\_\_\_\_  
Signature of Owner \_\_\_\_\_  
Business Address \_\_\_\_\_  
\_\_\_\_\_

---

(IF A CO-PARTNERSHIP) Firm Name \_\_\_\_\_  
By \_\_\_\_\_  
Business Address \_\_\_\_\_  
Name and Address of All Members of the Firm: \_\_\_\_\_  
\_\_\_\_\_

---

(IF A CORPORATION) Corporate Name \_\_\_\_\_  
By \_\_\_\_\_  
Signature of Authorized Representative \_\_\_\_\_  
Typed or printed name and title of Authorized Representative \_\_\_\_\_

(IF A JOINT VENTURE, USE THIS SECTION FOR THE MANAGING PARTY AND THE SECOND PARTY SHOULD SIGN BELOW) Attest \_\_\_\_\_  
Signature \_\_\_\_\_  
Business Address \_\_\_\_\_

---

(IF A JOINT VENTURE) Corporate Name \_\_\_\_\_  
By \_\_\_\_\_  
Signature of Authorized Representative \_\_\_\_\_  
Typed or printed name and title of Authorized Representative \_\_\_\_\_  
Attest \_\_\_\_\_  
Signature \_\_\_\_\_  
Business Address \_\_\_\_\_

If more than two parties are in the joint venture, please attach an additional signature sheet.



Return with Bid

Division of Highways
Proposal Bid Bond
(Effective November 1, 1992)

Item No. \_\_\_\_\_

Letting Date \_\_\_\_\_

KNOW ALL MEN BY THESE PRESENTS, That We \_\_\_\_\_

as PRINCIPAL, and \_\_\_\_\_

\_\_\_\_\_ as SURETY, are held jointly, severally and firmly bound unto the STATE OF ILLINOIS in the penal sum of 5 percent of the total bid price, or for the amount specified in Article 102.09 of the "Standard Specifications for Road and Bridge Construction" in effect on the date of invitation for bids, whichever is the lesser sum, well and truly to be paid unto said STATE OF ILLINOIS, for the payment of which we bind ourselves, our heirs, executors, administrators, successors and assigns.

THE CONDITION OF THE FOREGOING OBLIGATION IS SUCH, that whereas, the PRINCIPAL has submitted a bid proposal to the STATE OF ILLINOIS, acting through the Department of Transportation, for the improvement designated by the Transportation Bulletin Item Number and Letting Date indicated above.

NOW, THEREFORE, if the Department shall accept the bid proposal of the PRINCIPAL; and if the PRINCIPAL shall, within the time and as specified in the bidding and contract documents, submit a DBE Utilization Plan that is accepted and approved by the Department; and if, after award by the Department, the PRINCIPAL shall enter into a contract in accordance with the terms of the bidding and contract documents including evidence of the required insurance coverages and providing such bond as specified with good and sufficient surety for the faithful performance of such contract and for the prompt payment of labor and material furnished in the prosecution thereof; or if, in the event of the failure of the PRINCIPAL to make the required DBE submission or to enter into such contract and to give the specified bond, the PRINCIPAL pays to the Department the difference not to exceed the penalty hereof between the amount specified in the bid proposal and such larger amount for which the Department may contract with another party to perform the work covered by said bid proposal, then this obligation shall be null and void, otherwise, it shall remain in full force and effect.

IN THE EVENT the Department determines the PRINCIPAL has failed to comply with any requirement as set forth in the preceding paragraph, then Surety shall pay the penal sum to the Department within fifteen (15) days of written demand therefor. If Surety does not make full payment within such period of time, the Department may bring an action to collect the amount owed. Surety is liable to the Department for all its expenses, including attorney's fees, incurred in any litigation in which it prevails either in whole or in part.

In TESTIMONY WHEREOF, the said PRINCIPAL and the said SURETY have caused this instrument to be signed by

their respective officers this \_\_\_\_\_ day of \_\_\_\_\_ A.D., \_\_\_\_\_ .

PRINCIPAL

SURETY

\_\_\_\_\_  
(Company Name)

\_\_\_\_\_  
(Company Name)

By \_\_\_\_\_  
(Signature & Title)

By: \_\_\_\_\_  
(Signature of Attorney-in-Fact)

Notary Certification for Principal and Surety

STATE OF ILLINOIS,  
County of \_\_\_\_\_

I, \_\_\_\_\_, a Notary Public in and for said County, do hereby certify that

\_\_\_\_\_ and \_\_\_\_\_  
(Insert names of individuals signing on behalf of PRINCIPAL & SURETY)

who are each personally known to me to be the same persons whose names are subscribed to the foregoing instrument on behalf of PRINCIPAL and SURETY, appeared before me this day in person and acknowledged respectively, that they signed and delivered said instrument as their free and voluntary act for the uses and purposes therein set forth.

Given under my hand and notarial seal this \_\_\_\_\_ day of \_\_\_\_\_ A.D. \_\_\_\_\_

My commission expires \_\_\_\_\_

Notary Public

In lieu of completing the above section of the Proposal Bid Form, the Principal may file an Electronic Bid Bond. By signing the proposal and marking the check box next to the Signature and Title line below, the Principal is ensuring the identified electronic bid bond has been executed and the Principal and Surety are firmly bound unto the State of Illinois under the conditions of the bid bond as shown above.

Electronic Bid Bond ID# \_\_\_\_\_

Company / Bidder Name \_\_\_\_\_



Signature and Title \_\_\_\_\_

# PROPOSAL ENVELOPE



# PROPOSALS

for construction work advertised for bids by the  
Illinois Department of Transportation

Item No.	Item No.	Item No.

Submitted By:

Name:
Address:
Phone No.

Bidders should use an IDOT proposal envelope or affix this form to the front of a 10" x 13" envelope for the submittal of bids. If proposals are mailed, they should be enclosed in a second or outer envelope addressed to:

Engineer of Design and Environment - Room 326  
Illinois Department of Transportation  
2300 South Dirksen Parkway  
Springfield, Illinois 62764

## **NOTICE**

**Individual bids, including Bid Bond and/or supplemental information if required, should be securely stapled.**

# CONTRACTOR OFFICE COPY OF CONTRACT SPECIFICATIONS

## NOTICE

None of the following material needs to be returned with the bid package unless the special provisions require documentation and/or other information to be submitted.

**Contract No. 76C64  
ST CLAIR County  
Section DIST 8 ITS 2010-3  
Project ACHSIP-064-1(124)001  
Route FAI 64  
District 8 Construction Funds**



**Illinois Department of Transportation**



## NOTICE TO BIDDERS

- 1. TIME AND PLACE OF OPENING BIDS.** Sealed proposals for the improvement described herein will be received by the Department of Transportation at the Harry R. Hanley Building, 2300 South Dirksen Parkway, in Springfield, Illinois until 10:00 o'clock a.m., January 15, 2010. All bids will be gathered, sorted, publicly opened and read in the auditorium at the Department of Transportation's Harry R. Hanley Building shortly after the 10:00 a.m. cut off time.
- 2. DESCRIPTION OF WORK.** The proposed improvement is identified and advertised for bids in the Invitation for Bids as:

**Contract No. 76C64  
ST CLAIR County  
Section DIST 8 ITS 2010-3  
Project ACHSIP-064-1(124)001  
Route FAI 64  
District 8 Construction Funds**

**ITS-Dynamic Message Board-HSIP at westbound I-64 northeast of 37th Street Bridge in East St. Louis.**

- 3. INSTRUCTIONS TO BIDDERS.** (a) This Notice, the invitation for bids, proposal and letter of award shall, together with all other documents in accordance with Article 101.09 of the Standard Specifications for Road and Bridge Construction, become part of the contract. Bidders are cautioned to read and examine carefully all documents, to make all required inspections, and to inquire or seek explanation of the same prior to submission of a bid.  
  
(b) State law, and, if the work is to be paid wholly or in part with Federal-aid funds, Federal law requires the bidder to make various certifications as a part of the proposal and contract. By execution and submission of the proposal, the bidder makes the certification contained therein. A false or fraudulent certification shall, in addition to all other remedies provided by law, be a breach of contract and may result in termination of the contract.
- 4. AWARD CRITERIA AND REJECTION OF BIDS.** This contract will be awarded to the lowest responsive and responsible bidder considering conformity with the terms and conditions established by the Department in the rules, Invitation for Bids and contract documents. The issuance of plans and proposal forms for bidding based upon a prequalification rating shall not be the sole determinant of responsibility. The Department reserves the right to determine responsibility at the time of award, to reject any or all proposals, to readvertise the proposed improvement, and to waive technicalities.

By Order of the  
Illinois Department of Transportation

Gary Hannig,  
Acting Secretary

INDEX  
 FOR  
 SUPPLEMENTAL SPECIFICATIONS  
 AND RECURRING SPECIAL PROVISIONS

Adopted January 1, 2010

This index contains a listing of SUPPLEMENTAL SPECIFICATIONS and frequently used RECURRING SPECIAL PROVISIONS.

ERRATA            Standard Specifications for Road and Bridge Construction (Adopted 1-1-07) (Revised 1-1-10)

SUPPLEMENTAL SPECIFICATIONS

<u>Std. Spec. Sec.</u>	<u>Page No.</u>
201 Clearing, Tree Removal and Protection .....	1
205 Embankment .....	2
251 Mulch .....	3
253 Planting Woody Plants .....	4
280 Temporary Erosion Control .....	6
406 Hot-Mix Asphalt Binder and Surface Course .....	7
443 Reflective Crack Control Treatment .....	12
502 Excavation for Structures .....	15
503 Concrete Structures .....	16
504 Precast Concrete Structures .....	17
505 Steel Structures .....	18
540 Box Culverts .....	19
581 Waterproofing Membrane System .....	20
630 Steel Plate Beam Guardrail .....	21
633 Removing and Reerecting Guardrail and Terminals .....	22
637 Concrete Barrier .....	23
669 Removal and Disposal of Regulated Substances .....	24
672 Sealing Abandoned Water Wells .....	25
701 Work Zone Traffic Control and Protection .....	26
720 Sign Panels and Appurtenances .....	27
721 Sign Panel Overlay .....	28
722 Demountable Sign Legend Characters and Arrows .....	29
726 Mile Post Marker Assembly .....	30
733 Overhead Sign Structures .....	31
783 Pavement Marking and Marker Removal .....	32
801 Electrical Requirements .....	33
805 Electrical Service Installation – Traffic Signals .....	34
836 Pole Foundation .....	35
838 Breakaway Devices .....	36
862 Uninterruptable Power Supply .....	37
873 Electric Cable .....	39
878 Traffic Signal Concrete Foundation .....	41
1003 Fine Aggregates .....	42
1004 Coarse Aggregates .....	43
1005 Stone and Broken Concrete .....	44
1006 Metals .....	45
1008 Structural Steel Coatings .....	47
1010 Finely Divided Materials .....	48
1020 Portland Cement Concrete .....	49
1022 Concrete Curing Materials .....	58
1024 Nonshrink Grout .....	59
1030 Hot-Mix Asphalt .....	60
1032 Bituminous Materials .....	65



1042 Precast Concrete Products ..... 68  
1062 Reflective Crack Control System ..... 70  
1069 Pole and Tower ..... 72  
1074 Control Equipment ..... 75  
1076 Wire and Cable ..... 80  
1080 Fabric Materials ..... 81  
1081 Materials for Planting ..... 82  
1083 Elastomeric Bearings ..... 84  
1090 Sign Base ..... 85  
1091 Sign Face ..... 87  
1092 Sign Legend and Supplemental Panels ..... 95  
1093 Sign Supports ..... 96  
1094 Overhead Sign Structures ..... 98  
1095 Pavement Markings ..... 104  
1101 General Equipment ..... 106  
1102 Hot-Mix Asphalt Equipment ..... 107  
1103 Portland Cement Concrete Equipment ..... 109  
1106 Work Zone Traffic Control Devices ..... 110

RECURRING SPECIAL PROVISIONS

The following RECURRING SPECIAL PROVISIONS indicated by an "X" are applicable to this contract and are included by reference:

<u>CHECK SHEET #</u>	<u>PAGE NO.</u>
1 X Additional State Requirements For Federal-Aid Construction Contracts (Eff. 2-1-69) (Rev. 1-1-10) .....	111
2 X Subletting of Contracts (Federal-Aid Contracts) (Eff. 1-1-88) (Rev. 5-1-93) .....	114
3 X EEO (Eff. 7-21-78) (Rev. 11-18-80) .....	115
4 Specific Equal Employment Opportunity Responsibilities Non Federal-Aid Contracts (Eff. 3-20-69) (Rev. 1-1-94) .....	125
5 Required Provisions - State Contracts (Eff. 4-1-65) (Rev. 1-1-10) .....	130
6 Reserved .....	135
7 Reserved .....	136
8 Haul Road Stream Crossings, Other Temporary Stream Crossings, and In-Stream Work Pads (Eff. 1-2-92) (Rev. 1-1-98) .....	137
9 Construction Layout Stakes Except for Bridges (Eff. 1-1-99) (Rev. 1-1-07) .....	138
10 Construction Layout Stakes (Eff. 5-1-93) (Rev. 1-1-07) .....	141
11 Use of Geotextile Fabric for Railroad Crossing (Eff. 1-1-95) (Rev. 1-1-07) .....	144
12 Subsealing of Concrete Pavements (Eff. 11-1-84) (Rev. 1-1-07) .....	146
13 Hot-Mix Asphalt Surface Correction (Eff. 11-1-87) (Rev. 1-1-09) .....	150
14 Pavement and Shoulder Resurfacing (Eff. 2-1-00) (Rev. 1-1-09) .....	152
15 PCC Partial Depth Hot-Mix Asphalt Patching (Eff. 1-1-98) (Rev. 1-1-07) .....	153
16 Patching with Hot-Mix Asphalt Overlay Removal (Eff. 10-1-95) (Rev. 1-1-07) .....	155
17 Polymer Concrete (Eff. 8-1-95) (Rev. 1-1-08) .....	156
18 PVC Pipeliner (Eff. 4-1-04) (Rev. 1-1-07) .....	158
19 Pipe Underdrains (Eff. 9-9-87) (Rev. 1-1-07) .....	159
20 Guardrail and Barrier Wall Delineation (Eff. 12-15-93) (Rev. 1-1-97) .....	160
21 Bicycle Racks (Eff. 4-1-94) (Rev. 1-1-07) .....	164
22 Temporary Modular Glare Screen System (Eff. 1-1-00) (Rev. 1-1-07) .....	166
23 Temporary Portable Bridge Traffic Signals (Eff. 8-1-03) (Rev. 1-1-07) .....	168
24 Work Zone Public Information Signs (Eff. 9-1-02) (Rev. 1-1-07) .....	170
25 Night Time Inspection of Roadway Lighting (Eff. 5-1-96) .....	171
26 English Substitution of Metric Bolts (Eff. 7-1-96) .....	172
27 English Substitution of Metric Reinforcement Bars (Eff. 4-1-96) (Rev. 1-1-03) .....	173
28 Calcium Chloride Accelerator for Portland Cement Concrete (Eff. 1-1-01) .....	174
29 Reserved .....	175
30 Quality Control of Concrete Mixtures at the Plant (Eff. 8-1-00) (Rev. 1-1-09) .....	176
31 Quality Control/Quality Assurance of Concrete Mixtures (Eff. 4-1-92) (Rev. 1-1-09) .....	184
32 Asbestos Bearing Pad Removal (Eff. 11-1-03) .....	196
33 Asbestos Hot-Mix Asphalt Surface Removal (Eff. 6-1-89) (Rev. 1-1-09) .....	197

**TABLE OF CONTENTS**

LOCATION OF PROJECT ..... 1

DESCRIPTION OF PROJECT ..... 1

MONTHLY LABOR SUMMARY AND ACTIVITY REPORTING SYSTEM ..... 1

OFFICE COPY MACHINE ..... 4

TELEPHONE ANSWERING MACHINE ..... 4

TRAFFIC CONTROL PLAN ..... 5

CONSTRUCTION AND MAINTENANCE SIGN SUPPORTS ..... 5

TEMPORARY CLOSURE OF ALL LANES..... 5

TRAFFIC CONTROL AND PROTECTION, STANDARD 701406 (SPECIAL) ..... 6

FAILURE TO OPEN TRAFFIC LANES TO TRAFFIC FOR PEAK PERIODS..... 6

COOPERATION BETWEEN CONTRACTORS..... 7

STATUS OF UTILITIES TO BE ADJUSTED ..... 7

MAINTENANCE OF EXISTING ELECTRICAL DEVICES..... 7

CONCRETE FOUNDATION, TYPE D (SPECIAL) ..... 8

CONTROLLER CABINET TYPE III, SPECIAL ..... 8

FURNISH AND INSTALL TRUSS DAMPER ..... 9

HANDHOLE ..... 10

TRUSS MOUNTED LED DYNAMIC MESSAGE SIGN ..... 10

CELLULAR MODEM..... 51

CONDUIT ATTACHED TO STRUCTURE, 3” DIA., ALUMINUM ..... 52

CONDUIT IN TRENCH 4” DIA., PVC TYPE C ..... 52

APPROVAL OF PROPOSED BORROW AREAS, USE AREAS, AND/OR WASTE AREAS INSIDE ILLINOIS STATE BORDERS (BDE) ..... 53

CEMENT (BDE) ..... 53

CONCRETE ADMIXTURES (BDE) ..... 55

CONSTRUCTION AIR QUALITY - DIESEL VEHICLE EMISSIONS CONTROL (BDE) ..... 58

CONSTRUCTION AIR QUALITY - IDLING RESTRICTIONS (BDE)..... 59

DISADVANTAGED BUSINESS ENTERPRISE PARTICIPATION (BDE) ..... 60

ENGINEER’S FIELD OFFICE TYPE A (BDE) ..... 68

EQUIPMENT RENTAL RATES (BDE)..... 70

LIQUIDATED DAMAGES (BDE)..... 71

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM / EROSION AND SEDIMENT CONTROL DEFICIENCY DEDUCTION (BDE) ..... 71

PAYMENTS TO SUBCONTRACTORS (BDE) ..... 72

PERSONAL PROTECTIVE EQUIPMENT (BDE) ..... 73

PUBLIC CONVENIENCE AND SAFETY (BDE) ..... 74

REFLECTIVE SHEETING ON CHANNELIZING DEVICES (BDE) ..... 74

SUBCONTRACTOR MOBILIZATION PAYMENTS (BDE) ..... 75  
TRUCK MOUNTED/TRAILER MOUNTED ATTENUATORS (BDE) ..... 75  
WORKING DAYS (BDE) ..... 76  
STEEL COST ADJUSTMENT (BDE) (RETURN FORM WITH BID) ..... 76

## STATE OF ILLINOIS

---

### SPECIAL PROVISIONS

The following Special Provisions supplement the "Standard Specifications for Road and Bridge Construction," adopted January 1, 2007, the latest edition of the "Manual on Uniform Traffic Control Devices for Streets and Highways," and the "Manual of Test Procedures for Materials" in effect on the date of invitation for bids, and the Supplemental Specifications and Recurring Special Provisions indicated on the Check Sheet included herein which apply to and govern the construction of FAI Route 64 (I-64); Project ACHSIP-064-1 (124) 001, Section Dist 8 ITS 2010-3; St. Clair County; Contract No. 76C64 and in case of conflict with any part or parts of said Specifications, the said Special Provisions shall take precedence and shall govern.

#### LOCATION OF PROJECT

The project location is WB I-64 north east of 37<sup>th</sup> Street bridge at Station 161+00.

#### DESCRIPTION OF PROJECT

The project description is the installation of:

1. a truss mounted L.E.D. dynamic message sign and
2. an overhead structure.

#### MONTHLY LABOR SUMMARY AND ACTIVITY REPORTING SYSTEM

Effective: 1-1-1995

Revised June 2001

##### I. Monthly Labor Summary Report, Form SBE 148

The prime contractor and each first and second tier sub-contractor, (hereinafter referred to as "subcontractor") shall submit a certified Monthly Labor Summary Report directly to the District Engineer.

This report is in lieu of submittal of the Monthly Workforce Analysis Report, Form SBE 956.

This report must be received in District Eight no later than the tenth day of the next month.

This Report shall be submitted by the prime contractor and each subcontractor, for each consecutive month, from the start, to the completion of their work on the contract.

The data source for this Report will be a summation of all personnel and hours worked on each subject contract for the month based on weekly payrolls for that month.

The Monthly Labor Summary Report is required to be submitted in one of the following formats:

- a.) For contractors having IDOT contracts valued in the aggregate at \$250,000 or less, the report may be typed or clearly handwritten using Form SBE 148 for submittal to the District Engineer for District Eight.
- b.) For contractors having IDOT contracts valued in the aggregate at more than \$250,000, the report must be submitted in a specific "Fixed Length Comma Delimited ASCII Text File Format". The subject file format is detailed on the next page. Submittal of this file may be by 3.5 inch disk, modem, or by e-mail.

II. Monthly Contract Activity Report, Form SBE 248

The prime contractor and each subcontractor shall submit a monthly report directly to the District Engineer reflecting their contract activity on all Illinois Department of Transportation contracts they have in force in District Eight.

This report shall be submitted for each consecutive month, from the start, to the completion of all contracts in District Eight.

The report must be received in the District Office no later than the tenth day of the next month.

Monthly Labor Summary and Activity Reporting System Codes and Formats

Indicated below for your reference are the Employee Codes and File Formats required for this system.

I.) Monthly Labor Summary Report, Form SBE 148

The following employee codes are to be used to identify each individual on the Summary Report:

1. **Gender:** M - Male F - Female
2. **Ethnic Group:** 1 - White 2 - Black 3 - Hispanic  
4 - American Indian/Alaskan Native 5 - Asian/Pacific Islander
3. **Work Classification:** OF - Official SU - Supervisor FO - Foremen  
CL - Clerical CA - Carpenter EO - Operator ME - Mechanic  
TD - Truck Driver IW - Ironworker PA - Painter OT - Other  
EL - Electrician PP - Pipefitter TE - Technical LA - Laborer  
CM - Cement Mason
4. **Employee Status:** O - Owner Operator J - Journeyman  
C - Company A - Apprentice T - Trainee

Specific "Fixed Length Comma Delimited ASCII File Format"

Order	Field Name	Type	Size
1	Contractor Number	A	4
2	Contractor Reference Number	A	6
3	Contract Number	A	5
4	Period (07/28/2000)	D	10
5	SSN (111-11-1111)	A	11
6	Name	A	40
7	Gender	A	1
8	Ethnic Group	A	1
9	Work Classification	A	1
10	Employee Status	A	1
11	Total Hours (000060.00)	N	10

File Name Conventions: (Contractor Number + Report Month/Year).Txt  
 i.e. 20001298.Txt

II.) Monthly Contract Activity Report, Form SBE 248

The following activity codes are to be used to identify the contractor's contract status each month on the Monthly Activity Report, Form SBE 248:

- A. Contract Status:      1 - Not Started      2 - Active      3 - No Work  
                                  4 - Suspended      5 - Complete

Failure to comply with this special provision may result in the withholding of payments to the contractor, and/or cancellation, termination, or suspension of the contract in whole or part.

Compliance with this Special Provision shall be considered incidental to the cost of the contract and no additional compensation will be allowed for any costs incurred.

All prime and subcontractors having contracts in the aggregate exceeding \$250,000 must provide a "Fixed Length Comma Delimited ASCII File" for approval prior to the start of construction.

This Special Provision must be included in each subcontract agreement.

The Department of Transportation is requesting disclosure of information necessary to accomplish the statutory purpose as outlined under 23CFR part 230 and 41CFR part 60.4 and the Illinois Human Rights Act. Disclosure of this information is REQUIRED. Failure to comply with this special provision may result in the withholding of payments to the contractor, and/or cancellation, termination, or suspension of the contract in whole or part.

Compliance with this Special Provision shall be considered incidental to the cost of the contract and no additional compensation will be allowed for any costs incurred.

This Special Provision must be included in each subcontract agreement.

**OFFICE COPY MACHINE**

*Effective: January 1, 1987*

*Revised: November 1, 2006*

The copier specified in Article 670.02 shall meet the following specifications:

- (1) Edge-to-edge copying.
- (2) Up to 11 in x 17 in (275 mm x 425 mm) size for copy-size capabilities.
- (3) A detachable platen cover in order to copy portions of large-bound documents.
- (4) A cabinet stand for the copier.

**TELEPHONE ANSWERING MACHINE**

*Effective: January 11, 1990*

*Revised: November 1, 2006*

The telephone answering machine specified in Article 670.02 shall meet the following minimum specifications:

- (1) Time/Day Indication - A computerized voice records the date and time that each message is received.
- (2) Beeperless Remote - Any remote touch-tone phone can be used to review all messages by the use of an access code.
- (3) Digital System - Pre-recorded and received messages are managed on separate cassettes.
- (4) Conversation Record - The operator can record any phone call.
- (5) Remote Turn-On - Any remote touch-tone phone can be used to turn on the answering machine by the use of an access code.
- (6) Full Message - The Caller is advised if the memory is insufficient to record the call.
- (7) Battery Back-Up - The settings and messages are protected from power failures.
- (8) Two-Line Capacity - Projects that have a second phone line through the provision of a 670.05 Engineer's Field Laboratory shall provide a single phone answering machine that services both lines.

Prior to the purchase of this item, the Contractor shall submit specifications for the proposed machine to the Engineer for his approval.



**TRAFFIC CONTROL PLAN**

*Effective: July 12, 1993*

*Revised: May 12, 1997*

Traffic control shall be in accordance with the applicable sections of the "Standard Specifications for Road and Bridge Construction", the applicable guidelines contained in the "National Manual on Uniform Traffic Control Devices for Streets and Highways", Illinois Supplement to the National Manual of Uniform Traffic Control Devices, these Special Provisions, and any special details and Highway Standards contained herein and in the plans.

Special attention is called to Articles 107.09 and 107.14 of the "Standard Specifications for Road and Bridge Construction" and the following Highway Standards relating to traffic control:

701001 701006 701101 701106 701400 701406 701446 701901

In addition, the following Special Provision(s) will also govern traffic control for this project:

- CONSTRUCTION AND MAINTENANCE SIGN SUPPORTS
- PENALTY DURING PEAK HOURS
- TEMPORARY CLOSURE OF ALL LANES
- TEMPORARY CLOSURE OF LANES
- TRAFFIC CONTROL AND PROTECTION, STANDARD 701406 (SPECIAL)
- PORTABLE CHANGEABLE MESSAGE SIGN
- FAILURE TO OPEN TRAFFIC LANES TO TRAFFIC FOR PEAK PERIODS
- PERSONAL PROTECTIVE EQUIPMENT (BDE)
- PUBLIC CONVENIENCE AND SAFETY (BDE)
- TRUCK MOUNTED/TRAILER MOUNTED ATTENUATORS (BDE)
- REFLECTIVE SHEETING ON CHANNELIZING DEVICES (BDE)

**CONSTRUCTION AND MAINTENANCE SIGN SUPPORTS**

*Effective: April 21, 1981*

*Revised: November 1, 2006*

This work shall be done according to Section 1106 of the Standard Specifications and Highway Standard 701901 except as herein modified.

All construction signs mounted on permanent support for use in temporary traffic control having an area of 10 square feet (1 square meter) or more shall be mounted on two 4 in x 4 in (100 mm x 100 mm) or two 4 in x 6 in (100 mm x 150 mm) wood posts.

Type A metal post (two for each sign) conforming to Article 1006.29 of the Standard Specifications may be used in lieu of wood posts. Type A metal posts used for these signs may be unfinished.

This work shall not be paid for separately; but shall be considered included in the cost of the traffic control items in this contract.

**TEMPORARY CLOSURE OF ALL LANES**

The Contractor will be permitted to temporarily close all lanes to traffic on WB I-64 provided the following traffic control requirements are met:

1. Acquire 2 weeks prior approval from the Resident Engineer and use of the Department's specified Changeable Message Sign's special messages.
2. Work will be permitted during weekends (Friday-6:00 p.m. to Monday-6:00.a.m.) only, limited to periods less than 15 minutes, with an 1 hour interval or per the Engineer's directive before a subsequent closure.
3. Provide two (2) flaggers for the work site.

The Department will acquire the services of the Illinois State Police to facilitate the lane closures and re-openings.

### **TRAFFIC CONTROL AND PROTECTION, STANDARD 701406 (SPECIAL)**

A truck mounted attenuator (TMA) shall be required for crew protection during traffic control set up and removal.

The truck should have an actual weight of no less that 11,000 pounds and no greater than 26,000 pounds or as recommended by the TMA manufacturer. The truck should be positioned to allow a roll-ahead distance as follows (or as recommended by the TMA manufacturer):

Stationary operation – 100 ft.  
Moving operation – 160 ft.

The TMA shall also have a Type C (48" X 96" (min.)) arrow board attached

Note: When utilizing in a stationary work operation, the truck should be in neutral and the brakes engaged.

A Variable Message Sign board shall be placed in advance of closure of the lanes as directed by the Engineer.

The cost to pay for this requirement shall be included in the contract lump sum price for TRAFFIC CONTROL AND PROTECTION, STANDARD 701406 (SPECIAL).

### **FAILURE TO OPEN TRAFFIC LANES TO TRAFFIC FOR PEAK PERIODS**

During peak hours, 6:00 a.m. to 9:00 a.m., Monday – Friday, no WB lane closure will be permitted.

The Contractor is required to open the road to traffic at certain specified times described elsewhere in these Special Provisions. Should the Contractor fail to completely open and keep open the lanes to traffic, as described elsewhere in these Special Provisions, he shall be liable to the Department in the amount of \$1000.00 for each and every 15 minute interval or portion thereof, that a lane is blocked outside the allowable time limitations. No provisions of this clause shall be construed as a penalty but as liquidated and ascertained damages. Such damages may be deducted by the Department from any monies due the Contractor. These damages shall apply during the contract time and during any extensions of the contract time.

## **COOPERATION BETWEEN CONTRACTORS**

The Contractor for this contract is advised that other projects within or adjacent to the limits of this contract section may be under construction during construction operations for this contract. The Contractor for this section shall cooperate with the Contractor for the other projects in accordance with Article 105.08 of the Standard Specifications.

Projects that may be under construction while this contract is in force are as follows:

1. 76C47-FAI 64, Section 82-1-1HBR, St. Clair County, Pedestrian Overpass, Retaining Wall, Sidewalk and Lighting at I-64 and 14<sup>th</sup> Street
2. 76C48-FAI 64, Section 82-1T, St. Clair County, Storm Sewer Repair at I-64 from 9<sup>th</sup> Street to 18<sup>th</sup> Street
3. 76C38-FAU 9166/FAU 9180, Section 82-1-10N, TS, St. Clair County , Intersection Reconstruction , Resurfacing, and Removed Traffic Signals at St. Clair Avenue/Baugh Avenue from 16<sup>th</sup> Street to 20<sup>th</sup> Street and Roundabout at 18<sup>th</sup> Street and Baugh Avenue
4. FAI Route 64, Section 82-2VB-2, St. Clair County, Superstructure Replacement for the Structures Carrying I-64 over Metrolink, 0.79 miles east of Baugh Ave. in East St. Louis (SN 082-0162 and 082-0163).

## **STATUS OF UTILITIES TO BE ADJUSTED**

### **NO UTILITIES TO BE ADJUSTED**

The above represents the best information of the Department and is only included for the convenience of the bidder. The applicable provisions of Sections 102, 103, and Articles 105.07 and 107.20 of the Standard Specifications for Road and Bridge Construction shall apply.

If any utility adjustment or removal has not been completed when required by the Contractor's operation, the Contractor should notify the Engineer in writing. A request for an extension of time will be considered to the extent the Contractor's operations were affected.

## **MAINTENANCE OF EXISTING ELECTRICAL DEVICES**

*Effective: Unknown*

*Revised: November 1, 2006*

This work shall be performed according to the Articles 801.10 and 801.11, and as modified herein.

The existing electrical devices which lie within the construction limits of this project will continue to be the maintenance responsibility of the Illinois Department of Transportation. Electrical devices are defined to mean highway lighting installations, traffic signals, flashing beacons, sign truss illumination units, changeable message signs, ITS, motorist aid call boxes, dewatering pumps, speed monitoring devices, traffic volume count stations, wrong-way movement detectors, following-too-close monitors, ice/fog detectors or any such devices or facilities the Department may have to maintain.

Any damage or malfunctions of these devices, observed by the Contractor, shall be reported immediately to the Department.

If it is determined by the Engineer that the Contractor is responsible for damage of any type to above-mentioned existing electrical devices, including underground wiring, as a result of negligence or poor workmanship, the Contractor shall be responsible for the repair of these facilities. These repairs shall be accomplished by whatever method the Department deems necessary. In the event the repairs are not made by the Contractor, the Contractor shall be required to reimburse the Department for such repairs within 60 days of receiving written notification of said damage.

The Department will continue to maintain the existing electrical devices until such time as the Contractor removes these devices, if required by this Contract. Any new, rebuilt, or modernized equipment installed as a requirement of this Contract shall be the maintenance responsibility of the Contractor until such time as this equipment is final inspected and found to be installed in a satisfactory manner by the Department. Existing individual equipment not involved with the work of this Contract will continue to be the maintenance responsibility of the Department.

### **CONCRETE FOUNDATION, TYPE D (SPECIAL)**

This work shall consist of furnishing and installing a concrete foundation for the installation of a controller foundation per Standard 878001 and applicable portions of Section 878 of the Standard Specifications, except an additional apron for the rear controller cabinet door shall be required. The ground rod shall conform to the applicable portions of Article 1086.02 with the following additions:

1. The ground rod shall be  $\frac{3}{4}$ " X 12' long.
2. Four (4) ground rods shall be installed vertically in the concrete foundation and shall protrude 4" from the concrete foundation. Each of the four (4) ground rods shall be located inside of the controller cabinet and 3" diagonally from the cabinet corner.
3. A #6 AWG bare copper conductor shall be bonded to each rod with molded, sleeved, exothermic, N.E.C. approved field weld (Cadweld). One (1) of the rods and #6 AWG bare copper conductor shall be attached to the controller cabinet ground bus. The other unused ground conductors shall remain coiled along the bottom of the cabinet enclosure. The ground conductors shall be enough to reach ground bus. **PRESSURE CONNECTORS OR CLAMPS ARE NOT ACCEPTABLE.**

Anchor bolts, nuts, and washers are required this foundation.

This work shall be paid for at the contract unit price per foot of depth of CONCRETE FOUNDATION, TYPE D (SPECIAL), which price shall include all the work described in Article 878.05 of the Standard Specification.

### **CONTROLLER CABINET TYPE III, SPECIAL**

The cabinet shall be in accordance with the applicable portions of Section 863 of the Standard Specifications.

The TYPE III CABINET shall be a NEMA Type 3R (66"H X 24"W X 30"L) with (i) front and rear doors and (ii) four (4) shelves including one (1) for future use.

The cabinet shall have:

1. Two (2) Power panel surge protection (EDCO SHA-1250 or approved equal) (one (1) per phase)
2. One (1) Surge protection (Model ACP100 BWN3 or approved equal)
3. Two (2) GFCI receptacles
4. Four (4) circuit breakers (two (2) 15 Amp single pole, one (1) 15 Amp double pole and one (1) 20 Amp double pole main)
5. Single point ground
6. Heater lamp(s)
7. Fluorescent lamp(s)
8. Door locks & keys in accordance with the Article 1085.47(3)c (cabinet door shall be fitted with a number 2 Corbin lock)
9. Cabinet fan, thermostat and filtered vent
10. Uninterruptible power supply
11. Four shelves, one of which shall be a slide out, laptop computer work tray mounted on ball bearing glides
12. Environmentally hardened sign controller (paid for separately per the TRUSS MOUNTED CHANGEABLE MESSAGE SIGN" pay item)
13. RS-232 plug-in connection for laptop computer
14. RS-232 cable, 4 (minimum) foot long to connect the laptop computer to the sign controller
15. Cellular modem (paid for separately per the "CELLULAR MODEM" pay item)

Modifications to the panel and terminal facilities shall be made to the cabinet to meet the operating requirements of (i) the manufacturer of surveillance camera equipment, (ii) the field hardened controller equipment, and (iii) utility companies.

The cost of equipment housed inside the cabinet shall be included in the pay item for CLOSED CIRCUIT TELEVISION CAMERA SYSTEM and the pay items for the communications equipment (Wired Communication Data Converter, vehicle detectors, layer 2 switch, MPEG encoders, and fiber termination panel).

The cabinet shall be configured as similar to the existing modified cabinets as practical.

This work shall be paid for at the contract unit price each for CONTROLLER CABINET TYPE III, SPECIAL.

### **FURNISH AND INSTALL TRUSS DAMPER**

This work shall consist of furnishing and installing a truss damper on an aluminum overhead span sign structure. The damper shall be attached to the overhead sign structure as indicated on the attached details.

The damper design shall be similar to those shown in the plans. The Contractor shall submit shop drawings for the damper for approval prior to fabrication and before any materials are ordered.

This work will be paid for at the contract unit price each for FURNISH AND INSTALL TRUSS DAMPER which price shall include providing the shop drawings, fabricating the clamp, furnishing installing the damper complete with all necessary hardware.

## **HANDHOLE**

The handhole shall be constructed in accordance with Section 814 of the Standard Specifications, except Article 1088.05 of Article 814.02(a) will be deleted.

## **TRUSS MOUNTED LED DYNAMIC MESSAGE SIGN**

### **GENERAL REQUIREMENTS**

Equipment to be furnished at the dynamic message sign (DMS) field site shown in the plans shall include, but not be limited to the following:

LED DMS, pole-mounted local control box, all necessary electronics and communications hardware for a fully functional DMS, and required mounting hardware.

The sign shall be designed for a minimum life of 20 years.

The DMS shall be compatible with the Department's existing Gigabit Ethernet over single-mode fiber network. It shall communicate without error for all of the applicable National Transportation for Intelligent Transportation System Protocol (NTCIP) standards for DMS and, thus, be compliant with all applicable NTCIP standards for DMS. The DMS shall be compatible with the Department's existing Advanced Traffic Management System (ATMS) software and shall support all mandatory objects of all mandatory conformance groups of NTCIP for DMS. All costs associated with compatibility testing and coordination will not be paid for separate, and shall be included in the cost of the DMS.

### **LED DYNAMIC MESSAGE SIGN (DMS)**

The LED DMS shall enable the display of text, consisting of a string of alphanumeric and other characters. Each character shall be formed by a matrix of luminous pixels. The matrix of a standard character shall consist of 35 pixels over 5 columns and 7 rows. Each LED DMS shall be minimum 27 pixel high x 125 pixel wide, full matrix and capable of displaying three lines of text using a standard 5 wide x 7 high font size.

Each line shall be capable of displaying a minimum of 10 alphanumeric characters with 2 blank pixels spacing between each 5 x 7 character for maximum readability and a minimum of 14 alphanumeric characters with only one blank pixel between each character. All display elements and modules shall be solid state. No mechanical or electromechanical elements or shutters shall be used.

All characters, symbols, and digits shall be 18" nominal character size and shall be clearly visible and legible at a distance of 1100' within a minimum 30 degree cone of vision centered around the optical axis of the pixel.

The signs shall be capable of displaying the following:

- A static message
- A flashing message
- Alternating messages, either flashing or static

The changing from one message to another shall be instantaneous.

All field equipment shall remain fully functional over an ambient temperature range of -40° F to +149°F with relative humidity of up to 95%. All field equipment enclosures shall be designed to withstand the effects of sand, dust, and hose-directed water. All connections shall be watertight.

The size of the sign, along with other dimensions and configuration details of the sign covered by this specification, can be seen in Table 1.2 below:

TABLE 1.2: SPECIFIC SIGN DIMENSIONS / REQUIREMENTS	
Sign type:	Walk-in Access
Matrix type:	Full
Nominal character height:	18.0 inches
No. lines:	3
LED manufacturer/part number (if applicable):	Agilent(Avado) HLMP-EL30-STKDD or Agilent(Avado) HLMP-EL33
LED color/wavelength:	Amber / 592 nm
LED viewing angle:	30°
LED pixel brightness:	40 Cd @ 25mA
Display (H x W):	27 x 125 minimum (full matrix)
Display Module (H x W):	7 x 5
Power Service:	120/240 +12/-23 VAC, 60 Hz, single phase; 40 amps/leg (2 legs required)
Power consumption range:	3 – 18 Amps (@120VAC)
Maximum Width:	30 feet, 8 inches
Maximum Height:	8 feet, 6 inches
Maximum Depth:	37 inches
Approximate weight range:	4000 – 5200 lbs
Sign Controller Location:	Ground-mounted

## SUBMITTALS

The intent of this section is to summarize all the submittals required in the specifications. If a submittal is inadvertently omitted from this summary, but is included in another section of the specification, the DMS Manufacturer is still required to submit the information.

Submittal Description	Time Requirements	Department's Action
Experience	Include in Proposal	Review/Score
References	Include in Proposal	Review/Score
Factory Acceptance Test (FAT) procedures	After award and 60 days before test	Review/Approve or Reject
Factory Acceptance Test dates	After award and 30 days before test	Determine if a Rep. will attend
Factory Acceptance Test results	14 days after FAT	Review/Approve or Reject
Stand Alone Test (SAT) procedures	After award and 60 days before test	Review/Approve or Reject
Stand-Alone Test dates	After sign is installed	Determine if a Rep. will attend
Stand-Alone Test results	14 days after SAT	Review/Approve or Reject
System Test Procedures	After award and 60 days before test	Review/Approve or Reject
System Test dates	7 days before test	Determine if a Rep. will attend
System Test results	14 days after system test	Review/Approve or Reject
90 day test procedures	After award and 60 days before test	Review/Approve or Reject
NTCIP Testing	Prepare to have done for Short-listed Manufacturers	Perform test and score results
Shop Drawing Submittals	Within 15 days of award of contract	Review/Accept or Reject within 15 days of receipt
Sign Truss Details	Within 15 days of award of contract	Review/Accept or Reject within 15 days of receipt
Operator's Manuals	After installation and before final payment	Keep for future reference
Software Manuals	After installation and before final payment	Keep for future reference
Maintenance Manuals	After installation and before final payment	Keep for future reference
As-Builts	After installation and before final payment	Keep for future reference
DMS Weight (if over 5000 lbs) and size (if over spec amounts)	Within 15 days of award, part of Shop Drawing submittal	Review/Accept or Reject within 15 days of receipt
DMS Housing Fascia	Within 15 days of award, part of Shop Drawing submittal	Review/Accept or Reject within 15 days of receipt
Declaration of version of NTCIP Standards, compliance, etc.	Within 15 days of award, part of Shop Drawing submittal	Review/Accept or Reject within 15 days of receipt
Declaration of compliance of NTCIP 1101	Within 15 days of award, part of Shop Drawing submittal	Review/Accept or Reject within 15 days of receipt
Declaration of compliance of NTCIP 1201	Within 15 days of award, part of Shop Drawing submittal	Review/Accept or Reject within 15 days of receipt



Declaration of compliance of NTCIP 1203	Within 15 days of award, part of Shop Drawing submittal	Review/Accept or Reject within 15 days of receipt
Declaration of compliance of NTCIP 2001	Within 15 days of award, part of Shop Drawing submittal	Review/Accept or Reject within 15 days of receipt
Declaration of compliance of NTCIP 2101	Within 15 days of award, part of Shop Drawing submittal	Review/Accept or Reject within 15 days of receipt
Declaration of compliance of NTCIP 2102	Within 15 days of award, part of Shop Drawing submittal	Review/Accept or Reject within 15 days of receipt
Declaration of compliance of NTCIP 2104	Within 15 days of award, part of Shop Drawing submittal	Review/Accept or Reject within 15 days of receipt
Declaration of compliance of NTCIP 2201	Within 15 days of award	Review/Accept or Reject within 15 days of receipt
Agenda for training session	30 days before training	Review and comment
Certification, Warranty and/or Guarantee	Upon final acceptance, or sooner	Keep on file

The DMS Manufacturer shall also submit any additional documentation not previously described, but required by specification and necessary to fully describe the DMS and associated equipment including complete technical information, photographs, instruction manuals, security provisions, etc.

The DMS Manufacturer will be required to complete the sign mounting bracket structural details and the sign mounting bracket structural calculations. The miscellaneous members and hardware shall be furnished by the DMS Manufacturer.

#### QUALIFICATIONS FOR THE DMS MANUFACTURER

The DMS Manufacturer shall submit the references as specified below. Reference data shall include current name and address of organization, and the current name and telephone number of an individual from the organization who can be contacted to verify system operation, as well as date of system installation.

#### EXPERIENCE REQUIREMENTS

The DMS Manufacturer shall submit at least two references, preferably from other state departments of transportation, that are successfully operating a highway LED full matrix DMS system, supplied by this manufacturer under the current corporate name, which otherwise meets this specification, for a period of no less than two years. The LED DMS systems submitted shall be full-matrix and able to display at least 3 lines of 25 characters per line, 18" characters and have walk-in access housings.

#### REFERENCES

The DMS Manufacturer shall submit three references, preferably from other state departments of transportation, that are successfully operating a multi-unit, multi-lane state or interstate highway, permanently-mounted, overhead dynamic message sign system supplied by this manufacturer under the current corporate name, for a period of no less than five years.

## ISO 9001:2000 REQUIREMENTS

The company that designs and manufactures the LED DMS shall be currently ISO 9001:2000 certified as of the bid date for this project. The scope of this company's ISO 9001:2000 certification shall be for the manufacturing of Dynamic Message Sign Systems. The facility where this company actually designs and manufactures the LED DMS parts shall be ISO 9001:2000 certified. This company, this scope and the address of this facility shall all be listed on the ISO 9001:2000 certificate. This ISO 9001:2000 certificate shall be provided with the bid. The name, phone number and address of both the Authorized ISO 9001:2000 Registrar that certified this company and the Authorized ISO 9001:2000 Accreditation Body that accredited this Registrar shall be provided with the bid. ISO 9002 and ISO 9003 certifications are not adequate and do not meet this requirement. The Department will evaluate the company's submittals for quality assurance and determine if the quality control/quality assurance requirements are met.

## MATERIAL REQUIREMENTS GENERAL

All materials furnished, assembled, fabricated or installed under this item shall be new, corrosion resistant and in strict accordance with the details shown in the plans and as detailed in this specification. All details and functionality listed in this specification will be thoroughly inspected and tested by the department. Failure to meet all details and functionality detailed in this specification shall be grounds for rejection of the equipment.

The equipment design and construction shall utilize the latest available techniques with a minimum number of different parts, subassemblies, circuits, cards and modules to maximize standardization and commonalty. The equipment shall be designed for ease of maintenance. All component parts shall be readily accessible for inspection and maintenance. Test points shall be provided for checking essential voltages.

The sign shall be designed for a minimum life of 20 years.

The sign shall be designed and constructed so as to present a clean and neat appearance. Poor workmanship shall be cause for rejection of the sign.

All cables shall be securely clamped/tied in the sign housing. No adhesive attachments will be allowed.

The performance of the sign shall not be impaired due to continuous vibration caused by wind, traffic or other factors. This includes the visibility and legibility of the display.

The DMS hardware, along with the sign controller hardware, software and firmware, shall support all DMS functionality described throughout the remaining specification sections.

The DMS assembly shall be listed by an accredited 3<sup>rd</sup> party testing organization for conformance to Underwriters Laboratories (UL) standards 48 (Standard for Electric Signs) and 1433 (Control Centers for Changing Message Signs). Proof of this conformance shall be provided with submittal materials.

## ELECTRONIC MATERIALS AND COMPONENTS

All electronic components, except printed circuit boards, shall be commercially available, easily accessible, replaceable and individually removable using conventional electronics repair methods. All electronic assemblies shall meet or exceed IPC 610A workmanship standards.

### PRINTED CIRCUIT BOARDS

Each pixel shall have a device attached to the printed circuit board (PCB) to hold and protect the LEDs. These devices shall:

1. Hold the LEDs perpendicular to the display modules within 0.5 degree,
2. Prevent the LEDs from being crushed or bent during handling,
3. Protect the LEDs from damage when the display module is laid on the front surface (the side that the LED lamps are located),
4. Not put any stress on the LEDs due to differentials of expansion and contraction between the device and the LEDs over the herein specified temperature range,
5. Not become loose or fall off during handling or due to vibrations,
6. Not block airflow over the leads of the LEDs,
7. Securely hold each LED while allowing a gap between the device and a minimum of 95% of the body of each LED for airflow,
8. Not block the light output of the LEDs at the required viewing angle,
9. Be black in color to maximize contrast.

The LEDs shall be protected from the outside environmental conditions, including moisture, snow, ice, wind, dust, dirt and UV rays.

Printed Circuit Board (PCB) design shall be such that components may be removed and replaced without damage to boards, traces or tracks.

Only FR-4 0.062 inch minimum thickness material shall be used. Inter component wiring shall be copper clad track having a minimum weight of 2 ounces per square foot with adequate cross section for current to be carried. Jumper wires will not be permitted, except from plated-through holes to component. The maximum number of jumper wires allowed per circuit board is two.

All Printed Circuit Boards (PCBs), except for the power supply PCBs, UPS PCBs, modem PCBs and sign controller PCBs, shall be completely conformal coated with a silicone resin conformal coat.

All PCBs shall be finished with a solder mask and a component identifier silk screen.

### COMPONENTS

All external screws, nuts, and locking washers shall be stainless steel. No self-tapping screws shall be used. All parts shall be made of corrosion resistant materials, such as plastic, stainless steel, aluminum or brass. All materials used in construction shall be resistant to fungus growth and moisture deterioration. Dissimilar metals shall be separated by an inert dielectric material without compromising any intended electrical grounding functions.

## CAPACITORS

The DC and AC voltage ratings as well as the dissipation factor of a capacitor shall exceed the worst case design parameters of the circuitry by 50%.

A capacitor which can be damaged by shock or vibration shall be supported mechanically by a clamp or fastener.

Capacitor encasements shall be resistant to cracking, peeling and discoloration.

## RESISTORS

Any resistor shall not be operated in excess of 50% of its power rating.

## SEMICONDUCTOR DEVICES

All transistors, integrated circuits, and diodes shall be a standard type listed by EIA and clearly identifiable.

## CONNECTORS

All PCB edge connectors and cable connectors, except for those found in the power supply, UPS, modem and sign controller, shall be base plated with nickel and finished with 30 micro-inches of gold.

## MECHANICAL COMPONENTS

All external screws, nuts, and locking washers shall be stainless steel. No self-tapping external screws shall be used. All parts shall be made of corrosion resistant materials, such as plastic, stainless steel or aluminum. All materials used in construction shall be resistant to fungus growth and moisture deterioration. Dissimilar metals shall be separated by an inert dielectric material.

## DMS HOUSING

### GENERAL CONSTRUCTION

The sign shall be designed and constructed so as to present a clean and neat appearance. Poor quality work shall be cause for rejection of the sign. The equipment within the sign housing shall be protected from moisture, dust, dirt and corrosion. The sign shall be constructed of aluminum alloy 3003-H14, 5052-H32, or an approved equal which shall not be less than 1/8 inch thick. Framing structural members shall be made of aluminum alloy 6061-T6, 6063-T5, or approved equal. Seams shall be continuously welded by an inert gas process. The sign shall be designed for a minimum life of 20 years.

The sign enclosures shall be capable of withstanding wind loadings of 120 mph without permanent deformation.

The performance of the signs shall not be impaired due to continuous vibration caused by wind, traffic or other factors. This includes the visibility and legibility of the display.

The presence of ambient magnetic or electromagnetic fields, including those created by any components of the system, shall have no deleterious effect on the performance of the system. The system shall not conduct or radiate signals which will adversely affect other electrical or electronic equipment including, but not limited to, other control systems, data processing equipment, audio, radio and industrial equipment.

#### Walk-in Housing

Walk-in housing dimension shall not exceed 8'6" tall, 30'-8" wide, and 37" deep. The total weight added to the sign structure shall be no greater than 5200 pounds.

The walk-in housing dimensions and total weight shall be as shown in this specification or in the plans. The walk-in housing shall protect all internal components from rain, ice, dust, and corrosion in accordance with NEMA enclosure Type 3R standards as described in NEMA Standards Publication 2501997, Enclosures for Electrical Equipment (1000 Volts Maximum).

The sign housing shall be engineered and P.E. certified to 2001 AASHTO and NCHRP Report 411 specifications for AASHTO basic wind speeds. The sign housing shall also be engineered and P.E. certified to withstand group loading combinations as outlined in 2001 AASHTO including: sign weight, repair personnel and equipment, ice and wind loads, and shall also meet strength requirements for truck-induced gusts as specified in NCHRP Report 412. The sign housing shall be engineered to withstand snow loading (40 PSF) for applicable geographical regions.

Inside the sign housing, all 120 VAC service lines shall be independently protected by a thermomagnetic circuit breaker at the housing entry point. All 120 VAC wiring shall be located in conduit, pull boxes, raceways or control cabinets. No 120 VAC wiring shall be exposed to the inside or outside of the sign housing. The sign housing shall not be considered as a raceway or control cabinet.

#### Exterior Housing Panel

The exterior housing, door and end panels shall be 3003-H14, 5052-H32 or approved equal aluminum alloy sheet, 1/8 inch minimum thickness.

The number of seams in the top housing panel shall be kept to a minimum. All seams in the top housing panel shall be continuously welded.

All exterior seams and joints shall be continuously welded by an inert gas process.

The exterior housing panel material shall be stitch welded to the internal structural members to form a unitized structure.

#### Interior Structure

The interior structural members shall be 6061-T6, 6063-T5, or approved equal aluminum alloy with 3/16 inch minimum wall thickness.

## Mounting

The housing shall be designed to accommodate mounting on the rear vertical plane only.

The angular alignment of the sign housing shall be designed to optimize the viewing angle based on the sign location and 4-lane configuration as shown in the plans.

## Housing Face

The internal structural members shall be extruded aluminum and shall accommodate both display module mounting and air distribution. They shall retain the display modules in a manner to facilitate easy and rapid removal of each display module without disturbing adjacent display modules.

The external fascia panels shall be extruded aluminum and shall be designed to keep heat conduction to a minimum between the exterior surfaces and the interior components. They shall incorporate provisions for retaining and sealing the modular lens panels and have a closed cell resilient gasket. They shall be finished with a matte black, KYNAR 500, or approved equal, and be removable from within the main sign housing. The external fascia perimeter panels shall be a minimum of 12" wide. The external fascia panels shall be thermally isolated from the rest of the sign housing. There shall be a minimum amount of metal contact between the external fascia panels and the rest of the sign housing.

The lens panel assembly shall be modular in design, interchangeable without misalignment of the lens panel and the LED pixels and removable from within the main sign housing.

The lens panel aluminum mask shall be 0.040" minimum thickness and panel interiors contain 0.236-inch-polycarbonate sheeting. It shall be perforated to provide an aperture for each pixel on the display modules. Each aperture shall be as small as possible, without blocking the LED light output at the required viewing angle.

The lens panel clear glazing shall be 90% UV opaque, non-breakable, polycarbonate GE LEXAN XL, 1/4" minimum thickness and clear in color shall be laminated to the inside surface of the lens panel aluminum mask using an acrylic foam tape joining system, 3M Scotch VHB, or approved equal, to form the lens panel assembly.

## Surface Finish

The face shall be finished with a matte black, factory applied PVDF resin. All other exterior and all interior surfaces shall be a natural aluminum mill finish. No painted surfaces will be allowed.

## Accessibility

A three-point lockable aluminum access door shall be provided at each end of the housing as shown in the plans to enable easy access to the walk-in housing. This shall make it possible for a single maintenance person to easily access the display modules.

This access door shall be 2032 mm X 610 mm (6'-8" X 2'-0") minimum. The door shall be fitted with a handle operated locking mechanism, closed cell neoprene gasket and a stainless steel hinge.

The locking mechanism shall be a heavy-duty, industrial-strength, three-point, deadbolt, center-case lock with a zinc finish. There shall be a handle on both the inside and the outside of the door. These handles shall be heavy-duty, industrial-strength with a zinc finish on the inside handle and a chrome-plated finish on the outside handle. The outside handle shall be padlockable.

Included in the door assembly shall be a device to hold the door open at 90 degrees

#### INTERNAL WALKWAY

The sign housing shall have a continuous 455 mm (18-inch) wide walkway extending the full length of the sign. The walkway shall be made of 3 mm (1/8 inch) diamond tread 6061-J6 or 3003-H22 aluminum. All edges of the walkway grating must be finished to eliminate sharp edges or protrusions.

The sign housing shall be a minimum of 863 mm (2' 10") wide to allow adequate room inside the sign housing for maintenance personnel. There shall be 455 mm (18 inches) of clear area between all equipment along the entire length of the sign housing from the 455 mm (18-inch) walkway up to 1829 mm (6 feet) above the 455 mm (18-inch) walkway.

#### VENTILATION SYSTEM

The ventilation system shall be sufficiently cool both the display modules and the sign housing interior.

The sign housing shall have a minimum of two (2) exhaust ports. Each exhaust port shall be filtered and protected by an aluminum screened louver assembly, or other conformable method. The exhaust filters shall be sized for the required air volume.

The ventilation system shall have a minimum of two (2) blowers and shall exchange the DMS air volume to sufficiently cool the interior of the sign.

The filters shall be 1" thick, permanent, reusable, filters. These filters shall be easily removable from within the sign housing without the use of tools. Each sign shall include a complete set of replacement filters.

The internal housing temperature shall be automatically verified on command from the DMS Client software and existing IDOT ATMS software. Any over temperature condition shall cause an error message to be sent to the DMS Client software and existing IDOT ATMS software when the sign controller is polled.

The ventilation system shall be designed to keep the internal DMS air temperature from exceeding +140° F, even when the outdoor ambient temperature is as high as +115° F.

The ventilation system shall be activated by temperature sensors.

Temperature sensors shall be continuously measured and monitored by the sign controller. A temperature greater than a user selectable critical temperature shall cause the sign message to go to blank and an error message shall be sent to the DMS Client software and existing ATMS software automatically.

The DMS Client software, existing ATMS software and personnel on site with laptop computer at local control box position shall have the ability to read all temperature measurements from the sign controller. When the sign reaches a temperature of 130° F, it shall cut the LED intensity to half of its normal brightness to keep the sign from reaching the critical temperature and shutting down.

The temperature sensors shall have an accuracy of +/-3° F and a range from -40° F to +150° F.

The ventilation system shall be equipped with a manual override timer to provide ventilation for service personnel. The timer shall have a maximum "on" time of two (2) hours.

#### INTERNAL LIGHTING AND ELECTRICAL OUTLETS

The sign housing shall be furnished with four 100 watt incandescent lights with heavy duty fixtures. The lamps shall be spaced evenly above the walkway and shall be fitted with protective guards. The light switch shall be located near the door.

The sign housing shall be equipped with two 15 amp 120V (+/- 10%) grounded GFCI protected duplex electrical receptacles to accommodate inspection and maintenance requirements. One of these receptacles shall be located at each end of the sign housing. Additionally, the sign housing shall be equipped with sufficient and readily available power source in order to accommodate a fiber optic modem and all other necessary communications equipment required to transmit data from the sign to nearest controller cabinet with fiber optic communications for the backbone. The sign housing and display panel shall be designed to minimize any visible internal light from the outside of the DMS when the internal DMS lighting is on during nighttime maintenance activities.

#### ANTI-CONDENSATION/DEFOG/DEFROST

An effective, field-proven defogging and anti-condensation system shall be incorporated into the overall functionality of the sign. The face shall be heated to prevent fogging, frost and condensation.

A humidity sensor shall be provided and monitored by the sign controller from zero percent to 100 percent relative humidity in 1 percent or fewer increments. The sensor shall operate and survive from 0 percent to 100 percent relative humidity. The sensor shall have an accuracy that is better than +/- five percent relative humidity.

The sign controller shall read the internal temperature sensors, external ambient temperature sensor and the humidity sensor. The sign controller shall use these readings in an algorithm that turns on the heater and/or the fans at the appropriate times to reduce both frost on the face of the sign and condensation on the display modules and other electronic circuitry.

#### BASE BOARD HEATERS

Baseboard heaters shall be included in the sign housing. These heaters shall be capable of remote start up in anticipation of winter field service.



## LAPTOP SHELF

The interior of the sign shall include a fold-down shelf for a laptop computer.

## DISPLAY MODULES

### GENERAL

Display modules consisting of nominal 18" high characters shall be assembled to form the specified full matrix message configuration. These circuit boards shall be designed and constructed to allow a single service technician to troubleshoot, isolate, remove, and replace these boards with minimal impact to the overall operation of the sign.

All LED boards shall be fully interchangeable and not require any address switches or adjustment when interchanged or placed in service. Module addressing, where required, shall be accomplished in the connector. The DMS Manufacturer shall document all LED testing for color so that replacement LED boards shall match existing amber color.

Pixel status and diagnostics shall include string failure, pixel failure and failed pixel location (line, module, row and column numbers). Replacement of a complete display module shall be possible using only simple hand tools. Interconnection of modules shall be through connectors only. All connectors shall be keyed to preclude improper hookups.

The display modules shall be approximately  $\frac{3}{4}$ " behind the lens panel assembly.

### LED AND PIXEL CHARACTERISTICS

Each pixel shall be a maximum of 1-3/8" in diameter. The LEDs in each pixel shall be clustered to maximize long range visibility. The average light intensity of the LEDs in each pixel shall be 3 candela minimum. All pixels in the sign shall have equal color and on-axis intensity. All pixels shall have a minimum on-axis intensity of 40 candela @ 20 mA forward current, with an overbright capability of 60 cd.

All pixels in all signs in this project, including the spare parts, shall have equal color and on-axis intensity. The pixel strings shall be powered from a regulated DC power source and the LED current shall be maintained at the LED manufacturer's specified nominal operating current to maximize life of the pixel. The failure of an LED in one string within a pixel shall not affect the operation of any other string or pixel. Pixel power drawn from the DC supplies shall not exceed 1.5 W per pixel, including the driving circuitry.

The LEDs shall be individually mounted directly to a printed circuit board and shall be easily replaceable and individually removable using conventional electronics repair methods.

### DISPLAY MODULE CHARACTERISTICS

All display modules shall be mechanically, electrically, and optically interchangeable within the sign. Each display module shall contain a connector for power and a connector for controls and data.

The display module contains the control and memory elements and provides the signals to switch the LED pixels. All LED boards and driver boards shall be fully interchangeable and shall not require any manual addressing switches or adjustment when interchanged or placed in service. The driver board shall contain the solid state electronics necessary to control pixel data and read pixel status. A diagnostic indicator shall be included on each daughter board to provide visual indication of the operational status of the LED module. LED drive circuitry supports a minimum refresh rate of 100 frames per second and is able to support 255 intensity levels.

These pixels shall be arranged uniformly, capable of displaying an 18" dot matrix character. All LEDs shall be individually and directly mounted to the LED circuit board to form the LED board. The LED board shall also hold the supporting control electronics and have an extruded aluminum frame. The display modules shall be mounted to the display face in a manner that facilitates easy and rapid removal of each display module without disturbing adjacent display modules. Replacement of a complete display module shall be possible without the use of any tools.

Failure of any LED in the pixel shall not affect the ability to control any other pixel and remaining LEDs in that pixel.

All LEDs shall be mounted so that their mechanical axis is normal  $\pm 1.00^\circ$  to the face of the sign to ensure brightness uniformity over the face of the sign. The sign manufacturer shall propose a method, acceptable to the Engineer, to test the LEDs in the display modules to ensure they meet these criteria.

There shall be a power distribution system that connects each display module to all power supplies and minimizes the voltage drop over the face of the sign.

The LEDs shall be protected from the outside environmental conditions, including, but not limited to, moisture, snow, ice, wind, dust, dirt, and UV rays.

Pixel brightness shall be controlled by pulse width modulation of the DC current with an adjustable duty cycle of 2.0% to 99.9% in 0.5% or finer increments. The operational status of the LEDs in each pixel shall be tested and then transmitted to the DMS Client software, existing ATMS software, or laptop computer on site at local control box location. The pixel status test shall distinguish the difference between full-out, and fully stuck on pixels. A list of defective pixels shall be provided, listing x coordinate (from left hand edge of sign), y coordinate (measured down from the top of the sign) and the failure type (stuck on or stuck off) for each defective pixel. Pixels shall be arranged as such so that coordinate (1,1) is in the upper left corner and coordinate (125,27) is in the lower right corner.

The state of the LEDs (full on, or off) in each pixel of the sign shall be read by the sign controller when it is polled or when a message is downloaded from the DMS Client software, existing ATMS software, or laptop computer on site at local control box location, and shall allow the DMS Client software or laptop computer on site at local control box location show the actual message that is visibly displayed on the sign in a WYSIWYG format, including any full-out or fully stuck on pixels.

All printed circuit boards, except the LED circuit board, shall be conformal coated. The LED board shall be conformal coated except at the pixels. All printed circuit boards, including the LED circuit board, shall have a solder mask and a component identifier silk screen. The display modules shall be assembled in a full matrix configuration.

## CHARACTERS DISPLAYED

The sign shall be capable of displaying ASCII characters 32 through 126 and the following characters at any location in the message line:

“A” thru “Z”- All upper case letters.

“0” thru “9”- All decimal digits.

Space (i.e., ASCII code 0x20).

Punctuation marks shown in brackets [ . , ! ? - ‘ ’ “ ” / ( ) ]

Special characters shown in brackets [# & \* + < >]

3 pixel wide dash

The display modules shall be rectangular, and shall have an identical vertical and horizontal pitch between pixels. The pitch shall be no greater than 2 3/4”.

The separation between the last column of one display module and the first column of the next shall be equal to the horizontal distance between the columns of a single display module.

The characters shall be legible under all light conditions at a distance of 1100’ within a 30° degree cone of vision centered around the optical axis of the pixel.

The sign shall be the proper brightness in all lighting conditions for optimum legibility. It shall be bright enough to have a good target value, but not to the point where the pixels bloom, especially in low ambient light level conditions, as determined by the Department ITS Engineer, or those acting in his/her behalf.

The brightness and color of each pixel shall be uniform over the entire face of the sign within the fifteen degree cone of vision from 1100’ to 200’ in all lighting conditions. Non-uniformity of brightness or color over the face of the sign under these conditions shall be cause for rejection of the sign.

## DISPLAY MATRIX

The DMS shall be a full-matrix configuration. A matrix with a minimum of 27 x 125 pixels must be supplied. The operator shall be able to display normal (5 x 7) ,compressed (4 X 7), expanded (6 X 7) or double stroke (7 X 7) character fonts. Font access privileges shall be assigned by the system supervisor.

## LED DC POWER

Power to the LED display shall be provided by industrial-grade switching power supplies manufactured by Lambda (model number LZS1000) or a pre-approved equivalent. The power supplies shall have an efficiency of 75%. The voltage to the LED modules and associated electronics shall not exceed 25 VDC.

The power supplies shall be redundant. The power supplies shall be paralleled in a Diode-OR configuration such that one supply may completely fail and the sign will still be supplied with enough power to run 50% of all pixels at 100% duty cycle at 149° F. Functioning supplies must current share to within 10%. The combined effect of line (95 to 135 VAC) and load (10% to 100%) on the power supplies be 80% greater at 120 VAC 50% to 100% of maximum load. The power supplies shall have a power factor of 0.95 or greater at 120 VAC from 50% to 100% of maximum load.

The power supplies shall be continuously monitored for proper operation by the sign controller. If the voltage drops below its nominal operating value, an error message shall be generated and transmitted to the DMS Client software, existing ATMS software, or laptop computer on site at local control box location automatically.

#### PHOTOELECTRIC SENSOR DEVICES

The sign shall incorporate a means of changing the brightness level provided by the LEDs automatically in response to ambient lighting conditions as detected by photo-electric sensors, and remotely in response to commands received from the central computer system. The photo-electric sensors shall be positioned to sense in three (3) directions. A minimum of sixteen (16) settings shall be used to control the brightness level. The lowest settings shall be for night use. The highest settings shall be for over bright control. The middle settings shall be for normal day time use allowing for variable light levels. Photo-electric sensors shall be provided integral to the DMS. These devices shall direct the sign controller unit to modify the intensity of the light produced by the pixel elements. The mounting devices for the photo-electric sensors shall allow full adjustment of the sensor orientation. The photo-electric sensors shall be located such that they are easily accessible for maintenance.

#### ENVIRONMENTAL BEHAVIOR

The signs shall be capable of operating without any decrease in performance over an ambient temperature range of -40° F to +149° F with a relative humidity of up to 95%.

#### MAIN POWER SUPPLY AND ENERGY DISTRIBUTION

The sign and its controller shall be designed for use on the following:

Power line Voltage - 120/240 VAC Nominal, single-phase power, 40 amperes per leg - the system shall operate within a voltage range of 95VAC to 135VAC.

Frequency – 60Hz +/- 3Hz

Under normal operation, the drop in voltage between no load and full load of the sign and its controller shall not exceed 10% of the nominal voltage. The system shall be protected by transient suppression devices including, MOVs, RIS and spark gap arrestor.

The system shall report any power failures to the main controller when system power returns.

Power protection shall be provided by a thermal magnetic circuit breaker associated with a 5 mA ground fault circuit interruption (GFI) device. A GFI device shall protect all service outlets.

The sign shall have a 40 A two-pole (common trip) main, 120/240 VAC, single phase, four wire load center with 20 circuit capability. Each circuit in the sign shall be powered from a separate circuit breaker. The power cables shall be as required by the NEC for acceptable voltage drop to supply AC power to the sign. The power required for sign operation shall not exceed 7000 watts for the sign housing to include fans, heaters, sign controller, communication equipment and all pixels illuminated at 100% brightness.

## SURGE PROTECTION

The system power shall be protected by two (2) stages of transient voltage suppression devices including MOVs and spark gap arrestor. Tripping of each stage (or both if tripped simultaneously) of the surge protection shall cause the sign controller to call central and report the error condition (for dialup operation) or report the error condition to central on the next poll (for multi-drop operation). There shall be an option that is either enabled or disabled and is selected and downloaded from the central controller to the sign controller. When this option is enabled, tripping of both stages of surge protection shall prevent power from reaching any components of the sign until the surge protection has been replaced. When this option is disabled, the sign will continue to function normally after both stages of surge protection are tripped. Communication lines shall be protected by two (2) stages of transient voltage suppression devices including MOVs and spark gap arrestor. Tripping of each stage (or both if tripped simultaneously) of the surge protection shall cause the sign controller to call central and report the error condition (for dialup operation) or report the error condition to central on the next poll (for multi-drop operation). There shall be an option that is either enabled or disabled and is selected and downloaded from the central controller to the sign controller. When this option is enabled, tripping of both stages of surge protection shall disconnect the communication lines until the surge protection has been replaced. When this option is disabled, the sign will continue to function normally after both stages of surge protection are tripped.

## UNINTERRUPTIBLE POWER SUPPLY (UPS)

A UPS shall be provided to allow the sign controller to notify the DMS Client software or existing ATMS software (if available) when an improper power condition at the DMS persists for longer than a user selectable "short power loss time".

The UPS shall meet the following minimum specifications:

1. Line Transient Protection: Passes ANSI/IEEE C.62.41/C.62.45 Cat A&B
2. Safety Compliance: Satisfies US / CSA En50091-1 regulations.
3. Capacity: Must be able to operate controller & modem for 10 minutes
4. Voltage Nominal: 120VAC
5. Voltage Range: 92-135 VAC
6. Transfer time: <150 ms typical
7. Battery: Sealed, maintenance-free lead acid
8. Battery recharge time: 2-8 hours; must be temperature-compensated
9. Over current protection:
  - a. UPS automatic shutdown if overload exceeds 110% of nominal for 3 minutes.
  - b. Communications:
  - c. RS-232 Interface (monitor, control and calibrate), DB-9 connection
10. Front panel display indicators: Fault, Test, Low Battery, On Battery, On Line
11. Operating temperature range: -37°C to +74°C

(NOTE: The UPS shall be mounted and operated in a manner to meet the temperature range requirements of the DMS as outlined in Section 2.5 (-40°C to 74°C (-40°F to 165°F) with a relative humidity of up to 100% condensing).

### SIGN CONTROLLER UNIT (SCU)

The sign controller shall include a minimum of two 2 serial communications I/O ports; one (1) RS-232, one (1) RS-485; one (1) Ethernet port and one (1) fiber optic communications port (or fully tested compatible serial to fiber device).

The sign controller shall be programmed to receive NTCIP-compliant sign control commands from the central controller (DMS client software or existing ATMS) or laptop computer, transmit NTCIP-compliant responses as requested to the central controller (DMS client software or existing ATMS) or laptop computer, monitor sign and message status and control sign operation and message displays.

The controller will have power-up and auto-restart capabilities with a programmable default message (including a blank message) when recovering from a power off condition. A hardware watch dog circuit will be utilized to provide automatic reset to the controller and the modem. The DMS client software and existing ATMS software (if applicable) shall be capable of remotely commanding a controller and modem reset.

The sign controller shall be capable of being controlled from the Departments existing DMS control software, Skyline NTCIP Version 1.15, existing ATMS developed by the Delcan Corporation or the laptop computer. The DMS and sign controller functionality must be in compliance with all mandatory NTCIP objects for DMS. All integration necessary with the Delcan Corporation software for complete NTCIP compliance and functionality as described within this document shall be included in the cost of this contract. Bidders may contact Mr. Joseph Brahm at 847-925-0120 for any questions.

### GENERAL

The sign controller shall be programmed to receive sign control commands from the master controller, transmit responses as requested to the master controller and control sign operation and message displays.

The sign controller shall be able to receive and send messages and data via IEEE 802.3 (Ethernet), fiber optic modem, and cellular CDPD, CDMA or GSM/GPRS. Transmission speed shall be a minimum of 9.6 kbps. A test pattern shall be provided in the DMS controller.

The sign controller shall be designed for fail-safe prevention of improper information display in the case of a system malfunction. Failure of any sign shall not affect operation of any other sign in the system. The sign controller shall consist, but not be limited to, the following:

Local control panel status indicators, including:

1. power on/off
2. communication status with the electronics in the walk-in housing
3. sign display power supply status

4. controller address
5. Power supply module
6. Central processor module
7. Input/output circuits

The sign controller shall have power-up and auto-restart capabilities with automatic sign blanking when recovering from a power-off condition. A watch-dog circuit shall be utilized to provide automatic shut down of the sign in the event of power or sign controller failure.

Connections from the controller shall be accomplished via industry standard, keyed type connectors with a retaining mechanism.

#### DISPLAY SYSTEM HARDWARE

The sign controller shall communicate with the display modules via the system interface circuit consisting of data bus drivers and line address decoders. Communication and control lines between the sign controller and the system interface circuits shall be surge protected.

The following shall be mounted inside the ground mounted cabinet housing:

1. Sign controller
2. Fiber optic modem/Ethernet to fiber modem
3. IEEE 802.11b wireless access point for remote communication to sign controller from ground elevation
4. Display system interface circuits
5. Display modules
6. Power supplies
7. Local/remote control switch and LED indicator
8. RS-232 (or Ethernet) plug-in connection for the laptop computer
9. S-232 cable (or CAT 5 Ethernet cable) a minimum of 4' long to connect the laptop computer to the sign controller
10. Uninterruptible power supply
11. Work space for the laptop computer
12. Communication equipment and transient voltage surge suppressors (TVSS)
13. Type I duty rating 2 step ladder. Ladder shall be mounted so that it does not interfere with the workspace available in the housing and be easily removed for use.

#### SIGN CONTROLLER COMMUNICATION INTERFACE

The sign controller shall be able to communicate with the DMS Client software, existing ATMS software, or laptop computer on site at local control box location using event-driven operation. Upon any status changes initiated either remotely or locally to the DMS controller, controller shall automatically update the DMS Client software and existing ATMS software. It shall be possible for a maintenance technician to connect a laptop computer to the remote control port, either from ground level outside the sign at the local control box, or from within the sign's walk-in housing, and carry out all operations that could be carried out by the central computer. Connection of a laptop without disconnecting the sign controller shall be accomplished with additional control ports. The sign and sign controller shall also be capable of remote communication access via IEEE 802.11b from existing Department laptops for remote control, programming and diagnostics.

The sign manufacturer shall test and ensure compatibility with the existing IEEE 802.11b communications cards installed in two Department laptops. The sign manufacturer shall set up and configure appropriate security measures for all IEEE 802.11b hardware provided to ensure a secure network.

The DMS Manufacturer shall provide all required modems. The DMS equipment shall be able to support connection to Department's nearest single-mode fiber optic communications backbone controller cabinet location for remote control, programming and diagnostics by way of Ethernet over fiber optic cable.

For Ethernet operations, each controller shall be assigned a unique controller ID, a 4 bit IP Network Address determined by working with the Department to ensure the address is consistent with the established IP system. The IP address shall also be used to ensure that SNMP Trap messages are able to identify the originating sign.

### SIGN CONTROLLER FUNCTIONS

The sign controller shall be controlled from the DMS client software, existing ATMS software or the laptop computer, which shall specify the appropriate display. The sign controller and its software shall perform the following functions:

1. Display a message, including:
2. Static messages
3. Flashing messages
4. Alternating messages
5. Double brush stroke messages for maximum legibility
6. Full-Matrix type displays

It shall be possible to separately vary the flashing and alternating frequency. The flashing frequency shall vary between one-half and five seconds in one tenth second increments. The alternating frequency shall vary between one-half and five seconds in one-tenth second increments.

It shall be possible to flash any character or set of characters in a static or alternating message. In the case of alternating message, the flashing period shall be a submultiple of the alternating on time it is associated with.

Report errors and failures, including:

- Data transmission error
- Receipt of invalid data
- Communications failure recovery
- AC power failure
- Power recovery
- Pixel status
- Fan status
- Temperature status
- Power Supply status



The sign controller shall issue an SNMP trap under the following conditions:

Power Supply Failure – when the AC power supply at a DMS has failed.

Power Restoration - whenever it detects restoration of AC power at the sign controller.

Temperature Limit – Whenever internal DMS temperature initially exceeds a programmed safety limit. A new trap will not be issued until the temperature once again falls below the safety limit and then exceeds it.

Door Open – Whenever the door of the DMS housing or the door of the controller cabinet is opened.

Message and status monitoring:

The sign controller shall transmit a return message to the DMS client software and existing ATMS software whenever it receives a valid request for status. The return message shall contain the following:

Address of the sign controller

Actual message that is visibly displayed on the sign on an individual pixel basis

Current sign illumination level

Error and failure reports

Temperature readings

Power supply operational status

Origin of display message transmission (laptop, manual, central, etc)

Beacon status (for possible future enhancement)

Uninterruptible power supply status

The sign controller shall blank any message displayed in the event of power or sign controller failure. Also, in the event of power failure the sign controller shall immediately access the modems and notify the master controller of AC failure.

The sign shall normally display single stroke (5 X 7) characters, compressed (4 X 7), expanded (6 X 7) or double-stroke (7 X 7) character fonts. Each font shall be fully customizable, and modifications to a font may be downloaded to the sign controller from the DMS client software and existing ATMS software or laptop computer at any time without any software or hardware modifications. The sign shall be capable of displaying a different font and character spacing on each line.

The sign controller shall monitor the photo cell circuits in the sign and convert the measured light intensity into the desired pixel brightness. The photo circuit readings shall be correlated with a brightness table in the sign controller. The brightness table shall have a minimum of 255 brightness levels. Automatic adjustment of the LED driving waveform duty cycle shall occur in small enough increments so that brightness of the sign changes smoothly, with no perceivable brightness change between adjacent levels. The brightness levels shall be adjustable from the DMS client software.

The operational status of each pixel in the sign shall be automatically tested once a day and tested when a pixel test is required from the DMS client software and existing ATMS software or laptop computer. A list of defective pixels shall then be transmitted to the DMS client software and existing ATMS software or laptop computer and logged into the log file, listing pixel status, module number, column number and pixel number.

This pixel status test shall distinguish the difference between full out and fully stuck on pixels. This test shall not affect the displayed message for more than 0.5 seconds.

When the sign controller is polled and when a message is downloaded from the DMS client software and existing ATMS software or laptop computer, each pixel in the sign shall be read and its current state for the current displayed message, and shall be returned to the DMS client software and existing ATMS software to show either on a laptop computer or the controller itself, the actual message that is visibly displayed on the sign on an individual pixel basis in a WYSIWYG format.

The operational status of the fans shall have the ability to be automatically tested once a day and tested on command from the DMS client software and existing ATMS software or laptop computer. Any failure shall cause an error message to be sent to the DMS client software, existing ATMS software or laptop computer when the sign controller is polled by the DMS client software, existing ATMS software or laptop computer.

Temperature sensors shall be continuously measured and monitored by the sign controller. A temperature greater than a user selectable critical temperature shall cause the sign message to go to blank and an error message shall be sent to the DMS client software and existing ATMS software or laptop computer when the sign controller is polled by the DMS client software, existing ATMS software or laptop computer. This user selectable critical temperature shall be capable of being changed by the DMS client software, existing ATMS software (if available) or laptop computer. The DMS client software and existing ATMS software (if available) and laptop computers shall have the ability to read all temperature measurements from the sign controller. When the sign reaches an internal temperature of 130° F, it shall cut the LED intensity to half of its normal brightness to keep the sign from reaching the critical temperature and shutting down.

When the display time of a message has expired, the controller shall set the sign to neutral. A sign is considered to be neutral when the sign is blank.

In the event of a communications failure with the DMS client software or existing ATMS software, the sign controller shall set the sign to neutral after a user-defined number of minutes (1 to 60) unless communications have been restored within this period. This function shall apply only when the sign controller is in the Master Control mode.

All LED module power supplies shall be continuously monitored by the sign controller. A low voltage reading shall cause an error message to be sent to the DMS client software, existing ATMS software or laptop computer when the sign controller is polled by the DMS client software, existing ATMS software or laptop computer.

There shall be no perceivable flicker or ghosting of the pixels during sign erasure and writing periods.

Message additions, deletions and changes in the sign controller shall be made from either the DMS client software, existing ATMS software or the laptop computer.

In the event of an AC power loss, all non-volatile memory shall be retained for a minimum of 30 days. AC power failure shall cause the sign controller to notify the DMS client software and existing ATMS software and display an error message on the DMS client software and existing ATMS software CRT.

For cellular operation, the sign controller shall immediately access the modem to notify the DMS client software and existing ATMS of the AC power failure.

Failure of any sign shall not affect the operation of any other sign in the system.

The sign controller internal time clock shall ensure that a message is taken down at the correct time, even in the event of communications loss.

The sign controller shall maintain its internal clock during power outages of less than 4 hours and display the proper message when power is restored.

The sign controller shall be able to put a self-updating time, temperature and/or date display on the sign.

### MODES OF OPERATION

The mode of operation shall determine which level of control governs the DMS message selection. These two modes can change be an automatic function of the DMS system and controller. The two modes of operation shall be:

Master- the DMS Master Controller (the DMS client software or existing IDOT ATMS software) determines the appropriate message or test pattern.

Local - the sign controller keypad or laptop computer is used to determine the appropriate message or test pattern.

### SAFETY OF OPERATION

All DMS Equipment shall meet all of the requirements in Section 3.2.4 "Power Interruption" of the National Electrical Manufacturers Association (NEMA) Standard TSI for Traffic Control Systems.

All DMS Equipment shall meet all of the requirements in Section 2.1.6 "Transients, Power Service" of NEMA Standard TS1.

In the event of a communications failure with the DMS client software or existing IDOT ATMS software, the sign controller shall set the sign to neutral after a defined number of minutes, unless communications have been restored within this period (whatever the remaining display time).

The function described above shall apply only when the sign controller is in the Master Controller Mode.

### DESCRIPTION OF THE VARIOUS COMMANDS

As a minimum, the following commands shall be available at the sign controller:

1. Display command from the DMS client software and existing ATMS (Master Control Mode).
2. Display command from the laptop computer (Local Control Mode).
3. Sign Status request - This command shall provide a report concerning the:
4. Sign appearance (lit, blank or neutral)
5. Status of pixel, fan, temperature and power supply
6. Mode of the displayed message (local/master)
7. Status of the photoelectric sensors
8. Light output level (minimum of 255 user defined levels)
9. Sign number, location, or ID
10. Pixel status request - This command shall provide a current indication of the status of all the pixels.
11. Light output switching command (minimum of 255 user defined levels)
12. "Blank sign" command
13. Sign off command (set to neutral state)
14. Echo command - This command shall provide a report concerning the message currently displayed by the controller (pixels on, display parameters, remaining display time, font used, character spacing).
15. Any commands/functions detailed elsewhere in this specification.

#### SIGN CONTROLLER CABINET

The sign controller shall be installed in a series NEMA 3R double-door enclosure with minimum dimensions of (66"H x 24"W x 30"L). The cabinet shall be furnished with a standard No. 2 lock. 3 keys shall be provided for each cabinet.

The cabinet shall be mounted on a concrete pad as indicated in the plans.

At a minimum, the cabinet shall have:

- Two (2) Power panel surge protection (EDCO SHA-1250 or approved equal) (one (1) per phase)
- One (1) Surge protection (Model ACP100 BWN3 or approved equal)
- Two (2) GFCI receptacles
- Four (4) circuit breakers (Two (2)-15Amp single pole, One (1) 15Amp double pole and One (1) 20Amp double pole main)
- Single point ground
- Heater lamp(s)
- Fluorescent lamp(s)

The cabinet shall be completely weatherproofed to prevent the entry of water. All exterior seams for cabinets and doors shall be continuously welded. All exterior welds shall be smooth.

Door hinges shall be mounted so that it is not possible to remove it from the door or cabinet without first opening the door.

There shall be a hinged shelf which folds from inside the cabinet and is suitable for a laptop computer.

The cabinet shall be constructed using stainless steel with a minimum thickness of 0.125". Material used in the cabinet shall meet NEMA standards.

The sign controller cabinet and equipment it houses shall be included in the cost of TRUSS MOUNTED LED DYNAMIC MESSAGE SIGN.

#### SIGN TO SIGN CONTROLLER CABINET INTERCONNECTION

Cables between the sign and the pole-mounted local control cabinet shall be provided for operation of the sign. These cables shall terminate using CHAMP IDC type connectors. Power and signal cables shall be in separate conduits.

#### DMS REPLACEMENT PART ALLOWANCE

A total allowance of \$10,000 shall be included in the material cost of replacement parts for the DMS on this contract. The Contractor shall submit a list of recommended replacement parts with associated unit costs and quantity within 90 days after award.

The Contractor shall allow in the contract bid the allocated allowance amount as described above, and said amount shall be included under this Special Provision. The amount stated above is for material only. No other related costs associated with the purchase, delivery, and other related overhead costs shall be included in the above amount. The material and overhead costs associated with this item shall be included in the pay item TRUSS MOUNTED LED DYNAMIC MESSAGE SIGN.

#### TECHNICAL ASSISTANCE

The DMS manufacturer's technical representative shall provide on-site technical assistance in following areas:

1. Sign to structure installation
2. Controller cabinet installation
3. Sign housing to ground control cabinet cable termination
4. Initial sign turn on and stand alone test

The initial powering up of the sign(s) shall not be executed without the permission of the DMS manufacturer's technical representative.

Special or proprietary cables shall be provided by the DMS Manufacturer to the installation contractor.

#### TESTING REQUIREMENTS

The Department has the right to require performance testing of materials and equipment not previously tested and approved. If technical data are not considered adequate for approval, samples may be requested for testing.

The DMS Manufacturer shall provide five (5) copies of all factory acceptance tests, stand-alone, system test and 90 day test procedures and data forms for the Department's approval at least 60 calendar days prior to the day the tests are to begin.

The test procedures shall include the sequence in which the tests will be conducted. The test procedures shall have the Department's approval prior to submission of equipment for tests.

The DMS Manufacturer shall perform the factory acceptance tests, stand-alone and system test. The DMS Manufacturer shall furnish data forms containing all of the data taken, as well as quantitative results for all tests. The data forms shall be signed by an authorized representative (company official) of the equipment manufacturer. At least one (1) copy of the data forms shall be sent to the Department within 14 days of the test's conclusion.

The Department reserves the right to have a representative to witness all tests. The results of each test shall be compared with the requirements specified herein. Failure to conform to the requirements of any test shall be counted as a defect, and the equipment shall be subject to rejection by the Department. Rejected equipment may be offered again for a retest, provided that all non-compliances have been corrected and retested by the DMS Manufacturer and evidence thereof submitted to the Department.

Each of the tests on all or one type of equipment must be completed within five (5) working days of each other. Any delays in performing all these tests may result in the DMS Manufacturer paying the additional costs of providing the Department's representatives for the additional testing time.

Final inspection and acceptance of equipment shall be made after installation at the designated location as shown on the installation plans.

The DMS Manufacturer shall be responsible for providing the test fixtures and test instruments for all the tests.

The Stand-Alone and System Tests are separate tests, however, they may be performed by the DMS Manufacturer during the same visit.

Consequences of Test Failures: If any unit fails to pass its test, the unit shall be corrected or another unit substituted in its place and the test successfully repeated.

If a unit has been modified as a result of a test failure, a report shall be prepared and delivered to the Department prior to shipment of the unit. The report shall describe the nature of the failure and the corrective action taken.

If a failure pattern develops, the Department may direct that design and construction modifications be made to all units at no additional cost or extension of the contract period.

#### FACTORY ACCEPTANCE TESTS (FAT)

The DMS Manufacturer shall be responsible for conducting demonstration tests on all units at a DMS's Manufacturer's facility. These tests shall be performed on each unit supplied. The Department shall be notified a minimum of 30 calendar days before the start of tests. At a minimum, all equipment shall have passed the following individual tests:

## EXAMINATION OF PRODUCT

Each DMS unit shall be examined carefully to verify that the materials, design, construction, markings and quality of work comply with the requirements of these project specifications.

## CONTINUITY TESTS

The wiring shall be checked to determine conformance with the requirements of the appropriate paragraphs in these project specifications.

## OPERATIONAL TEST

Each DMS unit shall be operated long enough to permit equipment temperature stabilization, and to check and record an adequate number of performance characteristics to ensure compliance with the requirements of these project specifications.

## NTCIP TEST

A NTCIP test shall be performed at the DMS Manufacturer's facility. The Department may elect to perform and/or witness this test. The specifics of this FAT shall be proposed by the DMS Manufacturer to the Department for approval. The Department encourages the DMS Manufacturer to use the testing methods as described herein, but understands your company may not have the license to test the described software.

## STAND-ALONE TESTS

The DMS Manufacturer shall conduct an approved stand-alone test of the equipment installation at the field site. The test shall, as a minimum, exercise all stand-alone (non-network) functional operations of the field equipment with all of the equipment installed as per the contract documents.

Approved data forms shall be completed and turned over to the Department as the basis for review and rejection or acceptance. At least 30 working days notice shall be given prior to all tests to permit the Department to observe each test.

## SYSTEM TESTS

The DMS provided shall be compatible with the Department's existing Advanced Traffic Management System (ATMS) software. The DMS Manufacturer shall provide the latest version of Skyline Products NTCIP DMS Client and Server software. The Department currently uses Skyline Products NTCIP DMS Version 1.15.00. The DMS shall also be compatible with the latest version of Skyline Products NTCIP DMS Client and Server software. All costs associated with compatibility testing and coordination with the Department's existing ATMS vendor, Delcan Corporation and existing DMS vendor's client/server software, Skyline Products, will not be paid for separate and shall be included in the cost of the DMS.

The DMS Manufacturer shall conduct approved DMS system tests on the field equipment with the DMS manufacturer's software and the Department's existing Advanced Traffic Management System software and equipment for comparison.

The Department shall be notified a minimum of seven (7) calendar days before the start of tests. The tests shall, as a minimum, exercise all remote control functions and display the return status codes from the controller and all standard mandatory NTCIP functions for a minimum of 72 hours. Approved data forms for both the DMS manufacturer's software and Department's existing ATMS software shall be completed and turned over to the Department as the basis for review and for rejection or acceptance.

#### 72 HOURS AND 90 DAYS TEST

After the installation of the DMS system is completed and the successful completion of the System Test, the DMS system shall be subjected to one continuous 72-hour full operating test prior to a 90 day test period. The test shall consist primarily of exercising all control, monitor and communications functions of the field equipment by the central equipment.

The 90 days test period shall commence on the first day after the successful completion of the approved 72-hour continuous full operating test period.

During the 90 days test period, downtime, due to mechanical, electrical and/or other malfunctions, shall not exceed five (5) working days. The Engineer may extend the 90 days test period by a number of days equal to the downtime in excess of five (5) working days.

The Engineer will furnish the DMS vendor with a letter of approval stating the first day of the 90 days test period.

#### NTCIP STANDARDS TESTING

The Department and DMS Manufacturer shall test the DMS system for NTCIP compliance using Intelligent Devices Inc. (IDI) Device Tester. Any differences in the interpretation of the newly developed NTCIP Standards shall be decided by the NTCIP Joint Standards Committee.

The DMS manufacturer shall be responsible for ensuring that the DMS equipment complies with the NTCIP Standards as specified herein. The NTCIP field testing will be completed no later than 30 calendar days after the installation of the DMS.

#### NTCIP REQUIREMENTS

##### A. Definitions

The following terms shall apply within the scope of this specification:

DMS – A Dynamic Message Sign, includes the sign display, controller, cabinet, and other associated field equipment.

FSORS – Full Standardized Object Range Support.

Full Standardized object Range Support – Support for, and proper implementation of all valid values of an object as defined within the object's OBJECT\_TYPE macro in the NTCIP standard; this is defined in two distinct sub-requirements.



(1) If ACCESS of the object is read-write, a Management System shall be able to set the object to any valid value as defined by SYNTAX and DESCRIPTION fields (except that the value of 'other' need not be supported when such a value is defined) and the indicated functionality shall be provided. (2) The value indicated by the object (e.g. in response to a get), regardless of the access shall reflect the current conditions per the rules specified in the object's

#### DESCRIPTION.

Management System – A computer system used to control an NTCIP component. This includes any laptop software used for field control as well as the central software.

NTCIP Component – A DMS or management system.

NTCIP System – A management plus the various ASCs and DMSs controlled by the management system.

Response Time – The time to prepare and begin transmission of a complete response containing the requested application layer information. This is measured as the time from receipt of the closing flag of the request to the transmission of the opening flag of the response when the device has immediate access to transmit.

#### B. References.

Each DMS component shall support the most recent version of these standards, including all Recommended or Approved Amendments, currently in effect. The most recent versions of these standards and known Amendments are shown below. In many cases, the standards are more widely known by its original NEMA assigned number; in these cases the NEMA number is also identified. The content of the NEMA standard is identical to the NTCIP standard. It is the ultimate responsibility of the Manufacturer to monitor NTCIP actives to discover any recent documents.

#### NTCIP Standards

NTCIP 1101-NTCIP 1101:1997  
(NEMA TS 3.2-1996) Simple Transportation Management Framework Amendment #1 Dated  
November 2, 1998

NTCIP 1201-NTCIP 1201:1997  
(NEMA TS 3.4-1996) Global Object Definitions Amendment #1 Dated  
November 2, 1998

NTCIP 1203-NTCIP 1203:1997  
(NEMA TS 3.6-1997)  
Object Definitions for Dynamic Message Signs

NTCIP 2001-NTCIP 2001: 2000  
(NEMA TS-3.3) Class B Profile Amendment #1  
Dated Unknown

NTCIP 2101-NTCIP 2101: 2000  
(NEMA TS 3.PMP232-2000)  
Subnet Profile for PMPP over RS-232

NTCIP 2102-NTCIP 2102V01.03: (Draft)  
Point-to Point Protocol using RS 232 Subnet work Profile  
NTCIP 2104 NTCIP 2104 v01.10  
National Transportation Communications for ITS Protocol Ethernet Subnet work Profile

NTCIP 2201-NTCIP 2201 Transportation Profile

NTCIP 2301-NTCIP 2301: 2000  
(NEMA TS 3.STMF) Application Profile

## C. General Requirements

### 1. Subnet Level

Each serial port on each NTCIP Component shall support NTCIP 2102 over a dial-up connection with a external modem with data rates of 28.8 kbps, 19.2 kbps, 14.4 kbps, 9600 bps, 2400bps, 1200 bps, 600 bps and 300bps. The NTCIP Component shall be capable to make outgoing and receive incoming calls as necessary and support the following modem command sets:

- Hayes AT – Command Set
- MNP5
- MNP10
- V.42bis

Each serial port on each NTCIP Component shall support NTCIP 2102 over a null-modem connection with data rates of 19.2 kbps, 14.4 kbps, 9600 bps, 4800 bps, 2400 bps, 1200 bps, 600 bps and 300 bps.

Each serial port on each NTCIP Component shall support NTCIP 2101 with data rates of 9600 bps, 4800 bps, 2400 bps, 1200 bps, 600 bps and 300 bps.

NTCIP Components may support additional Subnet Profiles at the Manufacturer's option. At any one time, only one Subnet Profile shall be active on a given serial port of the NTCIP Component.

The NTCIP Component shall be configurable to allow the field technician to activate the desired Subnet Profile and shall provide a visual indication of the currently selected Subnet Profile.

### 2. Transport Level

Each NTCIP Component shall comply with NTCIP 2201 The transport layer shall be a NULL layer. NTCIP Components may support additional Transportation Profiles at the Manufacturer's option. Response datagram's shall use the same Transport Profile used in the request. Each NTCIP Component shall support receipt of datagram's conforming to any of the identified Transport Profiles at any time.

### 3. Application Level

Each NTCIP Component shall comply with NTCIP 1101 and shall meet the requirements for conformance Level 1.

Each NTCIP Component shall support STMP traps.

An NTCIP Component may support additional Application Profiles at the Manufacturer's option. Responses shall use the same Application Profile used by the request. Each NTCIP Component shall support the receipt of the Application data packets at any time allowed by the subject standards.

### 4. Information Level

Each NTCIP Component shall provide full Standardized Object Range Support of all objects required by this specification unless otherwise indicated below. The maximum response time for any object shall be 200 milliseconds.

The DMS shall support all mandatory objects of all Conformance Groups as defined in NTCIP 1201 and NTCIP 1203. The section below, Modified Object Ranges for Mandatory Objects, indicated the modified object requirements of these mandatory objects.

#### Modified Object Ranges for Mandatory Objects

Object: Module Table Entry  
Reference: NTCIP 1201 Clause 2.2.3  
Requirement: Shall contain at least one row with module Type equal to 3 (software). The module make shall specify the name of the Manufacturer, the module model shall specify the Manufacturer" name of the component and the model version shall indicate the model version number of the component

Object: Max Group Address  
Reference: NTCIP 1201 Clause 2.7.1  
Requirement: Shall be at least 1

Object: Community Name Address  
Reference: NTCIP 1201 Clause 2.8.2  
Requirement: Shall be at least 3

Object: dms Num Permanent Msg  
Reference: NTCIP 1203 Clause 2.6.1.1.1.1  
Requirement: Shall be at least 1\*

Object: dms changeable Msg  
Reference: NTCIP 1203 Clause 2.6.1.1.1.3  
Requirement: Shall be at least 21

Object: dms Free Changeable Memory  
Reference: NTCIP 1203 Clause 2.6.1.1.1.4  
Requirement: Shall be at least 20 when no message is stored

Object: dms Message Multi String  
Reference: NTCIP 1203 Clause 2.6.1.1.1.8.3  
Requirement: The DMS shall support any valid MULTI string containing any subset of those MULTI tags listed in the Required Multi Tags section.

Object: dms Control Mode  
Reference: NTCIP 1203 Clause 2.7.1.1.1.1  
Requirement: The DMS shall support any valid MULTI string containing any subset of those MULTI tags listed in the Required Multi Tags section.

\* The Permanent Messages shall display the content shown below in Content of Permanent Messages.

#### Content of Permanent Messages

1 - Permanent Message #1 shall blank the display (ie. consist of an empty MULTI string). It shall have a run-time priority of one (1),

#### Required Multi Tags

Code: f1, Feature: field 1 – time (12hr)

Code: f2, Feature: field 2 – time (24hr)

Code: f8, Feature: field 8 - day of month

Code: f9, Feature: field 9 - month

Code: f10, Feature: field 10 – 2 digit year

Code: f11, Feature: field 11 – 4 digit year

Code: fl (and/fl), Feature: flashing text on a line by line basis with flash rates controllable in 0.1 second increments

Code: fo, Feature: font

Code: jl2, Feature: justification – line- left

Code: jl3, Feature: justification – line-center

Code: jl4, Feature: justification – line-right

Code: jl5, Feature: justification – line-full

Code: jp2, Feature: justification – page - top

Code: jp3, Feature: justification – page -middle

Code: jp4, Feature: justification – page -bottom

Code: mv, Feature: moving text

Code: nl, Feature: new line

Code: np, Feature: new page, up to 2 instances in a message (ie., up to 3 pages/frames in a message counting first page)

Code: pt, Feature: page times controllable in 0.1 second increments

The NTCIP Component shall also implement all mandatory objects of the following optional conformance groups.

- (a) Time Management, as defined in NTCIP 1201
- (b) Time base Event Schedule, as defined in NTCIP 1201.

The following list indicates the modified object requirements of the conformance group.

Modified Object Ranges for the Time base Event Schedule Conformance Group

Object: max time base schedule entries  
Reference: NTCIP 1201 clause 2.4.3.1  
Project Requirements: Shall be at least 28

Object: max day plans  
Reference: NTCIP 1201 clause 2.4.4.1  
Project Requirements: Shall be at least 20

Object: max day plan events  
Reference: NTCIP 1201 clause 2.4.4.2  
Project Requirements: Shall be at least 10

- (c) Report, as defined in NTCIP 1201.
- (d) PMPP
- (e) The following list indicates the modified object requirements for this conformance group.

Modified Object Ranges for the Report Conformance Group

Object: max event log configs  
Reference: NTCIP 1201 Clause 2.5.1  
Project Requirement: Shall be at least 50

Object: Event configuration Mode  
Reference: NTCIP 1201 Clause 2.4.3.1  
Requirement: The NTCIP Component shall support the following event configuration: on change greater than value smaller than value.

Object: Max event log size  
Reference: NTCIP 1201 Clause 2.5.3  
Requirement: Shall be at least 200

Object: Max event classes  
Reference: NTCIP 1201 Clause 2.5.5  
Requirement: Shall be at least 7

- (f) Font Configuration, as defined in the NTCIP 1203.

The following list indicated the modified object requirements for this conformance group.

### Modified Object Ranges for the Font Configuration Conformance Group

Object: num Fonts  
Reference: NTCIP 1203 Clause 2.4.1.1.1.1  
Requirement: Shall be at least 8

Object: max Font Characters  
Reference: NTCIP 1203 Clause 2.4.1.1.1.3  
Requirement: Shall be at least 255

Upon delivery, the first three font sets shall be configured in accordance with ASCII character set for the following characters:

- “A” thru “Z” – in both upper and lower cases
- “0” thru “9” – all decimal digits
- A blank or space
- Eight (8) directional arrows
- Punctuation marks, such as . , ! ? - ‘ ”
- Other characters, such as # & \* / ( ) [ ] < >

(g) DMS configuration, as defined in NTCIP 1203

(h) Multi Configuration, as defined in the NTCIP 1203.

The following list indicates the modified object requirements for this conformance group.

### Modified Object Ranges for the MULTI Configuration Conformance Group

Object: default Background color  
Reference: NTCIP 1203 Clause 2.5.1.1.1.1  
Requirement: The DMS shall support the following background colors: black  
Object: default foreground color  
Reference: NTCIP 1203 Clause 2.5.1.1.1.2  
Requirement: The DMS shall support the following foreground colors: Amber

Object: Default flash on  
Reference: NTCIP 1203 Clause 2.5.1.1.1.3  
Requirement: The DMS shall support the full range of these objects.

Object: Default flash off  
Reference: NTCIP 1203 Clause 2.5.1.1.1.4  
Requirement: The DMS shall support the full range of these objects.

Object: default justification line  
Reference: NTCIP 1203 Clause 2.5.1.1.1.6  
Requirement: The DMS shall support the following forms of line justification:

- left
- center
- right

Object: default justification page

Reference: NTCIP 1203 Clause 2.5.1.1.1.7

Requirement: The DMS shall support the following forms of page justification:

- top
- middle
- bottom

Object: default page on time

Reference: NTCIP 1203 Clause 2.5.1.1.1.8

Requirement: The DMS shall support the full range of these objects with step sizes no larger than 0.5 seconds

Object: default page off time

Reference: NTCIP 1203 Clause 2.5.1.1.1.9

Requirement: The DMS shall support the full range of these objects with step sizes no larger than 0.5 seconds

Object: default character set

Reference: NTCIP 1203 Clause 2.5.1.1.1.10

Requirement: The DMS shall support the following character sets: eight bit

(i) Multi Error Configuration, as defined in NTCIP 1203

(j) Illumination/Brightness Control, as defined in NTCIP 1203.

The following list indicates the modified object requirements for the conformance group.

#### Modified Object Ranges for Illumination/Brightness Control Conformance Group

Object: dms illum control

Reference: NTCIP 1203 Clause 2.8.1.1.1.1

Requirement: The DMS shall support the following illumination control modes:

- photocell
- timer
- manual

Object: Dms illum num bright levels

Reference: NTCIP 1203 Clause 2.8.1.1.1.4

Requirement: Shall be at least 16

(k) Scheduling as defined in the NTCIP 1203. The following text indicates the modified object requirements for this conformance group.

#### Modified Object Ranges for Scheduling Conformance Group

Object: num action table entries

Reference: NTCIP 1203 Clause 2.9.1.1.1.1

Requirement: Shall be at least 200

- (l) Sign Status, as defined in NTCIP 1203
- (m) Status Error, as defined in NTCIP 1203
- (n) Pixel Error Status, as defined in NTCIP 1203
- (o) Power Status, as defined in the NTCIP 1203

The NTCIP Component shall also implement the following optional objects:

Object: global set ID parameter  
Reference: NTCIP 1201 Clause 2.2.1  
Requirement: FSORS

Object: event config log OID  
Reference: NTCIP 1201 Clause 2.5.4.7  
Requirement: FSORS

Object: event config action  
Reference: NTCIP 1201 Clause 2.5.4.8  
Requirement: FSORS

Object: event class description  
Reference: NTCIP 1201 Clause 2.5.6.4  
Requirement: FSORS

Object: default flash on  
Reference: NTCIP 1203 Clause 2.5.1.1.1.3  
Requirement: The DMS shall support the full range of these objects with step size no larger than 0.5 seconds

Object: default flash off  
Reference: NTCIP 1203 Clause 2.5.1.1.1.4  
Requirement: The DMS shall support the full range of these objects with step size no larger than 0.5 seconds.

Object: dms SW reset  
Reference: NTCIP 1203 Clause 2.7.1.1.1.2  
Requirement: FSORS

Object: dms message time remaining  
Reference: NTCIP 1203 Clause 2.7.1.1.1.4  
Requirement: FSORS

Object: dms short power recovery message  
Reference: NTCIP 1203 Clause 2.7.1.1.1.8  
Requirement: FSORS



Object: dms long power recovery message  
Reference: NTCIP 1203 Clause 2.7.1.1.1.9  
Requirement: FSORS

Object: dms short power loss time  
Reference: NTCIP 1203 Clause 2.7.1.1.1.10  
Requirement: FSORS

Object: dms reset message  
Reference: NTCIP 1203 Clause 2.7.1.1.1.11  
Requirement: FSORS

Object: dms communication loss message  
Reference: NTCIP 1203 Clause 2.7.1.1.1.12  
Requirement: FSORS

Object: dms time comm. loss  
Reference: NTCIP 1203 Clause 2.7.1.1.1.13  
Requirement: FSORS

Object: dms end duration message  
Reference: NTCIP 1203 Clause 2.7.1.1.1.15  
Requirement: FSORS

Object: dms memory mgmt  
Reference: NTCIP 1203 Clause 2.7.1.1.1.16  
Requirement: The DMS shall support the following Memory Management Modes:  
    clear changeable messages  
    clear volatile messages

Object: dms multi other error description  
Reference: NTCIP 1203 Clause 2.7.1.1.1.20

Requirement: If the vendor implements any vendor-specific MULTI tags, the DMS shall provide meaningful error messages with in the object whenever one of these tags generates an error.

Object: dms illume light output status  
Reference: NTCIP 1203 Clause 2.8.1.1.1.9  
Requirement: FSORS

Object: watchdog failure count  
Reference: NTCIP 1203 Clause 2.11.1.1.1.5  
Requirement: FSORS

Object: dms stat door open  
Reference: NTCIP 1203 Clause 2.11.1.1.1.6  
Requirement: FSORS

Object: fan failure  
Reference: NTCIP 1203 Clause 2.11.1.1.1.8  
Requirement: FSORS

Object: fan test activation  
Reference: NTCIP 1203 Clause 2.11.1.1.1.9  
Requirement: FSORS

Object: temp min ctrl cabinet  
Reference: NTCIP 1203 Clause 2.11.4.1.1.1  
Requirement: FSORS

Object: temp max ctrl cabinet  
Reference: NTCIP 1203 Clause 2.11.4.1.1.2  
Requirement: FSORS

Object: temp min sign housing  
Reference: NTCIP 1203 Clause 2.11.4.1.1.5  
Requirement: FSORS

Object: temp max sign housing  
Reference: NTCIP 1203 Clause 2.11.4.1.1.6  
Requirement: FSORS

## MAINTENANCE SERVICES

The installation contractor shall provide complete maintenance services for the entire DMS assembly until the final acceptance. All labor, travel, replacement parts and associated costs necessary to maintain the DMS assembly shall be included in the contract at no additional cost to the Department.

The installation contractor shall correct all failures in the DMS assembly within 48 hours of notification from the Department until final acceptance. A failure of a sign installation shall be defined as the inability of the sign to function as per these specifications. A failure shall also be defined as the sign becoming unreadable or illegible as determined by the Department.

## FINAL SYSTEM ACCEPTANCE

Final system acceptance will be defined as when all work and materials provided have been furnished and completely installed by the DMS Manufacturer, and all parts of the work have been approved and accepted by the Department and the Dynamic Message Sign System has been operated continuously and successfully for 90 calendar days with no more than 5 calendar days downtime due to mechanical, electrical and/or other malfunctions, as specified herein.

The warranty period, as specified in herein, will begin upon final acceptance.

## AS-BUILT DOCUMENTATION

The DMS Manufacturer shall provide to the Department the following documentation of the complete installed equipment prior to final payment.

Sufficient documentation shall be provided to reflect "as-built" conditions and to facilitate operation, maintenance, modification, and expansion of the system or any of its individual components. Manufacturer supplied documentation which covers the intent of this requirement may be used, subject to the approval of the Department:

The DMS Manufacturer shall prepare and submit the following detailed drawings for each sign:

- the DMS character set as detailed herein,
- all non-catalog or custom-made components,
- sign housing assembly details, including the component location details and a layout of all the display elements, complete with dimensions,
- sign housing structural details, including member details, support mechanism details required for installation of the DMS onto the sign truss, welding details, and miscellaneous hardware details; complete with dimensions and sizes,
- sign mounting bracket structural details, including miscellaneous members and hardware required to attach the DMS to the sign truss; complete with dimensions and sizes, and
- wiring schematics.

#### OPERATOR'S MANUALS

A manual containing a general description and detailed operating and installation instructions shall be provided for each different type or model of equipment. One (1) copy of the manual shall be provided and kept in the sign cabinet. An additional ten (10) copies of the manual shall be submitted to the Department for each model of equipment. An additional copy of the manual shall be submitted to the Department on CD for each model of equipment. The manual shall include the following information:

1. A general description of the equipment including all information necessary to describe the basic use or function of the system components. This shall include a general block diagram presentation of the equipment. Where auxiliary equipment is required, tabular charts shall be included, listing such equipment. These charts shall include the nomenclature physical and electrical characteristics and functions of the auxiliary equipment unless such information is contained elsewhere in an associated manual. In the latter case, a reference shall be made to the location of the information pertaining to the auxiliary equipment.
2. The theory of operation of the system components in a clear, concise manner supported by simplified schematics, logic, data flow diagrams, one-function diagrams, etc. Timing and waveform diagrams and voltage levels shall be shown as required. A logical development shall be used starting with a system block level and proceeding to a circuit analysis. Circuit analysis shall be detailed whenever circuits are not normally found in standard textbooks. The application of new theoretical concepts shall be fully described. Where the design allows operation in a number of different modes, an operational description of each mode shall be included.
3. In simple, clear language, the routine of operation, from necessary preparations for placing the equipment into operation, to securing the equipment after operation. This section shall contain appropriate illustrations, with the sequence of operations presented in tabular form wherever feasible.

This section shall also contain a list of applicable test instruments, aids and tools required in the performance of necessary measurements and technique of each system component. In addition, set-up test, and calibration procedures shall be described.

4. Schematic diagrams shall be complete and accurate as required to supplement the text material and to allow the books to be a self-contained technical information source. Maximum size of these diagrams should be limited to allow their use in close proximity of the equipment, in the classroom, etc., part reference symbols, test voltages, waveforms, and other aids to understanding of the circuit's function shall be included on the diagrams. Test voltages, waveforms, and other aids to understanding of the circuit's function may be shown on both the simplified schematics and other drawings (as required in the above sections) on theory of operation, or maintenance or on the schematic diagrams required for this section. The overall scope of information shall not be less, however, than that stated for the schematic diagrams.

## SOFTWARE MANUALS

The DMS Manufacturer shall provide manuals and data for the computer software system and components thereof. One (1) copy of the manual shall be provided and kept in the sign cabinet. Ten (10) additional copies of the manual shall be submitted to the Department for each version of software. One (1) copy of the manual shall be provided on CD. As software is upgraded, updated versions of the manual shall be provided. This submittal shall include the following:

1. Software user's manuals shall be supplied. Include instructions for performing a backup of all software and message libraries.
2. Manufacturer's documentation (including schematics) for all plug in circuit cards used in the microcomputer chassis.
3. Computer program logic in flowchart form.
4. Narrative descriptions of programs and input/output formats.
5. Two (2) copies of source programs, for master and sign controller software, shall be provided on CD-ROM. The Department shall have the right to duplicate the sign controller software as needed for use in controlling signs under its' jurisdiction.
6. The DMS Manufacturer's NTCIP MIB (Management Information Base) shall be provided to the Department.
7. Warranty information.
8. Preventive maintenance and maintenance information.

## MAINTENANCE MANUALS

A manual containing a general description and detailed maintenance instructions shall be provided for each different type or model of equipment. One (1) copy of the manual shall be provided and kept in the sign cabinet. An additional ten (10) copies of the manual shall be submitted to the Department for each model of equipment. One (1) copy of the manual shall be provided on CD. The manual shall include the following information:

1. The manufacturer's recommended procedures and checks necessary for preventive maintenance. This shall be specified for pre-operation, weekly, monthly, quarterly, semi-annual, annual, and "as required" checks as necessary to assure reliable equipment operation.

Specifications, including tolerances, for all electrical, mechanical, and other applicable measurement, adjustments, or both, shall be listed. The DMS Manufacturer shall provide the Department with a sample preventive maintenance schedule.

2. Data necessary for isolation and repair of failures or malfunctions, assuming the maintenance technicians to be capable of analytical reasoning using the information provided above. Accuracies, limits, and tolerances for all electrical, physical or other applicable measurements shall be described. General instructions shall be included for disassembly, overhaul, and reassembly, including shop specifications or performance requirements.
3. Detailed instructions shall be given only where failure to follow special procedures would result in damage to the equipment, improper operation, or danger to operating or maintenance personnel.
4. The parts list shall contain all information required to describe the characteristics of the individual parts, as required for identification. It shall include a list of all equipment within a group and list of all assemblies, subassemblies, and replacement parts of units. The tabular arrangement shall be in alphanumeric order of the schematic reference symbols and shall give the associated description, manufacturer's name, and part number. A table of contents or some other convenient means, e.g., appropriate grouping, shall be provided for the purpose of identifying major components, assemblies, etc.

#### FINAL DOCUMENTATION OF ALL HARDWARE AND SOFTWARE

Final documentation shall reflect all field changes and software modifications and shall be provided before final payment is made.

The DMS Manufacturer shall coordinate and take the lead on this effort with the installation contractor.

This documentation shall include drawings of conduit layouts, cable diagrams, wiring lists, cabinet layouts, wiring diagrams and schematics for all elements of the communications system. This shall also include detailed drawings identifying by cable type, color code and function, the routing of all conductors (pairs) in the communications system.

Four (4) copies of each As-Built installation shall be delivered to the Department. Copies shall go to:

1. Resident Construction Engineer
2. Maintenance supervisor
3. ITS Engineer
4. One will be left in the DMS

Drawings left in the DMS shall be attached to the door with stainless steel fasteners and protected from weather with a waterproof enclosure.

## TRAINING

Operational and maintenance training for the entire system shall be provided to designated personnel during installation, testing and debugging. This training shall be provided through practical demonstrations, seminars and other related technical procedures. Training shall be limited to a maximum of eight (8) people and shall be provided at a time and location approved by the Department. The training shall include, but not be limited to, the following:

1. "Hands-on" operation of all sign control hardware
2. Explanation of all system commands, their function and usage
3. Insertion of data
4. Required preventative maintenance procedures
5. Servicing procedures
6. System "troubleshooting" or problem identification procedures

A minimum of eight (8) hours of instruction shall be provided for the operational and maintenance procedures for the system.

The DMS Manufacturer shall submit an agenda for the training and one complete set of training material (manual and schematic) along with the qualification of proposed instructors) to the Department for approval at least 30 calendar days before the training is to begin. The Department will review material and approve or request changes.

The DMS Manufacturer shall record the entire training on DVD and shall provide DVD's to the Department for later use.

The training session(s) shall be conducted at a facility provided by the Department, after the completion of all system integration tests. The schedule of the training sessions shall be established by the DMS Manufacturer with the approval of the Department.

## WARRANTY

The equipment and parts furnished for the dynamic message sign system shall be new, of the latest model, fabricated under high quality standards.

Equipment and parts furnished for the dynamic message sign system shall be warranted by the manufacturer to be free from defects in assembly or fabrication and materials for a minimum of two (2) years from the date of final acceptance. If component manufacture's warranties are for a longer period, they shall apply. Any parts or equipment found to be defective and/or determined to be a failure in design, materials and workmanship during the warranty period shall be replaced free of charge.

The Department shall be furnished with a certification stating that the equipment, parts, and material are covered by a warranty. Company contact information and warranty dates should be clearly shown.

All manufacturer's warranties and guarantees for the dynamic message sign system shall be transferred to the Department on the date of final acceptance.

Replacement parts covered in the section shall be shipped within one week of the Department notifying the DMS Manufacturer of a failed part or operational problem.

## **BASIS OF PAYMENT**

The work performed and materials furnished in accordance with this Item and measured will be paid for at the contract unit price each for TRUSS MOUNTED LED DYNAMIC MESSAGE SIGN. This price shall be full compensation for furnishing, placing and testing all materials and equipment, and for all tools, labor, equipment, hardware, operational software package(s), supplies, support, personnel training, shop drawing and documentation necessary to complete the work.

## **CELLULAR MODEM**

The Cellular Modem shall be an Airlink model Raven-X or equivalent. The modem shall communicate to the Department's Local Area Network over the public internet protocol (IP) address procured with the modem. A static, non-changing IP address shall be configured by the Contractor for the modem. Only one IP address shall be provided for the modem. The IP address shall be determined by working with the Department to ensure the address is consistent with the established IP system. The Cellular Modem shall be configured by the Contractor in order to maximize the data transmission for the area the modem is being installed in. All necessary cabling, antennas, and ancillary equipment shall be included in the cost of this pay item.

The Cellular Modem shall be compatible with the Verizon Wireless cellular wireless network. The Contractor shall be responsible for all fees associated with the cellular service plan during the duration of the contract. The initialization and monthly cellular service fees shall be paid for under Article 109.05. The monthly cellular service fees shall be transferred to the Department at the end of the contract.

Documentation detailing the bandwidth availability and utilization for each site shall be provided to the Department by the Contractor. The device's necessary configuration software shall be loaded on three Department PCs and all required licenses shall be included in the cost of this pay item. The licenses shall be valid for a minimum of 2 years. The Cellular Modem shall have the following physical and operating properties or equivalent:

### **PHYSICAL CHARACTERISTICS:**

- Weight: < 1 lb.
- Size: 3" wide x 1.1" high x 5.1" long
- Status LEDs
- RF Primary Antenna Connector: 50 Ohm SMA
- RF Receive Diversity Antenna Connector: 50 Ohm SMA
- Ethernet 10/100 Mbps Interface: RJ-45 Connector
- RS-232: DB9 DCE (1200-230400 baud)

### **DATA SERVICES**

- CDMA EV-DO Rev A
- CDMA 1xEVDO Release 0
- CDMA 1xRTT
- CDMS IS-95

**ENVIRONMENTAL:**

Operating ranges: -30°C to 70°C  
Humidity: 5%-95% Non-condensing

**RF FEATURES:**

Full duplex transceiver  
Dual-band support for both 800 MHz cellular and 1.9 GHz PCS bands  
Dual band Receive Diversity

**POWER MANAGEMENT FEATURES:**

Transmit/Receive (Typ/Max) 239/270 mA  
Low power consumption  
Dormant connection: 85 ma at 12 VDC

This work will be paid for at the contract unit price each for CELLULAR MODEM, which price shall be payment in full for furnishing, installing, programming and configuring a Cellular Modem, with necessary ancillary equipment, connections and adjustments for proper operations to the satisfaction of the Engineer.

**CONDUIT ATTACHED TO STRUCTURE, 3" DIA., ALUMINUM**

This work shall consist of work that is described in Section 811 of the Standard Specifications.

This work shall be paid at the contract unit price per foot for CONDUIT ATTACHED TO STRUCTURE, 3" DIA., ALUMINUM.

**CONDUIT IN TRENCH 4" DIA., PVC TYPE C**

This work shall consist of work that is described in Section 810 of the Standard Specifications.

All in ground 4" conduit used in the installation for the fiber backbone will be Opti-com Type C PVC with Opti-com 44R Ribbed Polyethylene Inner duct with four (4) 1.263" inside diameter ducts or Carlon Multi Gard, Multi-Cell PVC Type C with four (4) 1.19" inside diameter ducts or equivalent. Each innerduct shall be of a different color. The color shall be consistent throughout the system so that the white inner duct is always matched with white, blue with blue, etc. A pull rope shall be installed in each inner duct.

This work shall consist of furnishing and installing 4" conduit in trench shall be Opti-com Standard Type C with Opti-com 44R Ribbed Polyethylene Inner duct with 4 1.263" inside diameter ducts or equivalent, including all fittings and accessories at the locations specified on the plans.

The conduit shall comply with NEMA TC10 with the exception of 3" bell (6" bell is acceptable). "NEMA TC10" shall be stamped on all conduit.

This work shall be paid at the contract unit price per foot for CONDUIT IN TRENCH 4" DIA., PVC TYPE C.



**APPROVAL OF PROPOSED BORROW AREAS, USE AREAS, AND/OR WASTE AREAS  
INSIDE ILLINOIS STATE BORDERS (BDE)**

Effective: November 1, 2008

Revise the title of Article 107.22 of the Standard Specifications to read:

**“107.22 Approval of Proposed Borrow Areas, Use Areas, and/or Waste Areas Inside Illinois State Borders.”**

Add the following sentence to the end of the first paragraph of Article 107.22 of the Standard Specifications:

“Proposed borrow areas, use areas, and/or waste areas outside of Illinois shall comply with Article 107.01.”

**CEMENT (BDE)**

Effective: January 1, 2007

Revised: April 1, 2009

Revise Section 1001 of the Standard Specifications to read:

**“SECTION 1001. CEMENT**

**1001.01 Cement Types.** Cement shall be according to the following.

- (a) Portland Cement. Acceptance of portland cement shall be according to the current Bureau of Materials and Physical Research’s Policy Memorandum, “Portland or Blended Cement Acceptance Procedure for Qualified and Non-Qualified Plants”.

Portland cement shall be according to ASTM C 150, and shall meet the standard physical and chemical requirements. Type I or Type II may be used for cast-in-place, precast, and precast prestressed concrete. Type III may be used according to Article 1020.04, or when approved by the Engineer. All other cements referenced in ASTM C 150 may be used when approved by the Engineer.

The total of all organic processing additions shall be a maximum of 1.0 percent by weight (mass) of the cement. The total of all inorganic processing additions shall be a maximum of 4.0 percent by weight (mass) of the cement. However, a cement kiln dust inorganic processing addition shall be limited to a maximum of 1.0 percent. Organic processing additions shall be limited to grinding aids that improve the flowability of cement, reduce pack set, and improve grinding efficiency. Inorganic processing additions shall be limited to granulated blast-furnace slag according to the chemical requirements of AASHTO M 302, Class C fly ash according to the chemical requirements of AASHTO M 295, and cement kiln dust.

- (b) Portland-Pozzolan Cement. Acceptance of portland-pozzolan cement shall be according to the current Bureau of Materials and Physical Research’s Policy Memorandum, “Portland or Blended Cement Acceptance Procedure for Qualified and Non-Qualified Plants”.

Portland-pozzolan cement shall be according to ASTM C 595 and shall meet the standard physical and chemical requirements. Type IP may be used for cast-in-place, precast, and precast prestressed concrete, except when Class PP concrete is used. The pozzolan constituent for Type IP shall be a maximum of 21 percent of the weight (mass) of the portland-pozzolan cement.

For cast-in-place construction, portland-pozzolan cement shall not be used in concrete mixtures when the air temperature is below 40 °F (4 °C) without permission of the Engineer. If permission is given, the mix design strength requirement may require the Contractor to increase the cement or eliminate the cement factor reduction for a water-reducing or high range water-reducing admixture which is permitted according to Article 1020.05(b).

The total of all organic processing additions shall be a maximum of 1.0 percent by weight (mass) of the cement. Organic processing additions shall be limited to grinding aids as defined in (a) above. Inorganic processing additions shall be limited to cement kiln dust at a maximum of 1.0 percent.

- (c) Portland Blast-Furnace Slag Cement. Acceptance of portland blast-furnace slag cement shall be according to the current Bureau of Materials and Physical Research's Policy Memorandum, "Portland or Blended Cement Acceptance Procedure for Qualified and Non-Qualified Plants".

Portland blast-furnace slag cement shall be according to ASTM C 595 and shall meet the standard physical and chemical requirements. Type IS portland blast-furnace slag cement may be used for cast-in-place, precast, and precast prestressed concrete, except when Class PP concrete is used. The blast-furnace slag constituent for Type IS shall be a maximum of 25 percent of the weight (mass) of the portland blast-furnace slag cement.

For cast-in-place construction, portland blast-furnace slag cement shall not be used in concrete mixtures when the air temperature is below 40 °F (4 °C) without permission of the Engineer. If permission is given, the mix design strength requirement may require the Contractor to increase the cement or eliminate the cement factor reduction for a water-reducing or high range water-reducing admixture which is permitted according to Article 1020.05(b).

The total of all organic processing additions shall be a maximum of 1.0 percent by weight (mass) of the cement. Organic processing additions shall be limited to grinding aids as defined in (a) above. Inorganic processing additions shall be limited to cement kiln dust at a maximum of 1.0 percent.

- (d) Rapid Hardening Cement. Rapid hardening cement shall be used according to Article 1020.04 or when approved by the Engineer. The cement shall be on the Department's current "Approved List of Packaged, Dry, Rapid Hardening Cementitious Materials for Concrete Repairs", and shall be according to the following.

- (1) The cement shall have a maximum final set of 25 minutes, according to Illinois Modified ASTM C 191.

- (2) The cement shall have a minimum compressive strength of 2000 psi (13,800 kPa) at 3.0 hours, 3200 psi (22,100 kPa) at 6.0 hours, and 4000 psi (27,600 kPa) at 24.0 hours, according to Illinois Modified ASTM C 109.
  - (3) The cement shall have a maximum drying shrinkage of 0.050 percent at seven days, according to Illinois Modified ASTM C 596.
  - (4) The cement shall have a maximum expansion of 0.020 percent at 14 days, according to Illinois Modified ASTM C 1038.
  - (5) The cement shall have a minimum 80 percent relative dynamic modulus of elasticity; and shall not have a weight (mass) gain in excess of 0.15 percent or a weight (mass) loss in excess of 1.0 percent, after 100 cycles, according to AASHTO T 161, Procedure B.
- (e) Calcium Aluminate Cement. Calcium aluminate cement shall be used only where specified by the Engineer. The cement shall meet the standard physical requirements for Type I cement according to ASTM C 150, except the time of setting shall not apply. The chemical requirements shall be determined according to ASTM C 114 and shall be as follows: minimum 38 percent aluminum oxide ( $Al_2O_3$ ), maximum 42 percent calcium oxide (CaO), maximum 1 percent magnesium oxide (MgO), maximum 0.4 percent sulfur trioxide ( $SO_3$ ), maximum 1 percent loss on ignition, and maximum 3.5 percent insoluble residue.

**1001.02 Uniformity of Color.** Cement contained in single loads or in shipments of several loads to the same project shall not have visible differences in color.

**1001.03 Mixing Brands and Types.** Different brands or different types of cement from the same manufacturing plant, or the same brand or type from different plants shall not be mixed or used alternately in the same item of construction unless approved by the Engineer.

**1001.04 Storage.** Cement shall be stored and protected against damage, such as dampness which may cause partial set or hardened lumps. Different brands or different types of cement from the same manufacturing plant, or the same brand or type from different plants shall be kept separate.”

## **CONCRETE ADMIXTURES (BDE)**

Effective: January 1, 2003

Revised: April 1, 2009

Replace the first paragraph of Article 1020.05(b) of the Standard Specifications to read:

- “(b) Admixtures. The use of admixtures to increase the workability or to accelerate the hardening of the concrete will be permitted when approved by the Engineer. Admixture dosages shall result in the mixture meeting the specified plastic and hardened properties. The Department will maintain an Approved List of Corrosion Inhibitors. Corrosion inhibitor dosage rates shall be according to Article 1020.05(b)(12). The Department will also maintain an Approved List of Concrete Admixtures, and an admixture technical representative shall be consulted when determining an admixture dosage from this list.

The dosage shall be within the range indicated on the approved list unless the influence by other admixtures, jobsite conditions (such as a very short haul time), or other circumstances warrant a dosage outside the range. The Engineer shall be notified when a dosage is proposed outside the range. To determine an admixture dosage, air temperature, concrete temperature, cement source and quantity, finely divided mineral sources(s) and quantity, influence of other admixtures, haul time, placement conditions, and other factors as appropriate shall be considered. The Engineer may request the Contractor to have a batch of concrete mixed in the lab or field to verify the admixture dosage is correct. An admixture dosage or combination of admixture dosages shall not delay the initial set of concrete by more than one hour. When a retarding admixture is required or appropriate for a bridge deck or bridge deck overlay pour, the initial set time shall be delayed until the deflections due to the concrete dead load are no longer a concern for inducing cracks in the completed work. However, a retarding admixture shall not be used to further extend the pour time and justify the alteration of a bridge deck pour sequence.

When determining water in admixtures for water/cement ratio, the Contractor shall calculate 70 percent of the admixture dosage as water, except a value of 50 percent shall be used for a latex admixture used in bridge deck latex concrete overlays.”

Revise Section 1021 of the Standard Specifications to read:

#### **“SECTION 1021. CONCRETE ADMIXTURES**

**1021.01 General.** Admixtures shall be furnished in liquid form ready for use. The admixtures shall be delivered in the manufacturer's original containers, bulk tank trucks or such containers or tanks as are acceptable to the Engineer. Delivery shall be accompanied by a ticket which clearly identifies the manufacturer and trade name of the material. Containers shall be readily identifiable as to manufacturer and trade name of the material they contain.

Corrosion inhibitors will be maintained on the Department's Approved List of Corrosion Inhibitors. All other concrete admixture products will be maintained on the Department's Approved List of Concrete Admixtures. For the admixture submittal, a report prepared by an independent laboratory accredited by the AASHTO Materials Reference Laboratory (AMRL) for Portland Cement Concrete shall be provided. The report shall show the results of physical tests conducted no more than five years prior to the time of submittal, according to applicable specifications. However, for corrosion inhibitors the ASTM G 109 test information specified in ASTM C 1582 is not required to be from and independent lab. All other information in ASTM C 1582 shall be from and independent lab.

Tests shall be conducted using materials and methods specified on a "test" concrete and a "reference" concrete, together with a certification that no changes have been made in the formulation of the material since the performance of the tests. Per the manufacturer's option, the cement content for all required tests shall either be according to applicable specifications or 5.65 cwt/cu yd (335 kg/cu m). Compressive strength test results for six months and one year will not be required.

Prior to the approval of an admixture, the Engineer reserves the right to request a sample for testing. The test and reference concrete mixtures tested by the Engineer will contain a cement content of 5.65 cwt/cu yd (335 kg/cu m).

For freeze-thaw testing, the Department will perform the test according to AASHTO T 161, Procedure B. The flexural strength test will be performed according to AASHTO T 177. If the Engineer decides to test the admixture, the manufacturer shall submit AASHTO T 197 water content and set time test results on the standard cement used by the Department. The test and reference concrete mixture shall contain a cement content of 5.65 cwt/cu yd (335 kg/cu m). The manufacturer may select their lab or an independent lab to perform this testing. The laboratory is not required to be accredited by AASHTO.

The manufacturer shall include in the submittal the following admixture information: the manufacturing range for specific gravity, the midpoint and manufacturing range for residue by oven drying, and the manufacturing range for pH. The submittal shall also include an infrared spectrophotometer trace no more than five years old.

For air-entraining admixtures according to Article 1021.02, the specific gravity allowable manufacturing range shall be established by the manufacturer and the test method shall be according to ASTM C 494. For residue by oven drying and pH, the allowable manufacturing range and test methods shall be according to ASTM C 260.

For admixtures according to Articles 1021.03, 1021.04, 1021.05, 1021.06, and 1021.07, the pH allowable manufacturing range shall be established by the manufacturer and the test method shall be according to ASTM E 70. For specific gravity and residue by oven drying, the allowable manufacturing range and test methods shall be according to ASTM C 494.

When test results are more than seven years old, the manufacturer shall re-submit the infrared spectrophotometer trace and the report prepared by an independent laboratory accredited by AASHTO.

All admixtures, except chloride-based accelerators, shall contain a maximum of 0.3 percent chloride by weight (mass).

Random field samples may be taken by the Department to verify an admixture meets specification. A split sample will be provided to the manufacturer if requested. Admixtures that do not meet specification requirements or an allowable manufacturing range established by the manufacturer shall be replaced with new material.

**1021.02 Air-Entraining Admixtures.** Air-entraining admixtures shall be according to AASHTO M 154.

**1021.03 Retarding and Water-Reducing Admixtures.** The admixture shall be according to the following.

- (a) The retarding admixture shall be according to AASHTO M 194, Type B (retarding) or Type D (water-reducing and retarding).
- (b) The water-reducing admixture shall be according to AASHTO M 194, Type A.
- (c) The high range water-reducing admixture shall be according to AASHTO M 194, Type F (high range water-reducing) or Type G (high range water-reducing and retarding).

**1021.04 Accelerating Admixtures.** The admixture shall be according to AASHTO M 194, Type C (accelerating) or Type E (water reducing and accelerating).

**1021.05 Self-Consolidating Admixtures.** The self-consolidating admixture system shall consist of either a high range water-reducing admixture only or a high range water-reducing admixture combined with a separate viscosity modifying admixture. The one or two component admixture system shall be capable of producing a concrete mixture that can flow around reinforcement and consolidate under its own weight without additional effort and without segregation.

The high range water-reducing admixture shall be according to AASHTO M 194, Type F.

The viscosity modifying admixture shall be according to ASTM C 494, Type S (specific performance).

**1021.06 Rheology-Controlling Admixture.** The rheology-controlling admixture shall be capable of producing a concrete mixture with a lower yield stress that will consolidate easier for slipform applications used by the Contractor. The rheology-controlling admixture shall be according to ASTM C 494, Type S (specific performance).

**1021.07 Corrosion Inhibitor.** The corrosion inhibitor shall be according to one of the following.

- (a) Calcium Nitrite. The corrosion inhibitor shall contain a minimum 30 percent calcium nitrite by weight (mass) of solution, and shall comply with the requirements of AASHTO M 194, Type C (accelerating).
- (b) Other Materials. The corrosion inhibitor shall be according to ASTM C 1582.”

## **CONSTRUCTION AIR QUALITY - DIESEL VEHICLE EMISSIONS CONTROL (BDE)**

Effective: April 1, 2009

Revised: July 1, 2009

Diesel Vehicle Emissions Control. The reduction of construction air emissions shall be accomplished by using cleaner burning diesel fuel. The term “equipment” refers to any and all diesel fuel powered devices rated at 50 hp and above, to be used on the project site in excess of seven calendar days over the course of the construction period on the project site (including any “rental” equipment).

All equipment on the jobsite, with engine ratings of 50 hp and above, shall be required to: use Ultra Low Sulfur Diesel fuel (ULSD) exclusively (15 ppm sulfur content or less).

Diesel powered equipment in non-compliance will not be allowed to be used on the project site, and is also subject to a notice of non-compliance as outlined below.

The Contractor shall submit copies of monthly summary reports and include certified copies of the ULSD diesel fuel delivery slips for diesel fuel delivered to the jobsite for the reporting time period, noting the quantity of diesel fuel used.

If any diesel powered equipment is found to be in non-compliance with any portion of this specification, the Engineer will issue the Contractor a notice of non-compliance and identify an appropriate period of time, as outlined below under environmental deficiency deduction, in which to bring the equipment into compliance or remove it from the project site.

Any costs associated with bringing any diesel powered equipment into compliance with these diesel vehicle emissions controls shall be considered as included in the contract unit prices bid for the various items of work involved and no additional compensation will be allowed. The Contractor's compliance with this notice and any associated regulations shall also not be grounds for a claim.

Environmental Deficiency Deduction. When the Engineer is notified, or determines that an environmental control deficiency exists, he/she will notify the Contractor in writing, and direct the Contractor to correct the deficiency within a specified time period. The specified time-period, which begins upon Contractor notification, will be from 1/2 hour to 24 hours long, based on the urgency of the situation and the nature of the deficiency. The Engineer shall be the sole judge regarding the time period.

The deficiency will be based on lack of repair, maintenance and diesel vehicle emissions control.

If the Contractor fails to correct the deficiency within the specified time frame, a daily monetary deduction will be imposed for each calendar day or fraction thereof the deficiency continues to exist. The calendar day(s) will begin when the time period for correction is exceeded and end with the Engineer's written acceptance of the correction. The daily monetary deduction will be \$1,000.00 for each deficiency identified.

If a Contractor or subcontractor accumulates three environmental deficiency deductions in a contract period, the Contractor will be shutdown until the deficiency is corrected. Such a shutdown will not be grounds for any extension of contract time, waiver of penalties, or be grounds for any claim.

### **CONSTRUCTION AIR QUALITY - IDLING RESTRICTIONS (BDE)**

Effective: April 1, 2009

Idling Restrictions. The Contractor shall establish truck-staging areas for all diesel powered vehicles that are waiting to load or unload material at the jobsite. Staging areas shall be located where the diesel emissions from the equipment will have a minimum impact on adjacent sensitive receptors. The Department will review the selection of staging areas, whether within or outside the existing highway right-of-way, to avoid locations near sensitive areas or populations to the extent possible. Sensitive receptors include, but are not limited to, hospitals, schools, residences, motels, hotels, daycare facilities, elderly housing and convalescent facilities. Diesel powered engines shall also be located as far away as possible from fresh air intakes, air conditioners, and windows. The Engineer will approve staging areas before implementation.

Diesel powered vehicle operators may not cause or allow the motor vehicle, when it is not in motion, to idle for more than a total of 10 minutes within any 60 minute period, except under any of the following circumstances:

- 1) The motor vehicle has a gross vehicle weight rating of less than 8000 lb (3630 kg).
- 2) The motor vehicle idles while forced to remain motionless because of on-highway traffic, an official traffic control device or signal, or at the direction of a law enforcement official.

- 3) The motor vehicle idles when operating defrosters, heaters, air conditioners, or other equipment solely to prevent a safety or health emergency.
- 4) A police, fire, ambulance, public safety, other emergency or law enforcement motor vehicle, or any motor vehicle used in an emergency capacity, idles while in an emergency or training mode and not for the convenience of the vehicle operator.
- 5) The primary propulsion engine idles for maintenance, servicing, repairing, or diagnostic purposes if idling is necessary for such activity.
- 6) A motor vehicle idles as part of a government inspection to verify that all equipment is in good working order, provided idling is required as part of the inspection.
- 7) When idling of the motor vehicle is required to operate auxiliary equipment to accomplish the intended use of the vehicle (such as loading, unloading, mixing, or processing cargo; controlling cargo temperature; construction operations, lumbering operations; oil or gas well servicing; or farming operations), provided that this exemption does not apply when the vehicle is idling solely for cabin comfort or to operate non-essential equipment such as air conditioning, heating, microwave ovens, or televisions.
- 8) When the motor vehicle idles due to mechanical difficulties over which the operator has no control.
- 9) The outdoor temperature is less than 32 °F (0 °C) or greater than 80 °F (26 °C).

When the outdoor temperature is greater than or equal to 32 °F (0 °C) or less than or equal to 80 °F (26 °C), a person who operates a motor vehicle operating on diesel fuel shall not cause or allow the motor vehicle to idle for a period greater than 30 minutes in any 60 minute period while waiting to weigh, load, or unload cargo or freight, unless the vehicle is in a line of vehicles that regularly and periodically moves forward.

The above requirements do not prohibit the operation of an auxiliary power unit or generator set as an alternative to idling the main engine of a motor vehicle operating on diesel fuel.

Environmental Deficiency Deduction. When the Engineer is notified, or determines that an environmental control deficiency exists based on non-compliance with the idling restrictions, he/she will notify the Contractor, and direct the Contractor to correct the deficiency.

If the Contractor fails to correct the deficiency a monetary deduction will be imposed. The monetary deduction will be \$1,000.00 for each deficiency identified.

#### **DISADVANTAGED BUSINESS ENTERPRISE PARTICIPATION (BDE)**

Effective: September 1, 2000

Revised: January 1, 2010

FEDERAL OBLIGATION. The Department of Transportation, as a recipient of federal financial assistance, is required to take all necessary and reasonable steps to ensure nondiscrimination in the award and administration of contracts. Consequently, the federal regulatory provisions of 49 CFR part 26 apply to this contract concerning the utilization of disadvantaged business enterprises. For the purposes of this Special Provision, a disadvantaged business enterprise (DBE) means a business certified by the Department in accordance with the requirements of 49 CFR part 26 and listed in the Illinois Unified Certification Program (IL UCP) DBE Directory.

STATE OBLIGATION. This Special Provision will also be used by the Department to satisfy the requirements of the Business Enterprise for Minorities, Females, and Persons with Disabilities Act, 30 ILCS 575.



When this Special Provision is used to satisfy state law requirements on 100 percent state-funded contracts, the federal government has no involvement in such contracts (not a federal-aid contract) and no responsibility to oversee the implementation of this Special Provision by the Department on those contracts. DBE participation on 100 percent state-funded contracts will not be credited toward fulfilling the Department's annual overall DBE goal required by the US Department of Transportation to comply with the federal DBE program requirements.

CONTRACTOR ASSURANCE. The Contractor makes the following assurance and agrees to include the assurance in each subcontract that the Contractor signs with a subcontractor:

The Contractor, subrecipient, or subcontractor shall not discriminate on the basis of race, color, national origin, or sex in the performance of this contract. The Contractor shall carry out applicable requirements of 49 CFR part 26 in the award and administration of contracts funded in whole or in part with federal or state funds. Failure by the Contractor to carry out these requirements is a material breach of this contract, which may result in the termination of this contract or such other remedy as the recipient deems appropriate.

OVERALL GOAL SET FOR THE DEPARTMENT. As a requirement of compliance with 49 CFR part 26, the Department has set an overall goal for DBE participation in its federally assisted contracts. That goal applies to all federal-aid funds the Department will expend in its federally assisted contracts for the subject reporting fiscal year. The Department is required to make a good faith effort to achieve the overall goal. The dollar amount paid to all approved DBE companies performing work called for in this contract is eligible to be credited toward fulfillment of the Department's overall goal.

CONTRACT GOAL TO BE ACHIEVED BY THE CONTRACTOR. This contract includes a specific DBE utilization goal established by the Department. The goal has been included because the Department has determined that the work of this contract has subcontracting opportunities that may be suitable for performance by DBE companies. This determination is based on an assessment of the type of work, the location of the work, and the availability of DBE companies to do a part of the work. The assessment indicates that, in the absence of unlawful discrimination, and in an arena of fair and open competition, DBE companies can be expected to perform 5.0% of the work. This percentage is set as the DBE participation goal for this contract. Consequently, in addition to the other award criteria established for this contract, the Department will only award this contract to a bidder who makes a good faith effort to meet this goal of DBE participation in the performance of the work. A bidder makes a good faith effort for award consideration if either of the following is done in accordance with the procedures set forth in this Special Provision:

- (a) The bidder documents that enough DBE participation has been obtained to meet the goal; or
- (b) The bidder documents that a good faith effort has been made to meet the goal, even though the effort did not succeed in obtaining enough DBE participation to meet the goal.

DBE LOCATOR REFERENCES. Bidders may consult the IL UCP DBE Directory as a reference source for DBE-certified companies. In addition, the Department maintains a letting and item specific DBE locator information system whereby DBE companies can register their interest in providing quotes on particular bid items advertised for letting.

Information concerning DBE companies willing to quote work for particular contracts may be obtained by contacting the Department's Bureau of Small Business Enterprises at telephone number (217)785-4611, or by visiting the Department's web site at [www.dot.il.gov](http://www.dot.il.gov).

**BIDDING PROCEDURES.** Compliance with this Special Provision is a material bidding requirement. The failure of the bidder to comply will render the bid not responsive.

- (a) The bidder shall submit a Disadvantaged Business Utilization Plan on Department forms SBE 2025 and 2026 with the bid.
- (b) The Utilization Plan shall indicate that the bidder either has obtained sufficient DBE participation commitments to meet the contract goal or has not obtained enough DBE participation commitments in spite of a good faith effort to meet the goal. The Utilization Plan shall further provide the name, telephone number, and telefax number of a responsible official of the bidder designated for purposes of notification of plan approval or disapproval under the procedures of this Special Provision.
- (c) The Utilization Plan shall include a DBE Participation Commitment Statement, Department form SBE 2025, for each DBE proposed for the performance of work to achieve the contract goal. For bidding purposes, submission of the completed SBE 2025 forms, signed by the DBEs and faxed to the bidder will be acceptable as long as the original is available and provided upon request. All elements of information indicated on the said form shall be provided, including but not limited to the following:
  - (1) The names and addresses of DBE firms that will participate in the contract;
  - (2) A description, including pay item numbers, of the work each DBE will perform;
  - (3) The dollar amount of the participation of each DBE firm participating. The dollar amount of participation for identified work shall specifically state the quantity, unit price, and total subcontract price for the work to be completed by the DBE. If partial pay items are to be performed by the DBE, indicate the portion of each item, a unit price where appropriate and the subcontract price amount;
  - (4) DBE Participation Commitment Statements, form SBE 2025, signed by the bidder and each participating DBE firm documenting the commitment to use the DBE subcontractors whose participation is submitted to meet the contract goal;
  - (5) If the bidder is a joint venture comprised of DBE companies and non-DBE companies, the plan must also include a clear identification of the portion of the work to be performed by the DBE partner(s); and,
  - (6) If the contract goal is not met, evidence of good faith efforts.

**GOOD FAITH EFFORT PROCEDURES.** The contract will not be awarded until the Utilization Plan submitted by the apparent successful bidder is approved. All information submitted by the bidder must be complete, accurate and adequately document the good faith efforts of the bidder before the Department will commit to the performance of the contract by the bidder. The Utilization Plan will be approved by the Department if the Utilization Plan commits sufficient commercially useful DBE work performance to meet the contract goal or the bidder submits sufficient documentation of a good faith effort to meet the contract goal pursuant to 49 CFR part 26, Appendix A. The Utilization Plan will not be approved by the Department if the Utilization Plan does not commit sufficient DBE participation to meet the contract goal unless the apparent successful bidder documented in the Utilization Plan that it made a good faith effort to meet the goal.

This means that the bidder must show that all necessary and reasonable steps were taken to achieve the contract goal. Necessary and reasonable steps are those which, by their scope, intensity and appropriateness to the objective, could reasonably be expected to obtain sufficient DBE participation, even if they were not successful. The Department will consider the quality, quantity, and intensity of the kinds of efforts that the bidder has made. Mere *pro forma* efforts, in other words, efforts done as a matter of form, are not good faith efforts; rather, the bidder is expected to have taken genuine efforts that would be reasonably expected of a bidder actively and aggressively trying to obtain DBE participation sufficient to meet the contract goal.

- (a) The following is a list of types of action that the Department will consider as part of the evaluation of the bidder's good faith efforts to obtain participation. These listed factors are not intended to be a mandatory checklist and are not intended to be exhaustive. Other factors or efforts brought to the attention of the Department may be relevant in appropriate cases, and will be considered by the Department.
  - (1) Soliciting through all reasonable and available means (e.g. attendance at pre-bid meetings, advertising and/or written notices) the interest of all certified DBE companies that have the capability to perform the work of the contract. The bidder must solicit this interest within sufficient time to allow the DBE companies to respond to the solicitation. The bidder must determine with certainty if the DBE companies are interested by taking appropriate steps to follow up initial solicitations.
  - (2) Selecting portions of the work to be performed by DBE companies in order to increase the likelihood that the DBE goals will be achieved. This includes, where appropriate, breaking out contract work items into economically feasible units to facilitate DBE participation, even when the prime Contractor might otherwise prefer to perform these work items with its own forces.
  - (3) Providing interested DBE companies with adequate information about the plans, specifications, and requirements of the contract in a timely manner to assist them in responding to a solicitation.
  - (4) a. Negotiating in good faith with interested DBE companies. It is the bidder's responsibility to make a portion of the work available to DBE subcontractors and suppliers and to select those portions of the work or material needs consistent with the available DBE subcontractors and suppliers, so as to facilitate DBE participation. Evidence of such negotiation includes the names, addresses, and telephone numbers of DBE companies that were considered; a description of the information provided regarding the plans and specifications for the work selected for subcontracting; and evidence as to why additional agreements could not be reached for DBE companies to perform the work.
    - b. A bidder using good business judgment would consider a number of factors in negotiating with subcontractors, including DBE subcontractors, and would take a firm's price and capabilities as well as contract goals into consideration. However, the fact that there may be some additional costs involved in finding and using DBE companies is not in itself sufficient reason for a bidder's failure to meet the contract DBE goal, as long as such costs are reasonable. Also, the ability or desire of a bidder to perform the work of a contract with its own organization does not relieve the bidder of the responsibility to make good faith efforts.

Bidders are not, however, required to accept higher quotes from DBE companies if the price difference is excessive or unreasonable.

- (5) Not rejecting DBE companies as being unqualified without sound reasons based on a thorough investigation of their capabilities. The bidder's standing within its industry, membership in specific groups, organizations, or associations and political or social affiliations (for example union vs. non-union employee status) are not legitimate causes for the rejection or non-solicitation of bids in the bidder's efforts to meet the project goal.
  - (6) Making efforts to assist interested DBE companies in obtaining bonding, lines of credit, or insurance as required by the recipient or Contractor.
  - (7) Making efforts to assist interested DBE companies in obtaining necessary equipment, supplies, materials, or related assistance or services.
  - (8) Effectively using the services of available minority/women community organizations; minority/women contractors' groups; local, state, and federal minority/women business assistance offices; and other organizations as allowed on a case-by-case basis to provide assistance in the recruitment and placement of DBE companies.
- (b) If the Department determines that the apparent successful bidder has made a good faith effort to secure the work commitment of DBE companies to meet the contract goal, the Department will award the contract provided that it is otherwise eligible for award. If the Department determines that the bidder has failed to meet the requirements of this Special Provision and that a good faith effort has not been made, the Department will notify the responsible company official designated in the Utilization Plan that the bid is not responsive. The notification shall include a statement of reasons why good faith efforts have not been found.
- (c) The bidder may request administrative reconsideration of a determination adverse to the bidder within the five working days after receipt of the notification date of the determination by delivering the request to the Department of Transportation, Bureau of Small Business Enterprises, Contract Compliance Section, 2300 South Dirksen Parkway, Room 319, Springfield, Illinois 62764 (Telefax: (217)785-1524). Deposit of the request in the United States mail on or before the fifth business day shall not be deemed delivery. The determination shall become final if a request is not made and delivered. A request may provide additional written documentation and/or argument concerning the issue of whether an adequate good faith effort was made to meet the contract goal. The request will be forwarded to the Department's Reconsideration Officer. The Reconsideration Officer will extend an opportunity to the bidder to meet in person in order to consider all issues of whether the bidder made a good faith effort to meet the goal. After the review by the Reconsideration Officer, the bidder will be sent a written decision within ten working days after receipt of the request for reconsideration, explaining the basis for finding that the bidder did or did not meet the goal or make adequate good faith efforts to do so. A final decision by the Reconsideration Officer that a good faith effort was made shall approve the Utilization Plan submitted by the bidder and shall clear the contract for award. A final decision that a good faith effort was not made shall render the bid not responsive.

CALCULATING DBE PARTICIPATION. The Utilization Plan values represent work anticipated to be performed and paid for upon satisfactory completion. The Department is only able to count toward the achievement of the overall goal and the contract goal the value of payments made for the work actually performed by DBE companies. In addition, a DBE must perform a commercially useful function on the contract to be counted. A commercially useful function is generally performed when the DBE is responsible for the work and is carrying out its responsibilities by actually performing, managing, and supervising the work involved. The Department and Contractor are governed by the provisions of 49 CFR part 26.55(c) on questions of commercially useful functions as it affects the work. Specific counting guidelines are provided in 49 CFR part 26.55, the provisions of which govern over the summary contained herein.

- (a) DBE as the Contractor: 100 percent goal credit for that portion of the work performed by the DBE's own forces, including the cost of materials and supplies. Work that a DBE subcontracts to a non-DBE does not count toward the DBE goals.
- (b) DBE as a joint venture Contractor: 100 percent goal credit for that portion of the total dollar value of the contract equal to the distinct, clearly defined portion of the work performed by the DBE's own forces.
- (c) DBE as a subcontractor: 100 percent goal credit for the work of the subcontract performed by the DBE's own forces, including the cost of materials and supplies, excluding the purchase of materials and supplies or the lease of equipment by the DBE subcontractor from the prime Contractor or its affiliates. Work that a DBE subcontractor in turn subcontracts to a non-DBE does not count toward the DBE goal.
- (d) DBE as a trucker: 100 percent goal credit for trucking participation provided the DBE is responsible for the management and supervision of the entire trucking operation for which it is responsible. At least one truck owned, operated, licensed, and insured by the DBE must be used on the contract. Credit will be given for the following:
  - (1) The DBE may lease trucks from another DBE firm, including an owner-operator who is certified as a DBE. The DBE who leases trucks from another DBE receives credit for the total value of the transportation services the lessee DBE provides on the contract.
  - (2) The DBE may also lease trucks from a non-DBE firm, including from an owner-operator. The DBE who leases trucks from a non-DBE is entitled to credit only for the fee or commission it receives as a result of the lease arrangement.
- (e) DBE as a material supplier:
  - (1) 60 percent goal credit for the cost of the materials or supplies purchased from a DBE regular dealer.
  - (2) 100 percent goal credit for the cost of materials or supplies obtained from a DBE manufacturer.
  - (3) 100 percent credit for the value of reasonable fees and commissions for the procurement of materials and supplies if not a regular dealer or manufacturer.

CONTRACT COMPLIANCE. Compliance with this Special Provision is an essential part of the contract.

The Department is prohibited by federal regulations from crediting the participation of a DBE included in the Utilization Plan toward either the contract goal or the Department's overall goal until the amount to be applied toward the goals has been paid to the DBE. The following administrative procedures and remedies govern the compliance by the Contractor with the contractual obligations established by the Utilization Plan. After approval of the Utilization Plan and award of the contract, the Utilization Plan and individual DBE Participation Statements become part of the contract. If the Contractor did not succeed in obtaining enough DBE participation to achieve the advertised contract goal, and the Utilization Plan was approved and contract awarded based upon a determination of good faith, the total dollar value of DBE work calculated in the approved Utilization Plan as a percentage of the awarded contract value shall become the amended contract goal.

- (a) No amendment to the Utilization Plan may be made without prior written approval from the Department's Bureau of Small Business Enterprises. All requests for amendment to the Utilization Plan shall be submitted to the Department of Transportation, Bureau of Small Business Enterprises, Contract Compliance Section, 2300 South Dirksen Parkway, Room 319, Springfield, Illinois 62764. Telephone number (217) 785-4611. Telefax number (217) 785-1524.
- (b) The Contractor must notify and obtain written approval from the Department's Bureau of Small Business Enterprises prior to replacing a DBE or making any change in the participation of a DBE. Approval for replacement will be granted only if it is demonstrated that the DBE is unable or unwilling to perform. The Contractor must make every good faith effort to find another certified DBE subcontractor to substitute for the original DBE. The good faith efforts shall be directed at finding another DBE to perform at least the same amount of work under the contract as the original DBE, to the extent needed to meet the contract goal.
- (c) Any deviation from the DBE condition-of-award or contract specifications must be approved, in writing, by the Department. The Contractor shall notify affected DBEs in writing of any changes in the scope of work which result in a reduction in the dollar amount condition-of-award to the contract.
- (d) In addition to the above requirements for reductions in the condition of award, additional requirements apply to the two cases of Contractor-initiated work substitution proposals. Where the contract allows alternate work methods which serve to delete or create underruns in condition of award DBE work, and the Contractor selects that alternate method or, where the Contractor proposes a substitute work method or material that serves to diminish or delete work committed to a DBE and replace it with other work, then the Contractor must demonstrate one of the following:
  - (1) That the replacement work will be performed by the same DBE (as long as the DBE is certified in the respective item of work) in a modification of the condition of award; or
  - (2) That the DBE is aware that its work will be deleted or will experience underruns and has agreed in writing to the change. If this occurs, the Contractor shall substitute other work of equivalent value to a certified DBE or provide documentation of good faith efforts to do so; or
  - (3) That the DBE is not capable of performing the replacement work or has declined to perform the work at a reasonably competitive price.

If this occurs, the Contractor shall substitute other work of equivalent value to a certified DBE or provide documentation of good faith efforts to do so.

- (e) Where the revision includes work committed to a new DBE subcontractor, not previously involved in the project, then a Request for Approval of Subcontractor, Department form BC 260A, must be signed and submitted.
- (f) If the commitment of work is in the form of additional tasks assigned to an existing subcontract, than a new Request for Approval of Subcontractor shall not be required. However, the Contractor must document efforts to assure that the existing DBE subcontractor is capable of performing the additional work and has agreed in writing to the change.
- (g) All work indicated for performance by an approved DBE shall be performed, managed, and supervised by the DBE executing the Participation Statement. The Contractor shall not terminate for convenience a DBE listed in the Utilization Plan and then perform the work of the terminated DBE with its own forces, those of an affiliate or those of another subcontractor, whether DBE or not, without first obtaining the written consent of the Bureau of Small Business Enterprises to amend the Utilization Plan. The Contractor shall notify the Bureau of Small Business Enterprises of any termination for reasons other than convenience, and shall obtain approval for inclusion of the substitute DBE in the Utilization Plan. If good faith efforts following a termination of a DBE for cause are not successful, the Contractor shall contact the Bureau of Small Business Enterprises and provide a full accounting of the efforts undertaken to obtain substitute DBE participation. The Bureau of Small Business Enterprises will evaluate the good faith efforts in light of all circumstances surrounding the performance status of the contract, and determine whether the contract goal should be amended.
- (h) The Contractor shall maintain a record of payments for work performed to the DBE participants. The records shall be made available to the Department for inspection upon request. After the performance of the final item of work or delivery of material by a DBE and final payment therefore to the DBE by the Contractor, but not later than thirty calendar days after payment has been made by the Department to the Contractor for such work or material, the Contractor shall submit a DBE Payment Agreement on Department form SBE 2115 to the Regional Engineer. If full and final payment has not been made to the DBE, the DBE Payment Agreement shall indicate whether a disagreement as to the payment required exists between the Contractor and the DBE or if the Contractor believes that the work has not been satisfactorily completed. If the Contractor does not have the full amount of work indicated in the Utilization Plan performed by the DBE companies indicated in the Utilization Plan and after good faith efforts are reviewed, the Department may deduct from contract payments to the Contractor the amount of the goal not achieved as liquidated and ascertained damages. The Contractor may request an administrative reconsideration of any amount deducted as damages pursuant to subsection (j) of this part.
- (i) The Department reserves the right to withhold payment to the Contractor to enforce the provisions of this Special Provision. Final payment shall not be made on the contract until such time as the Contractor submits sufficient documentation demonstrating achievement of the goal in accordance with this Special Provision or after liquidated damages have been determined and collected.

- (j) Notwithstanding any other provision of the contract, including but not limited to Article 109.09 of the Standard Specifications, the Contractor may request administrative reconsideration of a decision to deduct the amount of the goal not achieved as liquidated damages. A request to reconsider shall be delivered to the Contract Compliance Section and shall be handled and considered in the same manner as set forth in paragraph (c) of "Good Faith Effort Procedures" of this Special Provision, except a final decision that a good faith effort was not made during contract performance to achieve the goal agreed to in the Utilization Plan shall be the final administrative decision of the Department.

### **ENGINEER'S FIELD OFFICE TYPE A (BDE)**

Effective: April 1, 2007

Revised: August 1, 2008

Revise Article 670.02 of the Standard Specifications to read:

**"670.02 Engineer's Field Office Type A.** Type A field offices shall have a minimum ceiling height of 7 ft (2 m) and a minimum floor space 450 sq ft (42 sq m). The office shall be provided with sufficient heat, natural and artificial light, and air conditioning.

The office shall have an electronic security system that will respond to any breach of exterior doors and windows. Doors and windows shall be equipped with locks. Doors shall also be equipped with dead bolt locks or other secondary locking device.

Windows shall be equipped with exterior screens to allow adequate ventilation. All windows shall be equipped with interior shades, curtains, or blinds. Adequate all-weather parking space shall be available to accommodate a minimum of ten vehicles.

Suitable on-site sanitary facilities meeting Federal, State, and local health department requirements shall be provided, maintained clean and in good working condition, and shall be stocked with lavatory and sanitary supplies at all times.

Sanitary facilities shall include hot and cold potable running water, lavatory and toilet as an integral part of the office where available. Solid waste disposal consisting of two waste baskets and an outside trash container of sufficient size to accommodate a weekly provided pick-up service.

In addition, the following furniture and equipment shall be furnished.

- (a) Four desks with minimum working surface 42 x 30 in. (1.1 m x 750 mm) each and five non-folding chairs with upholstered seats and backs.
- (b) One desk with minimum working surface 48 x 72 in. (1.2 x 1.8 m) with height adjustment of 23 to 30 in. (585 to 750 mm).
- (c) One four-post drafting table with minimum top size of 37 1/2 x 48 in. (950 mm x 1.2 m). The top shall be basswood or equivalent and capable of being tilted through an angle of 50 degrees. An adjustable height drafting stool with upholstered seat and back shall also be provided.



- (d) Two free standing four drawer legal size file cabinet with lock and an underwriters' laboratories insulated file device 350 degrees one hour rating.
- (e) One 6 ft (1.8 m) folding table with six folding chairs.
- (f) One equipment cabinet of minimum inside dimension of 44 in. (1100 mm) high x 24 in. (600 mm) wide x 30 in. (750 mm) deep with lock. The walls shall be of steel with a 3/32 in. (2 mm) minimum thickness with concealed hinges and enclosed lock constructed in such a manner as to prevent entry by force. The cabinet assembly shall be permanently attached to a structural element of the field office in a manner to prevent theft of the entire cabinet.
- (g) One refrigerator with a minimum size of 16 cu ft (0.45 cu m) with a freezer unit.
- (h) One electric desk type tape printing calculator.
- (i) A minimum of two communication paths. The configuration shall include:
  - (1) Internet Connection. An internet service connection using telephone DSL, cable broadband, or CDMA wireless technology. Additionally, an 802.11g/N wireless router shall be provided, which will allow connection by the Engineer and up to four Department staff.
  - (2) Telephone Lines. Three separate telephone lines.
- (j) One plain paper copy machine capable of reproducing prints up to 11 x 17 in. (280 x 432 mm) with an automatic feed tray capable of storing 30 sheets of paper. Letter size and 11 x 17 in. (280 x 432 mm) paper shall be provided.
- (k) One plain paper fax machine with paper.
- (l) Two telephones, with touch tone, where available, and a digital telephone answering machine, for exclusive use by the Engineer.
- (m) One electric water cooler dispenser.
- (n) One first-aid cabinet fully equipped.
- (o) One microwave oven, 1 cu ft (0.03 cu m) minimum capacity.
- (p) One fire-proof safe, 0.5 cu ft (0.01 cu m) minimum capacity.
- (q) One electric paper shredder.
- (r) One post mounted rain gauge, located on the project site for each 5 miles (8 km) of project length."

Revise the first sentence of the first paragraph of Article 670.07 of the Standard Specifications to read:

“The building or buildings fully equipped as specified will be paid for on a monthly basis until the building or buildings are released by the Engineer.”

Revise the last sentence of the first paragraph of Article 670.07 of the Standard Specifications to read:

“This price shall include all utility costs and shall reflect the salvage value of the building or buildings, equipment, and furniture which become the property of the Contractor after release by the Engineer, except that the Department will pay that portion of the monthly long distance telephone bills that, when combined, exceed \$150.”

### **EQUIPMENT RENTAL RATES (BDE)**

Effective: August 2, 2007

Revised: January 2, 2008

Replace the second and third paragraphs of Article 105.07(b)(4)a. of the Standard Specifications with the following:

“Equipment idled which cannot be used on other work, and which is authorized to standby on the project site by the Engineer, will be paid for according to Article 109.04(b)(4).”

Replace Article 109.04(b)(4) of the Standard Specifications with the following:

“(4) Equipment. Equipment used for extra work shall be authorized by the Engineer. The equipment shall be specifically described, be of suitable size and capacity for the work to be performed, and be in good operating condition. For such equipment, the Contractor will be paid as follows.

- a. Contractor Owned Equipment. Contractor owned equipment will be paid for by the hour using the applicable FHWA hourly rate from the “Equipment Watch Rental Rate Blue Book” (Blue Book) in effect when the force account work begins. The FHWA hourly rate is calculated as follows.

$$\text{FHWA hourly rate} = (\text{monthly rate}/176) \times (\text{model year adj.}) \times (\text{Illinois adj.}) + \text{EOC}$$

Where: EOC = Estimated Operating Costs per hour (from the Blue Book)

The time allowed will be the actual time the equipment is operating on the extra work. For the time required to move the equipment to and from the site of the extra work and any authorized idle (standby) time, payment will be made at the following hourly rate:  $0.5 \times (\text{FHWA hourly rate} - \text{EOC})$ .

All time allowed shall fall within the working hours authorized for the extra work.

The rates above include the cost of fuel, oil, lubrication, supplies, small tools, necessary attachments, repairs, overhaul and maintenance of any kind, depreciation, storage, overhead, profits, insurance, and all incidentals. The rates do not include labor.

The Contractor shall submit to the Engineer sufficient information for each piece of equipment and its attachments to enable the Engineer to determine the proper equipment category. If a rate is not established in the Blue Book for a particular piece of equipment, the Engineer will establish a rate for that piece of equipment that is consistent with its cost and use in the industry.

- b. Rented Equipment. Whenever it is necessary for the Contractor to rent equipment to perform extra work, the rental and transportation costs of the equipment plus five percent for overhead will be paid. In no case shall the rental rates exceed those of established distributors or equipment rental agencies.

All prices shall be agreed to in writing before the equipment is used.”

**LIQUIDATED DAMAGES (BDE)**

Effective: April 1, 2009

Revise the table in Article 108.09 of the Standard Specifications to read:

“Schedule of Deductions for Each Day of Overrun in Contract Time			
Original Contract Amount		Daily Charges	
From More Than	To and Including	Calendar Day	Work Day
\$ 0	\$ 100,000	\$ 375	\$ 500
100,000	500,000	625	875
500,000	1,000,000	1,025	1,425
1,000,000	3,000,000	1,125	1,550
3,000,000	5,000,000	1,425	1,950
5,000,000	10,000,000	1,700	2,350
10,000,000	And over	3,325	4,650”

**NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM / EROSION AND SEDIMENT CONTROL DEFICIENCY DEDUCTION (BDE)**

Effective: April 1, 2007

Revised: November 1, 2009

Revise Article 105.03(a) of the Standard Specifications to read:

- “(a) National Pollutant Discharge Elimination System (NPDES) / Erosion and Sediment Control Deficiency Deduction When the Engineer is notified or determines an erosion and/or sediment control deficiency(s) exists, or the Contractor’s activities represents a violation of the Department’s NPDES permits, the Engineer will notify and direct the Contractor to correct the deficiency within a specified time. The specified time, which begins upon notification to the Contractor, will be from 1/2 hour to 1 week based on the urgency of the situation and the nature of the work effort required. The Engineer will be the sole judge.

A deficiency may be any lack of repair, maintenance, or implementation of erosion and/or sediment control devices included in the contract, or any failure to comply with the conditions of the Department's NPDES permits. A deficiency may also be applied to situations where corrective action is not an option such as the failure to participate in a jobsite inspection of the project, failure to install required measures prior to initiating earth moving operations, disregard of concrete washout requirements, or other disregard of the NPDES permit.

If the Contractor fails to correct a deficiency within the specified time, a daily monetary deduction will be imposed for each calendar day or portion of a calendar day until the deficiency is corrected to the satisfaction of the Engineer. The calendar day(s) will begin with notification to the Contractor and end with the Engineer's acceptance of the correction. The base value of the daily monetary deduction is \$1000.00 and will be applied to each location for which a deficiency exists. The value of the deficiency deduction assessed for each infraction will be determined by multiplying the base value by a Gravity Adjustment Factor provided in Table A. Except for failure to participate in a required jobsite inspection of the project prior to initiating earthmoving operations which will be based on the total acreage of planned disturbance at the following multipliers: <5 Acres: 1; 5-10 Acres: 2; >10-25 Acres: 3; >25 Acres: 5. For those deficiencies where corrective action was not an option, the monetary deduction will be immediate and will be valued at one calendar day multiplied by a Gravity Adjustment Factor.

Table A Deficiency Deduction Gravity Adjustment Factors				
Types of Violations	Soil Disturbed and Not Permanently Stabilized At Time of Violation			
	< 5 Acres	5 - 10 Acres	>10 - 25 Acres	> 25 Acres
Failure to Install or Properly Maintain BMP	0.1 - 0.5	0.2 - 1.0	0.5 - 2.5	1.0 - 5
Careless Destruction of BMP	0.2 - 1	0.5 - 2.5	1.0 - 5.	1.0 - 5
Intrusion into Protected Resource	1.0 - 5	1.0 - 5	2.0 - 10	2.0 - 10
Failure to properly manage Chemicals, Concrete Washouts or Residuals, Litter or other Wastes	0.2 - 1	0.2 - 1	0.5 - 2.5	1.0 - 5
Improper Vehicle and Equipment Maintenance, Fueling or Cleaning	0.1 - 0.5	0.2 - 1	0.2 - 1	0.5 - 2.5
Failure to Provide or Update Written or Graphic Plans Required by SWPPP	0.2 - 1	0.5 - 2.5	1.0 - 5	1.0 - 5
Failure to comply with Other Provisions of the NPDES Permit	0.1 - 0.5	0.2 - 1	0.2 - 1	0.5 - 2.5"

**PAYMENTS TO SUBCONTRACTORS (BDE)**

Effective: June 1, 2000

Revised: January 1, 2006

Federal regulations found at 49 CFR §26.29 mandate the Department to establish a contract clause to require Contractors to pay subcontractors for satisfactory performance of their subcontracts and to set the time for such payments.

State law also addresses the timing of payments to be made to subcontractors and material suppliers. Section 7 of the Prompt Payment Act, 30 ILCS 540/7, requires that when a Contractor receives any payment from the Department, the Contractor shall make corresponding, proportional payments to each subcontractor and material supplier performing work or supplying material within 15 calendar days after receipt of the Department payment. Section 7 of the Act further provides that interest in the amount of two percent per month, in addition to the payment due, shall be paid to any subcontractor or material supplier by the Contractor if the payment required by the Act is withheld or delayed without reasonable cause. The Act also provides that the time for payment required and the calculation of any interest due applies to transactions between subcontractors and lower-tier subcontractors and material suppliers throughout the contracting chain.

This Special Provision establishes the required federal contract clause, and adopts the 15 calendar day requirement of the State Prompt Payment Act for purposes of compliance with the federal regulation regarding payments to subcontractors. This contract is subject to the following payment obligations.

When progress payments are made to the Contractor according to Article 109.07 of the Standard Specifications, the Contractor shall make a corresponding payment to each subcontractor and material supplier in proportion to the work satisfactorily completed by each subcontractor and for the material supplied to perform any work of the contract. The proportionate amount of partial payment due to each subcontractor and material supplier throughout the contracting chain shall be determined by the quantities measured or otherwise determined as eligible for payment by the Department and included in the progress payment to the Contractor. Subcontractors and material suppliers shall be paid by the Contractor within 15 calendar days after the receipt of payment from the Department. The Contractor shall not hold retainage from the subcontractors. These obligations shall also apply to any payments made by subcontractors and material suppliers to their subcontractors and material suppliers; and to all payments made to lower tier subcontractors and material suppliers throughout the contracting chain. Any payment or portion of a payment subject to this provision may only be withheld from the subcontractor or material supplier to whom it is due for reasonable cause.

This Special Provision does not create any rights in favor of any subcontractor or material supplier against the State or authorize any cause of action against the State on account of any payment, nonpayment, delayed payment, or interest claimed by application of the State Prompt Payment Act. The Department will not approve any delay or postponement of the 15 day requirement except for reasonable cause shown after notice and hearing pursuant to Section 7(b) of the State Prompt Payment Act. State law creates other and additional remedies available to any subcontractor or material supplier, regardless of tier, who has not been paid for work properly performed or material furnished. These remedies are a lien against public funds set forth in Section 23(c) of the Mechanics Lien Act, 770 ILCS 60/23(c), and a recovery on the Contractor's payment bond according to the Public Construction Bond Act, 30 ILCS 550.

#### **PERSONAL PROTECTIVE EQUIPMENT (BDE)**

Effective: November 1, 2008

Revise the first sentence of Article 701.12 of the Standard Specifications to read:

“All personnel on foot, excluding flaggers, within the highway right-of-way shall wear a fluorescent orange, fluorescent yellow/green, or a combination of fluorescent orange and fluorescent yellow/green vest meeting the requirements of ANSI/ISEA 107-2004 for Conspicuity Class 2 garments.”

**PUBLIC CONVENIENCE AND SAFETY (BDE)**

Effective: January 1, 2000

Add the following paragraph after the fourth paragraph of Article 107.09 of the Standard Specifications.

“On weekends, excluding holidays, roadways with Average Daily Traffic of 25,000 or greater, all lanes shall be open to traffic from 3:00 P.M. Friday to midnight Sunday except where structure construction or major rehabilitation makes it impractical.”

**REFLECTIVE SHEETING ON CHANNELIZING DEVICES (BDE)**

Effective: April 1, 2007

Revised: November 1, 2008

Revise the seventh paragraph of Article 1106.02 of the Standard Specifications to read:

“At the time of manufacturing, the retroreflective prismatic sheeting used on channelizing devices shall meet or exceed the initial minimum coefficient of retroreflection as specified in the following table. Measurements shall be conducted according to ASTM E 810, without averaging. Sheeting used on cones, drums and flexible delineators shall be reboundable as tested according to ASTM D 4956. Prestriped sheeting for rigid substrates on barricades shall be white and orange. [The sheeting shall be uniform in color and devoid of streaks throughout the length of each roll. The color shall conform to the latest appropriate standard color tolerance chart issued by the U.S. Department of Transportation, Federal Highway Administration, and to the daytime and nighttime color requirements of ASTM D 4956.](#)

Initial Minimum Coefficient of Retroreflection candelas/foot candle/sq ft (candelas/lux/sq m) of material				
Observation Angle (deg.)	Entrance Angle (deg.)	White	Orange	Fluorescent Orange
0.2	-4	365	160	150
0.2	+30	175	80	70
0.5	-4	245	100	95
0.5	+30	100	50	40”

Revise the first sentence of the first paragraph of Article 1106.02(c) of the Standard Specifications to read:

“Barricades and vertical panels shall have alternating white and orange stripes sloping downward at 45 degrees toward the side on which traffic will pass.”

Revise the third sentence of the first paragraph of Article 1106.02(d) of the Standard Specifications to read:

“The bottom panels shall be 8 x 24 in. (200 x 600 mm) with alternating white and orange stripes sloping downward at 45 degrees toward the side on which traffic will pass.”

**SUBCONTRACTOR MOBILIZATION PAYMENTS (BDE)**

Effective: April 2, 2005

To account for the preparatory work and operations necessary for the movement of subcontractor personnel, equipment, supplies, and incidentals to the project site and for all other work or operations that must be performed or costs incurred when beginning work approved for subcontracting in accordance with Article 108.01 of the Standard Specifications, the Contractor shall make a mobilization payment to each subcontractor.

This mobilization payment shall be made at least 14 days prior to the subcontractor starting work. The amount paid shall be equal to 3 percent of the amount of the subcontract reported on form BC 260A submitted for the approval of the subcontractor’s work.

This provision shall be incorporated directly or by reference into each subcontract approved by the Department.

**TRUCK MOUNTED/TRAILER MOUNTED ATTENUATORS (BDE)**

Effective: January 1, 2010

Revise Article 701.03(k) of the Standard Specifications to read:

“(k) Truck Mounted/Trailer Mounted Attenuators ..... 1106.02”

Revise Article 701.15(h) of the Standard Specifications to read:

“(h) Truck Mounted/Trailer Mounted Attenuators (TMA). TMA units shall have a roll ahead distance in the event of an impact. The TMA shall be between 100 and 200 ft (30 and 60 m) behind the vehicle ahead or the workers. This distance may be extended by the Engineer.

TMA host vehicles shall have the parking brake engaged when stationary.

The driver and passengers of the TMA host vehicle should exit the vehicle if the TMA is to remain stationary for 15 minutes or more in duration.”

Revise Article 1106.02(g) of the Standard Specifications to read:

“(g) Truck Mounted/Trailer Mounted Attenuators. The attenuator shall be a NCHRP 350 approved unit for Test Level 3. Test Level 2 may be used as directed by the Engineer for normal posted speeds less than or equal to 45 mph.”

**WORKING DAYS (BDE)**

Effective: January 1, 2002

The Contractor shall complete the work within 25 working days.

**STEEL COST ADJUSTMENT (BDE) (RETURN FORM WITH BID)**

Effective: April 2, 2004

Revised: April 1, 2009

Description. Steel cost adjustments will be made to provide additional compensation to the Contractor, or a credit to the Department, for fluctuations in steel prices when optioned by the Contractor. The bidder shall indicate on the attached form whether or not this special provision will be part of the contract and submit the completed form with his/her bid. Failure to submit the form or failure to indicate contract number, company name, and sign and date the form shall make this contract exempt of steel cost adjustments for all items of steel. Failure to indicate "Yes" for any item of work will make that item of steel exempt from steel cost adjustment.

Types of Steel Products. An adjustment will be made for fluctuations in the cost of steel used in the manufacture of the following items:

- Metal Piling (excluding temporary sheet piling)
- Structural Steel
- Reinforcing Steel

Other steel materials such as dowel bars, tie bars, mesh reinforcement, guardrail, steel traffic signal and light poles, towers and mast arms, metal railings (excluding wire fence), and frames and grates will be subject to a steel cost adjustment when the pay items they are used in has a contract value of \$10,000 or greater.

Documentation. Sufficient documentation shall be furnished to the Engineer to verify the following:

- (a) The dates and quantity of steel, in lb (kg), shipped from the mill to the fabricator.
- (b) The quantity of steel, in lb (kg), incorporated into the various items of work covered by this special provision. The Department reserves the right to verify submitted quantities.

Method of Adjustment. Steel cost adjustments will be computed as follows:

$$SCA = Q \times D$$

Where: SCA = steel cost adjustment, in dollars  
Q = quantity of steel incorporated into the work, in lb (kg)  
D = price factor, in dollars per lb (kg)



$$D = MPI_M - MPI_L$$

Where:  $MPI_M$  = The Materials Cost Index for steel as published by the Engineering News-Record for the month the steel is shipped from the mill. The indices will be converted from dollars per 100 lb to dollars per lb (kg).

$MPI_L$  = The Materials Cost Index for steel as published by the Engineering News-Record for the month prior to the letting. The indices will be converted from dollars per 100 lb to dollars per lb (kg).

The unit weights (masses) of steel that will be used to calculate the steel cost adjustment for the various items are shown in the attached table.

No steel cost adjustment will be made for any products manufactured from steel having a mill shipping date prior to the letting date.

If the Contractor fails to provide the required documentation, the method of adjustment will be calculated as described above; however, the  $MPI_M$  will be based on the date the steel arrives at the job site. In this case, an adjustment will only be made when there is a decrease in steel costs.

Basis of Payment. Steel cost adjustments may be positive or negative but will only be made when there is a difference between the  $MPI_L$  and  $MPI_M$  in excess of five percent, as calculated by:

$$\text{Percent Difference} = \{(MPI_L - MPI_M) \div MPI_L\} \times 100$$

Steel cost adjustments will be calculated by the Engineer and will be paid or deducted when all other contract requirements for the items of work are satisfied. Adjustments will only be made for fluctuations in the cost of the steel as described herein. No adjustment will be made for changes in the cost of manufacturing, fabrication, shipping, storage, etc.

The adjustments shall not apply during contract time subject to liquidated damages for completion of the entire contract.

**Attachment**

Item	Unit Mass (Weight)
Metal Piling (excluding temporary sheet piling) Furnishing Metal Pile Shells 12 in. (305 mm), 0.179 in. (3.80 mm) wall thickness Furnishing Metal Pile Shells 12 in. (305 mm), 0.250 in. (6.35 mm) wall thickness Furnishing Metal Pile Shells 14 in. (356 mm), 0.250 in. (6.35 mm) wall thickness Other piling	23 lb/ft (34 kg/m) 32 lb/ft (48 kg/m) 37 lb/ft (55 kg/m) See plans
Structural Steel	See plans for weights (masses)
Reinforcing Steel	See plans for weights (masses)
Dowel Bars and Tie Bars	6 lb (3 kg) each
Mesh Reinforcement	63 lb/100 sq ft (310 kg/sq m)
Guardrail Steel Plate Beam Guardrail, Type A w/steel posts Steel Plate Beam Guardrail, Type B w/steel posts Steel Plate Beam Guardrail, Types A and B w/wood posts Steel Plate Beam Guardrail, Type 2 Steel Plate Beam Guardrail, Type 6 Traffic Barrier Terminal, Type 1 Special (Tangent) Traffic Barrier Terminal, Type 1 Special (Flared)	20 lb/ft (30 kg/m) 30 lb/ft (45 kg/m) 8 lb/ft (12 kg/m) 305 lb (140 kg) each 1260 lb (570 kg) each 730 lb (330 kg) each 410 lb (185 kg) each
Steel Traffic Signal and Light Poles, Towers and Mast Arms Traffic Signal Post Light Pole, Tenon Mount and Twin Mount, 30 - 40 ft (9 - 12 m) Light Pole, Tenon Mount and Twin Mount, 45 - 55 ft (13.5 - 16.5 m) Light Pole w/Mast Arm, 30 - 50 ft (9 - 15.2 m) Light Pole w/Mast Arm, 55 - 60 ft (16.5 - 18 m) Light Tower w/Luminaire Mount, 80 - 110 ft (24 - 33.5 m) Light Tower w/Luminaire Mount, 120 - 140 ft (36.5 - 42.5 m) Light Tower w/Luminaire Mount, 150 - 160 ft (45.5 - 48.5 m)	11 lb/ft (16 kg/m) 14 lb/ft (21 kg/m) 21 lb/ft (31 kg/m) 13 lb/ft (19 kg/m) 19 lb/ft (28 kg/m) 31 lb/ft (46 kg/m) 65 lb/ft (97 kg/m) 80 lb/ft (119 kg/m)
Metal Railings (excluding wire fence) Steel Railing, Type SM Steel Railing, Type S-1 Steel Railing, Type T-1 Steel Bridge Rail	64 lb/ft (95 kg/m) 39 lb/ft (58 kg/m) 53 lb/ft (79 kg/m) 52 lb/ft (77 kg/m)
Frames and Grates Frame Lids and Grates	250 lb (115 kg) 150 lb (70 kg)

**RETURN WITH BID**

**ILLINOIS DEPARTMENT  
OF TRANSPORTATION**

**OPTION FOR  
STEEL COST ADJUSTMENT**

The bidder shall submit this completed form with his/her bid. Failure to submit the form or properly complete contract number, company name, and sign and date the form shall make this contract exempt of steel cost adjustments for all items of steel. Failure to indicate "Yes" for any item of work will make that item of steel exempt from steel cost adjustment. After award, this form, when submitted shall become part of the contract.

**Contract No.:** \_\_\_\_\_

**Company Name:** \_\_\_\_\_

**Contractor's Option:**

Is your company opting to include this special provision as part of the contract plans for the following items of work?

- Metal Piling Yes
- Structural Steel Yes
- Reinforcing Steel Yes
- Dowel Bars, Tie Bars and Mesh Reinforcement Yes
- Guardrail Yes
- Steel Traffic Signal and Light Poles, Towers and Mast Arms Yes
- Metal Railings (excluding wire fence) Yes
- Frames and Grates Yes

**Signature:** \_\_\_\_\_ **Date:** \_\_\_\_\_

**REQUIRED CONTRACT PROVISIONS  
FEDERAL-AID CONSTRUCTION CONTRACTS**

	Page
I. General .....	1
II. Nondiscrimination .....	1
III. Nonsegregated Facilities .....	3
IV. Payment of Predetermined Minimum Wage.....	3
V. Statements and Payrolls .....	5
VI. Record of Materials, Supplies, and Labor.....	6
VII. Subletting or Assigning the Contract.....	6
VIII. Safety: Accident Prevention .....	7
IX. False Statements Concerning Highway Projects.....	7
X. Implementation of Clean Air Act and Federal .....Water Pollution Control Act .....	7
XI. Certification Regarding Debarment, Suspension, Ineligibility, and Voluntary Exclusion .....	8
XII. Certification Regarding Use of Contract Funds for Lobbying .....	9

**ATTACHMENTS**

- A. Employment Preference for Appalachian Contracts  
(included in Appalachian contracts only)

**I. GENERAL**

1. These contract provisions shall apply to all work performed on the contract by the contractor's own organization and with the assistance of workers under the contractor's immediate superintendence and to all work performed on the contract by piecework, station work, or by subcontract.

2. Except as otherwise provided for in each section, the contractor shall insert in each subcontract all of the stipulations contained in these Required Contract Provisions, and further require their inclusion in any lower tier subcontract or purchase order that may in turn be made. The Required Contract Provisions shall not be incorporated by reference in any case. The prime contractor shall be responsible for compliance by any subcontractor or lower tier subcontractor with these Required Contract Provisions.

3. A breach of any of the stipulations contained in these Required Contract Provisions shall be sufficient grounds for termination of the contract.

4. A breach of the following clauses of the Required Contract Provisions may also be grounds for debarment as provided in 29 CFR 5.12:

- Section I, paragraph 2;
- Section IV, paragraphs 1, 2, 3, 4 and 7;
- Section V, paragraphs 1 and 2a through 2g.

5. Disputes arising out of the labor standards provisions of Section IV (except paragraph 5) and Section V of these Required Contract Provisions shall not be subject to the general disputes clause of this contract. Such disputes shall be resolved in accordance with the procedures of the U.S. Department of Labor (DOL) as set forth in 29 CFR 5, 6 and 7. Disputes within the meaning of this clause include disputes between the contractor (or any of its subcontractors) and the contracting agency, the DOL, or the contractor's employees or their representatives.

6. Selection of Labor: During the performance of this contract, the contractor shall not:

- a. Discriminate against labor from any other State, possession, or territory of the United States (except for employment preference for Appalachian contracts, when applicable, as specified in Attachment A), or
- b. Employ convict labor for any purpose within the limits of the project unless it is labor performed by convicts who are on parole, supervised release, or probation.

**II. NONDISCRIMINATION**

(Applicable to all Federal-aid construction contracts and to all related subcontracts of \$10,000 or more.)

**1. Equal Employment Opportunity:** Equal employment opportunity (EEO) requirements not to discriminate and to take affirmative action to assure equal opportunity as set forth under laws, executive orders, rules, regulations (28 CFR 35, 29 CFR 1630 and 41 CFR 60 (and orders of the Secretary of Labor as modified by the provisions prescribed herein, and imposed pursuant to 23 U.S.C. 140 shall constitute the EEO and specific affirmative action standards for the contractor's project activities under this contract. The Equal Opportunity Construction Contract Specifications set forth under 41 CFR 60-4.3 and the provisions of the American Disabilities Act of 1990 (42 U.S.C. 12101 et seq.) set forth under 28 CFR 35 and 29 CFR 1630 are incorporated by reference in this contract. In the execution of this contract, the contractor agrees to comply with the following minimum specific requirement activities of EEO:

- a. The contractor will work with the State highway agency (SHA) and the Federal Government in carrying out EEO obligations and in their review of his/her activities under the contract.
- b. The contractor will accept as his operating policy the following statement: "It is the policy of this Company to assure that applicants are employed, and that employees are treated during employment, without regard to their race, religion, sex, color, national origin, age or disability. Such action shall include: employment, upgrading, demotion, or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship, preapprenticeship, and/or on-the-job-training."

**2. EEO Officer:** The contractor will designate and make known to the SHA contracting officers an EEO Officer who will have the responsibility for an must be capable of effectively administering and promoting an active contractor program of EEO and who must be assigned adequate authority and responsibility to do so.

**3. Dissemination of Policy:** All members of the contractor's staff who are authorized to hire, supervise, promote, and discharge employees, or who recommend such action, or who are substantially involved in such action, will be made fully cognizant of, and will implement, the contractor's EEO policy and contractual responsibilities to provide EEO in each grade and classification of employment. To ensure that the above agreement will be met, the following actions will be taken as a minimum:

- a. Periodic meetings of supervisory and personnel office employees will be conducted before the start of work and then not less often than once every six months, at which time the contractor's EEO policy and its implementation will be reviewed and explained. The meetings will be conducted by the EEO Officer.
- b. All new supervisory or personnel office employees will be given a thorough indoctrination by the EEO Officer, covering all major aspects of the contractor's EEO obligations within thirty days following their reporting for duty with the contractor.
- c. All personnel who are engaged in direct recruitment for the project will be instructed by the EEO Officer in the contractor's procedures for locating and hiring minority group employees.
- d. Notices and posters setting forth the contractor's EEO policy will be placed in areas readily accessible to employees, applicants for employment and potential employees.
- e. The contractor's EEO policy and the procedures to implement such policy will be brought to the attention of employees by means of meetings, employee handbooks, or other appropriate means.

**4. Recruitment:** When advertising for employees, the contractor will include in all advertisements for employees the notation: "An Equal Opportunity Employer." All such advertisements will be placed in publications having a large circulation among minority groups in the area from which the project work force would normally be derived.

- a. The contractor will, unless precluded by a valid bargaining agreement, conduct systematic and direct recruitment through public and private employees referral sources likely to yield qualified minority group applicants. To meet this requirement, the contractor will identify sources of potential minority group employees, and establish which such identified sources procedures whereby minority group applicants may be referred

to the contractor for employment consideration.

**b.** In the event the contractor has a valid bargaining agreement providing for exclusive hiring hall referrals, he is expected to observe the provisions of that agreement to the extent that the system permits the contractor's compliance with EEO contract provisions. (The DOL has held that where implementation of such agreements have the effect of discriminating against minorities or women, or obligates the contractor to do the same, such implementation violates Executive Order 11246, as amended.)

**c.** The contractor will encourage his present employees to refer minority group applicants for employment. Information and procedures with regard to referring minority group applicants will be discussed with employees.

**5. Personnel Actions:** Wages, working conditions, and employee benefits shall be established and administered, and personnel actions of every type, including hiring, upgrading, promotion, transfer, demotion, layoff, and termination, shall be taken without regard to race, color, religion, sex, national origin, age or disability. The following procedures shall be followed:

**a.** The contractor will conduct periodic inspections of project sites to insure that working conditions and employee facilities do not indicate discriminatory treatment of project site personnel.

**b.** The contractor will periodically evaluate the spread of wages paid within each classification to determine any evidence of discriminatory wage practices.

**c.** The contractor will periodically review selected personnel actions in depth to determine whether there is evidence of discrimination. Where evidence is found, the contractor will promptly take corrective action. If the review indicates that the discrimination may extend beyond the actions reviewed, such corrective action shall include all affected persons.

**d.** The contractor will promptly investigate all complaints of alleged discrimination made to the contractor in connection with his obligations under this contract, will attempt to resolve such complaints, and will take appropriate corrective action within a reasonable time. If the investigation indicates that the discrimination may affect persons other than the complainant, such corrective action shall include such other persons. Upon completion of each investigation, the contractor will inform every complainant of all of his avenues of appeal.

#### **6. Training and Promotion:**

**a.** The contractor will assist in locating, qualifying, and increasing the skills of minority group and women employees, and applicants for employment.

**b.** Consistent with the contractor's work force requirements and as permissible under Federal and State regulations, the contractor shall make full use of training programs, i.e., apprenticeship, and on-the-job training programs for the geographical area of contract performance. Where feasible, 25 percent of apprentices or trainees in each occupation shall be in their first year of apprenticeship or training. In the event a special provision for training is provided under this contract, this subparagraph will be superseded as indicated in the special provision.

**c.** The contractor will advise employees and applicants for employment of available training programs and entrance requirements for each.

**d.** The contractor will periodically review the training and promotion potential of minority group and women employees and will encourage eligible employees to apply for such training and promotion.

**7. Unions:** If the contractor relies in whole or in part upon unions as a source of employees, the contractor will use his/her best efforts to obtain the cooperation of such unions to increase opportunities for minority groups and women within the unions, and to effect referrals by such unions of minority and female employees. Actions by the contractor either directly or through a contractor's association acting as agent will include the procedures set forth below:

**a.** The contractor will use best efforts to develop, in cooperation with the unions, joint training programs aimed toward qualifying more minority group members and women

for membership in the unions and increasing the skills of minority group employees and women so that they may qualify for higher paying employment.

**b.** The contractor will use best efforts to incorporate an EEO clause into each union agreement to the end that such union will be contractually bound to refer applicants without regard to their race, color, religion, sex, national origin, age or disability.

**c.** The contractor is to obtain information as to the referral practices and policies of the labor union except that to the extent such information is within the exclusive possession of the labor union and such labor union refuses to furnish such information to the contractor, the contractor shall so certify to the SHA and shall set forth what efforts have been made to obtain such information.

**d.** In the event the union is unable to provide the contractor with a reasonable flow of minority and women referrals within the time limit set forth in the collective bargaining agreement, the contractor will, through independent recruitment efforts, fill the employment vacancies without regard to race, color, religion, sex, national origin, age or disability; making full efforts to obtain qualified and/or quailifiable minority group persons and women. (The DOL has held that it shall be no excuse that the union with which the contractor has a collective bargaining agreement providing for exclusive referral failed to refer minority employees.) In the event the union referral practice prevents the contractor from meeting the obligations pursuant to Executive Order 11246, as amended, and these special provisions, such contractor shall immediately notify the SHA.

**8. Selection of Subcontractors, Procurement of Materials and Leasing of Equipment:** The contractor shall not discriminate on the grounds of race, color, religion, sex, national origin, age or disability in the selection and retention of subcontractors, including procurement of materials and leases of equipment.

**a.** The contractor shall notify all potential subcontractors and suppliers of his/her EEO obligations under this contract.

**b.** Disadvantaged business enterprises (DBE), as defined in 49 CFR 23, shall have equal opportunity to compete for and perform subcontracts which the contractor enters into pursuant to this contract. The contractor will use his best efforts to solicit bids from and to utilize DBE subcontractors or subcontractors with meaningful minority group and female representation among their employees. Contractors shall obtain lists of DBE construction firms from SHA personnel.

**c.** The contractor will use his best efforts to ensure subcontractor compliance with their EEO obligations.

**9. Records and Reports:** The contractor shall keep such records as necessary to document compliance with the EEO requirements. Such records shall be retained for a period of three years following completion of the contract work and shall be available at reasonable times and places for inspection by authorized representatives of the SHA and the FHWA.

**a.** The records kept by the contractor shall document the following:

- (1)** The number of minority and non-minority group members and women employed in each work classification on the project;
- (2)** The progress and efforts being made in cooperation with unions, when applicable, to increase employment opportunities for minorities and women;
- (3)** The progress and efforts being made in locating, hiring, training, qualifying, and upgrading minority and female employees; and
- (4)** The progress and efforts being made in securing the services of DBE subcontractors or subcontractors with meaningful minority and female representation among their employees.

**b.** The contractors will submit an annual report to the SHA each July for the duration of the project, indicating the number of minority, women, and non-minority group employees currently engaged in each work classification required by the

contract work. This information is to be reported on Form FHWA-1391. If on-the-job training is being required by special provision, the contractor will be required to collect and report training data.

### III. NONSEGREGATED FACILITIES

(Applicable to all Federal-aid construction contracts and to all related subcontracts of \$10,000 or more.)

a. By submission of this bid, the execution of this contract or subcontract, or the consummation of this material supply agreement or purchase order, as appropriate, the bidder, Federal-aid construction contractor, subcontractor, material supplier, or vendor, as appropriate, certifies that the firm does not maintain or provide for its employees any segregated facilities at any of its establishments, and that the firm does not permit its employees to perform their services at any location, under its control, where segregated facilities are maintained. The firm agrees that a breach of this certification is a violation of the EEO provisions of this contract. The firm further certifies that no employee will be denied access to adequate facilities on the basis of sex or disability.

b. As used in this certification, the term "segregated facilities" means any waiting rooms, work areas, restrooms and washrooms, restaurants and other eating areas, timeclocks, locker rooms, and other storage or dressing areas, parking lots, drinking fountains, recreation or entertainment areas, transportation, and housing facilities provided for employees which are segregated by explicit directive, or are, in fact, segregated on the basis of race, color, religion, national origin, age or disability, because of habit, local custom, or otherwise. The only exception will be for the disabled when the demands for accessibility override (e.g. disabled parking).

c. The contractor agrees that it has obtained or will obtain identical certification from proposed subcontractors or material suppliers prior to award of subcontracts or consummation of material supply agreements of \$10,000 or more and that it will retain such certifications in its files.

### IV. PAYMENT OF PREDETERMINED MINIMUM WAGE

(Applicable to all Federal-aid construction contracts exceeding \$2,000 and to all related subcontracts, except for projects located on roadways classified as local roads or rural minor collectors, which are exempt.)

#### 1. General:

a. All mechanics and laborers employed or working upon the site of the work will be paid unconditionally and not less often than once a week and without subsequent deduction or rebate on any account [except such payroll deductions as are permitted by regulations (29 CFR 3) issued by the Secretary of Labor under the Copeland Act (40 U.S.C. 276c)] the full amounts of wages and bona fide fringe benefits (or cash equivalents thereof) due at time of payment. The payment shall be computed at wage rates not less than those contained in the wage determination of the Secretary of Labor (hereinafter "the wage determination") which is attached hereto and made a part hereof, regardless of any contractual relationship which may be alleged to exist between the contractor or its subcontractors and such laborers and mechanics. The wage determination (including any additional classifications and wage rates conformed under paragraph 2 of this Section IV and the DOL poster (WH-1321) or Form FHWA-1495) shall be posted at all times by the contractor and its subcontractors at the site of the work in a prominent and accessible place where it can be easily seen by the workers. For the purpose of this Section, contributions made or costs reasonably anticipated for bona fide fringe benefits under Section 1(b)(2) of the Davis-Bacon Act (40 U.S.C. 276a) on behalf of laborers or mechanics are considered wages paid to such laborers or mechanics, subject to the provisions of Section IV, paragraph 3b, hereof. Also, for the purpose of this Section, regular contributions made or costs incurred for more than a weekly period (but not less often than quarterly) under plans, funds, or programs, which cover the particular weekly period, are deemed to be constructively made or incurred

during such weekly period. Such laborers and mechanics shall be paid the appropriate wage rate and fringe benefits on the wage determination for the classification of work actually performed, without regard to skill, except as provided in paragraphs 4 and 5 of this Section IV.

b. Laborers or mechanics performing work in more than one classification may be compensated at the rate specified for each classification for the time actually worked therein, provided, that the employer's payroll records accurately set forth the time spent in each classification in which work is performed.

c. All rulings and interpretations of the Davis-Bacon Act and related acts contained in 29 CFR 1, 3, and 5 are herein incorporated by reference in this contract.

#### 2. Classification:

a. The SHA contracting officer shall require that any class of laborers or mechanics employed under the contract, which is not listed in the wage determination, shall be classified in conformance with the wage determination.

b. The contracting officer shall approve an additional classification, wage rate and fringe benefits only when the following criteria have been met:

(1) the work to be performed by the additional classification requested is not performed by a classification in the wage determination;

(2) the additional classification is utilized in the area by the construction industry;

(3) the proposed wage rate, including any bona fide fringe benefits, bears a reasonable relationship to the wage rates contained in the wage determination; and

(4) with respect to helpers, when such a classification prevails in the area in which the work is performed.

c. If the contractor or subcontractors, as appropriate, the laborers and mechanics (if known) to be employed in the additional classification or their representatives, and the contracting officer agree on the classification and wage rate (including the amount designated for fringe benefits where appropriate), a report of the action taken shall be sent by the contracting officer to the DOL, Administrator of the Wage and Hour Division, Employment Standards Administration, Washington, D.C. 20210. The Wage and Hour Administrator, or an authorized representative, will approve, modify, or disapprove every additional classification action within 30 days of receipt and so advise the contracting officer or will notify the contracting officer within the 30-day period that additional time is necessary.

d. In the event the contractor or subcontractors, as appropriate, the laborers or mechanics to be employed in the additional classification or their representatives, and the contracting officer do not agree on the proposed classification and wage rate (including the amount designated for fringe benefits, where appropriate), the contracting officer shall refer the question, including the views of all interested parties and the recommendation of the contracting officer, to the Wage and Hour Administrator for determination. Said Administrator, or an authorized representative, will issue a determination within 30 days of receipt and so advise the contracting officer or will notify the contracting officer within the 30-day period that additional time is necessary.

e. The wage rate (including fringe benefits where appropriate) determined pursuant to paragraph 2c or 2d of this Section IV shall be paid to all workers performing work in the additional classification from the first day on which work is performed in the classification.

#### 3. Payment of Fringe Benefits:

a. Whenever the minimum wage rate prescribed in the contract for a class of laborers or mechanics includes a fringe benefit which is not expressed as an hourly rate, the contractor or subcontractors, as

appropriate, shall either pay the benefit as stated in the wage determination or shall pay another bona fide fringe benefit or an hourly case equivalent thereof.

**b.** If the contractor or subcontractor, as appropriate, does not make payments to a trustee or other third person, he/she may consider as a part of the wages of any laborer or mechanic the amount of any cost reasonably anticipated in providing bona fide fringe benefits under a plan or program, provided that the Secretary of Labor has found, upon the written request of the contractor, that the applicable standards of the Davis-Bacon Act have been met. The Secretary of Labor may require the contractor to set aside in a separate account assets for the meeting of obligations under the plan or program.

#### **4. Apprentices and Trainees (Programs of the U.S. DOL) and Helpers:**

##### **a. Apprentices:**

**(1)** Apprentices will be permitted to work at less than the predetermined rate for the work they performed when they are employed pursuant to and individually registered in a bona fide apprenticeship program registered with the DOL, Employment and Training Administration, Bureau of Apprenticeship and Training, or with a State apprenticeship agency recognized by the Bureau, or if a person is employed in his/her first 90 days of probationary employment as an apprentice in such an apprenticeship program, who is not individually registered in the program, but who has been certified by the Bureau of Apprenticeship and Training or a State apprenticeship agency (where appropriate) to be eligible for probationary employment as an apprentice.

**(2)** The allowable ratio of apprentices to journeyman-level employees on the job site in any craft classification shall not be greater than the ratio permitted to the contractor as to the entire work force under the registered program. Any employee listed on a payroll at an apprentice wage rate, who is not registered or otherwise employed as stated above, shall be paid not less than the applicable wage rate listed in the wage determination for the classification of work actually performed. In addition, any apprentice performing work on the job site in excess of the ratio permitted under the registered program shall be paid not less than the applicable wage rate on the wage determination for the work actually performed. Where a contractor or subcontractor is performing construction on a project in a locality other than that in which its program is registered, the ratios and wage rates (expressed in percentages of the journeyman-level hourly rate) specified in the contractor's or subcontractor's registered program shall be observed.

**(3)** Every apprentice must be paid at not less than the rate specified in the registered program for the apprentice's level of progress, expressed as a percentage of the journeyman-level hourly rate specified in the applicable wage determination. Apprentices shall be paid fringe benefits in accordance with the provisions of the apprenticeship program. If the apprenticeship program does not specify fringe benefits, apprentices must be paid the full amount of fringe benefits listed on the wage determination for the applicable classification. If the Administrator for the Wage and Hour Division determines that a different practice prevails for the applicable apprentice classification, fringes shall be paid in accordance with that determination.

**(4)** In the event the Bureau of Apprenticeship and Training, or a State apprenticeship agency recognized by the Bureau, withdraws approval of an apprenticeship program, the contractor or subcontractor will no longer be permitted to utilize apprentices at less than the applicable predetermined rate for the comparable work performed by regular employees until an acceptable program is approved.

##### **b. Trainees:**

**(1)** Except as provided in 29 CFR 5.16, trainees will not be permitted to work at less than the predetermined rate for the work performed unless they are employed pursuant to and

individually registered in a program which has received prior approval, evidenced by formal certification by the DOL, Employment and Training Administration.

**(2)** The ratio of trainees to journeyman-level employees on the job site shall not be greater than permitted under the plan approved by the Employment and Training Administration. Any employee listed on the payroll at a trainee rate who is not registered and participating in a training plan approved by the Employment and Training Administration shall be paid not less than the applicable wage rate on the wage determination for the classification of work actually performed. In addition, any trainee performing work on the job site in excess of the ratio permitted under the registered program shall be paid not less than the applicable wage rate on the wage determination for the work actually performed.

**(3)** Every trainee must be paid at not less than the rate specified in the approved program for his/her level of progress, expressed as a percentage of the journeyman-level hourly rate specified in the applicable wage determination. Trainees shall be paid fringe benefits in accordance with the provisions of the trainee program. If the trainee program does not mention fringe benefits, trainees shall be paid the full amount of fringe benefits listed on the wage determination unless the Administrator of the Wage and Hour Division determines that there is an apprenticeship program associated with the corresponding journeyman-level wage rate on the wage determination which provides for less than full fringe benefits for apprentices, in which cases such trainees shall receive the same fringe benefits as apprentices.

**(4)** In the event the Employment and Training Administration withdraws approval of a training program, the contractor or subcontractor will no longer be permitted to utilize trainees at less than the applicable predetermined rate for the work performed until an acceptable program is approved.

##### **c. Helpers:**

Helpers will be permitted to work on a project if the helper classification is specified and defined on the applicable wage determination or is approved pursuant to the conformance procedure set forth in Section IV. 2. Any worker listed on a payroll at a helper wage rate, who is not a helper under a approved definition, shall be paid not less than the applicable wage rate on the wage determination for the classification of work actually performed.

#### **5. Apprentices and Trainees (Programs of the U.S. DOT):**

Apprentices and trainees working under apprenticeship and skill training programs which have been certified by the Secretary of Transportation as promoting EEO in connection with Federal-aid highway construction programs are not subject to the requirements of paragraph 4 of this Section IV. The straight time hourly wage rates for apprentices and trainees under such programs will be established by the particular programs. The ratio of apprentices and trainees to journeymen shall not be greater than permitted by the terms of the particular program.

#### **6. Withholding:**

The SHA shall upon its own action or upon written request of an authorized representative of the DOL withhold, or cause to be withheld, from the contractor or subcontractor under this contract or any other Federal contract with the same prime contractor or any other Federally-assisted contract subject to Davis-Bacon prevailing wage requirements which is held by the same prime contractor, as much of the accrued payments or advances as may be considered necessary to pay laborers and mechanics, including apprentices, trainee's and helpers, employed by the contractor or any subcontractor the full amount of wages required by the contract. In the event of failure to pay any laborer or mechanic, including any apprentice, trainee, or helper, employed or working on the site of the work, all or part of the wages required by the contract, the SHA contracting officer may, after written notice to the contractor, take

such action as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds until such violations have ceased.

#### **7. Overtime Requirements:**

No contractor or subcontractor contracting for any part of the contract work which may require or involve the employment of laborers, mechanics, watchmen, or guards (including apprentices, trainees, and helpers described in paragraphs 4 and 5 above) shall require or permit any laborer, mechanic, watchman, or guard in any workweek in which he/she is employed on such work, to work in excess of 40 hours in such workweek unless such laborer, mechanic, watchman, or guard receives compensation at a rate not less than one-and-one-half times his/her basic rate of pay for all hours worked in excess of 40 hours in such workweek.

#### **8. Violation:**

**Liability for Unpaid Wages; Liquidated Damages:** In the event of any violation of the clause set forth in paragraph 7 above, the contractor and any subcontractor responsible thereof shall be liable to the affected employee for his/her unpaid wages. In addition, such contractor and subcontractor shall be liable to the United States (in the case of work done under contract for the District of Columbia or a territory, to such District or to such territory) for liquidated damages. Such liquidated damages shall be computed with respect to each individual laborer, mechanic, watchman, or guard employed in violation of the clause set forth in paragraph 7, in the sum of \$10 for each calendar day on which such employee was required or permitted to work in excess of the standard work week of 40 hours without payment of the overtime wages required by the clause set forth in paragraph 7.

#### **9. Withholding for Unpaid Wages and Liquidated Damages:**

The SHA shall; upon its own action or upon written request of any authorized representative of the DOL withhold, or cause to be withheld, from any monies payable on account of work performed by the contractor or subcontractor under any such contract or any other Federal contract with the same prime contractor, or any other Federally-assisted contract subject to the Contract Work Hours and Safety Standards Act, which is held by the same prime contractor, such sums as may be determined to be necessary to satisfy any liabilities of such contractor or subcontractor for unpaid wages and liquidated damages as provided in the clause set forth in paragraph 8 above.

#### **V. STATEMENTS AND PAYROLLS**

(Applicable to all Federal-aid construction contracts exceeding \$2,000 and to all related subcontracts, except for projects located on roadways classified as local roads or rural collectors, which are exempt.)

##### **1. Compliance with Copeland Regulations (29 CFR 3):**

The contractor shall comply with the Copeland Regulations of the Secretary of Labor which are herein incorporated by reference.

##### **2. Payrolls and Payroll Records:**

- a.** Payrolls and basic records relating thereto shall be maintained by the contractor and each subcontractor during the course of the work and preserved for a period of 3 years from the date of completion of the contract for all laborers, mechanics, apprentices, trainees, watchmen, helpers, and guards working at the site of the work.
- b.** The payroll records shall contain the name, social security number, and address of each such employee; his or her correct classification; hourly rates of wages paid (including rates of

contributions or costs anticipated for bona fide fringe benefits or cash equivalent thereof the types described in Section 1(b)(2)(B) of the Davis Bacon Act); daily and weekly number of hours worked; deductions made; and actual wages paid. In addition, for Appalachian contracts, the payroll records shall contain a notation indicating whether the employee does, or does not, normally reside in the labor area as defined in Attachment A, paragraph 1. Whenever the Secretary of Labor, pursuant to Section IV, paragraph 3b, has found that the wages of any laborer or mechanic include the amount of any costs reasonably anticipated in providing benefits under a plan or program described in Section 1(b)(2)(B) of the Davis Bacon Act, the contractor and each subcontractor shall maintain records which show that the commitment to provide such benefits is enforceable, that the plan or program is financially responsible, that the plan or program has been communicated in writing to the laborers or mechanics affected, and show the cost anticipated or the actual cost incurred in providing benefits. Contractors or subcontractors employing apprentices or trainees under approved programs shall maintain written evidence of the registration of apprentices and trainees, and ratios and wage rates prescribed in the applicable programs.

- c.** Each contractor and subcontractor shall furnish, each week in which any contract work is performed, to the SHA resident engineer a payroll of wages paid each of its employees (including apprentices, trainees, and helpers, described in Section IV, paragraphs 4 and 5, and watchmen and guards engaged on work during the preceding weekly payroll period). The payroll submitted shall set out accurately and completely all of the information required to be maintained under paragraph 2b of this Section V. This information may be submitted in any form desired. Optional Form WH-347 is available for this purpose and may be purchased from the Superintendent of Documents (Federal stock number 029-005-0014-1), U.S. Government Printing Office, Washington, D.C. 20402. The prime contractor is responsible for submitting payroll copies of all subcontractors.
- d.** Each payroll submitted shall be accompanied by a "Statement of Compliance," signed by the Contractor or subcontractor or his/her agent who pays or supervises the payment of the persons employed under the contract and shall certify the following:
  - (1)** that the payroll for the payroll period contains the information required to be maintained under paragraph 2b of this Section V and that such information is correct and complete;
  - (2)** that such laborer or mechanic (including each helper, apprentice, and trainee) employed on the contract during the payroll period has been paid the full weekly wages earned, without rebate, either directly or indirectly, and that no deductions have been made either directly or indirectly from the full wages earned, other than permissible deductions as set forth in the Regulations, 29 CFR 3;
  - (3)** that each laborer or mechanic has been paid not less than the applicable wage rate and fringe benefits or cash equivalent for the classification of worked performed, as specified in the applicable wage determination incorporated into the contract.
- e.** The weekly submission of a properly executed certification set forth on the reverse side of Optional Form WH-347 shall satisfy the requirement for submission of the "Statement of Compliance" required by paragraph 2d of this Section V.
- f.** The falsification of any of the above certifications may subject the contractor to civil or criminal prosecution under 18 U.S.C. 1001 and 31 U.S.C. 231.
- g.** The contractor or subcontractor shall make the records required under paragraph 2b of this Section V available for inspection, copying, or transcription by authorized representatives of the SHA, the FHWA, or the DOL, and shall permit such representatives to interview employees during working hours on the job. If the contractor or subcontractor fails to submit the required records or to make them available, the SHA, the FHWA, the DOL, or all may, after written notice to the contractor, sponsor, applicant, or owner, take such



actions as may be necessary to cause the suspension of any further payment, advance, or guarantee of funds. Furthermore, failure to submit the required records upon request or to make such records available may be grounds for debarment action pursuant to 29 CFR 5.12.

## **VI. RECORD OF MATERIALS, SUPPLIES, AND LABOR**

1. On all federal-aid contracts on the national highway system, except those which provide solely for the installation of protective devices at railroad grade crossings, those which are constructed on a force account or direct labor basis, highway beautification contracts, and contracts for which the total final construction cost for roadway and bridge is less than \$1,000,000 (23 CFR 635) the contractor shall:

- a. Become familiar with the list of specific materials and supplies contained in Form FHWA-47, "Statement of Materials and Labor Used by Contractor of Highway Construction Involving Federal Funds," prior to the commencement of work under this contract.
  - b. Maintain a record of the total cost of all materials and supplies purchased for and incorporated in the work, and also of the quantities of those specific materials and supplies listed on Form FHWA-47, and in the units shown on Form FHWA-47.
  - c. Furnish, upon the completion of the contract, to the SHA resident engineer on /Form FHWA-47 together with the data required in paragraph 1b relative to materials and supplies, a final labor summary of all contract work indicating the total hours worked and the total amount earned.
2. At the prime contractor's option, either a single report covering all contract work or separate reports for the contractor and for each subcontract shall be submitted.

## **VII. SUBLETTING OR ASSIGNING THE CONTRACT**

1. The contractor shall perform with its own organization contract work amounting to not less than 30 percent (or a greater percentage if specified elsewhere in the contract) of the total original contract price, excluding any specialty items designated by the State. Specialty items may be performed by subcontract and the amount of any such specialty items performed may be deducted from the total original contract price before computing the amount of work required to be performed by the contractors' own organization (23 CFR 635).

- a. "Its own organization" shall be construed to include only workers employed and paid directly by the prime contractor and equipment owned or rented by the prime contractor, with or without operators. Such term does not include employees or equipment of a subcontractor, assignee, or agent of the prime contractor.
- b. "Specialty Items" shall be construed to be limited to work that requires highly specialized knowledge, abilities, or equipment not ordinarily available in the type of contracting organizations qualified and expected to bid on the contract as a whole and in general are to be limited to minor components of the overall contract.

2. The contract amount upon which the requirements set forth in paragraph 1 of Section VII is computed includes the cost of material and manufactured products which are to be purchased or produced by the contractor under the contract provisions.

3. The contractor shall furnish (a) a competent superintendent or supervisor who is employed by the firm, has full authority to direct performance of the work in accordance with the contract requirements, and is in charge of all construction operations (regardless of who performs the work) and (b) such other of its own organizational resources (supervision, management, and engineering services) as the SHA contracting officer determines is necessary to assure the performance of the contract.

4. No portion of the contract shall be sublet, assigned or otherwise disposed of except with the written consent of the SHA contracting officer, or authorized representative, and such consent when given shall not be construed to relieve the contractor of any responsibility for the fulfillment of the contract. Written consent will be given only after the SHA has assured that each subcontract is evidenced in writing and that it contains all pertinent provisions and requirements of the prime contract.

## **VIII. SAFETY: ACCIDENT PREVENTION**

1. In the performance of this contract the contractor shall comply with all applicable Federal, State, and local laws governing safety, health, and sanitation (23 CFR 635). The contractor shall provide all safeguards, safety devices and protective equipment and take any other needed actions as it determines, or as the SHA contracting officer may determine, to be reasonably necessary to protect the life and health of employees on the job and the safety of the public and to protect property in connection with the performance of the work covered by the contract.

2. It is a condition of this contract, and shall be made a condition of each subcontract, which the contractor enters into pursuant to this contract, that the contractor and any subcontractor shall not permit any employee, in performance of the contract, to work in surroundings or under conditions which are unsanitary, hazardous or dangerous to his/her health or safety, as determined under construction safety and health standards (29 CFR 1926) promulgated by the Secretary of Labor, in accordance with Section 107 of the Contract Work Hours and Safety Standards Act (40 U.S. C. 333).

3. Pursuant to 29 CFR 1926.3, it is a condition of this contract that the Secretary of Labor or authorized representative thereof, shall have right of entry to any site of contract performance to inspect or investigate the matter of compliance with the construction safety and health standards and to carry out the duties of the Secretary under Section 107 of the Contract Work Hours and Safety Standards Act (40 U.S.C. 333).

## **IX. FALSE STATEMENTS CONCERNING HIGHWAY PROJECTS**

In order to assure high quality and durable construction in conformity with approved plans and specifications and a high degree of reliability on statements and representations made by engineers, contractors, suppliers, and workers on Federal-aid highway projects, it is essential that all persons concerned with the project perform their functions as carefully, thoroughly, and honestly as possible. Willful falsification, distortion, or misrepresentation with respect to any facts related to the project is a violation of Federal law. To prevent any misunderstanding regarding the seriousness of these and similar acts, the following notice shall be posted on each Federal-aid highway project (23 CFR 635) in one or more places where it is readily available to all persons concerned with the project:

### **NOTICE TO ALL PERSONNEL ENGAGED ON FEDERAL-AID HIGHWAY PROJECTS**

18 U.S.C. 1020 reads as follows:

*"Whoever, being an officer, agent or employee of the United States, or of any State or Territory, or whoever, whether a person, association, firm, or corporation, knowingly makes any false statement, false representation, or false report as to the character, quality, quantity, or cost of the material used or to be used, or the quantity or quality of the work performed or to be performed, or the cost thereof in connection with the submission of plans, maps, specifications, contracts, or costs of construction on any highway or related project submitted for approval to the Secretary of Transportation; or*

Whoever knowingly makes any false statement, false representation, false report or false claim with respect to the character, quality, quantity, or cost of any work performed or to be performed, or materials furnished or to be furnished, in connection with the construction of any highway or related project approved by the Secretary of Transportation; or

Whoever knowingly makes any false statement or false representation as to material fact in any statement, certificate, or report submitted pursuant to provisions of the Federal-aid Roads Act approved July 1, 1916, (39 Stat. 355), as amended and supplemented;

Shall be fined not more than \$10,000 or imprisoned not more than 5 years or both."

## **X. IMPLEMENTATION OF CLEAN AIR ACT AND FEDERAL WATER POLLUTION CONTROL ACT**

(Applicable to all Federal-aid construction contracts and to all related subcontracts of \$100,000 or more).

By submission of this bid or the execution of this contract, or subcontract, as appropriate, the bidder, Federal-aid construction contractor, or subcontractor, as appropriate, will be deemed to have stipulated as follows:

1. That any facility that is or will be utilized in the performance of this contract, unless such contract is exempt under the Clean Air Act, as amended (42 U.S.C. 1857 *et seq.*, as amended by Pub.L. 91-604), and under the Federal Water Pollution Control Act, as amended (33 U.S.C. 1251 *et seq.*, as amended by Pub.L. 92-500), Executive Order 11738, and regulations in implementation thereof (40 CFR 15) is not listed, on the date of contract award, on the U.S. Environmental Protection Agency (EPA) List of Violating Facilities pursuant to 40 CFR 15.20.

2. That the firm agrees to comply and remain in compliance with all the requirements of Section 114 of the Clean Air Act and Section 308 of the Federal Water Pollution Control Act and all regulations and guidelines listed thereunder.

3. That the firm shall promptly notify the SHA of the receipt of any communication from the Director, Office of Federal Activities, EPA indicating that a facility that is or will be utilized for the contract is under consideration to be listed on the EPA List of Violating Facilities.

4. That the firm agrees to include or cause to be included the requirements of paragraph 1 through 4 of this Section X in every nonexempt subcontract, and further agrees to take such action as the government may direct as a means of enforcing such requirements.

## **XI. CERTIFICATION REGARDING DEBARMENT, SUSPENSION, INELIGIBILITY AND VOLUNTARY EXCLUSION**

1. Instructions for Certification - Primary Covered Transactions:

(Applicable to all Federal-aid contracts - 49 CFR 29)

a. By signing and submitting this proposal, the prospective primary participant is providing the certification set out below.

b. The inability of a person to provide the certification set out below will not necessarily result in denial of participation in this covered transaction. The prospective participant shall submit an explanation of why it cannot provide the certification set out below. The certification or explanation will be considered in connection with the department or agency's determination whether to enter into this transaction. However, failure of the prospective primary participant to furnish a certification or an explanation shall disqualify such a person from participation in

this transaction.

c. The certification in this clause is a material representation of fact upon which reliance was placed when the department or agency determined to enter into this transaction. If it is later determined that the prospective primary participant knowingly rendered an erroneous certification, in addition to other remedies available to the Federal Government, the department or agency may terminate this transaction for cause of default.

d. The prospective primary participant shall provide immediate written notice to the department or agency to whom this proposal is submitted if any time the prospective primary participant learns that its certification was erroneous when submitted or has become erroneous by reason of changed circumstances.

e. The terms "covered transaction," "debarred," "suspended," "ineligible," "lower tier covered transaction," "participant," "person," "primary covered transaction," "principal," "proposal," and "voluntarily excluded," as used in this clause, have the meanings set out in the Definitions and Coverage sections of rules implementing Executive Order 12549. You may contact the department or agency to which this proposal is submitted for assistance in obtaining a copy of those regulations.

f. The prospective primary participant agrees by submitting this proposal that, should the proposed covered transaction be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department or agency entering into this transaction.

g. The prospective primary participant further agrees by submitting this proposal that it will include the clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Lower Tier Covered Transaction," provided by the department or agency entering into this covered transaction, without modification in all lower tier covered transactions and in all solicitations for lower tier covered transactions.

h. A participant in a covered transaction may rely upon a certification of a prospective participant in a lower tier covered transaction that is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. A participant may decide the method and frequency by which it determines the eligibility of its principals. Each participant may, but is not required to, check the nonprocurement portion of the "Lists of Parties Excluded from Federal Procurement or Nonprocurement Programs" (Nonprocurement List) which is compiled by the General Services Administration.

i. Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of participant is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealings.

j. Except for transactions authorized under paragraph f of these instructions, if a participant in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible, or voluntarily excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department or agency may terminate this transaction for cause or default.

\*\*\*\*\*

## **Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Primary Covered Transactions**

1. The prospective primary participant certifies to the best of its knowledge and belief, that it and its principals:

a. Are not presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from

- covered transactions by any Federal department or agency;
- b.** Have not within a 3-year period preceding this proposal been convicted of or had a civil judgment rendered against them for commission of fraud or a criminal offense in connection with obtaining, attempting to obtain, or performing a public (Federal, State or local) transaction or contract under a public transaction; violation of Federal or State antitrust statutes or commission of embezzlement, theft, forgery, bribery, falsification or destruction of records, making false statements, or receiving stolen property;
  - c.** Are not presently indicted for or otherwise criminally or civilly charged by a governmental entity (Federal, State or local) with commission of any of the offenses enumerated in paragraph 1b of this certification; and
  - d.** Have not within a 3-year period preceding this application/proposal had one or more public transactions (Federal, State or local) terminated for cause or default.

2. Where the prospective primary participant is unable to certify to any of the statements in this certification, such prospective participant shall attach an explanation to this proposal.

\*\*\*\*\*

**2. Instructions for Certification - Lower Tier Covered Transactions:**

(Applicable to all subcontracts, purchase orders and other lower tier transactions of \$25,000 or more - 49 CFR 29)

- a.** By signing and submitting this proposal, the prospective lower tier is providing the certification set out below.
- b.** The certification in this clause is a material representation of fact upon which reliance was placed when this transaction was entered into. If it is later determined that the prospective lower tier participant knowingly rendered an erroneous certification, in addition to other remedies available to the Federal Government, the department, or agency with which this transaction originated may pursue available remedies, including suspension and/or debarment.
- c.** The prospective lower tier participant shall provide immediate written notice to the person to which this proposal is submitted if at any time the prospective lower tier participant learns that its certification was erroneous by reason of changed circumstances.
- d.** The terms "covered transaction," "debarred," "suspended," "ineligible," "primary covered transaction," "participant," "person," "principal," "proposal," and "voluntarily excluded," as used in this clause, have the meanings set out in the Definitions and Coverage sections of rules implementing Executive Order 12549. You may contact the person to which this proposal is submitted for assistance in obtaining a copy of those regulations.
- e.** The prospective lower tier participant agrees by submitting this proposal that, should the proposed covered transaction be entered into, it shall not knowingly enter into any lower tier covered transaction with a person who is debarred, suspended, declared ineligible, or voluntarily excluded from participation in this covered transaction, unless authorized by the department or agency with which this transaction originated.
- f.** The prospective lower tier participant further agrees by submitting this proposal that it will include this clause titled "Certification Regarding Debarment, Suspension, Ineligibility and Voluntary Exclusion-Lower Tier Covered Transaction," without modification, in all lower tier covered transactions and in all solicitations for lower tier covered transactions.
- g.** A participant in a covered transaction may rely upon a certification of a prospective participant in a lower tier covered transaction that is not debarred, suspended, ineligible, or voluntarily excluded from the covered transaction, unless it knows that the certification is erroneous. A participant may decide the method and frequency by which it determines the eligibility of its principals. Each participant may, but is not

- required to, check the Nonprocurement List.
- h.** Nothing contained in the foregoing shall be construed to require establishment of a system of records in order to render in good faith the certification required by this clause. The knowledge and information of participant is not required to exceed that which is normally possessed by a prudent person in the ordinary course of business dealing.
- i.** Except for transactions authorized under paragraph e of these instructions, if a participant in a covered transaction knowingly enters into a lower tier covered transaction with a person who is suspended, debarred, ineligible, or voluntarily excluded from participation in this transaction, in addition to other remedies available to the Federal Government, the department or agency with which this transaction originated may pursue available remedies, including suspension and/or debarment.

\*\*\*\*\*

**Certification Regarding Debarment, Suspension, Ineligibility And Voluntary Exclusion-Lower Tier Covered Transactions:**

- 1. The prospective lower tier participant certifies, by submission of this proposal, that neither it nor its principals is presently debarred, suspended, proposed for debarment, declared ineligible, or voluntarily excluded from participation in this transaction by any Federal department or agency.
- 2. Where the prospective lower tier participant is unable to certify to any of the statements in this certification, such prospective participant shall attach an explanation to this proposal.

\*\*\*\*\*

**XII. CERTIFICATION REGARDING USE OF CONTRACT FUNDS FOR LOBBYING**

(Applicable to all Federal-aid construction contracts and to all related subcontracts which exceed \$100,000 - 49 CFR 20)

- 1. The prospective participant certifies, by signing and submitting this bid or proposal, to the best of his or her knowledge and belief, that:
  - a.** No Federal appropriated funds have been paid or will be paid, by or on behalf of the undersigned, to any person for influencing or attempting to influence an officer or employee of any Federal agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with the awarding of any Federal contract, the making of any Federal grant, the making of any Federal loan, the entering into of any cooperative agreement, and the extension, continuation, renewal, amendment, or modification of any Federal contract, grant, loan, or cooperative agreement.
  - b.** If any funds other than Federal appropriated funds have been paid or will be paid to any person for influencing or attempting to influence an officer or employee of any Federal agency, a Member of Congress, an officer or employee of Congress, or an employee of a Member of Congress in connection with this Federal contract, grant, loan, or cooperative agreement, the undersigned shall complete and submit Standard Form-LLL, "Disclosure Form to Report Lobbying," in accordance with its instructions.

2. This certification is a material representation of fact upon which reliance was placed when this transaction was made or entered into. Submission of this certification is a prerequisite for making or entering into this transaction imposed by 31 U.S.C. 1352. Any person who fails to file the required certification shall be subject to a civil penalty of not less than \$10,000 and not

more than \$100,000 for each such failure.

**3.** The prospective participant also agrees by submitting his or her bid or proposal that he or she shall require that the language of this certification be included in all lower tier subcontracts, which exceed \$100,000 and that all such recipients shall certify and disclose accordingly.

**MINIMUM WAGES FOR FEDERAL AND FEDERALLY  
ASSISTED CONSTRUCTION CONTRACTS**

This project is funded, in part, with Federal-aid funds and, as such, is subject to the provisions of the Davis-Bacon Act of March 3, 1931, as amended (46 Sta. 1494, as amended, 40 U.S.C. 276a) and of other Federal statutes referred to in a 29 CFR Part 1, Appendix A, as well as such additional statutes as may from time to time be enacted containing provisions for the payment of wages determined to be prevailing by the Secretary of Labor in accordance with the Davis-Bacon Act and pursuant to the provisions of 29 CFR Part 1. The prevailing rates and fringe benefits shown in the General Wage Determination Decisions issued by the U.S. Department of Labor shall, in accordance with the provisions of the foregoing statutes, constitute the minimum wages payable on Federal and federally assisted construction projects to laborers and mechanics of the specified classes engaged on contract work of the character and in the localities described therein.

General Wage Determination Decisions, modifications and supersedes decisions thereto are to be used in accordance with the provisions of 29 CFR Parts 1 and 5. Accordingly, the applicable decision, together with any modifications issued, must be made a part of every contract for performance of the described work within the geographic area indicated as required by an applicable DBRA Federal prevailing wage law and 29 CFR Part 5. The wage rates and fringe benefits contained in the General Wage Determination Decision shall be the minimum paid by contractors and subcontractors to laborers and mechanics.

**NOTICE**

The most current **General Wage Determination Decisions** (wage rates) are available on the IDOT web site. They are located on the Letting and Bidding page at <http://www.dot.state.il.us/desenv/delett.html>.

In addition, ten (10) days prior to the letting, the applicable Federal wage rates will be e-mailed to subscribers. It is recommended that all contractors subscribe to the Federal Wage Rates List or the Contractor's Packet through IDOT's subscription service.

PLEASE NOTE: if you have already subscribed to the Contractor's Packet you will automatically receive the Federal Wage Rates.

The instructions for subscribing are at <http://www.dot.state.il.us/desenv/subsc.html>.

If you have any questions concerning the wage rates, please contact IDOT's Chief Contract Official at 217-782-7806.