



CLASS B PATCHES, TYPES II, III, IV (SEE SCHEDULES FOR DEPTH)

PAVEMENT PATCHING (PARTIAL DEPTH)

COMBINATION CURB AND GUTTER REMOVAL, COMBINATION CONCRETE CURB AND GUTTER, TYPE M-6.18 (MODIFIED)

DETECTABLE WARNINGS

SIDEWALK REMOVAL, PORTLAND CEMENT CONCRETE SIDEWALK 6 INCH

MANHOLES TO BE ADJUSTED; MANHOLES TO BE ADJUSTED WITH NEW TYPE 1 FRAME, CLOSED LID; VALVE VAULTS TO BE ADJUSTED; VALVE VAULTS TO BE ADJUSTED WITH NEW TYPE 1 FRAME, CLOSED LID; SANITARY MANHOLES TO BE ADJUSTED

JOB: 04-28-09-024

SHEET NO.

9

23

INLETS TO BE ADJUSTED (SPECIAL)





PLAN AND PROFILE	
LONGWOOD STREET (SECTION 09-00568-00-RS) WHITMAN STREET INTERCHANGE	ROCKFORD, ILLINOIS

FILE:H:\09-024 WHITMAN INTERCHANGE\DESIGN\DRAWINGS\09-024 LONGWOOD P&P.DWG