TRAFFIC SIGNAL LEGEND

ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	\bowtie R	\bowtie		EMERGENCY VEHICLE LIGHT DETECTOR	$\overset{R}{\leqslant}$	\bowtie	~	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE			
AILROAD CONTROL CABINET		B B		CONFIRMATION BEACON	R_{o-0}	0-0	••			\sim	
DMMUNICATIONS CABINET	C C R	E C C	СС	HANDHOLE	R □			COAXIAL CABLE		<u> </u>	<u> </u>
ASTER CONTROLLER		EMC	MC		R	H	Ш	VENDOR CABLE FOR CAMERA			(V)
ASTER MASTER CONTROLLER	R	EMMC	MMC	HEAVY DUTY HANDHOLE	R			COPPER INTERCONNECT CABLE,		/	_
NINTERRUPTIBLE POWER SUPPLY ERVICE INSTALLATION.	UPS	EUPS	UPS	DOUBLE HANDHOLE JUNCTION BOX	R 🔘		N	NO. 18 3 PAIR TWISTED, SHIELDED		<u></u>	<u>—6</u> —
P) POLE OR (G) GROUND MOUNT	-□- ^R	-□ ^P	- ■ P	GALVANIZED STEEL CONDUIT				FIBER OPTIC CABLE NO. 62.5/125, MM12F		— <u>12</u> F—	
ELEPHONE CONNECTION P) POLE OR (G) GROUND MOUNT	R	P	P	IN TRENCH (T) OR PUSHED (P)				FIBER OPTIC CABLE		— <u>24</u> F—	—(24F)—
TEEL MAST ARM ASSEMBLY AND POLE	R	0	•	TEMPORARY SPAN WIRE, TETHER WIRE, AND CABLE	<u>R</u>			NO. 62.5/125, MM12F SM12F		رسي الم	
LUMINUM MAST ARM ASSEMBLY AND POLE	R	0		COMMON TRENCH			СТ	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE		-	——
TEEL COMBINATION MAST ARM		0-×	•	COILABLE NONMETALLIC CONDUIT (EMPTY)			CNC	NOTED ON PLANS)		<i></i>	
SSEMBLY AND POLE WITH LUMINAIRE	R	-	_	SYSTEM ITEM		S	S	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM,		c _{il}	^C ∥ ⊢ •
TEEL COMBINATION MAST ARM SSEMBLY AND POLE WITH PTZ CAMERA		PTZ]1	PTZ	INTERSECTION ITEM		I	ΙP	OR (S) SERVICE		ч	•
IGNAL POST	R O	0	•	REMOVE ITEM	R			CONTROLLER CABINET AND FOUNDATION TO BE REMOVED	RCF		
EMPORARY WOOD POLE (CLASS 5 OR BETTER) 45 FOOT (13.7m) MINIMUM	R⊗	\otimes	•	RELOCATE ITEM ABANDON ITEM	RL A			STEEL MAST ARM POLE AND	RMF		
UY WIRE	R	>	>-	12" (300mm) TRAFFIC SIGNAL SECTION	Α	R	R	FOUNDATION TO BE REMOVED	<u> </u>		
IGNAL HEAD	R —	>	-	12// /Z00mm) DED WITH 0// /200				ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
IGNAL HEAD CONSTRUCTION STAGES NUMBERS INDICATE THE CONSTRUCTION STAGE)	-		→ ²	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE		N—4		STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF O-X		
IGNAL HEAD WITH BACKPLATE	+₽ R	+1>	+			R	R	FOUNDATION TO BE REMOVED			
IGNAL HEAD OPTICALLY PROGRAMMED	R —□>′′P′′	- >′′p′′	→ "P"	SIGNAL FACE		C	G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF		
LASHER INSTALLATION 5 DENOTES SOLAR POWER)	R O- - ≫"F"	O-D"F"	• "F"			(• Y) (• G)	∢ Y ∢ G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		IS	IS
EDESTRIAN SIGNAL HEAD	R -□	-[]	-			R	R	SAMPLING (SYSTEM) DETECTOR		[5]	S
EDESTRIAN PUSHBUTTON DETECTOR	R	©	•	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD		(<u>)</u>	Y G	EXISTING INTERSECTION LOOP DETECTOR		[<u>P</u>]	
CCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R APS	@APS	APS O O O O O O O O O O O O O				◆ Y ◆ G	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR)R		
LUMINATED SIGN	R					"P"	"P"	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR)R	PP]	
NO LEFT TURN"	9		•	12" (300mm) PEDESTRIAN SIGNAL HEAD		(W)		PREFORMED INTERSECTION AND SAMPLING		PIS	PIS
LLUMINATED SIGN NO RIGHT TURN''	R (C)			WALK/DON'T WALK SYMBOL		(W)		(SYSTEM) DETECTOR			
				12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		ÎPSÎ	[PS]
ETECTOR LOOP, TYPE I		a		12" (300mm) PEDESTRIAN SIGNAL HEAD		()		BAUBOAB			
REFORMED DETECTOR LOOP		F - 4	P	INTERNATIONAL SYMBOL, SOLID			*	RAILROAD	21MR0	LS	
ICROWAVE VEHICLE SENSOR	R M	M	M	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		(C) C	₽ C ★ D			EXISTING	<u>PROPOSE</u> [
IDEO DETECTION CAMERA	R	(V)	V	RADIO INTERCONNECT	##*O	##••	₩	RAILROAD CONTROL CABINET		R ≥ B	
IDEO DETECTION ZONE					1.		<u> </u>	RAILROAD CANTILEVER MAST ARM	×		X Q X X
	R			RADIO REPEATER	R ERR	ERR	RR	FLASHING SIGNAL		X0 X	_ · X ⊖ X
AN, TILT, ZOOM CAMERA	PTZ]1	PTZ)1	PTZ¶	DENOTES NUMBER OF CONDUCTORS, ELECTRIC CABLE NO. 14, UNLESS NOTED OTHERWISE,		_5_					
VIRELESS DETECTOR SENSOR	RW	W	W	ALL DETECTOR LOOP CABLE TO BE SHIELDED		/-	-	CROSSING GATE		X0 X -	X ⊕ X-
VIRELESS ACCESS POINT	R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		1	1	CROSSBUCK		≥	*
NAME = USER NAME = konthophixoy		ESIGNED - DAG/BCK RAWN - BCK	REVISED REVISED		OE II I INCI			DISTRICT 1	F.A. P. RTE. 307	SECTION	COUNTY TO
<pre>v_work\PWIDOT\KANTHAPHIXAYBC\d01126 4\troffic_legend_v7.dgn PLOT SCALE = 20.0000 / / I</pre>				STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION			STANDARD TRAFFIC SIGNAL DESIGN DETAILS			131B-BR	DuPAGE CONTRACT NO