

PLOT DATE :

CHECKED - MTH

REVISED

## PART "B" SHEET 92 OF 136

NOTES

Detail I - With Bar Splicer or Couplers: Connect one (I) 1" x 7" (x "W" steel P to the top layer of couplers with 2-58" \$ boils screwed to coupler at approximate & of each barrier panel. Detail II - With Extended Reinforcement Bars; Connect one (J) 1" x 7" x "W" steel L to the concrete slab or concrete wearing surface with  $2 - \frac{5}{8}$ "  $\phi$ Expansion Anchors or cast in place inserts spaced between the top layer of reinforcement at approximate  $\varphi$  of each barrier panel. Cost of anchorage is included with Temporary Concrete Barrier, The I'' x 7'' x 'W'' plate shall not be removed until stage II construction forms and all reinforcement bars are in place and the concrete is ready



<sup>\*</sup> Required only with Detail II

FOR STAGE CONSTRUCTION	F.A.I. RTE.	SECTION	COUNTY	TOTAL	SHEET NO.
F.A.I72 - S.N. 0840154	72	• -10-1RS-3, 84-10-2RS-R)BR.I	SANGAMON CONTRACT	194 NO 7	150 2090
S SHEETS	FED. ROAD DIST. NO. 6  ILLINDIS FED. AND PROJECT				