				,,,,,,	w		JOOJE		
	F.A.P. RTE.	SECTION COUNT			′	TOTAL	SHEET NO.		
	338	112 N-2		DU PAGE		42	2 .		
	STA. TO STA.								
	FFD. ROAL	D DIST. NO.	THE TNOTS	FED.	ATD	PROJECT	-		

INDEX OF SHEETS

SHE	EET NO.	DESCRIPTION
	1	TITLE SHEET
	2	INDEX OF SHEETS, STATE STANDARDS AND GENERAL NOTES
	3 - 5	SUMMARY OF QUANTITIES
	6 - 8	TYPICAL CROSS SECTIONS
	9-10	ROADWAY PLANS
	11	PAVEMENT MARKING PLANS
	12-26	TRAFFIC SIGNAL PLANS
	27	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING
	28	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT
	29	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMEN
	30	BUTT JOINT AND HMA TAPER DETAILS
	. 31	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS
	32	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)
	33-34	DISTRICT ONE TYPICAL PAVEMENT MARKINGS
	35	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)
	36	SIGNING FOR FLAGGING OPERATIONS AT WORK ZONE OPENINGS
	37	PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING
	38	ARTERIAL ROAD INFORMATION SIGN
	39-41	DISTRICT ONE STANDARD TRAFFIC SIGNAL DESIGN DETAILS
	. 42	DISTRICT ONE DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING

STANDARDS

000001-05	STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS
424001- <i>0</i> 5	CURB RAMPS FOR SIDEWALKS
442201- <i>03</i>	CLASS C AND D PATCHES
482011 <i>-03</i>	HMA SHOULDER STRIPS/SHPULDERS WITH RESURFACING OR WIDENING & RESURFACING PROJECTS
604016 <i>-01</i>	FRAME AND GRATE, TYPE 4
606001- <i>03</i>	CONCRETE CURB & COMBINATION CONCRETE CURB & GUTTER
606301- <i>03</i>	PC CONCRETE ISLANDS AND MEDIANN
606306- 02	CORRUGATED PC CONCRETE MEDIAN
701301 - 02	LANE CLOSURE, 2L, 2W, SHORT TIME OPERATIONS
701311- <i>0</i> 2	LANE CLOSURE, 2L, 2W, MOVING DAY ONLY OPERATIONS
701606- 05	URBAN LANE CLOSURE, MULTILANE, 2W WITH MOUNTABLE MEDIAN
701701- <i>05</i>	LANE CLOSURE, MULTILANE, 1W OR 2W, CROSSWALK OR SIDEWALK CLOSURE
701801- <i>03</i>	TRAFFIC CONTROL DEVICES
701901	TYPICAL APPLICATIONS, RAISED REFLECTIVE PAVEMENT MARKERS
· · · · · · · · · · · · · · · · · · ·	and the control of th

GENERAL NOTES

BEFORE STARTING ANY EXCAVATION, THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES.(48 HOUR NOTIFICATION IS REQUIRED)

THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH UTILITY COMPANIES AND THE CITY OF WARRENVILLE.

THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.

THE CONTRACTOR SHALL CONTACT THE DISTRIC ONE ARTERIAL TRAFFIC CONTROL SUPERVISOR AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO START OF WORK.

BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PARVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HOT-MIX ASPHALT TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.

THE RESIDENT ENGINEER SHALL CONTACT MR. DON CHIARUGI, AREA TRAFFIC ENGINEER, AT (847) 741-9857 A MINIMUM OF 2 WEEKS PRIOR TO PLACEMENT OF PERMANENT PAVEMENT MARKING.

WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC, THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1 1/2 INCHES WHERE THE POSTED SPEED IS 45 MPH OR LESS AND 1 INCH WHERE THE POSTED SPEED IS GREATER THAN 45 MPH. WITH WRITTEN APROVAL FROM THE ENGINNER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED AT A MINIMUM OF 1:3 (V:H).

PAVEMENT MARKING TAPE, TYPE III SHALL BE USED FOR SHORT TERM PAVEMENT MARKING ON ALL FINAL SURFACES, THE COST OF THE PAVEMENT MARKING TAPE, TYPE III AND ITS REMOVAL SHALL BE INCLUDED IN THE COST OF SHORT TERM PAVEMENT MARKING.

REVISIONS
NAME
DATE
ILLINOIS DEPARTMENT OF TRANSPORTATION
INDEX OF SHEETS,
STATE STANDARDS &
GENERAL NOTES

SCALE: VERT.
HORIZ.
DATE
CHECKED BY