TRAFFIC SIGNAL LEGEND

ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	\bowtie R	\bowtie		EMERGENCY VEHICLE LIGHT DETECTOR	R≪	∞ <	~	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE			
AILROAD CONTROL CABINET		R I	▶ ◀	CONFIRMATION BEACON	R_{o-1}	\circ	•-(~	
MMUNICATIONS CABINET	C C R	E C C	СС	HANDHOLE	R			COAXIAL CABLE		—(c)—	— <u>c</u> —
ASTER CONTROLLER		EMC	MC		R			VENDOR CABLE FOR CAMERA		(v)	
ASTER MASTER CONTROLLER	R	ЕММС	MMC	HEAVY DUTY HANDHOLE	D	Н		COPPER INTERCONNECT CABLE,		,	<u></u>
NINTERRUPTIBLE POWER SUPPLY	UPS	EUPS	UPS	DOUBLE HANDHOLE	~ <u>\</u> \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		0	NO. 18 3 PAIR TWISTED, SHIELDED			<u>—6</u> —
ERVICE INSTALLATION,) POLE OR (G) GROUND MOUNT	-□ ^{-R}	- <u></u> -	- ■ P	JUNCTION BOX GALVANIZED STEEL CONDUIT IN TRENCH (T) OR PUSHED (P)				FIBER OPTIC CABLE NO. 62.5/125, MM12F		—(12F)—	
ELEPHONE CONNECTION POLE OR (G) GROUND MOUNT	R	P	P	TEMPORARY SPAN WIRE, TETHER WIRE,	R			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		—24F—	—24F—
TEEL MAST ARM ASSEMBLY AND POLE	R	0	•	AND CABLE						,	
UMINUM MAST ARM ASSEMBLY AND POLE	R	0		COMMON TRENCH			СТ	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE		-	——
EEL COMBINATION MAST ARM SEMBLY AND POLE WITH LUMINAIRE	^R O→¤	0-¤	•*	COILABLE NONMETALLIC CONDUIT (EMPTY) SYSTEM ITEM		S	CNC S	NOTED ON PLANS) GROUND ROD AT (C) CONTROLLER,		, ,	C .
EEL COMBINATION MAST ARM	R	PTZ]1	PTZ	INTERSECTION ITEM		I	ΙΡ	(H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE		C	^c ⊪•
SEMBLY AND POLE WITH PTZ CAMERA	PIZI		PIZ	REMOVE ITEM	R	•		CONTROLLER CABINET AND	RCF		
IGNAL POST EMPORARY WOOD POLE (CLASS 5 OR	KO R	0	•	RELOCATE ITEM	RL			FOUNDATION TO BE REMOVED			
ETTER) 45 FOOT (13.7m) MINIMUM	^R ⊗	\otimes		ABANDON ITEM	А			STEEL MAST ARM POLE AND	ORMF		
Y WIRE	>R	>	>	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	FOUNDATION TO BE REMOVED	DIVE		
SNAL HEAD	R ⊢	>	-	12" (300mm) RED WITH 8" (200mm)		(R)		ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF		
SNAL HEAD CONSTRUCTION STAGES IMBERS INDICATE THE CONSTRUCTION STAGE)			-	YELLOW AND GREEN TRAFFIC SIGNAL FACE				STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF O-X		
SNAL HEAD WITH BACKPLATE	+ ○ R	+->	+			R	R	FOUNDATION TO BE REMOVED	<i>5</i> //		
CNAL HEAD OPTICALLY PROGRAMMED	R →⊃′′P′′	-[>"P"	─ ─"P"	SIGNAL FACE		G	G ◀Y	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF		
ASHER INSTALLATION DENOTES SOLAR POWER)	R O-⊠''F''	O-⊳"F"	●→ "F"			4 0	 G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		[IS]	IS
DESTRIAN SIGNAL HEAD	R ⊣∏	-0	-			R	R	SAMPLING (SYSTEM) DETECTOR		[5]	S
DESTRIAN PUSHBUTTON DETECTOR	R (©	©	®	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD		Ŷ G	Y	EXISTING INTERSECTION LOOP DETECTOR		1 <u>-</u> -1	[3]
CESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R APS	(©) APS	APS				4 Y	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETE	CTOR	L'_'	
LUMINATED SIGN	R	<u> </u>	Ü			"P"	4 G	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETE	CTOR	ÎPPÎ	
O LEFT TURN"	•			12" (300mm) PEDESTRIAN SIGNAL HEAD WALK/DON'T WALK SYMBOL		(W)		PREFORMED INTERSECTION AND SAMPLING		PIS	PIS
LUMINATED SIGN IO RIGHT TURN''	R			12" (300mm) PEDESTRIAN SIGNAL HEAD				(SYSTEM) DETECTOR			
TECTOR LOOP, TYPE I		F-1		INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		ÎPSÎ	[PS]
11201011 2001, 1112 1		»	•	12" (300mm) PEDESTRIAN SIGNAL HEAD		(•	DAUDOAD	CVMD	OL C	
REFORMED DETECTOR LOOP		7-4 1-1	Р	INTERNATIONAL SYMBOL, SOLID			*	RAILROAD	21MR	nr9	
CROWAVE VEHICLE SENSOR	R [M][1]	M	M	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		(C) C	₽ C			<u>EXISTING</u>	PROPOSED
DEO DETECTION CAMERA	R [V]	(V)	(V)■	RADIO INTERCONNECT	 	##+0		RAILROAD CONTROL CABINET		R B	₽⋖
DEO DETECTION ZONE				RADIO REPEATER	R ERR	ERR	RR	RAILROAD CANTILEVER MAST ARM		X OX X X	XeX X
N, TILT, ZOOM CAMERA	R PTZ[1	PIZM	PīZ	DENOTES NUMBER OF CONDUCTORS, ELECTRIC	LIM	E-1017		FLASHING SIGNAL		$\times \rightarrow \times$	$X \oplus X$
RELESS DETECTOR SENSOR	RW	W	W	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED				CROSSING GATE		$\times \times \times$	X 0 X
RELESS ACCESS POINT	R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		(1)	(1)	CROSSBUCK		≥	*
NAME = USER NAME = bouerdl	DE	SIGNED - DAG/BCK	REVISED	-	or united			DISTRICT ONE	F.A.P. RTE.	SECTION	COUNTY TOTA
work\PWIDOT\BAUERDL\dØ108315\ts05 dgn PLOT SCALE = 50.0000 '/		AWN - BCK ECKED - DAD	REVISED REVISED	STATE DEPARTMENT	OF ILLINOIS			STANDARD TRAFFIC SIGNAL DESIGN DETAILS	326	106X-B TS05	KANE 87 CONTRACT NO.