TRAFFIC SIGNAL LEGEND

ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM -	REMOVAL EXIS	TING	PROPOSED
CONTROLLER CABINET	R	\boxtimes		EMERGENCY VEHICLE LIGHT DETECTOR	R ≪	\bowtie	~	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE		1)—	
AILROAD CONTROL CABINET		R R		CONFIRMATION BEACON	R_{o-1}	0-(]	⊷ (~	
OMMUNICATIONS CABINET	CC	C C	СC	HANDHOLE	R			COAXIAL CABLE	—	9)—	— <u>c</u> —
ASTER CONTROLLER		EMC	MC				-	VENDOR CABLE FOR CAMERA		<u>v</u>	
ASTER MASTER CONTROLLER	R	EMMC	ММС	HEAVY DUTY HANDHOLE	K _H	Н	H		\rightarrow	<u> </u>	
NINTERRUPTIBLE POWER SUPPLY	UPS	EUPS	UPS	DOUBLE HANDHOLE	R R			COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED	_	<u> </u>	<u>—6</u> —
ERVICE INSTALLATION,) POLE OR (G) GROUND MOUNT	R	P	<u> </u>	JUNCTION BOX GALVANIZED STEEL CONDUIT		<u> </u>	•	FIBER OPTIC CABLE	—(1	5 —	
ELEPHONE CONNECTION POLE OR (G) GROUND MOUNT	R	P	P	IN TRENCH (T) OR PUSHED (P) TEMPORARY SPAN WIRE, TETHER WIRE,	D			NO. 62.5/125, MM12 ⁻ FIBER OPTIC CABLE NO. 62.5/125, MM12 ⁻ SM12F	<i>'</i>	45—	—24F—
TEEL MAST ARM ASSEMBLY AND POLE	R	0	•	AND CABLE							
LUMINUM MAST ARM ASSEMBLY AND POLE	R 0	0		COMMON TRENCH			СТ	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE	—	5-	
TEEL COMBINATION MAST ARM	R	O - ¤	• × ·	COILABLE NONMETALLIC CONDUIT (EMPTY)			CNC	NOTED ON PLANS)	<i>'</i>		
SSEMBLY AND POLE WITH LUMINAIRE TEEL COMBINATION MAST ARM	R	Q	PTZ	SYSTEM ITEM INTERSECTION ITEM		S	S IP	GROUND ROD AT (C) CONTROLLER, (H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE	C		c
SSEMBLY AND POLE WITH PTZ CAMERA			FIZ	REMOVE ITEM	R			CONTROLLER CABINET AND	RCF		
IGNAL POST EMPORARY WOOD POLE (CLASS 5 OR	R _O	0	•	RELOCATE ITEM	RL			FOUNDATION TO BE REMOVED			
EMPORARY WOOD POLE (CLASS 5 OR ETTER) 45 FOOT (13.7m) MINIMUM	^R ⊗	\otimes	•	ABANDON ITEM	А				RMF		
UY WIRE	R	>	>-	12" (300mm) TRAFFIC SIGNAL SECTION		R	R	FOUNDATION TO BE REMOVED			
IGNAL HEAD	R —	\rightarrow	-	12// (300mm) PED WITH 9// (200)		R		ALUMINUM MAST ARM POLE AND FOUNDATION TO BE REMOVED	RMF X		
GNAL HEAD CONSTRUCTION STAGES UMBERS INDICATE THE CONSTRUCTION STAGE)			-	12" (300mm) RED WITH 8" (200mm) YELLOW AND GREEN TRAFFIC SIGNAL FACE				AND POLE WITH LUMINAIRE AND	ŘMF)—α∕———		
IGNAL HEAD WITH BACKPLATE	+C>R	+	+-			R	R	FOUNDATION TO BE REMOVED			
GNAL HEAD OPTICALLY PROGRAMMED	R —⇔′′P′′	—[>"P"	— ▶ "P"	SIGNAL FACE			G	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF O		
ASHER INSTALLATION DENOTES SOLAR POWER)	R O-E>″F″	O-t>"F"	●▶ "F"				∢ Y ∢ G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR	[5]	IS
EDESTRIAN SIGNAL HEAD	R_III	-0	4			R	R	SAMPLING (SYSTEM) DETECTOR	_		S
	R _C		_	SIGNAL FACE WITH BACKPLATE.			Y		i_	5_	3
EDESTRIAN PUSHBUTTON DETECTOR	(9)	(0)	©	"P" INDICATES PROGRAMMED HEAD		(G) (4 Y)	G ◀Y	EXISTING INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		5]	
CCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	APS B	⊚APS	APS		<u>"</u>		√ G	EXISTING PREFORMED INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR	Ŷ-	- 1	
LLUMINATED SIGN NO LEFT TURN''	6	8	9	12" (300mm) PEDESTRIAN SIGNAL HEAD		[5W]		PREFORMED INTERSECTION AND SAMPLING			•—•
LUMINATED SIGN	R			WALK/DON'T WALK SYMBOL		W		(SYSTEM) DETECTOR	6-	IS.	PIS
NO RIGHT TURN"				12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR	q - L	- • S	[PS]
ETECTOR LOOP, TYPE I							a .				
REFORMED DETECTOR LOOP			P	12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, SOLID		A	*	RAILROAD S	SYMBOLS		
ICROWAVE VEHICLE SENSOR	R M		••••••••••••••••••••••••••••••••••••••	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER		() C (3) D	₽ C		EXISTI	<u>NG</u>	PROPOSED
IDEO DETECTION CAMERA	R [V]		V ■	DADIO INTERCONNECT	In R =			RAILROAD CONTROL CABINET	r. r		₽✓₽
IDEO DETECTION ZONE				RADIO INTERCONNECT	##*O	##+0	71111	RAILROAD CANTILEYER MAST ARM	<u> </u>		XeX
	D			RADIO REPEATER	R ERR	ERR	RR				
AN, TILT, ZOOM CAMERA	R PZI	PT	PIZ	DENOTES NUMBER OF CONDUCTORS, ELECTRIC		Œ\	Œ	FLASHING SIGNAL	∑ ⊖∑	2	X ⊕ X
TRELESS DETECTOR SENSOR	RW	(W)	W	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED			—5—	CROSSING GATE	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	35-	XOX
IRELESS ACCESS POINT	R			GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)		1	1	CROSSBUCK	75		*
USER NAME = rmamucod		SIGNED JA	REVISED -					DISTRICT 1	F.A.P. SEC	TION	COUNTY TOTA
PLOT SCALE = \$SCALE\$		AWN RM ECKED HS	REVISED -	STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION			S	STANDARD TRAFFIC SIGNAL DESIGN DETAILS	330 0105	-WRS	COOK 537