SINGLE LANE WEAVE MULTI-LANE WEAVE GENERAL NOTES 84-94-IW ① EXISTING CONFLICTING PAVEMENT MARKING LINES SHALL BE REMOVED. PAVEMENT MARKING REMOVAL SHALL NOT BE REQUIRED FOR SINGLE LANE VERTICAL PANELS OR BARRICADES WEAVES UNDER 24 HOURS IN DURATION. @ 200'(60 m)ON TANGENT (3) @ 100' (30 m) ON CURVE ② CONTINOUS REFLECTIVE TEMPORARY PAVEMENT MARKING TAPE SHALL BE PLACED THROUGHOUT THE TAPER AND FOR 300' (90 m) ALONG SIDE THE WORK AREA WHERE STING LANE LINES SH, COVERED WITH BLACK THE CLOSURE TIME IS GREATER THAN FOURTEEN DAYS. THE LEFT EDGE LINE SHALL BE YELLOW AND THE RIGHT EDGE LINE SHALL BE WHITE. FOR MULTI-LANE WEAVES ပ် ခြ LANE LINES SHALL BE 5 INCH, 10'-30' (3 m-9 m) SKIP DASH, WHITE. (3) PLASTIC DRUMS WITH STEADY BURN LIGHTS AT 50' (15 m) C-C SPACING IN TAPERS AND WI-6RO-6030 $(\bar{1})(\bar{2})$ 100' (30 m) C-C SPACING IN TANGENTS. ABOVE TYPE II BARRICADE (4) ALL SIGNS SHALL BE POST MOUNTED IF THE CLOSURE TIME EXCEEDS FOUR DAYS. (5) (5) IF A TYPE III BARRICADE WITH AN ATTACHED SIGN PANEL WHICH MEETS NCHRP 350 IS WI-6R0-6030 NOT AVAILABLE, THE SIGNS MAY BE MOUNTED ON NCHRP 350 TEMPORARY SIGN SUPPORTS. ABOVE TYPE TYPE III BARRICADES MAY BE OMMITTED FOR SINGLE-LANE WEAVES UNDER 24-HOURS IN BARRICADE DURATION. W1-6 SIGNS WILL STILL BE REQUIRED. IF THE WIDTH OF OFFSET IS LESS THAN 6' THEN THE TYPE III BARRICADE WITH ATTACHED ARROW SIGN PANE_ CAN BE ELIMINATED IN THE TAPER AREAS. 6 WHEN THE LENGTH OF THE SHIFTED SEGMENT (DISTANCE BETWEEN WEAVE POINTS) IS (3)1 LESS THAN 1500', DOUBLE REVERSE CURVE SIGNS (W24-1) SHOULD BE USED INSTEAD OF THE REVERSE CURVE (W1-4) SIGNS. ARROWS ON THE 4'X8' "ALL TRAFFIC" SIGNS SHALL BE (3) (7) THE NUMBER OF ARROWS ON THESE SIGNS SHALL MATCH THE NUMBER OF LANES OPEN TO TRAFFIC. 2002 $4' \times 8'$ (1.2 m \times 2.4 m); 1 (25) BORDER; 10 (250) CAPITAL ALL TRAFFIC LETTERS BACKGROUND SHEETING SHALL BE THE SAME AS ALL DIAMOND SHAPED CONSTRUCTION SIGNS. 67 (3)-SHOULDER SYMBOLS (1)(2)(3) DIRECTION OF TRAFFIC WI-6RO-6030 ABOVE TYPE III BARRICADE SIGN ON PORTABLE OR PERMANENT SUPPORT TYPE II BARRICADE OR DRUM WITH MONO-DIRECTIONAL STEADY BURNING LIGHT SIGNING, BARRICADING, & PAVEMENT MARKING W1-4R-48 ACCORDING TO FREEWAY STANDARD FOR A ONE LANE CLOSURE. W24-1-48 RIGHT LANE CLOSED SIGNING & BARRICADING ACCORDING TO W1-4R-48 FREEWAY STANDARD FOR A ONE LANE CLOSURE ALL DIMENSIONS ARE IN INCHES (MILLIMETERS) UNLESS OTHERWISE SHOWN

FILE NAME DESIGNED - DWS USER NAME loopa REVISED - JAF 01-03 COUNTY TRAFFIC CONTROL DETAILS FOR W:\drs to td\22x34\ tc:8%dq RAWN REVISED - JAF 02-06 STATE OF ILLINOIS COOK 919 541 305 (1920,.01,1518,2022&1922.4B)R FREEWAY SINGLE & MULTI-LANE WEAVE PLOT SCALE 50.000 1/ IN. CHECKED REVISED -SPB 01-07 **DEPARTMENT OF TRANSPORTATION** TC-09 CONTRACT NO. 60T35 SHEET NO. 1 OF 1 SHEETS STA. PLDT DATE 1/26/2010 SCALE: NONE DATE 02-87 REVISED - SPB 12-09