


VALVE VAULT DETAIL N.T.S.



TAKE UP SLACK IN THE TUBE ALONG THE BARREL OF THE PIPE TO MAKE A SNUG, BUT NOT TIGHT, FIT.

FOLD EXCESS POLY-ETHYLENE BACK OVER THE TOP OF THE PIPE


SECURE THE FOLD AT SEVERAL LOCATIONS ALONG THE PIPE BARREL (APPROX. EVERY THREE FEET).


## POLYETHYLENE ENCASEMENT FOR DUCTILE IRON PIPE

N.T.S.

## NOTES:

- REPAIR ALL SMALL RIPS, TEARS OR
  OTHER TUBE DAMAGE WITH ADHESIVE TAPE.
  ONE LENGTH OF POLYETHYLENE TUBE FOR
- EACH LENGTH OF PIPE, OVERLAPPED AT JOINT.






CASING PIPE DETAIL

2. MECHANICAL RESTRAINED JOINT PIPE SHALL BE USED IN

VALVE BOX COVER W/ GROUND ELEV "WATER" CAST IN 6" VALVE BOX-VALVE BOX STABILIZER-VALVE OR APPROVED THRUST BLOCKS (8" X 8" X 16" TYP.)

\*\*VALVE BOXES PERMITTED ONLY WHERE APPROVED BY THE VILLAGE.

VALVE BOX DETAIL N.T.S.



٠٥,		REMOVAL
INSIDE DIAMETER OF CONDUIT IN INCHES "D"	MAXIMUM TRENCH WIDTH IN FEET FOR PAYMENT	MAXIMUM PAVEMENT F WIDTH IN FEET FOR PAYMENT
6	3.58	5.58
8	3.78	5.78
10	3.97	5.97
12	4.17	6.17
14	4.36	6.36
15	4.46	6.46
16	4.56	6.56
18	4.75	6.75
20	4.94	6.94
21	5.04	7.04
24	5.33	7.33

\*\*PAVEMENT SHALL INCLUDE ALL AREAS WITHIN 2FT OF STREETS, CURBS, GUTTERS, DRIVEWAYS, AND SIDEWALKS.

## TRENCH SECTION IN PAVEMENT \*\* N.T.S.

SCALE: N.T.S.

CMT SCOPPIGN CAT, NO CRANFORD, NEIRPHY & TELLY, CAC. CONSULTING ENGINEERS LICENSE No. 184-000613

	USER NAME = Jeff Sedig	DESIGNED	-	MNB	REVISED	-
٠.		DRAWN	-	MNB	REVISED	-
ı	PLBT SCALE = 40.0000 '/ in.	CHECKED		CMC	REVISED	-
}	PLOT DATE = 11/12/2012 1:03:19 PM	DATE		10/22/2012	REVISED	to .

STATE OF ILLINOIS **DEPARTMENT OF TRANSPORTATION** 

			 _		F.A.U. RTE.	SECTION	
WATER MAIN NOTES AND DETAILS				0192	06-00153-07-CH		
SHEET NO. 1	OF 2	SHEETS	STA.	 TO STA.	_	EED 0/	DAD OTET NO. IN TRIOSE

COUNTY

LAKE

CONTRACT NO. 63682