TRAFFIC SIGNAL LEGEND

ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED	ITEM	REMOVAL	EXISTING	PROPOSED
CONTROLLER CABINET	⊠ ^R	\boxtimes	\blacksquare	EMERGENCY VEHICLE LIGHT DETECTOR	R≪	≪J	₩	ELECTRIC CABLE IN CONDUIT, TRACER, NO. 14 1/C, UNLESS NOTED OTHERWISE		(1)	 1)
RAILROAD CONTROL CABINET		B		CONFIRMATION BEACON	²०-()	○ -(⊷(~~'	
COMMUNICATIONS CABINET	00	<u>ecc</u>	CC	HANDHOLE	8			COAXIAL CABLE		(c)	<u> </u>
MASTER CONTROLLER		EMC.	MC				Name of the last o	VENDOR CABLE FOR CAMERA		a	
MASTER MASTER CONTROLLER	R	EMMC	MMC	HEAVY DUTY HANDHOLE	E R	7	H			─ (v) ─	
UNINTERRUPTIBLE POWER SUPPLY	UPS	[LUPS]	UPS	DOUBLE HANDHOLE	R _{ISIS;} R _{ISIS;}	DD 1781		COPPER INTERCONNECT CABLE, NO. 18 3 PAIR TWISTED, SHIELDED		− €	-6-
SERVICE INSTALLATION, (P) POLE OR (G) GROUND MOUNT	- <u>-</u> -	~ <u>\</u>	- ∰ ^P	JUNCTION BOX GALVANIZED STEEL CONDULT	M	<u> </u>		FIBER OPTIC CABLE NO. 62.5/125, MM12F		(12F)	
TELEPHONE CONNECTION (2) POLE OR (G) GROUND MOUNT	R	P Y	P	IN TRENCH (T) OR PUSHED (P) TEMPORARY SPAN WIRE, TETHER WIRE,	lir.			FIBER OPTIC CABLE NO. 62.5/125, MM12F SM12F		245	— <u>(24F)</u> —
STEEL MAST ARM ASSEMBLY AND POLE	RO	·	•	AND CABLE	.lt					7	
ALUMINUM MAST ARM ASSEMBLY AND POLE	R (T.:23==			COMMON TRENCH			СТ	FIBER OPTIC CABLE NO. 62.5/125, (NUMBER OF FIBERS & TYPE TO BE		-55-	
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE	^R O→x———	○	• ×	COILABLE NONMETALLIC CONDUIT (EMPTY)		_	CNC	NOTED ON PLANS) GROUND ROD AT (C) CONTROLLER,		,	
STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH PTZ CAMERA	R Q <u>=====</u>	Q	₽TZ¶	SYSTEM ITEM INTERSECTION ITEM		S	S IP	(H) HANDHOLE, (P) POST, (M) MAST ARM, OR (S) SERVICE		C. <u> </u> 0	G
SIGNAL POST		0	•	REMOVE ITEM	R			CONTROLLER CABINET AND	ROF		
TEMPORARY WOOD POLE (CLASS 5 OR	^R O R⊗	8	∞	RELOCATE ITEM	RL			FOUNDATION TO BE REMOVED			
BETTER) 45 FOOT (13.7m) MINIMUM				ABANDON ITEM	Α			STEEL MAST ARM POLE AND FOUNDATION TO BE REMOVED	O		
GUY WIRE	>-	>	>	12" (300mm) TRAFFIC SIGNAL SECTION		3	R	ALUMINUM MAST ARM POLE AND	RMF		
SIGNAL HEAD		—[::»·	*** **	12" (300mm) RED WITH 8" (200mm)		(R)		FOUNDATION TO BE REMOVED	O		
SIGNAL HEAD CONSTRUCTION STAGES (NUMBERS INDICATE THE CONSTRUCTION STAGE)			2	YELLOW AND GREEN TRAFFIC SIGNAL FACE			R	STEEL COMBINATION MAST ARM ASSEMBLY AND POLE WITH LUMINAIRE AND	RMF O—XII		
SIGNAL HEAD WITH BACKPLATE	+CS	+-[:>-	+			\\	Y	FOUNDATION TO BE REMOVED			
SIGNAL HEAD OPTICALLY PROGRAMMED	—⇔"b"	* () * () 11:	- - "P"	SIGNAL FACE		G	G ◆Y	SIGNAL POST AND FOUNDATION TO BE REMOVED	RMF O		
FLASHER INSTALLATION (S DENOTES SOLAR POWER)	O B″F″	O-€> ^{46,4}	● ► "F"			Ğ	4 -G	INTERSECTION & SAMPLING (SYSTEM) DETECTOR		4 KG	IS
PEDESTRIAN SIGNAL HEAD	\$2. Tell	- <u>[]</u>	-1			R	R	SAMPLING (SYSTEM) DETECTOR			S
PEDESTRIAN PUSHBUTTON DETECTOR	~ ©	®	©	SIGNAL FACE WITH BACKPLATE. "P" INDICATES PROGRAMMED HEAD			Y G + Y + C	EXISTING INTERSECTION LOOP DETECTOR PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR	NE.	(P)	_
ACCESSIBLE PEDESTRIAN PUSHBUTTON DETECTOR	R ⊚ APS	@APS						EXISTING PREFORMED INTERSECTION LOOP DETECTOR)rt		
ILLUMINATED SIGN "NO LEFT TURN"	R S	8	9	12" (300mm) PEDESTRIAN SIGNAL HEAD		5W	ubn paraman	PROPOSED INTERSECTION AND SAMPLING (SYSTEM) DETECT(DR	ĵ.P.	
ILLUMINATED SIGN	े स्टब्स			WALK/DON'T WALK SYMBOL		M		PREFORMED INTERSECTION AND SAMPLING (SYSTEM) DETECTOR		PIS	PIS
"NO RIGHT TURN"	Œ)			12" (300mm) PEDESTRIAN SIGNAL HEAD INTERNATIONAL SYMBOL, OUTLINED				PREFORMED SAMPLING (SYSTEM) DETECTOR		1-51 1-51	PS
DETECTOR LOOP, TYPE I		<u> </u>		12" (300mm) PEDESTRIAN SIGNAL HEAD				**************************************			
PREFORMED DETECTOR LOOP		Î.P.Î	Р	INTERNATIONAL SYMBOL, SOLID		Ř	*	RAILROAD SYMBOLS			
MICROWAVE VEHICLE SENSOR	* M1	<u>M</u> I	M	PEDESTRIAN SIGNAL HEAD, INTERNATIONAL SYMBOL, WITH COUNTDOWN TIMER			PC XD			EXISTING	PROPOSED
VIDEO DETECTION CAMERA	R V	(V)p	(RADIO INTERCONNECT	##0	-	- 	RAILROAD CONTROL CABINET			
VIDEO DETECTION ZONE				RADIO REPEATER	8 ERR	ERR	RR	RAILROAD CANTILEVER MAST ARM	Σ	<u> </u>	XeX
PAN, TILT, ZOOM CAMERA	8 © J		Fiz] (DENOTES NUMBER OF CONDUCTORS, ELECTRIC	L103	<u>. = = 11 </u>		FLASHING SIGNAL		XoX	X ⊕ X
WIRELESS DETECTOR SENSOR	R(W)	®	(W)	CABLE NO. 14, UNLESS NOTED OTHERWISE, ALL DETECTOR LOOP CABLE TO BE SHIELDED		<u>—(5</u>)—		CROSSING GATE		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	X=X=
WIRELESS ACCESS POINT	R		——————————————————————————————————————	GROUND CABLE IN CONDUIT NO. 6 SOLID COPPER (GREEN)			(1)	CROSSBUCK		755	*
FILE NAME = USER NAME = konthaphtysor\pw,work\PWIDOT\YANTHAPHIXAYSC\chilla6 4\traffic.lugund.v7.dgv PLDT SEALE = 20.8603 1/	rybe DE	ESIGNED - DAG/BCK RAWN - BCK HECKED - DAG	REVISED - REVISED - REVISED -		OF ILLINOIS			DISTRICT 1 STANDARD TRAFFIC SIGNAL DESIGN DETAILS	F.A.U. RTE. 2503	SECTION 12-00073-01-TL	COUNTY TOTAL SHEET NO. KANE 88 54 CONTRACT NO. 6376:
PL03 14 f6 = 1076/2004		ATE 10/28/09	REVISED -					NE , SHEET NO. 6 OF 6 SHEETS STA. TO STA.	FED. ROAD	FED. ROAD DIST. NO. 1 ILLINOIS FED. AID PROJECT	