

TRENCH BACKFILL SCHEDULES (1 OF 1)						
LOCATION STATION	OFFSET	CULVERT SIZE	TRENCH BACKFILL			TRENCH BACKFILL
			LENGTH	AVG DEPTH	VOL./LENGTH	
		IN	FT	FT	CU YD/FT	CU YD
US ROUTE 34						
526+80 EX		36	61.1	13.0	2.330	182.1
529+85 EX		24	78.0	4.9	0.938	73.2
532+93 EX		30	46.3	8.4	1.913	88.6
537+26 EX		2' X 2' BOX	42.0	7.0	1.470	61.7
541+48 EX (N END)		2' X 2' BOX	31.6	6.2	1.300	41.1
541+48 EX (S END)		2' X 2' BOX	8.3	4.5	0.700	7.8
BOGUS HOLLOW ROAD						
6+24.50 EX		3' X 2' BOX / 36	28.9	10.9	2.699	78.0
6+77.05		42	35.2	16.9	3.805	133.9
TR 94 (1400 E)						
51+17.48		60	43.2	9.7	1.877	81.1
51+85.00 EX	RT	18	14.0	7.5	1.297	18.2
54+01.00 EX		18	55.0	1.3	0.311	8.4
IL ROUTE 94/116						
12+37.00 EX	RT	15	35.5	1.3	0.141	5.0
13+30.00 EX	LT	15	54.0	2.5	0.141	7.6
13+32.00	LT	15	51.0	1.9	0.104	5.3
15+00.00		36	62.3	8.7	1.582	98.6
15+62.00 EX		42	58.6	7.4	1.986	116.4
17+83.00 EX	LT	45 X 29 ELLIP	44.7	9.4	2.611	116.7
TR 119 (1425 N)						
50+30.00 EX		18	41.4	0.6	0.075	3.1
TR 122 CUL-DE-SACS						
641+61.90		15	19.8	3.1	0.248	4.9
641+68.51		24	19.0	3.5	0.279	5.3
TR 138 (1650 E)						
53+39.00		36	22.0	8.0	1.409	31.0
53+40.00 EX		15	22.0	3.2	0.373	8.2
SUBTOTAL 1						1,176.2

TRENCH BACKFILL SCHEDULES (2 OF 2)						
LOCATION STATION	OFFSET	CULVERT SIZE	TRENCH BACKFILL			TRENCH BACKFILL
			LENGTH	AVG DEPTH	VOL./LENGTH	
		IN	FT	FT	CU YD/FT	CU YD
TR 150 (1700 E)						
43+55.00		42	24.0	6.9	1.120	26.9
60+74.00	RT	24	22.0	2.7	0.161	3.5
66+40.00		24	28.6	5.7	0.866	24.8
66+40.00 EX		24	28.6	5.0	0.741	21.2
67+30.00 EX	RT	18	44.0	2.6	0.327	14.4
TR 178 (1800 E)						
53+32.00		18	46.3	5.5	0.811	37.5
53+32.00 EX		18	35.0	2.9	0.366	12.8
DETOUR 1						
2551+16.02		60	32.9	16.7	4.210	138.5
DETOUR 3						
117+90.00 (TEMP)	LT	15	28.0	4.1	0.364	10.2
117+90.00 (TEMP) REM	LT	15	28.0	4.1	0.421	11.8
142+05.00 (TEMP)	LT	24	22.9	2.9	0.190	4.4
142+05.00 (TEMP) REM	LT	24	22.9	2.9	0.376	8.6
SUBTOTAL 2						314.6
SUBTOTAL 1						1,176.2
TOTAL						1,490.8
USE						1,491

SHOULDER INLET SCHEDULE								
LOCATION		PIPE DRAINS 12"	TYPE F INLET BOX, STANDARD 610001	TYPE G INLET BOX, STANDARD 610001	CONCRETE THRUST BLOCK	PORTLAND CEMENT CONCRETE SHOULDERS 8"	METAL END SECTIONS 12"	SEEPAGE COLLAR 601401-D4
STATION	OFFSET							
		FOOT	EACH	EACH	EACH	SO YD	EACH	EACH
US ROUTE 34								
755+29.04	LT	80	1		1	13.4	1	1
755+34.50	RT	72	1		1	13.4	1	1
755+36.08	LT	15		1	1	9.7	1	1
755+41.53	RT	15		1	1	9.7	1	1
TOTAL		182	2	2	4	46	4	4