GENERAL NOTES

THE CONTRACTOR SHALL PROVIDE INTERNET ACCESS TO THE HOT-MIX ASPHALT PLANT QUALITY CONTROL LAB SO THAT HOT-MIX ASPHALT PLANT REPORTS CAN BE E-MAILED TO THE DISTRICT HEADQUARTERS. THIS WORK SHALL BE INCLUDED IN THE COST OF HOT-MIX ASPHALT ITEMS.

CONCRETE HEADWALL REMOVAL SHALL BE INCLUDED IN THE COST OF PIPE CULVERT REMOVAL.

THE MATERIAL USED FOR AGGREGATE WEDGE SHOULDER. TYPE B SHALL BE CRUSHED STONE. CRUSHED CONCRETE, OR RAP.

THE MATERIAL USED FOR AGGREGATE SURFACE COURSE, TYPE B SHALL BE CRUSHED STONE OR CRUSHED CONCRETE.

THE MILLINGS COLLECTED FROM THE EXCAVATION OF THE HMA SHOULDERS SHALL BE USED AS BACKFILL FOR THE PROPOSED PIPE CULVERTS. THE PIPE CULVERTS SHALL BE BACKFILLED PER ARTICLE 542.06 (D) OF THE STANDARD SPECIFICATIONS. THE COST OF USING THE MILLINGS AS BACKFILL MATERIAL SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE PER UNIT FOR EXCAVATING AND GRADING EXISTING SHOULDER.

THE TOTAL QUANTITY OF PAINT PAVEMENT MARKING - LINE 4" CONSISTS OF 136, 364 FEET OF WHITE-AND 17, 247 FEET OF YELLOW.

THE FOLLOWING MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT:

HMA SHOULDER

MIXTURE USE: APPLICATION: HMA SHOULDERS, 8"

HOT-MIX ASPHALT SHOULDERS

PG GRADE:

PG 64-22 4.0% © ND IL-19.0L

N/A

DESIGN AIR VOIDS:

4.0% @ NDESIGN = 30

MIXTURE COMPOSITION:

FRICTION AGGREGATE:

INCIDENTAL HMA SURFACING

MIXTURE USE: APPLICATION:

INCIDENTAL HMA SURFACING (DRIVEWAYS/SIDEROADS)
HOT-MIX ASPHALT SURFACE COURSE, MIX "C", N70

PG GRADE:

DESIGN AIR VOIDS: MIXTURE COMPOSITION: PG 64-22 4.0% & NDESIGN = 70

FRICTION AGGREGATE:

IL-9.5 MIXTURE C

INDEX OF SHEETS

SHEET NO. ITEM

COVER SHEET

2 INDEX OF SHEETS & GENERAL NOTES

3 SUMMARY OF QUANTITIES

4 TYPICAL SECTION

5-6 SCHEDULES

7 ENTRANCE SCHEDULE AND DETAILS

B TYPICAL APPLICATIONS OF PAVEMENT MARKING

THE FOLLOWING STANDARDS ARE A PART OF THESE PLANS AND ARE INCLUDED AFTER SHEET NO. 11:

STD. NO. DESCRIPTION

000001-06 STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS 001006 DECIMAL OF AN INCH AND OF A FOOT

482001-02 HMA SHOULDER ADJACENT TO FLEXIBLE PAVEMENT 642006 SHOULDER RUMBLE STRIPS, 8 in.

701011-03 OFF-RD MOVING OPERATIONS, 2L. 2W, DAY ONLY

701201-04 LANE CLOSURE, 2L 2W, DAY ONLY, FOR SPEEDS => 45 MPH

701311-03 LANE CLOSURE, ZL. 2W. MOVING OPERATIONS - DAY ONLY

701326-04 LANE CLOSURE. 2L. 2W, PAVEMENT WIDENING, FOR SPEEDS => 45 MPH

701901-03 TRAFFIC CONTROL DEVICES

FILE NAME &	USER NAME : teaslayck	DESIGNED	-	REVISED	-	
c:\px.work\pxidot\teasleyck\d8279424\BY		DRAWN	•	REVISED	.**	
	PLOT SCALE = 188,0000 ' / in.	CHECKED	-	REVISED	-	
Dafoult	PLOT DATE : 9/H/2012	DATE	-	REVISED	-	

STATE OF ILLINOIS						
DEPARTMENT	OF	TRANSPORTATION				

	GENERAL NOTES &			F.A.P. SECTION		COUNTY	TOTAL SHEETS	SHEET NO.		
	INDEX OF SHEETS				770	*	**	8	2	
							CONTRACT	NO.	74552	
	SCALE:	SHEET	OF	SHEETS STA.	TO STA.		ILLINOIS FED. AID PROJECT			
						• 07 H	MA SAFETY SHLD 2013-1	** She	Hby & F	viouitrie