

<u>NOTES</u>:

- Existing reinforcement extending into the removal area shall be cleaned, straightened and incorporated into the new construction. Any reinforcement bars that are damaged during concrete removal shall be replaced with an approved bar splicer or anchorage system. Cost shall be included with Concrete Removal.
- 2. Trim existing reinforcement to accommodated proposed expansion joint.
- 3. See sheet 11 for section A-A, B-B, C-C and D-D.
- Bars indicated thus: "4x2-#5 etc...", indicates 4 lines of bars with 2 lengths per line.

MIN. LAP

#5 Bar 2'-7" Min. Lap. #6 Bar 3'-1" Min. Lap.

BILL OF MATERIAL

Item	Unit	Total	
Concrete Removal	Cu. Yd.	4.8	
Concrete Superstructure	Cu. Yd.	5.6	
Protective Coat	Sq. Yd.	10	



<u>DETAIL A</u>



<u>LEGEND</u>



Concrete Removal

ION JOINT CONCRETE	F.A.I. RTE	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.
. 060–0214	255	60-(7,8) RS-2	MADISON	261	234
		CONTR		CT NO. 76A89	
16 SHEETS	ILLINOIS FED. AID PROJECT				