ELEC	CTRICAL LEGEND — ONE—LINE DIAGRAM	
	CABLE TERMINATOR/LUG	
***	TRANSFORMER	
	DISCONNECT SWITCH	
CIRCUIT BREAKER		
~~~	THERMAL MAGNETIC CIRCUIT BREAKER	
	FUSE	
<b>‡</b>	TRANSIENT VOLTAGE SURGE SUPPRESSOR OR SURGE PROTECTOR DEVICE	
#	GROUND — GROUND ROD, GROUNDING ELECTRODE, OR AT EARTH POTENTIAL	
¤	INDICATING LIGHT	
•	MOTOR	
(#)	LOAD, MOTOR, # = HORSEPOWER	
0	ELECTRIC UTILITY METER BASE	
0	JUNCTION BOX WITH SPLICE	
XXX	EQUIPMENT, XXX = DEVICE DESCRIPTION	
GND	GROUND BUS OR TERMINAL	
S/N	NEUTRAL BUS	
	Panelboard with main lugs	
<b>1</b>	PANELBOARD WITH MAIN BREAKER	
<b>-</b> ♣□ <b>&gt;</b>	FUSE PANEL WITH MAIN FUSE PULLOUT	
₽	DUPLEX RECEPTACLE 120V SINGLE PHASE GROUNDING TYPE	
	CONTROL STATION	
N EM	Transfer swiich	
	ENGINE GENERATOR SET	

·····		
ELECTRICAL LEGEND - SCHEMATIC		
→ H NORMALLY OPEN (N.O.) CONTACT		
NORMALLY CLOSED (N.C.) CONTACT		
(3)	STARTER COIL, * = STARTER NUMBER	
OL -H	OVERLOAD RELAY CONTACT	
(CR*)	CONTROL RELAY, * = CONTROL RELAY NUMBER	
R*) RELAY, * = RELAY NUMBER		
o Toggle Switch / 2 Position Switch (OPEN-CLOSED)		
OFF AUTO		
ΙΥ	2-POSITION SELECTOR SWITCH	
ox		
10GGLE SWITCH 2-POSITION		
OFF	TOGGLE SWITCH 3-POSITION CENTER OFF	
	ROTARY SWITCH/ 4—POSTION	
٩	ROTARY SWITCH/ 6-POSITION	
HAND F AUTO	3-position selector switch (H-0-a shown)	
2 POLE DISCONNECT SWITCH		
3 POLE DISCONNECT SWITCH		
<u> </u>	PHOTOCELL	
	TERMINAL BLOCK, * = TERMINAL NUMBER	
	DEVICE TERMINAL, * = DEVICE TERMINAL NUMBER	
	INTERNAL PANEL WIRING	
	FIELD WIRING	
ш	FUSE	
GND	GROUND BUS OR TERMINAL	
S/N	NEUTRAL BUS	
<b>#</b>	GROUND, GROUND ROD, GROUND BUS	
0 0	INDUSTRIAL CONTROL RELAY OR LIGHTING CONTACTOR	
S1 CUTOUT HANDLE REMOVED		
中中	S1 CUTOUT HANDLE INSERTED	
⁴ / ₂	N.O. THERMAL SWITCH	
مير	N.C. THERMAL SWITCH	
(3)	L-830 SERIES ISOLATION TRANSFORMER	

	ELECTRICAL ABBREVIATIONS	
A.F.F.	ABOVE FINSHED FLOOR	
A, AMP	AMPERES	
ATS	AUTOMATIC TRANSFER SWITCH	
AWG	AMERICAN WIRE GAUGE	
BKR	BREAKER	
С	CONDUIT	
CB	CIRCUIT BREAKER	
CKT	CIRCUIT	
CR	CONTROL RELAY	
cu	COPPER	
DPDT	DOUBLE POLE DOUBLE THROW	
	DOUBLE POLE SINGLE THROW	
DPST		
EM	EMERGENCY	
EMT	ELECTRICAL METALLIC TUBING	
ENCL.	ENCLOSURE	
EP	EXPLOSION PROOF	
ES	EMERGENCY STOP	
ETL	INTERTEK ELECTRICAL TESTING LABS	
ETM	ELAPSE TIME METER	
GFCI	GROUND FAULT CIRCUIT INTERRUPTER	
GFI	GROUND FAULT INTERRUPTER	
GND	GROUND	
GRSC	CALVANIZED RIGID STEEL CONDUIT	
HID	HIGH INTENSITY DISCHARGE	
HOA	HAND OFF AUTOMATIC	
HP	HORSEPOWER	
HPS	HIGH PRESSURE SODIUM	
J	JUNCTION BOX	
KVA	KILOVOLT AMPERE(S)	
KW	KILOWATTS	
LC	LIGHTING CONTACTOR	
LTFMC	LIQUID TIGHT FLEXIBLE METAL CONDUIT (UL LISTED)	
LTG	LIGHTING	
LP	LIGHTING PANEL	
MAX	MAXINUM	
MCB	MAIN CIRCUIT BREAKER	
	THOUSAND CIRCLUAR MIL	
MCM		
MDP	MAIN DISTRIBUTION PANEL	
MFR	MANUFACTURER	
MH	METAL HALIDE	
MIN	MINIMUM	
MLO	MAIN LUGS ONLY	
NEC	NATIONAL ELECTRICAL CODE (NFPA 70)	
NC	NORMALLY CLOSED	
NO	NORMALLY OPEN	
nts	NOT TO SCALE	
OHE	OVERHEAD ELECTRIC	
	OVERLOAD	

EL	ECTRICAL ABBREVIATIONS (CONTINUED)
PB	PULL BOX
PC	PHOTO CELL
PDB	POWER DISTRIBUTION BLOCK
PNL	PANEL
RCPT	RECEPTACLE
R	RELAY
s	STARTER
SPD	SURGE PROTECTION DEVICE
SPST	SINGLE POLE SINGLE THROW
TVSS	TRANSIENT VOLTAGE SURGE SUPPRESSOR
TYP	TYPICAL
UG	UNDERGROUND
UGE	UNDERGROUND ELECTRIC
UL	UNDERWRITER'S LABORATORIES
٧	VOLTS
W/	wпн
W/O	WITHOUT
WP	WEATHER PROOF
XFER	TRANSFER
XFMR	TRANSFORMER

	AIRPORT EQUIPMENT ABBREVIATIONS		
ATCT	AIR TRAFFIC CONTROL TOWER		
CCR	CONSTANT CURRENT REGULATOR		
HIRL	HIGH INTENSITY RUNWAY LIGHT		
MIRL	MEDIUM INTENSITY RUNWAY LIGHT		
MITL	MEDIUM INTENSITY TAXIWAY LIGHT		
NDB	NON-DIRECTIONAL BEACON		
PAPI	PRECISION APPROACH PATH INDICATOR		
PLASI	PULSE LIGHT APPROACH SLOPE INDICATOR		
REIL	RUNWAY END IDENTIFIER LIGHT		
VADI	VISUAL APPROACH DESCENT INDICATOR		
VASI	visual approach slope indicator		
WC	WIND CONE		

#### MOTES

- ALL ELECTRICAL EQUIPMENT SHALL BE INSTALLED IN CONFORMANCE WITH NFPA
  70 (MOST CURRENT ISSUE IN FORCE), THE RESPECTIVE EQUIPMENT
  MANUFACTURER'S DIRECTIONS AND ALL OTHER APPLICABLE LOCAL CODES, LAWS,
  ORDINANCES, AND REQUIREMENTS IN FORCE. ANY INSTALLATIONS WHICH VOID
  THE U.L. LISTING, ETL LISTING (OR OTHER THIRD PARTY LISTING) AND/OR THE
  MANUFACTURER'S WARRANTY OF A DEVICE SHALL NOT BE PERMITTED.
- 2. CONTRACTOR SHALL COORDINATE WORK AND ANY POWER OUTAGES WITH THE RESPECTIVE FACILITY OWNER PERSONNEL AND THE AIRPORT DIRECTOR.
- 3. COLOR CODE PHASE AND NEUTRAL CONDUCTOR INSULATION FOR NO. 6 AWG OR SMALLER. PROVIDE COLORED INSULATION OR COLORED MARKING TAPE FOR PHASE AND NEUTRAL CONDUCTORS FOR NO. 4 AWG AND LARGER. INSULATED GROUND CONDUCTORS SHALL HAVE GREEN COLORED INSULATION FOR ALL CONDUCTOR AWG AND/OR KCMIL. STANDARD COLORS FOR POWER WIRING AND BRANCH CIRCUITS SHALL BE AS FOLLOWS:

240/120 VAC, 3 PHASE, 4 WIRE
PHASE A BLACK
PHASE B ORANGE
PHASE C BLUE
NEUTRAL WHITE
GROUND GREEN

## WA057



### HANSON PROFESSIONAL SERVICES INC.

815 Commerce Drive, Suite 200 Oak Brook, Illinois 60523 Telephone: 630.990.3800 Fax: 630.990.3801



#### WAUKEGAN REGIONAL AIRPORT WAUKEGAN PORT DISTRICT

3580 North McAree Road Waukegan, Illinois 60087 Telephone: 847.244.0066 Fax: 847.244.3813

## AIRFIELD SIGNAGE IMPROVEMENTS

AIP PROJECT NO. 3-17-0105-B35 IDA PROJECT NO. UGN-3650

			Т
			T
			Τ
			Ι
			L
No.	Drawing Issue Description	Date	Ву

Date

NOVEMBER 10, 2006

Sheet Title

# ELECTRICAL LEGEND AND ABBREVIATIONS

831-064	\8004
Project Numbe	r
KNL	09/01/06
Layout By	Date
KNL	09/01/06
Dusigned By	Date
RMH	11/10/06
Reviewed By	Date
A434 1	1

28

Sheet No.