

GENERAL NOTES

CITY
COORDINATION:

THE CONTRACTOR SHALL NOTIFY THE CITY ENGINEER (847 866-2966), AT LEAST 72 HOURS IN ADVANCE OF BEGINNING WORK AND SHALL COORDINATE ALL CONSTRUCTION OPERATIONS WITH THE ENGINEER. SPECIAL ATTENTION IS CALLED TO ARTICLE 105.07 OF THE STANDARD SPECIFICATIONS AND THE SPECIAL PROVISIONS FOR TRAFFIC CONTROL AND PROTECTION. THE STORAGE OF EQUIPMENT AND/OR MATERIALS WITHIN THE PARKWAYS SHALL REQUIRE PRIOR APPROVAL OF THE ENGINEER. THE CONTRACTOR SHALL NOTIFY THE CITY OF EVANSTON PUBLIC WORKS DEPARTMENT 48 HOURS PRIOR TO ANY WORK IN ORDER TO OBTAIN CITY UTILITY LOCATIONS. THE CONTRACTOR SHALL ALSO CONTACT THE CITY OF EVANSTON PUBLIC WORKS DEPARTMENT UTILITY DIVISION FOR ALL WATER MAIN SHUTOFFS. UNDER NO CONDITION SHALL THE CONTRACTOR OPERATE ANY VALVES OR HYDRANTS WITHIN THE PROJECT AREA.

PUBLIC OR PRIVATE
UTILITIES:

THE LOCATION OF PUBLIC OR PRIVATE UTILITIES SHOWN ON THE PLANS ARE APPROXIMATE AND THE CITY DOES NOT GUARANTEE THEIR ACCURACY. THE CONTRACTOR WILL BE REQUIRED TO ASCERTAIN THE EXACT LOCATIONS OF SUCH OPERATIONS SO AS NOT TO DAMAGE THEM IN ACCORDANCE WITH THE SPECIAL PROVISIONS AND ARTICLE 105.07 OF THE STANDARD SPECIFICATIONS. THEIR FACILITIES MAY BE ADJUSTED OR RELOCATED, IF NECESSARY.

THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE OR DESTRUCTION OF PUBLIC OR PRIVATE PROPERTY, AND SHALL RESTORE SUCH PROPERTY AT HIS OWN EXPENSE. COORDINATION OF ALL UTILITY WORK INVOLVED IN THE CONSTRUCTION AREA WILL BE DISCUSSED AT A PRE-CONSTRUCTION CONFERENCE. THE CONTRACTOR SHALL USE ALL NECESSARY PRECAUTIONS AND PROTECTIVE MEASURES REQUIRED TO MAINTAIN EXISTING UTILITIES, SEWERS, AND APPURTENANCES THAT MUST BE KEPT IN OPERATION. IN PARTICULAR, THE CONTRACTOR WILL TAKE ADEQUATE MEASURES TO PREVENT THE UNDERMINING OF UTILITIES AND SEWERS WHICH ARE STILL IN SERVICE.

WHENEVER THE CONTRACTOR ENCOUNTERS FACILITIES AND APPURTENANCES WITHIN THE LIMITS OF THE IMPROVEMENTS DURING TRENCHING OPERATION, HE WILL BE REQUIRED TO HAND TRENCH IN THAT AREA IN ORDER NOT TO DAMAGE THE FACILITIES.

DISPOSAL OF
MATERIALS:

THE CONTRACTOR WILL BE REQUIRED TO DISPOSE OF ALL SIDEWALK, CURB AND GUTTER, PAVEMENT, AND ALL OTHER MATERIAL EXCAVATED OR REMOVED DUE TO CONSTRUCTION OPERATIONS, AT HIS EXPENSE. ALL EXCESS EXCAVATED MATERIAL SHALL BE REMOVED FROM SITE ON THE DAY IT IS EXCAVATED. NO PAYMENT WILL BE MADE FOR HAULING OR TRUCKING MATERIAL TO LOCATIONS, PROVIDED BY THE CONTRACTOR, OUTSIDE THE LIMITS OF THE IMPROVEMENT.

EXISTING DRAINAGE
STRUCTURES:

DURING CONSTRUCTION OPERATIONS, WHENEVER ANY LOOSE MATERIAL IS DEPOSITED IN THE FLOW LINE OF DRAINAGE STRUCTURES, SUCH THAT THE NATURAL FLOW OF WATER IS OBSTRUCTED, IT SHALL BE REMOVED BY THE CONTRACTOR AT THE CLOSE OF EACH WORKING DAY. AT THE CONCLUSION OF CONSTRUCTION OPERATIONS, ALL DRAINAGE STRUCTURES SHALL BE FREE FROM ALL DIRT AND DEBRIS. THIS WORK SHALL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF THE CONTRACT.

DRAINAGE STRUCTURE
ADJUSTMENT AND
RECONSTRUCTION:

ONLY PRECAST CONCRETE ADJUSTMENT RINGS WILL BE ALLOWED IN THE ADJUSTMENT OR RECONSTRUCTION OF CATCH BASIN, MANHOLE, INLET AND VALVE VAULT STRUCTURES. COMMON BRICK WILL NOT BE ALLOWED.

FRAMES AND GRATES:

FRAMES ON ALL NEW STRUCTURES WILL BE ADJUSTED TO THE FINAL ELEVATION OF THE AREA IN WHICH THEY ARE LOCATED AS PART OF THE STRUCTURE COST. ALL FRAMES, GRATES, LIDS AND BOXES REMOVED FROM EXISTING WATER SERVICE OR SEWER STRUCTURES WHICH ARE TO BE ABANDONED OR ADJUSTED WITH A NEW OR DIFFERENT FRAME AND LID SHALL BECOME THE PROPERTY OF THE MUNICIPALITY DEPENDING ON JURISDICTION. ANY OF THESE ITEMS WHICH ARE DAMAGED OR BROKEN DURING HANDLING SHALL BE REPLACED BY THE CONTRACTOR AT HIS OWN EXPENSE. NO ADDITIONAL COMPENSATION SHALL BE ALLOWED FOR SALVAGING THESE EXISTING FRAMES, GRATES, LIDS OR BOXES AND STOCKPILING THEM ON THE JOB SITE AND DELIVERING THEM TO THE MAINTENANCE FACILITY OF THE MUNICIPALITY HAVING JURISDICTION. THE CONTRACTOR SHALL NOTIFY THE MUNICIPALITY 24 HOURS PRIOR TO DELIVERY.

TYPE 1 FRAME,
CLOSED LID:

A QUANTITY OF TYPE 1 FRAMES AND CLOSED LIDS HAS BEEN INCLUDED TO REPLACE FRAMES AND LIDS WHICH ARE BROKEN OR BREAK DURING MILLING OPERATIONS. THESE FRAME AND LIDS SHALL BE EAST JORDAN IRON WORKS 1050 FRAME AND 1020 TYPE A EXTRA HEAVY DUTY COVER WITH LARGE (2½" NOMINAL) PICK HOLE OR APPROVED EQUAL. ALL FRAMES WITH CLOSED LIDS TO BE FURNISHED AS PART OF THIS CONTRACT FOR CONSTRUCTION, ADJUSTMENT OR RECONSTRUCTION OF ANY STORM SEWER MANHOLE, CATCH BASIN, AND/OR INLET, SHALL HAVE THE WORD "STORM" CAST INTO THE LID. ALL WATER MANHOLES SHALL HAVE THE WORD "WATER" CAST INTO THE LID AND ALL SANITARY MANHOLES SHALL HAVE THE WORD "SANITARY" CAST INTO THE LID.

TYPE 21 OR TYPE 3
FRAME, OPEN LID:

ALL CURB AND GUTTER GRATES SHALL BE EAST JORDAN TYPE 7045 MI SINUSOIDAL GRATES OR APPROVED EQUIVALENT.

TRAFFIC CONTROL:

STAGING PROCEDURES PRESENTED ARE THE SUGGESTED SEQUENCE OF OPERATIONS. AT HIS OPTION, THE CONTRACTOR MAY SUBMIT AN ALTERNATIVE STAGING PROPOSAL TO THE ENGINEER FOR HIS APPROVAL. THE CONTRACTOR WILL BE REQUIRED TO RELOCATE OR REMOVE AND REPLACE SIGNS WHICH INTERFERE WITH CONSTRUCTION OPERATIONS, AND TO TEMPORARILY RESET ALL SUCH SIGNS DURING CONSTRUCTION OPERATIONS AT THE DIRECTION OF THE ENGINEER. THIS WORK WILL NOT BE PAID FOR SEPARATELY BUT SHALL BE INCLUDED IN THE COST OF THE CONTRACT. SIGNS SHALL NOT BE MOVED UNTIL PROGRESS OF WORK NECESSITATES. EVERY SIGN REMOVED MUST BE RE-ERECTED TO A TEMPORARY LOCATION IN AN APPROVED MANNER AND BE VISIBLE TO TRAFFIC FOR WHICH IT IS INTENDED. ALL SUCH SIGNS MUST BE MAINTAINED STRAIGHT AND CLEAN FOR THE DURATION OF THE PROJECT. ALL SIGNS SHALL BE RE-ERECTED IN PERMANENT LOCATIONS AS THE ROADWAY IS COMPLETED. HORIZONTAL LOCATION FROM THE EDGE OF PAVEMENT SHALL BE AS DESIGNATED BY THE ENGINEER. ALL UNUSED SIGNS WILL BE RETURNED TO THE AGENCY HAVING JURISDICTION.

CURB & GUTTER:

AN EXPANSION JOINT SHALL BE PLACED A MINIMUM OF THREE (3) FEET ON EITHER SIDE OF ADJACENT TREES. THE CURB GAP SHALL BE HAND FORMED IN ORDER TO PROTECT THE TREE ROOT SYSTEM.

BARRICADES:

THE CONTRACTOR SHALL PROVIDE AND INSTALL TWO (2) WEIGHTED SAND BAGS ON EACH TYPE I OR TYPE II BARRICADE USED. ONE (1) WEIGHTED SAND BAG SHALL BE PLACED ACROSS EACH BOTTOM RAIL. FOR STABILIZATION, ALL TYPE III BARRICADES SHALL REQUIRE A MINIMUM OF FOUR (4) SANDBAGS PER BARRICADE.

TOP OF CURB
ELEVATIONS:

BEFORE SETTING THE TOP OF CURB ELEVATIONS, THE ENGINEER SHALL CHECK THE EXISTING ELEVATIONS AT THE PROPERTY LINE AND IF NECESSARY, REQUIRE THE CONTRACTOR TO VARY THE CURB EXPOSURE AND/OR GUTTER ELEVATIONS IN ORDER TO MORE CLOSELY FOLLOW THE PROPERTY LINE GRADES.

SAW CUTS:

ALL SAW CUTS REQUIRED DUE TO CONSTRUCTION STAGING SHALL BE INCLUDED IN THE COST OF PAVEMENT REMOVAL. ALL SAW CUTS REQUIRED FOR REMOVAL ITEMS SHALL BE INCIDENTAL TO THAT ITEM.

DRIVEWAYS:

LOCAL ACCESS FOR RESIDENTS AND BUSINESSES SHALL BE MAINTAINED AT ALL TIMES AS SHOWN IN THE PLANS.

SIDEWALKS:

ADJACENT PAVEMENT OR SIDEWALK DISTURBED DURING CONSTRUCTION SHALL BE RESTORED TO THE ORIGINAL CONDITION BY THE CONTRACTOR. THE COST FOR THIS WORK SHALL BE INCLUDED IN THIS CONTRACT. ANY SIDEWALKS PLACED THROUGH DRIVEWAYS SHALL BE THE SAME THICKNESS AS THE DRIVEWAYS. THIS ADDITIONAL THICKNESS SHALL BE INCIDENTAL TO P.C. CONCRETE SIDEWALK. A 4" GRANULAR LEVELING BASE SHALL BE CONSTRUCTED BENEATH ALL PROPOSED SIDEWALK. THE COST FOR THIS WORK SHALL BE INCLUDED IN THE CONTRACT UNIT PRICE FOR P.C. CONCRETE SIDEWALK.

WATER:

THE CONTRACTOR MUST OBTAIN A FIRE HYDRANT PERMIT FROM THE CITY OF EVANSTON IN ORDER TO OBTAIN ACCESS TO CITY WATER. THE CONTRACTOR WILL BE REQUIRED TO SUPPLY THEIR OWN RPZ BACKFLOW PREVENTOR WHEN ACCESSING CITY WATER. THE CONTRACTOR SHALL NOTIFY THE DISTRIBUTION & SEWER CHIEF, TOM JACKSON, 48 HOURS IN ADVANCE OF WHEN THEY WILL DO ANY FIRE HYDRANT OR WATER MAIN WORK AT (847) 866-2945.

MWRD NOTES:

- THE MWRD LOCAL SEWER SYSTEMS SECTION FIELD OFFICE MUST BE NOTIFIED AT LEAST TWO (2) WORKING DAYS PRIOR TO THE COMMENCEMENT OF ANY WORK (CALL 708-588-4055).
- THE ELEVATION DATUM IS USGS.
- THERE ARE NO FLOOR DRAINS ON THIS PROJECT.
- THERE ARE NO FOOTING DRAINS AND DOWNSPOUTS ON THIS PROJECT.
- ALL SANITARY SEWER PIPE MATERIALS AND JOINTS (AND STORM SEWER PIPE MATERIALS AND JOINTS IN A COMBINED SEWER AREA) SHALL CONFORM TO:
PIPE MATERIAL SPEC. JOINT SPEC.

VITRIFIED CLAY PIPE	
VCP C-700	
VCP (NO BEL) C-700	C-425
JOINT	
COLLAR	C-425
CONCRETE PIPE C-14	D-1784
RCP C-76	C-443
ACP C-428	C-443
ABS SEWER PIPE	D-1869
SOLID WALL 6" DIA. SDR 23.5	
ABS D-2751	
ABS COMPOSITE/TRUSS PIPE	D-2751
8"-15" DIA.	
ABS D-2680	
PVC GRAVITY SEWER PIPE	D-2680
6"-15" DIA. SDR 26	
D-3034	
18"-27" DIA. F/DY=46	D-3212 OR D-2855
F-679	
CISP A-74	D-3212 OR D-2855
DIP A-21.51	C-564
	A-21.11

(NOTE: THE DISTRICT HAS APPROVED LESS COMMON PIPE MATERIALS ON A QUALIFIED BASIS IN ADDITION TO THOSE ABOVE. PLEASE CONTACT THE DISTRICT IF CONSIDERING USING PIPE NOT LISTED ABOVE.)
- ALL STORM SEWER CONSTRUCTION IN COMBINED SEWER AREAS, REQUIRES STONE BEDDING WITH STONE ¼" TO 1" IN SIZE, WITH MINIMUM BEDDING THICKNESS EQUAL TO ¼ THE OUTSIDE DIAMETER OF THE SEWER PIPE, BUT NOT LESS THAN FOUR (4) INCHES NOR MORE THAN EIGHT (8) INCHES. MATERIAL SHALL BE CA-11 OR CA-13 AND SHALL BE EXTENDED AT LEAST 12" ABOVE THE TOP OF THE PIPE WHEN USING PVC.
- "BAND SEAL" OR SIMILAR FLEXIBLE-TYPE COUPLINGS SHALL BE USED IN THE CONNECTION OF SEWER PIPES OF DISSIMILAR MATERIALS.
- WHEN CONNECTING TO AN EXISTING SEWER MAIN BY MEANS OTHER THAN AN EXISTING WYE, TEE, OR AN EXISTING MANHOLE, ONE OF THE FOLLOWING METHODS SHALL BE USED: (SEE DETAIL SHEET)
 - CIRCULAR SAW-CUT OF SEWER MAIN BY PROPER TOOLS ("SEWER-TAP" MACHINE OR SIMILAR) AND PROPER INSTALLATION OF HUB-WYE SADDLE OR HUB-TEE SADDLE.
 - REMOVE AN ENTIRE SECTION OF PIPE (BREAKING ONLY THE TOP OF ONE BELL) AND REPLACE WITH A WYE OR TEE BRANCH SECTION.
 - WITH PIPE CUTTER, NEATLY AND ACCURATELY CUT OUT DESIRED LENGTH OF PIPE FOR INSERTION OF PROPER FITTING, USING "BAND SEAL" OR SIMILAR COUPLINGS TO HOLD IT FIRMLY IN PLACE.
- WHENEVER A SANITARY/COMBINED SEWER CROSSES UNDER A WATER MAIN, THE MINIMUM VERTICAL DISTANCE FROM THE TOP OF THE SEWER TO THE BOTTOM OF THE WATER MAIN SHALL BE 18 INCHES. FURTHERMORE, A MINIMUM HORIZONTAL DISTANCE OF 10 FEET BETWEEN SANITARY/COMBINED SEWERS AND WATER MAINS SHALL BE MAINTAINED UNLESS: THE SEWER IS LAID IN A SEPARATE TRENCH, KEEPING A MINIMUM 18" VERTICAL SEPARATION; OR THE SEWER IS LAID IN THE SAME TRENCH WITH THE WATER MAIN LOCATED AT THE OPPOSITE SIDE ON A BENCH OF UNDISTURBED EARTH, KEEPING A MINIMUM 18" VERTICAL SEPARATION. IF EITHER THE VERTICAL OR HORIZONTAL DISTANCES DESCRIBED ABOVE CAN NOT BE MAINTAINED, OR THE SEWER CROSSES ABOVE THE WATER MAIN, THE SEWER SHALL BE CONSTRUCTED TO WATER MAIN STANDARDS.
- ALL STORM MANHOLES IN COMBINED SEWER AREAS, SHALL HAVE A MINIMUM INSIDE DIAMETER OF 48 INCHES, AND SHALL BE CAST IN PLACE OR PRE-CAST REINFORCED CONCRETE.
- RESILIENT CONNECTORS, CONFORMING TO ASTM C-293, SHALL BE USED BETWEEN MANHOLE AND PIPES.

INDEX OF SHEETS

SHEET NO.

SHEET DESCRIPTION

1	COVER SHEET
1B-1C	MWRDGC STORM SEWER ROUTING EXHIBIT
2	INDEX OF SHEETS, GENERAL NOTES AND STATE STANDARDS
3-6	SUMMARY OF QUANTITIES
7	SCHEDULE OF QUANTITIES
8-9	TYPICAL SECTIONS
10	ALIGNMENT, TIES AND BENCHMARKS
11-12	DETOUR PLANS
13	TYPICAL SECTIONS (SUGGESTED STAGES OF CONSTRUCTION AND TRAFFIC CONTROL)
14	SUGGESTED STAGES OF CONSTRUCTION AND TRAFFIC CONTROL - STAGE I
15	SUGGESTED STAGES OF CONSTRUCTION AND TRAFFIC CONTROL - STAGE II
16-18	LANDSCAPING AND EROSION CONTROL PLANS
19-24	PLAN AND PROFILE
25-29	DRAINAGE AND UTILITIES
30-32	DRAINAGE AND UTILITIES PROFILES
33	INTERSECTION PAVING PLAN
34	ECOLOGY CENTER CIRCLE DRIVE
35-37	PAVEMENT MARKING AND SIGNING PLAN
38-42	TRAFFIC SIGNAL DETAILS
43-45	TRAFFIC SIGNAL PLANS - BRIDGE STREET
46-48	TRAFFIC SIGNAL PLANS - GREEN BAY ROAD
49-50	ROADWAY LIGHTING PLANS
51-53	STREET LIGHTING DETAILS
54-55	BD-01/BD-02 DRIVEWAY DETAILS
56	BD-07 DETAIL OF STORM SEWER CONNECTION TO EXISTING SEWER
57	BD-08 DETAILS FOR FRAMES AND LIDS ADJUSTMENT FOR MILLING
58	BD-36 FIRE HYDRANT TO BE MOVED
59	CITY OF EVANSTON FIRE HYDRANT DETAIL
60	MWRD MH ADJ. DETAILS
61	TC-10 TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS AND DRIVEWAYS
62	TC-11 TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS (SNOW-PLOW RESISTANT)
63	TC-13 DISTRICT ONE TYPICAL PAVEMENT MARKINGS
64	TC-14 TRAFFIC CONTROL AND PROTECTION AT TURN BAYS (TO REMAIN OPEN TO TRAFFIC)
65	TC-16 PAVEMENT MARKING LETTERS AND SYMBOLS FOR TRAFFIC STAGING
66-100	CROSS SECTIONS -- MCCORMICK BLVD
101-108	CROSS SECTIONS -- GREEN BAY ROAD

STATE STANDARDS

STD. NO.

DESCRIPTION

000001-04	STANDARD SYMBOLS, ABBREVIATIONS, AND PATTERNS
280001-02	TEMPORARY EROSION CONTROL SYSTEMS
353001-02	PCC BASE COURSE WITH BITUMINOUS CONCRETE BINDER AND SURFACE COURSES
420001-06	PAVEMENT JOINTS
424001-04	CURB RAMPS FOR SIDEWALKS
442201-01	CLASS C AND D PATCHES
542101	REINFORCED CONCRETE END SECTIONS FOR PIPE CULVERTS 15" THRU 36" DIAMETER AT RIGHT ANGLES WITH ROADWAY
601001	SUB-SURFACE DRAINS
602001	CATCH BASIN, TYPE A
602011	CATCH BASIN, TYPE C
602301	INLET, TYPE A
602401	MANHOLE, TYPE A
602501	VALVE VAULT, TYPE A
602601	PRECAST REINFORCED CONCRETE FLAT SLAB TOP
604001-02	FRAME AND LIDS, TYPE 1
604006-02	FRAME AND GRATE, TYPE 3
604036-01	GRATE, TYPE 8
604076-02	FRAME AND GRATE, TYPE 21
606001-02	CONCRETE CURB TYPE B AND COMBINATION CONCRETE CURB AND GUTTER
664001-01	CHAIN LINK FENCE
701501-03	URBAN LANE CLOSURE, 2L, 2W, UNDIVIDED
701701-04	URBAN LANE CLOSURE, MULTILANE INTERSECTION
701801-03	LANE CLOSURE, MULTILANE 1W OR 2W CROSSWALK OR SIDEWALK CLOSURE
702001-05	TRAFFIC CONTROL DEVICES
720001	SIGN PANEL MOUNTING DETAILS
720006	SIGN PANEL ERECTION DETAILS
720011	METAL POSTS FOR SIGNS, MARKERS AND DELINEATORS
720016-01	MAST ARM MOUNTED STREET NAME SIGNS
729001	APPLICATIONS OF TYPE A AND B METAL POSTS (FOR SIGNS & MARKERS)
780001-01	TYPICAL PAVEMENT MARKINGS
781001-02	TYPICAL APPLICATIONS RAISED REFLECTIVE PAVEMENT MARKERS
805001	ELECTRICAL SERVICE INSTALLATION DETAILS
814001	CONCRETE HANDHOLES
814006	DOUBLE HANDHOLES
857001	STANDARD PHASE DESIGNATION DIAGRAMS AND PHASE SEQUENCES
877001-02	STEEL MAST ARM ASSEMBLY AND POLE
878001-03	CONCRETE FOUNDATION DETAILS
880001	SPAN WIRE MOUNTED SIGNALS AND FLASHING BEACON INSTALLATION
880006	TRAFFIC SIGNAL MOUNTING DETAILS
886001	DETECTOR LOOP INSTALLATIONS

GEOTECHNICAL:

A GEOTECHNICAL REPORT HAS BEEN DEVELOPED FOR THIS PROJECT BY GREAT LAKES SOIL & ENVIRONMENTAL CONSULTANTS. INFORMATION FOR GEOTECHNICAL DATA ALONG THE NORTH SHORE CHANNEL IS ALSO AVAILABLE. A COPY OF THE GEOTECHNICAL INFORMATION FOR THIS PROJECT IS AVAILABLE FOR REVIEW AT THE CITY OF EVANSTON OR AT TRANSYSTEMS CORPORATION.

REVISIONS	
NAME	DATE
CEC/PAS	5/23/05
CEC/PAS	12/02/05

ILLINOIS DEPARTMENT OF TRANSPORTATION

INDEX OF SHEETS, GENERAL NOTES
AND STATE STANDARDS

MCCORMICK BOULEVARD

NO SCALE

DATE 9/03/04
DRAWN BY GEW
CHECKED BY PAS

CONTRACT NO. 83773