Structure Number	Station	Design Truss Type	Exterior Units (2)			Interior Unit			Upper & Lower Chord		Verticals; Horizontals; Vertical, Horizontal, and Interior Diagonals		Camber	Splicing Flange						
			No. Panels per Unit	Unit Lgth.(L _e)	Panel Lgth.(P)	No. Req′d.	No. Panels per Unit	Unit Lgth.(L _i)	Panel Lgth.(P)		Wall	0.D.	Wall	ui Midspan	Boli No./Splice		Weld W	Sizes W1	A	В
5 S 057 1074 L134.10	647+84	III-A	5	27'-8 ¹ 2"	5'-2"	1	6	32'- 3"	5'-2"	7"	516 "	3'4"	5 ₁₆ "	1 ¹ 2"	6	1"	7,6 "	5 _{/6} "	11 ¹ 2"	15"
5 S 057 1055 R156.20	645+76	III-A	RE-US	E EXIST.	ING TRUS	S				7" (E	XISTING)	3'4" (EX)	(STING)							
5 S 057 U055 R000.20	71+67	II- A	7	35′-8 ¹ 2"	4'-10"	0	-	-	-	5'2"	516 "	3"	5 ₁₆ "	1'2"	6	⁷ 8"	3 ₈ "	1 <u>,</u> "	9′ <u>4</u> ″	12'4'
																				+
																				+

TRUSS UNIT TABLE

SCALE:

SHEET NO. 5 OF 24 SHEETS



054-A-2

PLOT DATE = 10/7/2011

DATE

- 04/26/11

REVISED

FILE NAME =



ł

ł

ł



TRUSS TYPES II-A & III-A SPLICING FLANGES

*To fit 0.D. of Chord with maximum gap of l_{16} ".

STA.	TO STA.			ILLINDIS FED. AID PROJECT								
II-A AND	III–A		•	**	Various	178	72					
LUMINUM	TRUSS	DETAILS	F.A. RTE.	SECTION	COUNTY	SHEETS	SHEET NO.					
	•VARIOUS COUNTIES ••D-5 OVD SIN STR REPL 2012-06											

ASTM B221, Alloy 6061-T6 or ASTM B209, Alloy 6061-T651