

INDEX OF SHEETS									
SHEET NO.	DESCRIPTION	STATE STANDARDS				GENERAL NOTES			
1	COVER SHEET	000001- <del>06</del> STANDARD SYMBOLS, ABBREVIATIONS AND PATTERNS				BEFORE STARTING ANY EXCAVATION THE CONTRACTOR SHALL CALL "JULIE" AT 800-892-0123 OR "CUAN" (CHICAGO UTILITY ALERT NETWORK) AT 312-744-7000 FOR FIELD LOCATIONS OF BURIED ELECTRIC, TELEPHONE AND GAS FACILITIES, (48 HOURS NOTIFICATION IS REQUIRED).			
2	INDEX OF SHEETS, STATE STANDARDS, AND GENERAL NOTES	442201- <del>03</del> CLASS C AND D PATCHES							
3	SUMMARY OF QUANTITIES	424001- <del>06</del> PERPENDICULAR CURB RAMPS FOR SIDEWALKS							
4-7	EXISTING AND PROPOSED TYPICAL SECTIONS	424021    DEPRESSED CORNER FOR SIDEWALKS				10 FEET (3 METERS) TRANSITIONS SHALL BE USED TO MATCH PROPOSED CURB AND GUTTER AND MEDIAN ITEMS OF WORK TO EXISTING CURBS AND GUTTERS AND MEDIANS IN THE FIELD, UNLESS OTHERWISE SHOWN. THE TRANSITION SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE FOR THE PROPOSED ITEMS OF WORK SPECIFIED.			
8-10	ROADWAY AND PAVEMENT MARKING PLANS	424031    MEDIAN PEDESTRIAN CROSSINGS							
11	PEDESTRIAN REFUGE MEDIAN DETAIL (NORTH AVE. - BETWEEN MAJOR AVE. AND PARKSIDE AVE.)	604011- <del>04</del> FRAME AND LIDS, TYPE 1							
12	DETAILS FOR FRAMES AND LIDS ADJUSTMENT WITH MILLING	606001- <del>04</del> CONCRETE CURB AND COMBINATION CONCRETE CURB AND GUTTER				THE CONTRACTOR SHALL COORDINATE CONSTRUCTION ACTIVITIES WITH THE UTILITY COMPANIES AND THE CITY OF CHICAGO AND THE VILLAGE OF OAK PARK.			
13	PAVEMENT PATCHING FOR HMA SURFACED PAVEMENT	606301- <del>04</del> PCC CONCRETE ISLANDS AND MEDIANS							
14	CURB OR CURB AND GUTTER REMOVAL AND REPLACEMENT	701601- <del>07</del> LANE CLOSURE, MULTILANE, 1-W OR 2-W, WITH NON TRANSVERSABLE MEDIAN							
15	BUTT JOINT AND HMA TAPER DETAILS	701606- <del>08</del> URBAN LANE CLOSURE, MULTILANE 2-W WITH MOUNTABLE MEDIAN				THE CONTRACTOR WILL NOT BE ALLOWED TO SET UP A YARD OR FIELD OFFICE ON STATE PROPERTY WITHOUT WRITTEN PERMISSION FROM THE DEPARTMENT.			
16	CITY OF CHICAGO CATCH BASIN, INLET AND MANHOLE DETAILS	701701- <del>08</del> LANE CLOSURE, MULTILANE, INTERSECTION, FOR SPEEDS < 45 MPH							
17	TRAFFIC CONTROL AND PROTECTION FOR SIDE ROADS, INTERSECTIONS, AND DRIVEWAYS	701801- <del>05</del> LANE CLOSURE, MULTILANE, 1W OR 2W, CROSSWALK OR SIDEWALK CLOSURE							
18	TYPICAL APPLICATIONS FOR RAISED REFLECTIVE PAVEMENT MARKERS (SNOW PLOW RESISTANT)	701901- <del>02</del> TRAFFIC CONTROL DEVICES				THE CONTRACTOR SHALL CONTRACT THE DISTRICT ONE TRAFFIC CONTROL SUPERVISOR CORY JUCIUS AT (847) 705-4470 A MINIMUM OF 72 HOURS PRIOR TO START OF WORK.			
19	DISTRICT ONE TYPICAL PAVEMENT MARKINGS	720001- <del>01</del> SIGN PANEL MOUNTING DETAILS							
20-21	CITY OF CHICAGO TYPICAL PAVEMENT MARKINGS	720006- <del>03</del> SIGN PANEL ERECTION DETAILS							
22	TRAFFIC CONTROL AND PROTECTION AT TURN BAYS	720011- <del>01</del> METAL POST FOR SIGNS, MARKERS & DELINEATORS				WHEN MILLED PAVEMENT IS OPEN TO TRAFFIC THE MAXIMUM GRADE DIFFERENTIAL BETWEEN PASSES OF THE MILLING MACHINE SHALL NOT EXCEED 1½ INCHES (40MM) WHERE THE SPEED LIMIT IS 45 MPH (80 KM/H). WITH WRITEN APPROVAL FROM THE ENGINEER, A MAXIMUM GRADE DIFFERENTIAL OF 3 INCHES (75MM) MAY BE ALLOWED IF THE EDGE OF THE MILLING IS SLOPED A MINIMUM 1:3 (V:H) BUTT JOINTS WILL BE INSTALLED AT THE ENDS OF ALL RESURFACING (WHERE RESURFACING MEETS EXISTING PAVEMENT), IN ACCORDANCE WITH THE "BUTT JOINT AND HMA TAPER DETAILS" SHEET INCLUDED IN THE PLANS, UNLESS OTHERWISE SPECIFIED.			
23	TEMPORARY PAVEMENT MARKING--LETTERS AND SYMBOLS FOR TRAFFIC STAGING	729001- <del>01</del> APPLICATION FOR TYPES A & B METAL POSTS (FOR SIGNS & MARKERS)							
24-29	STANDARD TRAFFIC SIGNAL DESIGN DETAILS	780001- <del>03</del> TYPICAL PAVEMENT MARKINGS							
30	DETECTOR LOOP INSTALLATION DETAILS FOR ROADWAY RESURFACING	886001- <del>01</del> DETECTOR LOOP INSTALLATIONS				PERMANENT PAVEMENT MARKINGS SHALL BE THERMOPLASTIC (OF THE EXTRUDED TYPE) AND SHOULD BE PLACED IN ACCORDANCE WITH THE "CITY OF CHICAGO TYPICAL PAVEMENT MARKINGS" DETAIL. (TC-24) RAISED REFLECTIVE PAVEMENT MARKERS SHALL BE IN ACCORDANCE WITH THE DISTRICT ONE "TYPICAL APPLICATION RAISED REFLECTIVE PAVEMENT MARKERS" DETAIL.			
31-33	DETECTOR LOOP LOCATION DETAILS	886006- <del>01</del> TYPICAL LAYOUT FOR DETECTION LOOPS							
34	ARTERIAL ROAD INFORMATION SIGNING								