

## **EXISTING LEGEND**

- 1 EXISTING HMA SURFACE 11/2"- 2"
- 2 EXISTING HMA BINDER 21/2"
- EXISTING HMA BASE 10.25"
- BITUMINOUS SHOULDER 10"
- EXISTING COMB CONC. CURB AND GUTTER, TYPE B-6.24
- AGGREGATE SHOULDER

## PROPOSED LEGEND

- POLYMERIZED HOT-MIX ASPHALT SURFACE COURSE, MIX "F", N90, 2"
- GEOTECHNICAL FABRIC FOR GROUND STABILIZATION
- HOT-MIX ASPHALT BASE COURSE WIDENING, 91/4"/ HOT-MIX ASPHALT BASE COURSE, 91/4"
- HOT-MIX ASPHALT SHOULDERS, 8"
- HOT-MIX ASPHALT BINDER COURSE, IL-19.0, N70 21/4" & VARIES
- AGGREGATE SUBGRADE, 12"
- AGGREGATE SHOULDER, TYPE B 6"
- COMBINATION CONCRETE CURB AND GUTTER, TYPE B-6.24
- PIPE UNDERDRAINS, FABRIC LINED TRENCH 4"
- SURFACE REMOVAL, VARIABLE DEPTH (SPECIAL) (3/4" MIN. & VARIES)

SECTION

CONTRACT NO. 63623

- K LEVELING BINDER (MACHINE METHOD), N70 (0" - 21/4" MAX.)
- (L) NOT USED

TO STA.

- TOPSOIL FURNISH AND PLACE, 4"
- SEEDING, CLASS 2A N
- 0 PC CONCRETE ISLANDS AND MEDIANS
- POROUS GRANULAR EMBANKMENT, SUBGRADE/REMOVAL AND DISPOSAL OF UNSUITABLE MATERIAL