

- 21						
1	À	USER NAME = nparris	DESIGNED - HLF	REVISED -		STRUCTURAL STEEL DETAIL
ų	WILLS BURKE KELSEY ASSOCIATES LTD.		CHECKED - AEU	REVISED -	STATE OF ILLINOIS	STRUCTURE NO. 045–3080
Ν	WBK 116 West Main Street, Suite 201 St. Charles, Illinois 60174	PLOT SCALE =	DRAWN - HLF	REVISED -	DEPARTMENT OF TRANSPORTATION	
ILE	American M.	PLOT DATE = 11/17/2011	CHECKED - AEU	REVISED -		SHEET NO. 14 OF 20 SHEETS
14						

NOTES:

Anchor bolts shall be ASTM F1554 all-thread (or an Engineer-approved alternate material) of the grade(s) and diameter(s) specified. The corresponding specified grade of AASHTO M314 anchor bolts may be used in lieu of ASTM F1554.

Anchor bolts at fixed bearings may be either cast in place or installed in holes drilled after the supported member is in place.

Drilled and set anchor bolts shall be installed according to Article 521.06 of the Standard Specifications. Two 1/8 in. adjusting shims shall be provided for each bearing location in addition to all other plates or shims and placed as shown on bearing details.

<u> </u>	LL	OF	MA7	'ER	IAL	

Item	Unit	Total
Anchor Bolts, 1"	Each	20

DETAILS			SECTION				COUNTY		TOTAL SH SHEETS N		
-3080	019	4	08-14117-00-BR			Γ	KANE		76	47	
HEETS								CONTRAC	T	NO. 6	3645
HEEIS	FED.	ROAD	DIST.	NO.	ILLINOIS	FED.	AID	PROJECT			